

003623

REPORT
of the
RIO GRANDE COMPACT
COMMISSION

1971



TO THE GOVERNORS OF
Colorado, New Mexico and Texas

009625

CONTENTS

	Page
Thirty-third Annual Report to Governors	1
Rio Grande Compact	2
Resolution of the Commission	15
Rules and Regulations	19
Records of Deliveries and Releases	26
Deliveries by Colorado at State line	27
Deliveries by New Mexico at Elephant Butte	28
Release and Spill from Project Storage	29
Cost of Operation and Budget	30
Acknowledgments	31
Accuracy of Records	32
Streamflow	33
Rio Grande near Del Norte, Colo.	33
Conejos River below Platoro Reservoir, Colo.	33
Conejos River near Mogote, Colo.	34
San Antonio River at Ortiz, Colo.	34
Los Pinos River near Ortiz, Colo.	35
Conejos River near Lasausas, Colo.	35
Rio Grande near Lobatos, Colo.	36
Willow Creek above Azotea Creek, near Park View, N. Mex.	36
Willow Creek above Heron Reservoir, near Park View, N. Mex.	37
Horse Lake Creek above Heron Reservoir, near Park View, N. Mex.	37
Willow Creek below Heron Dam, N. Mex.	38
Rio Chama below El Vado Dam, N. Mex.	38
Rio Chama below Abiquiu Dam, N. Mex.	39
Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.	39
Santa Fe River near Santa Fe, N. Mex.	40
Galisteo Creek below Galisteo Dam, N. Mex.	40
Jemez River below Jemez Canyon Dam, N. Mex.	41
Rio Grande below Elephant Butte Dam, N. Mex.	41
Rio Grande below Caballo Dam, N. Mex.	42
Bonito ditch below Caballo Dam, N. Mex.	42
Storage in Reservoirs	43
Transmountain Diversions	49
Evaporation and Precipitation	50

ILLUSTRATIONS

Map, Rio Grande Basin above Ft. Quitman, Tex.	Frontispiece
Map, Rio Grande Basin above Bernalillo, N. Mex.	52

003626

RIO GRANDE COMPACT COMMISSION
COLORADO TEXAS NEW MEXICO

The Honorable Bruce King
Governor of the State of New Mexico
Santa Fe, New Mexico

April 21, 1972

The Honorable Preston Smith
Governor of the State of Texas
Austin, Texas

The Honorable John A. Love
Governor of the State of Colorado
Denver, Colorado

Sirs:

The 33rd annual meeting of the Rio Grande Compact Commission was held at El Paso, Texas, on April 20-21, 1972.

The Commission reviewed its prior reports and the current reports of the Secretary relative to streamflow at Compact gaging stations and storage in reservoirs. The Commission found that:


(a) Deliveries of water at the Colorado-New Mexico State line by Colorado amounted to 206,800 acre-feet, which was 36,800 acre-feet in excess of the scheduled delivery in 1971. The accrued debit for Colorado was reduced to 793,700 acre-feet as of December 31, 1971. However, in light of the, as yet unresolved, controversy between the States, Colorado cannot agree with the conclusions as to her indebtedness.

(b) Deliveries of water into Elephant Butte Reservoir by New Mexico, as measured by the Elephant Butte Effective Supply, amounted to 367,800 acre-feet which was 42,800 acre-feet in excess of scheduled delivery in 1971. The accrued debit of New Mexico was reduced to 107,200 acre-feet as of December 31, 1971.


(c) Releases of usable water in 1971 from Project Storage amounted to 499,100 acre-feet, which was about 63 percent of the normal release defined by the Compact.

(d) Expenses of administration of the Rio Grande Compact were \$37,792 in the fiscal year ending June 30, 1971. The United States bore \$16,330 of this total; the balance of \$21,462 was borne equally by the three States party to the Compact.

Respectfully,


S. E. Reynolds, Commissioner for New Mexico


B. Gilmer, Commissioner for Texas


C. J. Kuiper, Commissioner for Colorado

729300

RIO GRANDE COMPACT

The State of Colorado, the State of New Mexico, and the State of Texas, desiring to remove all causes of present and future controversy among these States and between citizens of one of these States and citizens of another State with respect to the use of the waters of the Rio Grande above Fort Quitman, Texas, and being moved by considerations of interstate comity, and for the purpose of effecting an equitable apportionment of such waters, have resolved to conclude a Compact for the attainment of these purposes, and to that end, through their respective Governors, have named as their respective Commissioners:

For the State of Colorado	M. C. Hinderlider
For the State of New Mexico	Thomas M. McClure
For the State of Texas	Frank B. Clayton

who, after negotiations participated in by S. O. Harper, appointed by the President as the representative of the United States of America, have agreed upon the following articles, to-wit:

ARTICLE I

(a) The State of Colorado, the State of New Mexico, the State of Texas, and the United States of America, are hereinafter designated "Colorado," "New Mexico," "Texas," and the "United States," respectively.

(b) "The Commission" means the agency created by this Compact for the administration thereof.

(c) The term "Rio Grande Basin" means all of the territory drained by the Rio Grande and its tributaries in Colorado, in New Mexico, and in Texas above Fort Quitman, including the Closed Basin in Colorado.

(d) The "Closed Basin" means that part of the Rio Grande Basin in Colorado where the streams drain into the San Luis Lakes and adjacent territory, and do not normally contribute to the flow of the Rio Grande.

(e) The term "tributary" means any stream which naturally contributes to the flow of the Rio Grande.

(f) "Transmountain Diversion" is water imported into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, exclusive of the Closed Basin.

(g) "Annual Debits" are the amounts by which actual deliveries in any calendar year fall below scheduled deliveries.

003028

(h) "Annual Credits" are the amounts by which actual deliveries in any calendar year exceed scheduled deliveries.

(i) "Accrued Debits" are the amounts by which the sum of all annual debits exceeds the sum of all annual credits over any common period of time.

(j) "Accrued Credits" are the amounts by which the sum of all annual credits exceeds the sum of all annual debits over any common period of time.

(k) "Project Storage" is the combined capacity of Elephant Butte Reservoir and all other reservoirs actually available for the storage of usable water below Elephant Butte and above the first diversion to lands of the Rio Grande Project, but not more than a total of 2,638,860 acre feet.

(l) "Usable Water" is all water, exclusive of credit water, which is in project storage and which is available for release in accordance with irrigation demands, including deliveries to Mexico.

(m) "Credit Water" is that amount of water in project storage which is equal to the accrued credit of Colorado, or New Mexico, or both.

(n) "Unfilled Capacity" is the difference between the total physical capacity of project storage and the amount of usable water then in storage.

(o) "Actual Release" is the amount of usable water released in any calendar year from the lowest reservoir comprising project storage.

(p) "Actual Spill" is all water which is actually spilled from Elephant Butte Reservoir, or is released therefrom for flood control, in excess of the current demand on project storage and which does not become usable water by storage in another reservoir; provided, that actual spill of usable water cannot occur until all credit water shall have been spilled.

(q) "Hypothetical Spill" is the time in any year at which usable water would have spilled from project storage if 790,000 acre feet had been released therefrom at rates proportional to the actual release in every year from the starting date to the end of the year in which hypothetical spill occurs; in computing hypothetical spill the initial condition shall be the amount of usable water in project storage at the beginning of the calendar year following the effective date of this Compact, and thereafter the initial condition shall be the amount of usable water in project storage at the beginning of the calendar year following each actual spill.

ARTICLE II

The Commission shall cause to be maintained and operated a stream gaging station equipped with an automatic water stage recorder at each of the following points, to-wit:

- (a) On the Rio Grande near Del Norte above the principal points of diversion to the San Luis Valley;
- (b) On the Conejos River near Mogote;
- (c) On the Los Pinos River near Ortiz;
- (d) On the San Antonio River at Ortiz;
- (e) On the Conejos River at its mouths near Los Sauces;
- (f) On the Rio Grande near Lobatos;
- (g) On the Rio Chama below El Vado Reservoir;
- (h) On the Rio Grande at Otowi Bridge near San Ildefonso;
- (i) On the Rio Grande near San Acacia;
- (j) On the Rio Grande at San Marcial;
- (k) On the Rio Grande below Elephant Butte Reservoir;
- (l) On the Rio Grande below Caballo Reservoir.

Similar gaging stations shall be maintained and operated below any other reservoir constructed after 1929, and at such other points as may be necessary for the securing of records required for the carrying out of the Compact; and automatic water stage recorders shall be maintained and operated on each of the reservoirs mentioned, and on all others constructed after 1929.

Such gaging stations shall be equipped, maintained and operated by the Commission directly or in cooperation with an appropriate Federal or State agency, and the equipment, method and frequency of measurement at such stations shall be such as to produce reliable records at all times. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE III

The obligation of Colorado to deliver water in the Rio Grande at the Colorado-New Mexico State Line, measured at or near Lobatos, in each calendar year, shall be ten

003629

thousand acre feet less than the sum of those quantities set forth in the two following tabulations of relationship, which correspond to the quantities at the upper index stations:

DISCHARGE OF CONEJOS RIVER

Quantities in thousands of acre feet

Conejos Index Supply (1)	Conejos River at Mouths (2)
100	0
150	20
200	45
250	75
300	109
350	147
400	188
450	232
500	278
550	326
600	376
650	426
700	476

Intermediate quantities shall be computed by proportional parts.

(1) Conejos Index Supply is the natural flow of Conejos River at the U.S.G.S. gaging station near Mogote during the calendar year, plus the natural flow of Los Pinos River at the U.S.G.S. gaging station near Ortiz and the natural flow of San Antonio River at the U.S.G.S. gaging station at Ortiz, both during the months of April to October, inclusive.

(2) Conejos River at Mouths is the combined discharge of branches of this river at the U.S.G.S. gaging stations near Los Sauces during the calendar year.

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER

Quantities in thousands of acre feet

Rio Grande at Del Norte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
200	60
250	65
300	75
350	86
400	98
450	112
500	127

003631

6 RIO GRANDE COMPACT COMMISSION REPORT

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER--Con.

Quantities in thousands of acre feet

Rio Grande at Del Norte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
550	144
600	162
650	182
700	204
750	229
800	257
850	292
900	335
950	380
1,000	430
1,100	540
1,200	640
1,300	740
1,400	840

Intermediate quantities shall be computed by proportional parts.

(3) Rio Grande at Del Norte is the recorded flow of the Rio Grande at the U.S.G.S. gaging station near Del Norte during the calendar year (measured above all principal points of diversion to San Luis Valley) corrected for the operation of reservoirs constructed after 1937.

(4) Rio Grande at Lobatos less Conejos at Mouths is the total flow of the Rio Grande at the U.S.G.S. gaging station near Lobatos, less the discharge of Conejos River at its Mouths, during the calendar year.

The application of these schedules shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) any new or increased depletion of the runoff above inflow index gaging stations; and (c) any transmountain diversions into the drainage basin of the Rio Grande above Lobatos.

In event any works are constructed after 1937 for the purpose of delivering water into the Rio Grande from the Closed Basin, Colorado shall not be credited with the amount of such water delivered, unless the proportion of sodium ions shall be less than forty-five percent of the total positive ions in that water when the total dissolved solids in such water exceeds three hundred fifty parts per million.

003632

ARTICLE IV

The obligation of New Mexico to deliver water in the Rio Grande at San Marcial, during each calendar year, exclusive of the months of July, August, and September, shall be that quantity set forth in the following tabulation of relationship, which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND AT
SAN MARCIAL EXCLUSIVE OF JULY, AUGUST AND SEPTEMBER

Quantities in thousands of acre feet

Otowi Index Supply (5)	San Marcial Index Supply (6)
100	0
200	65
300	141
400	219
500	300
600	383
700	469
800	557
900	648
1,000	742
1,100	839
1,200	939
1,300	1,042
1,400	1,148
1,500	1,257
1,600	1,370
1,700	1,489
1,800	1,608
1,900	1,730
2,000	1,856
2,100	1,985
2,200	2,117
2,300	2,253

Intermediate quantities shall be computed by proportional parts.

(5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, exclusive of the flow during the months of July, August and September, corrected for the operation of reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi Bridge.

003633

(6) San Marcial Index Supply is the recorded flow of the Rio Grande at the gaging station at San Marcial during the calendar year exclusive of the flow during the months of July, August and September.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico at any time of the year of the natural runoff at Otowi Bridge; (c) depletion of the runoff during July, August and September of tributaries between Otowi Bridge and San Marcial, by works constructed after 1937; and (d) any transmountain diversions into the Rio Grande between Lobatos and San Marcial.

Concurrent records shall be kept of the flow of the Rio Grande at San Marcial, near San Acacia, and of the release from Elephant Butte Reservoir to the end that the records at these three stations may be correlated. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE V

If at any time it should be the unanimous finding and determination of the Commission that because of changed physical conditions, or for any other reason, reliable records are not obtainable, or cannot be obtained, at any of the stream gaging stations herein referred to, such stations may, with the unanimous approval of the Commission, be abandoned, and with such approval another station, or other stations, shall be established and new measurements shall be substituted which, in the unanimous opinion of the Commission, will result in substantially the same results, so far as the rights and obligations to deliver water are concerned, as would have existed if such substitution of stations and measurements had not been so made. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE VI

Commencing with the year following the effective date of this Compact, all credits and debits of Colorado and New Mexico shall be computed for each calendar year; provided, that in a year of actual spill no annual credits nor annual debits shall be computed for that year.

In the case of Colorado, no annual debit nor accrued debit shall exceed 100,000 acre feet, except as either or both may be caused by holdover storage of water in reservoirs constructed after 1937 in the drainage basin of the

003634

Rio Grande above Lobatos. Within the physical limitations of storage capacity in such reservoirs, Colorado shall retain water in storage at all times to the extent of its accrued debit.

In the case of New Mexico, the accrued debit shall not exceed 200,000 acre feet at any time, except as such debit may be caused by holdover storage of water in reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and San Marcial. Within the physical limitations of storage capacity in such reservoirs, New Mexico shall retain water in storage at all times to the extent of its accrued debit. In computing the magnitude of accrued credits or debits, New Mexico shall not be charged with any greater debit in any one year than the sum of 150,000 acre-feet and all gains in the quantity of water in storage in such year.

The Commission by unanimous action may authorize the release from storage of any amount of water which is then being held in storage by reason of accrued debits of Colorado or New Mexico; provided, that such water shall be replaced at the first opportunity thereafter.

In computing the amount of accrued credits and accrued debits of Colorado or New Mexico, any annual credits in excess of 150,000 acre feet shall be taken as equal to that amount.

In any year in which actual spill occurs, the accrued credits of Colorado, or New Mexico, or both, at the beginning of the year shall be reduced in proportion to their respective credits by the amount of such actual spill; provided, that the amount of actual spill shall be deemed to be increased by the aggregate gain in the amount of water in storage, prior to the time of spill, in reservoirs above San Marcial constructed after 1929; provided, further, that if the Commissioners for the States having accrued credits authorize the release of part, or all, of such credits in advance of spill, the amount so released shall be deemed to constitute actual spill.

In any year in which there is actual spill of usable water, or at the time of hypothetical spill thereof, all accrued debits of Colorado, or New Mexico, or both, at the beginning of the year shall be cancelled.

In any year in which the aggregate of accrued debits of Colorado and New Mexico exceeds the minimum unfilled capacity of project storage, such debits shall be reduced proportionally to an aggregate amount equal to such minimum unfilled capacity.

003635

To the extent that accrued credits are impounded in reservoirs between San Marcial and Courchesne, and to the extent that accrued debits are impounded in reservoirs above San Marcial, such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bore to the total amount of water in such reservoirs during the year.

ARTICLE VII

Neither Colorado nor New Mexico shall increase the amount of water in storage in reservoirs constructed after 1929 whenever there is less than 400,000 acre feet of usable water in project storage; provided, that if the actual releases of usable water from the beginning of the calendar year following the effective date of this Compact, or from the beginning of the calendar year following actual spill, have aggregated more than an average of 790,000 acre feet per annum, the time at which such minimum stage is reached shall be adjusted to compensate for the difference between the total actual release and releases at such average rate; provided, further, that Colorado, or New Mexico, or both, may relinquish accrued credits at any time, and Texas may accept such relinquished water, and in such event the state, or states, so relinquishing shall be entitled to store water in the amount of the water so relinquished.

ARTICLE VIII

During the month of January of any year the Commissioner for Texas may demand of Colorado and New Mexico, and the Commissioner for New Mexico may demand of Colorado, the release of water from storage reservoirs constructed after 1929 to the amount of the accrued debits of Colorado and New Mexico, respectively, and such releases shall be made by each at the greatest rate practicable under the conditions then prevailing, and in proportion to the total debit of each, and in amounts, limited by their accrued debits, sufficient to bring the quantity of usable water in project storage to 600,000 acre feet by March first and to maintain this quantity in storage until April thirtieth, to the end that a normal release of 790,000 acre feet may be made from project storage in that year.

ARTICLE IX

Colorado agrees with New Mexico that in event the United States or the State of New Mexico decides to construct the necessary works for diverting the waters of the San Juan River, or any of its tributaries, into the Rio Grande, Colorado hereby consents to the construction of said works and the diversion of waters from the San Juan

River, or the tributaries thereof, into the Rio Grande in New Mexico, provided the present and prospective uses of water in Colorado by other diversions from the San Juan River, or its tributaries, are protected.

ARTICLE X

In the event water from another drainage basin shall be imported into the Rio Grande Basin by the United States or Colorado or New Mexico, or any of them jointly, the State having the right to the use of such water shall be given proper credit therefor in the application of the schedules.

ARTICLE XI

New Mexico and Texas agree that upon the effective date of this Compact all controversies between said States relative to the quantity or quality of the water of the Rio Grande are composed and settled; however, nothing herein shall be interpreted to prevent recourse by a signatory state to the Supreme Court of the United States for redress should the character or quality of the water, at the point of delivery, be changed hereafter by one signatory state to the injury of another. Nothing herein shall be construed as an admission by any signatory state that the use of water for irrigation causes increase of salinity for which the user is responsible in law.

ARTICLE XII

To administer the provisions of this Compact there shall be constituted a Commission composed of one representative from each state, to be known as the Rio Grande Compact Commission. The State Engineer of Colorado shall be ex-officio the Rio Grande Compact Commissioner for Colorado. The State Engineer of New Mexico shall be ex-officio the Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for Texas shall be appointed by the Governor of Texas. The President of the United States shall be requested to designate a representative of the United States to sit with such Commission, and such representative of the United States, if so designated by the President, shall act as Chairman of the Commission without vote.

The salaries and personal expenses of the Rio Grande Compact Commissioners for the three States shall be paid by their respective States, and all other expenses incident to the administration of this Compact, not borne by the United States, shall be borne equally by the three States.

063637

In addition to the powers and duties hereinbefore specifically conferred upon such Commission, and the members thereof, the jurisdiction of such Commission shall extend only to the collection, correlation and presentation of factual data and the maintenance of records having a bearing upon the administration of this Compact, and, by unanimous action, to the making of recommendations to the respective States upon matters connected with the administration of this Compact. In connection therewith, the Commission may employ such engineering and clerical aid as may be reasonably necessary within the limit of funds provided for that purpose by the respective States. Annual reports compiled for each calendar year shall be made by the Commission and transmitted to the Governors of the signatory States on or before March first following the year covered by the report. The Commission may, by unanimous action, adopt rules and regulations consistent with the provisions of this Compact to govern their proceedings.

The findings of the Commission shall not be conclusive in any court or tribunal which may be called upon to interpret or enforce this Compact.

ARTICLE XIII

At the expiration of every five-year period after the effective date of this Compact, the Commission may, by unanimous consent, review any provisions hereof which are not substantive in character and which do not affect the basic principles upon which the Compact is founded, and shall meet for the consideration of such questions on the request of any member of the Commission; provided, however, that the provisions hereof shall remain in full force and effect until changed and amended within the intent of the Compact by unanimous action of the Commissioners, and until any changes in this Compact are ratified by the legislatures of the respective states and consented to by the Congress, in the same manner as this Compact is required to be ratified to become effective.

ARTICLE XIV

The schedules herein contained and the quantities of water herein allocated shall never be increased nor diminished by reason of any increase or diminution in the delivery or loss of water to Mexico.

ARTICLE XV

The physical and other conditions characteristic of the Rio Grande and peculiar to the territory drained and served thereby, and to the development thereof, have actuated this Compact and none of the signatory states admits that any provisions herein contained establishes any general principle or precedent applicable to other interstate streams.

ARTICLE XVI

Nothing in this Compact shall be construed as affecting the obligations of the United States of America to Mexico under existing treaties, or to the Indian Tribes, or as impairing the rights of the Indian Tribes.

ARTICLE XVII

This Compact shall become effective when ratified by the legislatures of each of the signatory states and consented to by the Congress of the United States. Notice of ratification shall be given by the Governor of each state to the Governors of the other states and to the President of the United States, and the President of the United States is requested to give notice to the Governors of each of the signatory states of the consent of the Congress of the United States.

IN WITNESS WHEREOF, the Commissioners have signed this Compact in quadruplicate original, one of which shall be deposited in the archives of the Department of State of the United States of America and shall be deemed the authoritative original, and of which a duly certified copy shall be forwarded to the Governor of each of the signatory States.

RIO GRANDE COMPACT COMMISSION REPORT

Done at the City of Santa Fe, in the State of New Mexico, on the 18th day of March, in the year of our Lord, One Thousand Nine Hundred and Thirty-eight.

(Sgd.) M. C. HINDERLIDER

(Sgd.) THOMAS M. McCLURE

(Sgd.) FRANK B. CLAYTON

APPROVED:

(Sgd.) S. O. HARPER

RATIFIED BY:

Colorado, February 21, 1939
New Mexico, March 1, 1939
Texas, March 1, 1939

Passed Congress as Public Act No. 96, 76th Congress,
Approved by the President May 31, 1939.

003640

RESOLUTION ADOPTED BY RIO GRANDE COMPACT
COMMISSION AT THE ANNUAL MEETING HELD AT
EL PASO, TEXAS, FEBRUARY 22-24, 1948,
CHANGING GAGING STATIONS AND MEASUREMENTS
OF DELIVERIES BY NEW MEXICO

15

R E S O L U T I O N

Whereas, at the Annual Meeting of the Rio Grande Compact Commission in the year 1945, the question was raised as to whether or not a schedule for delivery of water by New Mexico during the entire year could be worked out, and

Whereas, at said meeting the question was referred to the Engineering Advisers for their study, recommendations and report, and

Whereas, said Engineering Advisers have met, studied the problems and under date of February 24, 1947, did submit their Report, which said Report contains the findings of said Engineering Advisers and their recommendations, and

Whereas, the Compact Commission has examined said Report and finds that the matters and things therein found and recommended are proper and within the terms of the Rio Grande Compact, and

Whereas, the Commission has considered said Engineering Advisers' Report and all available evidence, information and material and is fully advised:

Now, Therefore, Be it Resolved:

The Commission finds as follows:

- (a) That because of change of physical conditions, reliable records of the amount of water passing San Marcial are no longer obtainable at the stream gaging station at San Marcial and that the same should be abandoned for Compact purposes.
- (b) That the need for concurrent records at San Marcial and San Acacia no longer exists and that the gaging station at San Acacia should be abandoned for Compact purposes.
- (c) That it is desirable and necessary that the obligations of New Mexico under the Compact to deliver water in the months of July, August, September, should be scheduled.

003641

- (d) That the change in gaging stations and substitution of the new measurements as hereinafter set forth will result in substantially the same results so far as the rights and obligations to deliver water are concerned, and would have existed if such substitution of stations and measurements had not been so made.

Be it Further Resolved:

That the following measurements and schedule thereof shall be substituted for the measurements and schedule thereof as now set forth in Article IV of the Compact:

"The obligation of New Mexico to deliver water in the Rio Grande into Elephant Butte Reservoir during each calendar year shall be measured by that quantity set forth in the following tabulation of relationship which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY

Quantities in thousands of acre-feet

Otowi Index Supply (5)	Elephant Butte Effective Index Supply (6)
100	57
200	114
300	171
400	228
500	286
600	345
700	406
800	471
900	542
1,000	621
1,100	707
1,200	800
1,300	897
1,400	996
1,500	1,095
1,600	1,195
1,700	1,295
1,800	1,395
1,900	1,495
2,000	1,595

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND
ELEPHANT BUTTE EFFECTIVE SUPPLY--Continued

Quantities in thousands of acre-feet

Otowi Index Supply (5)	Elephant Butte Effective Index Supply (6)
2,100	1,695
2,200	1,795
2,300	1,895
2,400	1,995
2,500	2,095
2,600	2,195
2,700	2,295
2,800	2,395
2,900	2,495
3,000	2,595

Intermediate quantities shall be computed by proportional parts.

- (5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, corrected for the operation of reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi Bridge.
- (6) Elephant Butte Effective Index Supply is the recorded flow of the Rio Grande at the gaging station below Elephant Butte Dam during the calendar year plus the net gain in storage in Elephant Butte Reservoir during the same year or minus the net loss in storage in said reservoir, as the case may be.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico of the natural runoff at Otowi Bridge; and (c) any transmountain diversions into the Rio Grande between Lobatos and Elephant Butte Reservoir."

003642

003643

Be it Further Resolved:

That the gaging stations at San Acacia and San Marcial be, and the same are hereby abandoned for Compact purposes.

Be it Further Resolved:

That this Resolution has been passed unanimously and shall be effective January 1, 1949, if within 120 days from this date the Commissioner for each State shall have received from the Attorney General of the State represented by him, an opinion approving this Resolution, and shall have so advised the Chairman of the Commission, otherwise, to be of no force and effect.

(Note: The following paragraph appears in the Minutes of the Annual Meeting of the Commission held at Denver, Colorado, February 14-16, 1949:

"The Chairman announced that he had received, pursuant to the Resolution adopted by the Commission at the Ninth Annual Meeting on February 24, 1948, opinions from the Attorneys General of Colorado, New Mexico and Texas that the substitution of stations and measurements of deliveries by New Mexico set forth in said resolution was within the powers of the Commission").

003644

A Compact, known as the Rio Grande Compact, between the States of Colorado, New Mexico and Texas, having become effective on May 31, 1939 by consent of the Congress of the United States, which equitably apportions the waters of the Rio Grande above Fort Quitman and permits each State to develop its water resources at will, subject only to its obligations to deliver water in accordance with the schedules set forth in the Compact, the following Rules and Regulations have been adopted for its administration by the Rio Grande Compact Commission; to be and remain in force and effect only so long as the same may be satisfactory to each and all members of the Commission, and provided always that on the objection of any member of the Commission, in writing, to the remaining two members of the Commission after a period of sixty days from the date of such objection, the sentence, paragraph or any portion or all of these rules to which any such objection shall be made, shall stand abrogated and shall thereafter have no further force and effect; it being the intent and purpose of the Commission to permit these rules to obtain and be effective only so long as the same may be satisfactory to each and all of the Commissioners.

GAGING STATIONS /1

Responsibility for the equipping, maintenance and operation of the stream gaging stations and reservoir gaging stations required by the provisions of Article II of the Compact shall be divided among the signatory States as follows:

(a) Gaging stations on streams and reservoirs in the Rio Grande Basin above the Colorado-New Mexico boundary shall be equipped, maintained, and operated by Colorado in cooperation with the U.S. Geological Survey.

(b) Gaging stations on streams and reservoirs in the Rio Grande Basin below Lobatos and above Caballo Reservoir shall be equipped, maintained and operated by New Mexico in cooperation with the U.S. Geological Survey to the extent that such stations are not maintained and operated by some other Federal Agency.

(c) Gaging stations on Elephant Butte Reservoir and on Caballo Reservoir, and the stream gaging stations on the Rio Grande below those reservoirs shall be equipped, maintained and operated by or on behalf of Texas through the agency of the U.S. Bureau of Reclamation.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

003645

The equipment, method and frequency of measurements at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Water-stage recorders on the reservoirs specifically named in Article II of the Compact shall have sufficient range below maximum reservoir level to record major fluctuations in storage. Staff gages may be used to determine fluctuations below the range of the water-stage recorders on these and other large reservoirs, and staff gages may be used upon approval of the Commission in lieu of water-stage recorders on small reservoirs, provided that the frequency of observation is sufficient in each case to establish any material changes in water levels in such reservoirs.

RESERVOIR CAPACITIES /1

Colorado shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin above Lobatos constructed after 1937; New Mexico shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin between Lobatos and San Marcial constructed after 1929; and Texas shall file with the Commission tables of areas and capacities for Elephant Butte Reservoir and for all other reservoirs actually available for the storage of water between Elephant Butte and the first diversion to lands under the Rio Grande Project.

Whenever it shall appear that any table of areas and capacities is in error by more than five per cent, the Commission shall use its best efforts to have a re-survey made and a corrected table of areas and capacities to be substituted as soon as practicable. To the end that the Elephant Butte effective supply may be computed accurately, the Commission shall use its best efforts to have the rate of accumulation and the place of deposition of silt in Elephant Butte Reservoir checked at least every three years.

ACTUAL SPILL /2

(a) Water released from Elephant Butte in excess of Project requirements, which is currently passed through Caballo Reservoir, prior to the time of spill, shall be deemed to have been Usable Water released in anticipation of spill, or Credit Water if such release shall have been authorized.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.
/2 Adopted at Fourth Annual Meeting, February 24, 1943.

003646

(b) Excess releases from Elephant Butte Reservoir, as defined in (a) above, shall be added to the quantity of water actually in storage in that reservoir, and Actual Spill shall be deemed to have commenced when this sum equals the total physical capacity of that reservoir, to the level of the uncontrolled spillway, i.e. -2,219,000 acre-ft in 1942.

(c) All water actually spilled at Elephant Butte Reservoir, or released therefrom, in excess of Project requirements, which is currently passed through Caballo Reservoir, after the time of spill, shall be considered as Actual Spill, provided that the total quantity of water then in storage in Elephant Butte Reservoir exceeds the physical capacity of that reservoir at the level of the sill of the spillway gates, i.e. -1,830,000 acre-ft in 1942.

(d) Water released from Caballo Reservoir in excess of Project requirements and in excess of water currently released from Elephant Butte Reservoir, shall be deemed Usable Water released, excepting only flood water entering Caballo Reservoir from tributaries below Elephant Butte Reservoir.

DEPARTURES FROM NORMAL RELEASES /3

For the purpose of computing the time of Hypothetical Spill required by Article VI and for the purpose of the adjustment set forth in Article VII, no allowance shall be made for the difference between Actual and Hypothetical Evaporation, and any under-release of usable water from Project Storage in excess of 150,000 acre-ft in any year shall be taken as equal to that amount.

EVAPORATION LOSSES /4, /5, /6

The Commission shall encourage the equipping, maintenance and operation, in cooperation with the U.S. Weather Bureau or other appropriate agency, of evaporation stations at Elephant Butte Reservoir and at or near each major reservoir in the Rio Grande Basin within Colorado constructed after 1937 and in New Mexico constructed after 1929. The net loss by evaporation from a reservoir surface shall be taken as the difference between the actual evaporation loss and the evapo-transpiration losses which would have occurred naturally, prior to the construction of such reservoir. Changes in evapo-transpiration losses along stream channels below reservoirs may be disregarded.

/3 Adopted June 2, 1959; made effective January 1, 1952.

/4 Amended at Tenth Annual Meeting, February 15, 1949.

/5 Amended at Twelfth Annual Meeting, February 24, 1951.

/6 Amended June 2, 1959.

003647

Net losses by evaporation, as defined above, shall be used in correcting Index Supplies for the operation of reservoirs upstream from Index Gaging Stations as required by the provisions of Article III and Article IV of the Compact.

In the application of the provisions of the last unnumbered paragraph of Article VI of the Compact:

(a) Evaporation losses for which accrued credits shall be reduced shall be taken as the difference between the gross evaporation from the water surface of Elephant Butte Reservoir and rainfall on the same surface.

(b) Evaporation losses for which accrued debits shall be reduced shall be taken as the net loss by evaporation as defined in the first paragraph.

ADJUSTMENT OF RECORDS

The Commission shall keep a record of the location, and description of each gaging station and evaporation station, and, in the event of change in location of any stream gaging station for any reason, it shall ascertain the increment in flow or decrease in flow between such locations for all stages. Wherever practicable, concurrent records shall be obtained for one year before abandonment of the previous station.

NEW OR INCREASED DEPLETIONS

In the event any works are constructed which alter or may be expected to alter the flow at any of the Index Gaging Stations mentioned in the Compact, or which may otherwise necessitate adjustments in the application of the schedules set forth in the Compact, it shall be the duty of the Commissioner specifically concerned to file with the Commission all available information pertaining thereto, and appropriate adjustments shall be made in accordance with the terms of the Compact; provided, however, that any such adjustments shall in no way increase the burden imposed upon Colorado or New Mexico under the schedules of deliveries established by the Compact.

TRANSMOUNTAIN DIVERSIONS

In the event any works are constructed for the delivery of waters into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, such waters shall be measured at the point of delivery into the Rio Grande Basin and proper allowances shall be made for losses in transit from such points to the Index Gaging Station on the stream with which the imported waters are comingled.

003648

QUALITY OF WATER

In the event that delivery of water is made from the Closed Basin into the Rio Grande, sufficient samples of such water shall be analyzed to ascertain whether the quality thereof is within the limits established by the Compact.

SECRETARY 7

The Commission, subject to the approval of the Director, U.S. Geological Survey, to a cooperative agreement for such purposes, shall employ the U.S. Geological Survey on a yearly basis, to render such engineering and clerical aid as may reasonably be necessary for administration of the Compact. Said agreement shall provide that the Geological Survey shall:

(1) Collect and correlate all factual data and other records having a material bearing on the administration of the Compact and keep each Commissioner advised thereof.

(2) Inspect all gaging stations required for administration of the Compact and make recommendations to the Commission as to any changes or improvements in methods of measurement or facilities for measurement which may be needed to insure that reliable records be obtained.

(3) Report to each Commissioner by letter on or before the fifteenth day of each month, except January, a summary of all hydrographic data then available for the current year - on forms prescribed by the Commission - pertaining to:

- (a) Deliveries by Colorado
- (b) Deliveries by New Mexico
- (c) Operation of Project Storage

(4) Make such investigations as may be requested by the Commission in aid of its administration of the Compact.

(5) Act as Secretary to the Commission and submit to the Commission at its regular meeting in February a report on its activities and a summary of all data needed for determination of debits and credits and other matters pertaining to administration of the Compact.

7 The substitution of this section for the section titled "Reports to Commissioners" was adopted at Ninth Annual Meeting, February 22, 1948.

COSTS /1

In February of each year, the Commission shall adopt a budget for the ensuing fiscal year beginning July first.

Such budget shall set forth the total cost of maintenance and operating of gaging stations, of evaporation stations, the cost of engineering and clerical aid, and all other necessary expenses excepting the salaries and personal expenses of the Rio Grande Compact Commissioners.

Contributions made directly by the United States and the cost of services rendered by the United States without cost shall be deducted from the total budget amount; the remainder shall then be allocated equally to Colorado, New Mexico and Texas.

Expenditures made directly by any State for purposes set forth in the budget shall be credited to that State; contributions in cash or in services by any State under a cooperative agreement with any federal agency shall be credited to such State, but the amount of the federal contribution shall not so be credited; in event any State, through contractual relationships, causes work to be done in the interest of the Commission, such State shall be credited with the cost thereof, unless such cost is borne by the United States.

Costs incurred by the Commission under any cooperative agreement between the Commission and any U.S. Government Agency, not borne by the United States, shall be apportioned equally to each State, and each Commissioner shall arrange for the prompt payment of one-third thereof by his State.

The Commissioner of each State shall report at the annual meeting each year the amount of money expended during the year by the State which he represents, as well as the portion thereof contributed by all cooperating federal agencies, and the Commission shall arrange for such proper reimbursement in cash or credits between States as may be necessary to equalize the contributions made by each State in the equipment, maintenance and operation of all gaging stations authorized by the Commission and established under the terms of the Compact.

It shall be the duty of each Commissioner to endeavor to secure from the Legislature of his State an appropriation of sufficient funds with which to meet the obligations of his State, as provided by the Compact.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

003649

MEETING OF COMMISSION 1, 8

003650

The Commission shall meet in Santa Fe, New Mexico, on the third Thursday of February of each year for the consideration and adoption of the annual report for the calendar year preceding, and for the transaction of any other business consistent with its authority; provided that the Commission may agree to meet elsewhere. Other meetings as may be deemed necessary shall be held at any time and place set by mutual agreement, for the consideration of data collected and for the transaction of any business consistent with its authority.

No action of the Commission shall be effective until approved by the Commissioner from each of the three signatory States.

(Signed) M. C. HINDERLIDER

M. C. Hinderlider
Commissioner for Colorado

(Signed) THOMAS M. McCLURE

Thomas M. McClure
Commissioner for New Mexico

(Signed) JULIAN P. HARRISON

Julian P. Harrison
Commissioner for Texas

Adopted December 19, 1939.

1 Amended at Eleventh Annual Meeting, February 23, 1950.

8 Amended at Thirteenth Annual Meeting, February 25, 1952.

RECORDS OF DELIVERIES AND RELEASES

003651

At the annual meeting of the Compact Commission on April 20, 1972, the records of deliveries and releases for calendar year 1971 were examined and the computations of debits and credits based thereon were reviewed. The records and computations as reviewed by the Commission are reproduced on the next three pages.

The delivery of water in the Rio Grande at the Colorado-New Mexico State line was obtained from record of streamflow near Lobatos, Colorado; the obligation of Colorado to deliver water at the State line was computed as prescribed in Article III. Item C5, the Reduction of Debits prescribed in Article VI, was computed in accordance with the Rules and Regulations.

The delivery of water by New Mexico to Project Storage was computed from the actual streamflow record and the record of operation of Elephant Butte Reservoir; the scheduled delivery was computed as prescribed in the Resolution of the Commission adopted at the Tenth Annual Meeting, and published in this Report. Item NM4, Reduction of Debits by Evaporation, was computed in accordance with the Rules and Regulations.

The actual release from Project Storage during the year was measured at stations below Caballo Dam. The Accrued Departure from Normal Release is an under-release but is omitted in accordance with a decision of the Commission at the meeting on February 15, 1968.

RIO GRANDE COMPACT
DELIVERIES BY NEW MEXICO AT ELEPHANT BUTTE

003653

YEAR 1971

Quantities in Thousands of Acre Feet to Nearest Hundred

MONTH	OTOWI INDEX SUPPLY										Total Water Stored in New Mexico Above San Marcial at End of Month ^a			ELEPHANT BUTTE EFFECTIVE SUPPLY			
	Recorded Flow at Otwi Bridge	ADJUSTMENTS					INDEX SUPPLY					Accumulated Total	STORAGE IN ELEPHANT BUTTE RESERVOIR		Recorded Flow Below Elephant Butte Dam	EFFECTIVE SUPPLY	
		Storage - End of Month ^a	Reservoir Evaporation	Other Adjustments	Transmountain Diversions	Net Adjustment	During Month	Accumulated Total	End of Month	Change Gain (+) Loss (-)	During Month		Accumulated Total				
														Change in Storage		Reservoir Evaporation	Other Adjustments
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16		
		63.0								4.7	324.5						
JAN	44.3	3.2	+0.2	0	0	0	+0.2	44.5	44.5	4.8	367.8	+43.3	1.0	44.3	44.3		
FEB	48.7	3.9	+ .7	0	0	0	+ .7	49.4	93.9	5.5	361.1	-6.7	57.1	50.4	94.7		
MAR	70.1	6.8	+2.9	0	0	0	+2.9	73.0	166.9	8.3	316.5	-44.6	85.1	40.5	135.2		
APR	72.3	25.7	+18.9	.1	0	0	+19.0	91.3	258.2	27.0	289.0	-27.5	78.1	50.6	185.8		
MAY	55.2	25.9	+ .2	.2	0	0	+ .4	55.6	313.8	27.0	221.2	-67.8	84.2	16.4	202.2		
JUN	31.4	24.9	-1.0	.1	0	-6.0	-6.9	24.5	338.3	25.7	154.0	-67.2	68.4	1.2	203.4		
JUL	35.0	22.0	-2.9	.1	0	-5.4	-8.2	26.8	365.1	23.0	98.4	-55.6	55.8	.2	203.6		
AUG	28.5	22.5	+ .5	.1	0	0	+ .6	29.1	394.2	23.6	47.3	-51.1	68.3	17.2	220.8		
SEPT	23.6	24.0	+1.5	.3	0	-3.3	-1.5	22.1	416.3	25.3	35.4	-11.9	16.5	4.6	225.4		
OCT	56.0	22.1	-1.9	.2	0	0	-1.7	54.3	470.6	23.3	64.5	+29.1	.4	29.5	254.9		
NOV	68.5	3.8	-18.3	.1	0	0	-18.2	50.3	520.9	4.8	128.0	+63.5	.1	63.6	318.5		
DEC	45.2	3.7	- .1	c .1	0	0	0	45.2	566.1	4.8	177.0	+49.0	.3	49.3	367.8		
YEAR	578.8		+ .7	1.3	0	-14.7	-12.7	566.1				-147.5	515.3	367.8			

REMARKS:

- a Exclusive of San Juan water and storage in recreational reservoirs.
- b New capacity table for Abiquiu Reservoir effective Jan. 1, 1971.
- c Annual loss from recreational reservoirs.

SUMMARY OF DEBITS AND CREDITS

ITEM	DEBIT	CREDIT	BALANCE
NM1 Balance at Beginning of Year			DI. 150.5
NM2 Scheduled Delivery at Elephant Butte	325.0		DI. 475.5
NM3 Actual Elephant Butte Effective Supply		367.8	DI. 107.7
NM4 Reduction of Debits % Evaporation		0.5	DI. 107.2
NM5 Reduction of Credits % Evaporation			
NM6			
NM7			
NM8 Balance at End of Year			DI. 107.2

003654

RIO GRANDE COMPACT
RELEASE AND SPILL FROM PROJECT STORAGE

YEAR 1971

Quantities in Thousands of Acre Feet to Nearest Hundred

DATE	USABLE WATER IN STORAGE			UNFILLED CAPACITY OF PROJECT STORAGE AT END OF MONTH			CREDIT WATER IN STORAGE			TOTAL WATER IN PROJECT STORAGE AT END OF MONTH	FLOOD WATER IN STORAGE IN CABALLO RESERVOIR AT END OF MONTH	TOTAL WATER IN PROJECT STORAGE AT END OF MONTH	MEASURED FLOW AT CABALLO GAGING STATION	INTERVIEWING DIVISIONS TO CANALS	TOTAL RELEASE AND SPILL	SPILL FROM STORAGE			USABLE RELEASE	
	ELEPHANT BUTTE RESERVOIR	CABALLO RESERVOIR	TOTAL AT END OF MONTH	CABALLO RESERVOIR	PROJECT STORAGE	TOTAL AT END OF MONTH	COLORADO CREDIT WATER	NEW MEXICO CREDIT WATER	TOTAL AT END OF MONTH							CABALLO FLOOD WATER	CREDIT WATER	USABLE WATER	NET DURING MONTH	ACCUMULATED TOTAL
2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19			
	2,481.2	324.5	27.8	2,128.9	0	0	0	0	352.3											
W	2,481.2	367.8	30.2	2,083.2	0	0	0	0	398.0	0.1	0	0.1	0	0	0	0.1	0.1			
Th	2,481.2	361.1	74.5	2,045.6	0	0	0	0	435.6	4.8	0	4.8	0	0	0	4.8	4.9			
Fr	2,481.2	316.5	44.7	2,120.0	0	0	0	0	361.2	106.8	.2	107.0	0	0	0	107.0	111.9			
Sa	2,481.2	289.0	58.2	2,134.0	0	0	0	0	347.2	53.0	0	53.0	0	0	0	53.0	164.9			
Su	2,481.2	221.2	73.0	2,187.0	0	0	0	0	294.2	60.0	.1	60.1	0	0	0	60.1	225.0			
M	2,381.2	154.0	55.1	2,172.1	0	0	0	0	209.1	81.8	.1	81.9	0	0	0	81.9	306.9			
Tu	2,381.2	98.4	17.2	2,265.6	0	0	0	0	115.6	93.1	.1	93.2	0	0	0	93.2	400.1			
We	2,381.2	47.3	7.3	2,326.6	0	0	0	0	54.6	78.6	.1	78.7	0	0	0	78.7	478.8			
Th	2,381.2	35.4	6.1	2,339.7	0	0	0	0	41.5	20.0	.1	20.1	0	0	0	20.1	498.9			
Fr	2,481.2	64.5	11.0	2,405.7	0	0	0	0	75.5	.1	0	.1	0	0	0	.1	499.0			
Sa	2,481.2	128.0	12.9	2,340.3	0	0	0	0	140.9	0	0	0	0	0	0	0	499.0			
Su	2,481.2	177.0	15.1	2,289.1	0	0	0	0	192.1	.1	0	.1	0	0	0	.1	499.1			
AR										498.4	.7	499.1	0	0	0	499.1				

REMARKS: * See minutes of meeting Feb. 15, 1968.

The quantities of Project Storage and the unfilled portion of such storage do not include any of the 100,000 acre-feet of Caballo Reservoir capacity which the Regional Director, U.S. Bureau of Reclamation by letter of Feb. 12, 1960 stated is held in violation by the Bureau of Reclamation for flood control purposes from June 1 to October 1.

Project Storage was less than 400,000 acre-feet from Jan. 1 through Feb. 1 and Mar. 18 through Dec. 31.

ACCRUED DEPARTURE FROM NORMAL RELEASE

ITEM	DEBIT	CREDIT	BALANCE
P1	Accrued Departure at Beginning of Year		
P2	Actual Release during Year		
P3	Normal Release for Year		
P4	Actual Evaporation from Elephant Butte Reservoir		
P5	Evaporation Loss if No Accrued Departure		
P6			
P7	Accrued Departure at End of Year		

TIME OF HYPOTHETICAL SPILL

RIO GRANDE COMPACT COMMISSION REPORT

COST OF OPERATION, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1971

Adopted at the Thirty-third Annual Meeting

Item	Total Cost	Borne by United States	Borne by		
			Colorado	New Mexico	Texas
GAGING STATIONS					
In Colorado	10,480	5,240	5,240		
In New Mexico above Caballo Reservoir	14,460	9,180		4,880	400
In New Mexico, Caballo Reservoir and below	5,560	360		360	4,840
Sub-total	30,500	14,780	5,240	5,240	5,240
ADMINISTRATION					
U.S.G.S. Contract	6,200	1,550	1,550	1,550	1,550
Other expenses	1,092		364	364	364
Sub-total	7,292	1,550	1,914	1,914	1,914
GRAND TOTAL	37,792	16,330	7,154	7,154	7,154
EQUAL SHARES OF STATES			7,154	7,154	7,154
CASH ADJUSTMENT BETWEEN STATES			0	0	0

BUDGET, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1973

Adopted at the Thirty-third Annual Meeting

Item	Total Cost	Borne by United States	Borne by		
			Colorado	New Mexico	Texas
GAGING STATIONS					
In Colorado	10,800	5,400	5,400		
In New Mexico above Caballo Reservoir	15,210	9,740		5,020	450
In New Mexico, Caballo Reservoir and below	5,710	380		380	4,950
Sub-total	31,720	15,520	5,400	5,400	5,400
ADMINISTRATION					
U.S.G.S. Contract	6,800	1,700	1,700	1,700	1,700
Other expenses	1,500		500	500	500
Sub-total	8,300	1,700	2,200	2,200	2,200
GRAND TOTAL	40,020	17,220	7,600	7,600	7,600
EQUAL SHARES OF STATES			7,600	7,600	7,600
CASH ADJUSTMENT BETWEEN STATES			0	0	0

The water-supply data contained in this report have been furnished by various Federal and State Agencies.

The office of the State Engineer of Colorado furnished records of discharge on the following:

- Rio Grande near Del Norte, Colo.
- Conejos River below Platoro Reservoir, Colo.
- Conejos River near Mogote, Colo.
- San Antonio River at Ortiz, Colo.
- Los Pinos River near Ortiz, Colo.
- Conejos River near Lasausas, Colo.
- Rio Grande near Lobatos, Colo.

Records of 6 transmountain diversions and of storage in Squaw and Shaw Lakes, Rito Hondo, Hermit Lakes Reservoir No. 3, Troutvale No. 2, Jumper Creek, Alberta Park, Big Meadows, Mill Creek, Fuchs, and Trujillo Meadows Reservoirs were also furnished by the office of the State Engineer of Colorado.

The U.S. Bureau of Reclamation, Amarillo, Texas furnished records for Platoro Reservoir.

The U.S. Bureau of Reclamation, Albuquerque, N. Mex. furnished the following records:

- Willow Creek above Azotea Creek near Park View, N. Mex.
- Azotea tunnel at outlet, near Chama, N. Mex.
- Willow Creek above Heron Res., near Park View, N. Mex.
- Horse Lake Creek above Heron Res., near Park View, N. Mex.
- Storage in Heron Reservoir near Park View, N. Mex.
- Willow Creek below Heron Dam, N. Mex.
- Storage in El Vado Reservoir near Tierra Amarilla, N. Mex.

The U.S. Geological Survey supplied the record for Rio Grande below Elephant Butte Dam, and in cooperation with the New Mexico Interstate Stream Commission, also furnished the following:

- Rio Chama below El Vado Dam, N. Mex.
- Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.
- Storage in McClure Reservoir near Santa Fe, N. Mex.
- Santa Fe River near Santa Fe, N. Mex.
- Storage in Nichols Reservoir near Santa Fe, N. Mex.

The Corps of Engineers, Albuquerque, N. Mex. furnished the record of storage in Abiquiu Reservoir, Galisteo Reservoir, and Jemez Canyon Reservoir and, in cooperation with the U.S. Geological Survey, also furnished the record for Rio Chama below Abiquiu Dam, Galisteo Creek below Galisteo Dam, and Jemez River below Jemez Canyon Dam, N. Mex.

The United Pueblos Agency, Albuquerque, N. Mex. supplied the records of storage in Acomita Reservoir near San Fidel, N. Mex.

The U.S. Bureau of Reclamation, El Paso, Texas furnished the following records:

- Storage in Elephant Butte Reservoir, N. Mex.
- Storage in Caballo Reservoir, N. Mex.
- Rio Grande below Caballo Dam, N. Mex.
- Bonito ditch below Caballo Dam, N. Mex.

The Rio Grande Compact Commission gratefully acknowledges the cooperation received from these agencies.

ACCURACY OF RECORDS

003657

The Rules and Regulations of the Commission state that the equipment, method, and frequency of measurement at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Within the physical limitations of stream gaging, the agencies obtaining the records at Compact gaging stations have complied with these regulations.

The station description states the degree of accuracy of the records. "Excellent" indicates that, in general, the error in the daily records is believed to be less than 5 percent; "good" less than 10 percent; "fair" less than 15 percent; and "poor" probably more than 15 percent. The records of monthly runoff are, in general, more accurate than the daily records. These standards of accuracy are the same as those followed by the U.S. Geological Survey.

855030

STREAMFLOW

Rio Grande near Del Norte, Colo.

Location.--Water-stage recorder, lat 37°41'22", long 106°27'38", in NW¼ sec. 29, T. 40 N., R. 5 E., on right bank, 20 ft downstream from county highway bridge, 5 miles upstream from Pinos Creek, and 6 miles west of Del Norte. Datum of gage is 7,980.25 ft above mean sea level, datum of 1929. Prior to May 16, 1908, staff gage at site 4 miles downstream. Records are equivalent.

Drainage area.--1,320 sq mi, approximately.

Average discharge.--82 years (1890-1971), 906 cfs (656,400 acre-ft per year).

Extremes.--1889-1971: Maximum discharge, 18,000 cfs Oct. 5, 1911 (gage height, 6.80 ft), from rating curve extended above 6,000 cfs; minimum daily, 69 cfs Aug. 21, 1902.

Remarks.--Records excellent except for some winter months, which are fair. Flow regulated by four reservoirs, total capacity 126,100 acre-ft, and by several smaller ones. Six transmountain diversions import water into basin above station.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	7,180	310	150	232	14,240
February	6,300	280	175	225	12,500
March	10,173	796	180	328	20,180
April	20,699	1,160	449	690	41,060
May	37,922	2,520	494	1,223	75,220
June	79,030	3,080	1,650	2,634	156,800
July	38,265	1,980	641	1,234	75,900
August	12,168	641	286	393	24,140
September	8,234	462	203	274	16,330
October	10,501	813	221	339	20,830
November	7,962	330	198	265	15,790
December	5,935	198	150	191	11,770
Calendar year 1971	244,369	3,080	150	670	484,700

Conejos River below Platoro Reservoir, Colo.

Location.--Water-stage recorder and concrete control, lat 37°21'18", long 106°32'37", in NW¼NW¼ sec. 22, T. 36 N., R. 4 E., on left bank 1,100 ft downstream from valve house for Platoro Reservoir and 0.7 mile northwest of Platoro. Datum of gage is 9,866.60 ft above mean sea level (levels by Bureau of Reclamation).

Drainage area.--40 sq mi, approximately.

Average discharge.--19 years (1953-71), 84.5 cfs (61,220 acre-ft per year).

Extremes.--1952-71: Maximum discharge, 1,160 cfs Nov. 1, 1957; maximum gage height, 4.29 ft June 15, 1958; no flow Oct. 16-20, 1955.

Remarks.--Records good except for those for winter months, which are poor. No diversions above station. Flow completely regulated by Platoro Reservoir (capacity, 60,000 acre-ft).

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	288.3	-	-	9.30	572
February	263.2	-	-	9.40	522
March	294.5	-	-	9.50	584
April	463.5	76	9.5	15.4	919
May	4,074	368	43	131	8,080
June	11,510	546	209	384	22,830
July	5,696	330	24	184	11,300
August	1,198.7	150	6.2	38.7	2,380
September	626.60	52	.60	20.9	1,240
October	1,308	61	27	42.2	2,590
November	264.0	-	-	8.80	524
December	279.0	-	-	9.00	553
Calendar year 1971	26,265.80	546	-	72.0	52,100

RIO GRANDE COMPACT COMMISSION REPORT

Conejos River near Mogote, Colo.

Location.--Water-stage recorder, lat 37°03'14", long 106°11'13", in SE¼SE¼ sec. 34, T. 33 N., R. 7 E., on right bank 25 ft upstream from bridge on State Highway 174, 0.4 mile downstream from Fox Creek, and 5.3 miles west of Mogote. Datum of gage is 8,271.54 ft above mean sea level.

Drainage area.--282 sq mi.

Average discharge.--61 years (1904, 1912-71), 334 cfs (242,000 acre-ft per year).

Extremes.--1903-05, 1911-71: Maximum discharge, 9,000 cfs Oct. 5, 1911 (gage height, 8.50 ft, from rating curve extended above 3,000 cfs; minimum daily determined, 10 cfs July 18, 1904.

Remarks.--Records good except those for winter months, which are fair. Diversions above station for irrigation of about 500 acres. Since 1951 flow partly regulated by Platoro Reservoir.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	1,756	80	33	56.6	3,480
February	1,544	68	47	55.1	3,060
March	4,044	450	50	130	8,020
April	8,878	432	221	296	17,610
May	15,302	1,110	280	494	30,350
June	28,537	1,250	550	951	56,600
July	11,432	655	136	369	22,680
August	3,564	213	67	115	7,070
September	2,431	221	52	81.0	4,820
October	4,504	276	104	145	8,930
November	2,243	113	45	74.8	4,450
December	1,603	70	40	51.7	3,180
Calendar year 1971	85,838	1,250	33	235	170,300

San Antonio River at Ortiz, Colo.

Location.--Water-stage recorder, lat 36°59'35", long 106°02'17", in New Mexico in NE¼SE¼ sec. 24., T. 32 N., R. 8 E., on left bank 800 ft south of New Mexico-Colorado State line, 0.4 mile southeast of Ortiz, and 0.4 mile upstream from Los Pinos River. Altitude of gage is 7,970 ft.

Drainage area.--110 sq mi.

Average discharge.--31 years (1941-71), 25.2 cfs (18,260 acre-ft per year).

Extremes.--1920, 1925-71: Maximum discharge, 1,750 cfs Apr. 15, 1937 (gage height, 5.38 ft), from rating curve extended above 1,000 cfs; no flow at times.

Remarks.--Records good above 10 cfs and fair below. A few small diversions above station for irrigation.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	113.4	6.0	1.3	3.66	225
February	136.5	7.2	2.5	4.88	271
March	1,369.6	186	2.7	44.2	2,720
April	1,718	79	37	57.3	3,410
May	838.4	47	9.3	27.0	1,660
June	93.74	9.3	0	3.12	186
July	57.33	23	0	1.85	114
August	42.13	6.3	0	1.36	84
September	25.04	5.4	0	.83	50
October	153.2	13	2.0	4.94	304
November	93.2	6.3	1.4	3.11	185
December	103.9	5.5	2.3	3.35	206
Calendar year 1971	4,744.44	186	0	13.0	9,410

Los Pinos River near Ortiz, Colo.

Location.--Water-stage recorder, lat 36°58'56", long 106°04'23", in New Mexico on line between secs. 26 and 27, T. 32 N., R. 8 E., on left bank 0.9 mile south of New Mexico-Colorado State line, 2.1 miles southwest of Ortiz, and 2.9 miles upstream from mouth. Altitude of gage is 8,040 ft.

Drainage area.--167 sq mi.

Average discharge.--53 years (1915-20, 1925-71), 122 cfs (88,390 acre-ft per year).

Extremes.--1915-20, 1925-71: Maximum discharge, 3,160 cfs May 12, 1941 (gage height, 5.77 ft, site and datum then in use), from rating curve extended above 1,600 cfs; minimum observed, 4.0 cfs Dec. 17, 1945.

Remarks.--Records good except those for winter months, which are fair. Diversions above station for irrigation.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	592	29	10	19.1	1,170
February	603	27	15	21.5	1,200
March	2,625	326	26	84.7	5,210
April	7,596	371	179	253	15,070
May	7,008	287	185	226	13,900
June	4,259	198	57	142	8,450
July	1,312	76	23	42.3	2,600
August	726	34	18	23.4	1,440
September	537	96	12	17.9	1,070
October	1,075	73	23	34.7	2,130
November	763	41	17	25.4	1,510
December	674	28	17	21.7	1,340
Calendar year 1971	27,770	371	10	76.1	55,080

Conejos River near Lasausas, Colo.

Location.--Water-stage recorders, lat 37°18'01", long 105°44'47", in secs. 2 and 11 (two channels), T. 35 N., R. 11 E., on left bank of main channel 125 ft downstream from bridge on State Highway 158 and on left bank of secondary channel 230 ft upstream from bridge, 1.0 mile upstream from mouth, and 2.1 miles north of Lasausas. Datum of gage on main channel is 7,495.02 ft and on secondary (south) channel is 7,496.89 ft above mean sea level (levels by Bureau of Reclamation).

Drainage area.--887 sq mi.

Average discharge.--50 years (1922-71), 185 cfs (134,000 acre-ft per year).

Extremes.--1921-71: Maximum discharge, 3,890 cfs May 15, 1941; no flow at times in some years.

Remarks.--Records good except those for winter months, which are poor. Diversions for irrigation of about 75,000 acres above station.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	2,731	126	45	88.1	5,420
February	3,127	138	88	112	6,200
March	7,680	886	98	248	15,230
April	3,206.5	432	8.2	107	6,360
May	322.7	24	4.1	10.4	640
June	349.8	27	2.8	11.7	694
July	115.0	17	1.5	3.71	228
August	80.00	10	0	2.58	159
September	247.63	19	.11	8.25	491
October	2,032.1	184	1.3	65.6	4,030
November	2,763	113	19	92.1	5,480
December	2,627	138	58	84.7	5,210
Calendar year 1971	25,281.73	886	0	69.3	50,150

199661
(00300)

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande near Lobatos, Colo.

Location.--Water-stage recorder, lat 37°04'42", long 105°45'22", in sec. 22, T. 33 N., R. 11 E., on right bank just downstream from highway bridge, 6 miles north of Colorado-New Mexico State line, 10 miles east of Lobatos, and 14 miles east of Antonito. Datum of gage is 7,427.63 ft above mean sea level, datum of 1929.

Drainage area.--7,700 sq mi, approximately (includes 2,940 sq mi in closed basin San Luis Valley).

Average discharge.--72 years (1900-71), 598 cfs (433,300 acre-ft per year).

Extremes.--1899-1971: Maximum discharge observed, 13,200 cfs June 8, 1905, (gage height, 9.1 ft), from rating curve extended above 8,000 cfs; no flow at times in 1950-51, 1956.

Remarks.--Records good except those for winter months, which are fair. Natural flow of streams affected by transmountain diversions, storage reservoirs, ground-water withdrawals and diversions for irrigation, and return flow from irrigated areas.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	10,650	460	250	344	21,120
February	13,110	550	380	468	26,000
March	20,370	1,640	350	657	40,400
April	8,469	934	105	282	16,800
May	3,164	160	78	102	6,280
June	4,090	178	98	136	8,110
July	4,461	254	69	144	8,850
August	2,519	174	38	81.3	5,000
September	3,236	151	76	108	6,420
October	11,618	678	164	375	23,040
November	12,646	484	234	422	25,080
December	9,930	410	230	320	19,700
Calendar year 1971	104,263	1,640	38	286	206,800

Willow Creek above Azotea Creek, near Park View, N. Mex.

Location.--Water-stage recorder, lat 36°48'15", long 106°39'30", in Tierra Amarilla Grant, on right bank 200 ft upstream from Azotea Creek, 7.1 miles northwest of Park View, and 8.3 miles southwest of Chama. Datum of gage is 7,404.00 ft above mean sea level.

Drainage area.--42 sq mi.

Extremes.--April 1971 to December 1971: Maximum daily discharge, 15 cfs Aug. 8, 1971; no flow Sept. 2-7, Oct. 14-17, 1971.

Remarks.--Nonrecording gage prior to Nov. 18, 1971. Six-inch Parshall flume Apr. 21 to Nov. 18.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	-	-	-	-	-
February	-	-	-	-	-
March	-	-	-	-	-
April	49.79	7.1	0.35	1.66	99
May	35.96	4.5	.01	1.16	71
June	88.30	6.2	1.1	2.94	175
July	68.74	9.6	.43	2.21	136
August	88.45	15	.03	2.85	175
September	27.66	12	0	.92	55
October	73.56	14	0	2.37	146
November	4.47	.85	.02	.15	8.9
December	9.73	1.1	.10	.31	19
Calendar year 1971	-	-	-	-	-

003662

STREAMFLOW

Willow Creek above Heron Reservoir, near Park View, N. Mex.

Location.--Water-stage recorder, lat 36°44'33", long 106°37'34", in Tierra Amarilla Grant, on right bank 200 ft downstream from bridge, 0.2 mile downstream from Iron Spring Creek, 3.3 miles west of Park View, and at mile 9.7. Datum of gage is 7,196.29 ft above mean sea level. Prior to Apr. 1, 1971 at site 900 ft downstream.

Drainage area.--112 sq mi.

Average discharge.--7 years (1963-69) 11.5 cfs (8,330 acre-ft per year) prior to completion of Azotea tunnel.

Extremes.--1962-71: Maximum discharge, 1,600 cfs Aug. 11, 1967 (gage height, 3.88 ft); no flow at times most years.

Remarks.--Records good except those for winter months, which are fair. Subsequent to Nov. 16, 1970, flow affected by transmountain diversions through Azotea tunnel. Flow in Rutherford Drain included prior to Apr. 1, 1971.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet Creek	*Drain
January	9.95	1.4	0.10	0.32	20	-
February	136.35	23	1.6	4.87	270	-
March	757.75	112	.50	24.4	1,500	-
April	5,361	291	54	179	10,630	6.6
May	6,552	427	118	211	13,000	19
June	10,397	509	146	347	20,620	24
July	2,320	172	23	75	4,600	5.0
August	2,022.7	189	8.1	65	4,010	0
September	706.03	251	.67	24	1,400	.3
October	1,532	164	10	49	3,040	.6
November	1,356.4	80	8.4	45	2,690	0
December	376.7	22	1.7	12	747	0
Calendar year 1971	31,527.88	509	.10	86.4	62,540	55.5

*Rutherford Drain

Horse Lake Creek above Heron Reservoir, near Park View, N. Mex.

Location.--Water-stage recorder, lat 36°42'24", long 106°44'42", in Tierra Amarilla Grant, on right bank 3.7 miles northwest of Heron Dam, 7.8 miles downstream from Horse Lake, and 9.9 miles west of Park View. Datum of gage is 7,188.85 ft above mean sea level. Prior to July 1, 1971 at site 1,100 ft upstream.

Drainage area.--45 sq mi, approximately.

Average discharge.--9 years (1963-71) 0.99 cfs (717 acre-ft per year).

Extremes.--1963-71: Maximum discharge, 3,960 cfs July 30, 1968 (gage height, 4.9 ft); no flow most of time.

Remarks.--Records good. Diversions above station for irrigation of meadows and for off-channel stock tanks.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	0	0	0	0	0
February	6.49	1.7	0	.23	13
March	3.02	.78	0	.097	6.0
April	.39	.12	0	.013	.8
May	0	0	0	0	0
June	0	0	0	0	0
July	0	0	0	0	0
August	6.00	1.7	0	.19	12
September	8.26	6.0	0	.28	16
October	8.15	3.3	0	.26	16
November	0	0	0	0	0
December	1.71	.77	0	.055	3.4
Calendar year 1971	34.02	6.0	0	.093	67.0

003663

RIO GRANDE COMPACT COMMISSION REPORT

Willow Creek below Heron Dam, N. Mex.

Location.--Totalizing flowmeters, lat 36°39'56", long 106°42'12", in Tierra Amarilla Grant, in outlet conduits at Heron Dam, 0.2 mile upstream from Rio Chama, 5.1 miles northeast of El Vado Dam, and 8.7 miles southwest of Park View. Prior to Nov. 9, 1965 water-stage recorder at site 0.2 mile upstream. Nov. 9, 1965 to Oct. 21, 1970, water-stage recorders, 0.7 mile upstream on Horse Lake Creek and 3 miles upstream on Willow Creek.

Drainage area.--193 sq mi.

Average discharge.--32 years (1937-69) 21.2 cfs (15,360 acre-feet per year) prior to completion of Azotea tunnel and Heron Dam.

Extremes.--1937-71: Maximum discharge, 4,500 cfs Apr. 23, 1942 (gage height, 10.45 ft); no flow at times.

Remarks.--Records good. Subsequent to Oct. 21, 1970 flow has been completely regulated by Heron Dam. Releases of transmountain water amounted to 6,100 acre-ft in June; 5,460 acre-ft in July; and 3,820 acre-ft in September.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	0	0	0	0	0
February	0	0	0	0	0
March	0	0	0	0	0
April	903.5	257	0	30.1	1,790
May	115.8	6.2	1.9	3.74	230
June	3,303.3	514	3.3	110	6,550
July	2,925.9	256	2.5	94.4	5,800
August	209.7	27	0	6.76	416
September	2,028.6	257	1.5	67.6	4,020
October	411.2	101	0	13.3	816
November	62.6	6.6	0	2.09	124
December	63.0	6.0	0	2.03	125
Calendar year 1971	10,023.6	514	0	2.75	19,880

Rio Chama below El Vado Dam, N. Mex.

Location.--Water-stage recorder, lat 36°34'48", long 106°43'24", in Tierra Amarilla Grant, 1.5 miles downstream from El Vado Dam, 2.8 miles upstream from Rio Nutrias, and 13 miles southwest of Tierra Amarilla, Rio Arriba County. Datum of gage is 6,696.12 ft above mean sea level, datum of 1929. Prior to October 1935, at site 1.5 miles upstream and October 1935 to September 1938, at site 1.1 miles upstream at different datum.

Drainage area.--877 sq mi.

Average discharge.--4 years (1914, 1921-23), 444 cfs prior to completion of El Vado Dam; 35 years (1936-70), 372 cfs (269,500 acre-feet per year) subsequent to completion of El Vado Dam but prior to completion of Heron Dam and Azotea tunnel.

Extremes.--1914-16, 1920-24, 1936-71: Maximum discharge observed, 9,000 cfs May 22, 1920 (gage height, 12 ft); no flow Mar. 25, 26, 31, 1955.

Remarks.--Records good except those for some winter months, which are poor. Diversions above station for irrigation of about 8,000 acres. Since 1935 flow regulated by El Vado Reservoir and since October 1970 flow partly regulated by Heron Reservoir. Flow in June, July, and September affected by releases of San Juan water released from Heron Reservoir.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	1,903	78	50	61.4	3,770
February	2,061	103	57	73.6	4,090
March	6,251	882	57	202	12,400
April	14,563	868	205	485	28,890
May	19,252	920	395	621	38,190
June	10,078	690	93	336	19,990
July	5,622	627	20	181	11,150
August	1,686	156	19	54.4	3,340
September	3,078	277	21	103	6,110
October	3,534	490	47	114	7,010

Rio Chama below Abiquiu Dam, N. Mex.

Location.--Water-stage recorder, lat 36°14'12", long 106°24'59", in SE¼SE¼ sec. 8, T. 23 N., R. 5 E., on right bank 0.8 mile downstream from Abiquiu Dam and 5.9 miles northwest of Abiquiu. Altitude of gage is 6,040 ft (from river-profile map and topographic map).

Drainage area.--2,147 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.--10 years (1926-71), 363 cfs (263,000 acre-feet per year).

Extremes.--1961-71: Maximum discharge, 2,990 cfs July 1, 1965 (gage height, 6.69 ft); minimum about 0.5 cfs Mar. 17, 1966.

Remarks.--Records good except those for winter months, which are fair. Flow regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 17,000 acres. Subsequent to May 1971 flow affected by the release of transmountain water.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	2,497	99	43	80.5	4,950
February	2,635	148	63	94.1	5,230
March	6,465	824	21	209	12,820
April	16,046	918	219	535	31,830
May	19,510	957	383	629	38,700
June	9,588	692	93	320	19,020
July	6,695	657	26	216	13,280
August	3,584	410	26	116	7,110
September	3,300	584	19	110	6,550
October	5,918	1,350	51	191	11,740
November	11,956	970	74	399	23,710
December	2,728	192	48	88.0	5,410
Calendar year 1971	90,922	1,350	19	249	180,300

Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.

Location.--Water-stage recorder, lat 35°52'29", long 106°08'30", in San Ildefonso Pueblo Grant, 400 ft downstream from bridge on State Highway 4, 1.8 miles southwest of San Ildefonso Pueblo, 2.5 miles downstream from Pojoaque River, and 6.8 miles west of Pojoaque. Datum of gage is 5,488.48 ft above mean sea level, datum of 1929. Prior to May 19, 1904, and July 25 to Oct. 1, 1904, staff gage at site 180 ft upstream at datum 2.02 ft lower.

Drainage area.--14,300 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.)

Average discharge.--72 years (1896-1905, 1910-71) 1,519 cfs (1,105,000 acre-ft per year).

Extremes.--1895-1905, 1910-71: Maximum discharge, 24,400 cfs May 23, 1920 (gage height, 14.1 ft); minimum daily, 60 cfs July 4, 5, 1902.

Remarks.--Records good. Flow partly regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 600,000 acres in Colorado and 75,000 acres in New Mexico. Subsequent to May 1971 flow affected by releases of transmountain water from Heron Reservoir.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	22,351	852	520	721	44,330
February	24,562	1,060	682	877	48,720
March	35,357	2,860	643	1,141	70,130
April	36,437	2,700	716	1,215	72,270
May	27,828	1,220	575	898	55,200
June	15,854	858	279	528	31,450
July	17,620	1,260	210	568	34,950
August	14,356	1,120	281	463	28,480
September	11,890	1,430	218	396	23,580
October	28,207	2,000	604	910	55,950
November	34,544	1,800	648	1,151	68,520
December	22,793	1,040	591	735	45,210
Calendar year 1971	291,799	2,860	210	799	578,800

003665

RIO GRANDE COMPACT COMMISSION REPORT

Santa Fe River near Santa Fe, N. Mex.

Location.---Water-stage recorder and concrete control, lat 35°41'12", long 105°50'35", in NE¼SE¼ sec. 23, T. 17 N., R. 10 E., 0.4 mile downstream from McClure Dam, and 5.3 miles east of Santa Fe. Datum of gage is 7,718 ft above mean sea level, datum of 1929. Prior to Nov. 4, 1930, at site 1.5 mile downstream and April 11, 1931, to September 1947 at site 0.3 mile upstream.

Drainage area.---18.2 sq mi.

Average discharge.---59 years (1913-71), 8.01 cfs (5,800 acre-ft per year).

Extremes.---1813-71: Maximum discharge, 1,500 cfs Aug. 14, 1921; minimum daily, 0.1 cfs Feb. 7-10, 20, 21, 1927, Aug. 1-4, 1951.

Remarks.---Records good. Flow regulated by McClure Reservoir, completed in 1926, raised in 1935 and again in 1947.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	37.0	1.3	1.1	1.19	73
February	36.1	1.3	1.1	1.29	72
March	37.2	1.8	1.1	1.20	74
April	225.2	15	1.8	7.51	447
May	100.1	9.8	1.8	3.23	199
June	247.7	9.4	6.4	8.26	491
July	158.9	6.7	4.3	5.13	315
August	186.4	7.3	4.5	6.01	370
September	170.0	7.3	4.1	5.67	337
October	85.29	4.3	.13	2.75	169
November	7.71	.38	.17	.26	15
December	13.20	1.3	.34	.43	26
Calendar year 1971	1,304.80	15	.13	3.57	2,590

Galisteo Creek below Galisteo Dam, N. Mex.

Location.---Water-stage recorder, lat 35°27'56", long 106°12'57", in SE¼SE¼ sec. 5, T. 14 N., R. 7 E., on right bank, 0.6 mile downstream from Galisteo Dam, and 5.5 miles northwest of Cerrillos. Altitude of gage is 5,450 feet.

Drainage area.---597 sq mi.

Extremes.---1970-71: Maximum discharge, 2,000 cfs July 27 (gage height, 7.00 ft); maximum gage-height, 7.33 ft July 20, 1971; no flow many days.

Remarks.---Records fair. Flow partly regulated by uncontrolled outlet in Galisteo Dam. Capacity of outlet, 5,000 cfs when reservoir is full. Diversions for irrigation of about 50 acres above reservoir.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	37.50	1.6	0.10	1.21	74
February	10.52	1.0	.09	.38	21
March	4.44	.86	0	.14	8.8
April	1.69	.52	0	.056	3.4
May	0	0	0	0	0
June	0	0	0	0	0
July	3,408.02	1,170	0	110	6,760
August	483.46	76	.80	15.6	959
September	136.77	101	.25	4.56	271
October	327.94	128	.92	10.6	650
November	88.93	6.8	.50	2.96	176
December	91.2	14	1.6	2.94	181
Calendar year 1971	4,590.47	1,170	0	12.6	9,110

003666

STREAMFLOW

Jemez River below Jemez Canyon Dam, N. Mex.

Location.--Water-stage recorder, lat 35°23'24", long 106°32'03", in NE¼ sec. 5, T. 13 N., R. 4 E., on right bank 0.8 mile downstream from Jemez Canyon Dam, 1.5 miles upstream from mouth, and 6 miles north of Bernalillo. Datum of gage is 5,095.60 ft above mean sea level, datum of 1929. Prior to April 24, 1951, at site three-quarters of a mile upstream at datum 24.51 ft higher. April 24, 1951 to June 25, 1958, at site 37 ft upstream at datum 4.40 ft higher.

Drainage area.--1,038 sq mi.

Average discharge.--29 years (1937, 1944-71), 51.3 cfs (37,170 acre-ft per year).

Extremes.--1937, 1944-71: Maximum discharge, 16,300 cfs Aug. 29, 1943 (gage height, 5.62 ft) no flow at times.

Remarks.--Records poor. Flow regulated by Jemez Canyon Dam since October 1953. Diversions for irrigation of about 3,000 acres above station.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	276.0	26	0	8.90	547
February	395.5	27	5.0	14.1	784
March	780.5	67	6.5	25.2	1,550
April	1,426	87	12	47.5	2,830
May	541.9	60	0	17.5	1,070
June	0	0	0	0	0
July	131.3	44	0	4.24	260
August	1,813.1	260	3.9	58.5	3,600
September	232.0	227	0	7.73	460
October	2,659	569	12	85.8	5,270
November	1,047	93	18	34.9	2,080
December	541.5	79	2.5	17.5	1,070
Calendar year 1971	9,843.8	569	0	27.0	19,530

Rio Grande below Elephant Butte Dam, N. Mex.

Location.--Water-stage recorder, lat 33°08'54", long 107°12'22", in SW¼ sec. 25, T. 13 S., R. 4 W., (projected) in Pedro Armendariz Grant, on left bank 1.0 mile downstream from dam and 1.5 miles upstream from Cuchillo Negro River. Datum of gage is 4,242.09 ft above mean sea level, datum of 1929. Prior to April 23, 1942 at several different sites and datums.

Drainage area.--29,450 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--57 years (1915-71), 1,009 cfs (731,000 acre-ft per year).

Extremes.--1915-71: Maximum daily discharge, 8,200 cfs May 22, 1942; no flow at times prior to 1929.

Remarks.--Records good. Flow regulated by Elephant Butte Reservoir. Diversions for irrigation of about 800,000 acres above station.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	514.5	22	8.5	16.6	1,020
February	28,789	1,380	11	1,028	57,100
March	42,910	1,440	1,350	1,384	85,110
April	39,369	1,490	506	1,312	78,090
May	42,430	1,490	1,300	1,369	84,160
June	34,504	1,390	836	1,150	68,440
July	28,138	1,910	44	908	55,810
August	34,417	1,980	554	1,110	68,270
September	8,334.9	1,570	2.9	278	16,530
October	211.2	44	1.1	6.81	419
November	37.4	1.8	1.1	1.25	74
December	139.1	15	1.5	4.49	276
Calendar year 1971	259,794.1	1,980	1.1	712	515,300

693667

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande below Caballo Dam, N. Mex.

Location.--Water-stage recorder, lat 32°53'05", long 107°17'31", in NE¼SW¼ sec. 30, T. 16 S., R. 4 W., 2,000 ft upstream from Interstate Highway 25, 4,200 ft downstream from Caballo Dam, 1.3 miles upstream from Percha diversion dam, and 3 miles northeast of Arrey. Datum of gage is 4,140.9 ft above mean sea level, datum of 1929. October 13, 1938 to December 31, 1945 at datum 5.0 ft higher.

Drainage area.--30,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--34 years (1938-71) 883 cfs (639,700 acre-ft per year).

Extremes.--1938-71: Maximum daily discharge, 7,650 cfs May 20, 1942; minimum daily, 0.1 cfs Oct. 31 to Nov. 14, 1954, Nov. 7 to Dec. 31, 1955.

Remarks.--Records good. Considerable diversion above station for irrigation. Flow regulated by Caballo and Elephant Butte Reservoirs.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	31.7	1.1	1.0	1.02	63
February	2,400	1,040	1.0	86	4,760
March	53,840	2,210	990	1,737	106,800
April	26,740	1,570	696	891	53,040
May	30,272	1,220	721	977	60,040
June	41,250	1,960	1,010	1,375	81,820
July	46,930	2,020	1,060	1,514	93,090
August	39,670	1,640	1,020	1,280	78,690
September	10,061.9	1,520	1.8	335	19,960
October	46.1	1.9	1.1	1.49	91
November	30.2	1.1	1.0	1.01	60
December	31.0	1.0	1.0	1.00	61
Calendar year 1971	251,302.9	2,210	1.0	689	498,500

Bonito ditch below Caballo Dam, N. Mex.

Records available.--January 1938 to December 1971. Published as supplementary data with Rio Grande below Caballo Dam in U.S.G.S. Water-Supply Papers beginning with October 1947.

Remarks.--Ditch diverts directly from Caballo Reservoir for irrigation of lands on right bank of river. The total release from Project Storage, as used in computations of Compact Commission, is the combined flow of this ditch and Rio Grande below Caballo Dam.

Monthly and yearly discharge, in cubic feet per second

Month	Second-foot-days	Maximum daily	Minimum daily	Mean	Runoff in Acre-feet
January	0	0	0	0	0
February	0	0	0	0	0
March	90.7	10	0	2.93	180
April	25.5	6.7	0	.85	51
May	28.2	12	0	.91	56
June	53.9	8.0	0	1.80	107
July	36.6	8.0	0	1.18	73
August	64.8	8.0	0	2.09	129
September	36.1	6.0	0	1.20	72
October	0	0	0	0	0
November	0	0	0	0	0
December	0	0	0	0	0
Calendar year 1971	335.8	12	0	.92	666

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in Colorado or New Mexico
(Constructed or enlarged since 1937)

Fuchs Reservoir.--Staff gage in sec. 2, T. 37 N., R. 4 E., on East Pinos Creek. Completed in 1939; capacity, 237 acre-feet with 2 feet of flash boards in spillway. Pinos Creek enters Rio Grande below station near Del Norte.

Month-end gage height, in feet, and contents, in acre-feet													
Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	6.1	6.1	9.1	13.7	15.2	15.2	15.2	15.2	15.2	15.2	15.2	15.2	-
Contents	40	40	80	161	192	192	192	192	192	192	192	192	-
Change	+40	0	+40	+81	+31	0	0	0	0	0	0	0	+192

Platoro Reservoir.--Water-stage recorder in NW $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 22, T. 36 N., R. 4 E., on Conejos River. Completed in 1951; capacity, 60,000 acre-feet at crest of spillway. Reservoir is used for irrigation and flood control. Storage affects Conejos Index Supply.

Month-end elevation, in feet, and contents, in acre-feet			
Date	Elevation	Contents	Change in Contents
December 31, 1970	-	a 2,900	-
January 31, 1971	-	a 2,900	0
February 28	-	a 2,900	0
March 31	-	a 3,000	+100
April 30	9,958.5	8,300	+5,300
May 31	9,958.5	8,300	0
June 30	9,958.4	8,300	0
July 31	9,942.0	2,900	-5,400
August 31	9,942.0	2,900	0
September 30	9,942.0	2,900	0
October 31	9,942.0	2,900	0
November 30	-	a 2,900	0
December 31	-	a 2,900	0
Calendar year 1971	-	-	0

a - Estimated

Trujillo Meadows Reservoir.--In sec. 5, T. 32 N., R. 5 E., on Los Pinos River. Completed in 1957; capacity, 913 acre-feet. Water is used for fish culture. Storage affects Conejos Index Supply. Storage removed from debit status by exchange of transmountain water. (See minutes of meeting on Feb. 19, 1960.)

Month-end gage height, in feet, and contents, in acre-feet													
Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	-
Contents	913	913	913	913	913	913	913	913	913	913	913	913	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

Heron Reservoir.--Lat 36°39'56", long 106°42'12", at dam on Willow Creek. Storage began in October 1970. Capacity, 400,070 acre-feet at elevation 7,186.1 (low point on crest of spillway); dead storage, 1,470 acre-feet at elevation 7,003.0 ft. As of December 31, 1971 storage included 570 acre-feet of Rio Grande water. Used for storage of transmountain water.

Month-end elevation, in feet, and contents, in acre-feet			
Date	Elevation	Contents	Change in Contents
December 31, 1970	6,991.8	540	-
January 31, 1971	6,992.5	570	+30
February 28	6,997.5	860	+290
March 31	7,009.6	2,190	+1,330
April 30	7,039.0	11,180	+8,990
May 31	7,059.1	23,650	+12,470
June 30	7,074.5	37,410	+13,760
July 31	7,073.4	36,270	-1,140
August 31	7,077.1	40,180	+3,910
September 30	7,074.7	37,620	-2,560
October 31	7,076.6	39,640	+2,020
November 30	7,078.7	41,950	+2,310
December 31	7,079.3	42,630	+680
Calendar year 1971	-	-	+42,090

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in New Mexico
(Constructed or enlarged since 1929)

El Vado Reservoir.--Water-stage recorder and surface follower, lat 36°35'39", long 106°44'00", on Rio Chama. Storage began in January 1935. Capacity, 196,500 acre-feet at gage height 6,902.0 feet (crest of spillway), as determined by survey in 1966. Datum of gage is 8.21 ft above mean sea level, datum of 1929.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1970	6,775.3	1,110	-
January 31, 1971	6,775.2	1,100	-10
February 28	6,775.3	1,110	+10
March 31	6,781.9	2,840	+1,730
April 30	6,814.2	23,430	+20,590
May 31	6,814.3	23,530	+100
June 30	6,813.0	22,340	-1,190
July 31	6,809.5	19,310	-3,030
August 31	6,809.5	19,310	0
September 30	6,809.6	19,390	+80
October 31	6,809.5	19,310	-80
November 30	6,775.8	1,190	-18,120
December 31	6,775.4	1,130	-60
Calendar year 1971	-	-	+20

Abiquiu Reservoir.--Water-stage recorder in SW $\frac{1}{4}$ sec. 8, T. 23 N., R. 5 E., on Rio Chama. Completed in February 1963; capacity, 1,216,000 acre-feet at elevation of 6,350 ft (crest of spillway). Reservoir is operated by Corps of Engineers for flood control and sediment storage.

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation	Contents	Change in contents
December 31, 1970	6,105.52	1,470	-
January 31, 1971	6,106.52	1,610	+140
February 28	6,108.62	1,940	+330
March 31	6,110.18	2,240	+300
April 30	6,108.77	1,970	-270
May 31	6,109.20	2,040	+70
June 30	6,108.90	1,990	-50
July 31	6,109.12	2,030	+40
August 31	6,110.17	2,240	+210
September 30	6,115.28	3,660	+1,420
October 31	6,109.39	2,080	-1,580
November 30	6,108.81	1,970	-110
December 31	6,109.15	2,040	+70
Calendar year 1971	-	-	+570

McClure (Granite Point) Reservoir.--Water-stage recorder in NE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 24, T. 17 N., R. 10 E., on Santa Fe River. Original reservoir, capacity, 561 acre-ft, completed in 1926 and not subject to terms of Rio Grande Compact; in 1935, permanent flash boards were installed in spillway increasing capacity to 650 acre-ft; in 1947 both dam and spillway were raised increasing capacity to 3,060 acre-ft (gage height, 102.6 ft). Maximum water surface elevation on permit to store. Spillway equipped with radial gates that open automatically.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1970	69.1	1,010	-
January 31, 1971	69.0	1,010	0
February 28	69.0	1,010	0
March 31	69.0	1,010	0
April 30	61.5	718	-292
May 31	62.4	749	+31
June 30	49.0	371	-378
July 31	43.9	267	-104
August 31	50.8	412	+145
September 30	43.3	256	-156
October 31	48.9	369	+113
November 30	58.7	627	+258
December 31	65.0	846	+219
Calendar year 1971	-	-	-164

003672

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico

Nichols Reservoir.--Water-stage recorder in E $\frac{1}{2}$ NE $\frac{1}{4}$ sec. 21, T. 17 N., R. 10 $\frac{1}{2}$ E. on Santa Fe River. Completed in 1942; capacity, 685 acre-feet. Water is for municipal use in Santa Fe.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	155.0	155.7	155.3	158.9	148.9	150.5	152.6	159.5	162.6	165.3	163.5	162.5	-
Contents	375	391	382	465	262	288	329	479	561	634	585	558	-
Change	+25	+16	-9	+83	-203	+26	+41	+150	+82	+73	-49	-27	+208

Galisteo Reservoir.--Water-stage recorder and manometer in NW $\frac{1}{4}$ sec. 9, T. 14 N., R. 7 E., at dam on Galisteo Creek. Storage records begin in October 1970. Capacity 89,800 acre-feet at elevation 5,608.0 feet (crest of spillway). Reservoir is operated by Corps of Engineers for flood control and sediment storage.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	-	-	-	-	-	-	-	-	-	-	-	-	-
Contents	0	0	0	0	0	0	0	0	0	0	0	0	0
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

San Gregorio Reservoir.--Staff gage in SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 20, T. 21 N., R. 1 E. (projected), on Clear Creek tributary to Rio Las Vacas and Jemez River. Completed in October 1958; capacity, 254 acre-feet at elevation 9,408.0 ft (crest of spillway).

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	-	-	-	-	-	15.5	-	-	-	-	-	-	-
Contents	230	240	250	290	280	180	170	160	170	180	190	200	-
Change	0	+10	+10	+40	-10	-100	-10	-10	+10	+10	+10	+10	-30

Jemez Canyon Reservoir.--Water-stage recorder in SW $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 32, T. 14 N., R. 4 E., on Jemez River 2.3 miles above mouth. Completed in 1953; capacity, 181,800 acre-feet at elevation of 5,252.3 ft. Capacity at elevation 5,232.0 ft (crest of spillway), 112,600 acre-feet by 1969 survey. Reservoir is operated by Corps of Engineers for flood control and sediment storage.

Month-end elevation, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Elevation	-	-	-	-	-	-	-	-	^a 178	-	-	-	-
Contents	0	0	0	0	0	0	0	0	178	0	0	0	0
Change	0	0	0	0	0	0	0	0	+178	-178	0	0	0

a 5,147.80 ft.

Acomita Reservoir.--Staff gage in SE $\frac{1}{4}$ sec. 29, T. 10 N., R. 7 W., on San Fidel Arroyo; water for reservoir is diverted from Rio San Jose. Completed in 1938; original capacity, 850 acre-feet; present capacity 650 acre-feet on basis of 1956 sediment survey. Water is used for irrigation on Acoma and Laguna Indian Reservations.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	Jun	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Contents	550	500	450	405	400	380	405	405	380	365	150	50	-
Change	-30	-50	-50	-45	-5	-20	+25	0	-25	-15	-215	-100	-530

003679

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in New Mexico

Elephant Butte Reservoir.--Water-stage recorder in NW $\frac{1}{4}$ sec. 30, T. 13 S., R. 3 W., at dam on Rio Grande. Storage began Jan. 6, 1915; capacity, 2,137,200 acre-feet at gage height 4,407.0 ft (crest of spillway), by survey of 1969. Datum of gage is 43.3 ft above mean sea level, datum of 1929. Water is used for power development and irrigation in New Mexico and Texas. Records furnished by Bureau of Reclamation.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1970	4,321.29	324,500	-
January 31, 1971	4,325.33	367,800	+43,300
February 28	4,324.73	361,100	-6,700
March 31	4,320.51	316,500	-44,600
April 30	4,317.72	289,000	-27,500
May 31	4,310.13	221,200	-67,800
June 30	4,301.01	154,000	-67,200
July 31	4,291.17	98,400	-55,600
August 31	4,277.67	47,300	-51,100
September 30	4,273.19	35,400	-11,900
October 31	4,283.13	64,500	+29,100
November 30	4,296.75	128,000	+63,500
December 31	4,304.39	177,000	+49,000
Calendar year 1971	-	-	-147,500

Caballo Reservoir.--Water-stage recorder in SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 19, T. 16 S., R. 4 W., at dam on Rio Grande. Storage began Feb. 8, 1938; capacity, 344,000 acre-feet (by 1958 survey), at gage height 4,182.0 ft (above which spillway gates open automatically). Datum of gage is 43.3 ft above mean sea level, datum of 1929. 100,000 acre-feet of storage reserved for flood control. Records furnished by Bureau of Reclamation.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1970	4,135.70	27,830	-
January 31, 1971	4,136.57	30,160	+2,330
February 28	4,148.70	74,540	+44,380
March 31	4,141.31	44,660	-29,880
April 30	4,144.95	58,170	+13,510
May 31	4,148.36	72,960	+14,790
June 30	4,144.18	55,130	-17,830
July 31	4,131.23	17,220	-37,910
August 31	4,125.46	7,280	-9,940
September 30	4,124.54	6,120	-1,160
October 31	4,127.99	11,040	+4,920
November 30	4,129.03	12,860	+1,820
December 31	4,130.20	15,100	+2,240
Calendar year 1971	-	-	-12,730

Project Storage.--This is the combined storage in Elephant Butte and Caballo Reservoirs. Total Project Storage capacity is 2,381,200 acre-feet which excludes the 100,000 acre-ft reserved for flood control in Caballo Reservoir.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1970	-	352,300	-
January 31, 1971	-	398,000	+45,700
February 28	-	435,600	+37,600
March 31	-	361,200	-74,400
April 30	-	347,200	-14,000
May 31	-	294,200	-53,000
June 30	-	209,100	-85,100
July 31	-	115,600	-93,500
August 31	-	54,580	-61,020
September 30	-	41,520	-13,060
October 31	-	75,540	+34,020
November 30	-	140,900	+65,360
December 31	-	192,100	+51,200
Calendar year 1971	-	-	-160,200

03674

TRANSMOUNTAIN DIVERSIONS

Fuchs ditch.--Water-stage recorder and 3-ft Parshall flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from North Fork Los Pinos River in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.

Raber-Lohr ditch.--Water-stage recorder and 4-ft rectangular flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from Rincon la Vaca Creek in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.

Squaw Pass ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 21, T. 39 N., R. 3 W., at Squaw Pass in Colorado. Diversion is from Williams Creek in San Juan River Basin into Squaw Creek in Rio Grande Basin. Constructed in 1938. Diversion for irrigation is from Rio Grande below Del Norte gaging station.

Taber ditch.--Water-stage recorder and 3-ft Parshall flume in sec. 35, T. 43 N., R. 3 W., at Spring Creek Pass in Colorado. Diversion is from Cebolla Creek in Gunnison River Basin into tributary of Clear Creek in Rio Grande Basin. Completed in 1910 or 1911. Diversion for irrigation is from Rio Grande below Del Norte gaging station.

Piedra Pass ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 4, T. 38 N., R. 1 W., at Piedra Pass in Colorado. Diversion is from tributaries of Piedra River in San Juan River Basin to South River in Rio Grande Basin. Original ditch completed in 1938, first enlargement completed in 1940. Water is imported by Colorado Game and Fish Department, beginning in 1959, to offset losses from fish culture reservoirs.

Treasure Pass ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 31, T. 38 N., R. 2 E., at Wolf Creek Pass in Colorado. Diversion is from Wolf Creek in San Juan River Basin to a tributary of South Fork Rio Grande. Completed in 1923 or 1924. Water is diverted for irrigation from Rio Grande above the Del Norte gaging station, beginning in 1959. Prior to 1959 it was diverted below gaging station.

Azotea tunnel.--Water-stage recorder and 10-ft Parshall flume, lat 36°51'12", long 106°40'18", at south portal of Azotea tunnel, San Juan-Chama Project. Diversion is from Rio Blanco, Little Navajo River, and Navajo River in Colorado and discharge is into Azotea Creek in New Mexico. Construction completed in 1970.

Imported quantities, in acre-feet, 1971

Month	Fuchs ditch	Raber-Lohr ditch	Squaw Pass ditch	Taber ditch	Piedra Pass ditch	Treasure Pass ditch	Azotea tunnel
January	0	0	0	0	0	0	0
February	0	0	0	0	0	0	0
March	0	0	0	0	0	0	520
April	0	0	0	0	0	0	10,490
May	0	79	0	70	0	29	12,650
June	110	956	108	271	0	250	20,160
July	155	380	72	88	0	24	4,510
August	24	31	0	2	0	0	3,900
September	0	0	0	0	0	0	1,460
October	0	0	0	0	0	0	2,360
November	0	0	0	0	0	0	2,510
December	0	0	0	0	0	0	740
Calendar year	289	1,446	180	431	0	303	59,300

003675

EVAPORATION AND PRECIPITATION

The last paragraph of Article VI of the Compact states, in part, --- "such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bear to the total amount of water in such reservoirs during the year."

To provide the data needed for the computation of such evaporation losses, the Commission has encouraged the establishment and operation of evaporation stations near each major reservoir in the basin and at other selected locations.

Evaporation and other climatological data collected at the several stations in Colorado and New Mexico are tabulated on the next page. At some of the stations, it was not possible to obtain evaporation records throughout the winter period.

The measurements of evaporation were made in accordance with standard practice for the type of pan in use. Measurements of precipitation were made in standard 8-inch rain gages, which were supplemented at some of the stations by recording rain gages.

Records for the evaporation stations at the State University, Elephant Butte Dam, and El Vado Dam antedated the creation of the Commission; the station at Bosque del Apache was established for the U.S. Fish and Wildlife Service; the stations at Abiquiu Dam, Cochiti Dam, and Jemez Canyon Dam were established by the Corps of Engineers. All others were established at the request of the Commission.

The Rio Grande Compact Commission gratefully acknowledges the cooperation of the U. S. Environmental Science Services Administration, U. S. Corps of Engineers, and U. S. Bureau of Reclamation for furnishing the climatological records contained in this report.

Wagon Wheel Gap.--Lat 37°46', long 106°49', in Mineral County near Creede, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 8,500 ft.

Alamosa.--Lat 37°27', long 105°52', in Alamosa County at airport near Alamosa, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 7,536 ft.

Platoro Dam.--Lat 37°21', long 106°30', in Conejos County near Platoro, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, fan type psychrometer, standard 8-inch and recording rain gages at elevation 9,826 ft. Records furnished by Bureau of Reclamation.

El Vado Dam.--Lat 36°36', long 106°44', in Rio Arriba County at El Vado Dam near Tierra Amarilla, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,750 ft.

Abiquiu Dam.--Lat 36°14', long 106°26', in Rio Arriba County at Abiquiu Dam near Abiquiu, N. Mex. Standard class A pan, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,380 ft.

Santa Fe.--Lat 35°39', long 105°56', in Santa Fe, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 7,045 ft.

Cochiti Dam.--Lat 35°38', long 106°19', in Sandoval County at operations building, at Cochiti Damsite, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,560 ft.

Jemez Dam.--Lat 35°23', long 106°32', in Sandoval County at Jemez Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,388 ft.

Bosque del Apache.--Lat 33°46', long 106°54', in Socorro County, 7 miles south of San Antonio, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 4,520 ft.

Elephant Butte Dam.--Lat 33°09', long 107°11', in Sierra County at Elephant Butte Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, and standard 8-inch rain gage at elevation 4,576 ft.

Caballo Dam.--Lat 32°54', long 107°18', in Sierra County at Caballo Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 4,190 ft.

New Mexico State University.--Lat 32°17', long 106°45', in Dona Ana County at University Park, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 3,909 ft.

92676

EVAPORATION AND PRECIPITATION

Evaporation and precipitation, in inches

Station		Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Annual
Wagon Wheel Gap	Evap.	-	-	-	-	7.03	7.94	-	5.83	-	-	-	-	-
	Precip.	-	-	-	0.29	.99	.00	-	1.65	2.06	-	-	1.30	-
Alamosa Airport	Evap.	-	-	-	-	9.83	11.56	9.61	8.73	7.74	4.63	-	-	-
	Precip.	0.15	0.26	0.03	.33	1.07	.08	2.59	1.21	1.45	.71	0.44	.45	8.77
Platoro Dam	Evap.	-	-	-	-	4.93	6.78	6.25	5.33	5.13	2.40	-	-	-
	Precip.	-	-	-	-	1.23	.36	3.09	1.76	2.98	3.44	-	-	-
El Vado Dam	Evap.	-	-	-	-	7.57	10.07	9.29	7.09	6.83	3.43	-	-	-
	Precip.	.72	.48	.29	.70	.56	.32	2.14	2.47	2.73	1.72	.62	1.44	14.19
Abiquiu Dam	Evap.	-	-	-	7.77	10.68	11.46	11.23	8.25	7.83	-	-	-	-
	Precip.	.07	.27	.02	.42	.26	.09	2.78	1.74	2.64	.70	.23	1.19	10.41
Santa Fe	Evap.	-	-	-	-	9.70	13.18	10.40	-	7.05	-	-	-	-
	Precip.	.40	.48	.13	1.26	.20	.40	3.15	.91	2.31	4.05	2.06	1.14	16.49
Cochiti Dam	Evap.	-	-	3.54	9.28	12.42	15.66	14.38	10.20	11.22	4.40	-	-	-
	Precip.	.94	.20	.16	.87	.18	.14	3.23	1.85	1.01	1.67	.60	1.21	12.06
Jemez Dam	Evap.	-	-	2.83	9.07	12.75	15.93	13.86	10.71	9.94	4.09	-	-	-
	Precip.	.60	.19	.04	.83	.07	.04	2.59	1.01	1.14	1.49	.51	1.01	9.52
Bosque del Apache	Evap.	-	-	-	9.25	11.43	12.63	10.54	10.34	7.46	6.06	-	-	-
	Precip.	T	.17	.00	.00	.00	.00	.78	.74	1.23	1.14	.76	1.00	5.82
Elephant Butte Dam	Evap.	3.85	6.18	10.01	11.66	16.58	17.71	15.92	11.89	10.18	7.15	4.01	2.30	117.44
	Precip.	.00	T	.00	.12	.04	.07	.86	2.15	.88	2.00	.51	1.20	7.83
Caballo Dam	Evap.	-	6.63	11.86	12.15	15.79	16.58	15.54	11.98	11.37	6.95	4.06	3.17	-
	Precip.	.00	.00	.00	.15	.00	.37	.92	.99	1.00	2.35	.33	.84	6.95
State University	Evap.	4.16	5.35	9.17	10.77	13.51	12.94	13.63	9.77	8.86	5.95	3.90	2.47	100.48
	Precip.	.11	T	.00	.17	.00	T	1.77	.80	.57	1.29	.42	.64	5.77

