

والمعاجبين والمستحد والمتح والمتح أتعاقق ومرواف والمصف فمانته أرار المقاو

Autor States

3 C .



A. Marine

. مربع کرد. بود کرد. بود کرد.

San and a state of the second s

#### CONTENTS

and which a second state of the second se

Fortieth Annual Report to Covernors	Page
Rio Grande Compact	. 1
	2
Resolution of the Commission	4
Rules and Regulations	15
Records of Deliveries and Release	19
	26
Deliveries by Colorado at State line. Deliveries by New Mexico at Elephant Butte Release and Spill from Project State	27
Cost of Operation and Budget	29
Reproved a	30
Acknowledgments	
Accuracy of Records	31
Streamflow	32
Pio Crando nove - 1	3-43
Conejos River below Platoro Posomojo and	33
Conejos River near Mogote, Colorado	33
San Antonio River at Ortiz, Colorado	34
Conejos River near Ortiz, Colorado	34
Rio Grande near Lobatos, Colorado	35
Willow Creek above Heron Reservoir	36
Horse Lake Creek above Heron Reservoir, near Park View, New Mexico	36
Willow Creek below Heron Dam, New Mexico.	37
Rio Chama below El Vado Dam, New Mexico	37
Rio Chama below Abiquiu Dam, New Mexico.	38
Rio Grando at Nambe Falls, near Nambe, New Mexico.	38
Santa Fe Biver town Bridge, near San Ildefonso, New Mexico	39
Rio Grande below Coshidi Fe, New Mexico	39
Galisteo Creek below Collision, New Mexico	40
Jemez River below Jemon Garisteo Dam, New Mexico	40
Rio Grande below Elephant Butter B	41 1
Rio Grande below Caballo Dom New Mexico	42
Bonito ditch below Caballo Dam, New Mexico	42
Cabario Dam, New Mexico	43
Storage in Reservoirs	
Transmountain Diversions	-50
	51
Evaporation and Precipitation	F <b>h</b>
52,	101

#### ILLUSTRATIONS

nap,	RIO	Grande	Basin	above	Ft.	Quitman,	Te	kasFronti	Eniogo
Мар,	Rio	Grande	Basin	above	Berr	nalillo,	New	Mexico	54 55

#### RIO GRANDE COMPACT COMMISSION

TEXAS

#### COLORADO

NEW MEXICO

The Honorable William P. Clements Governor of the State of Texas Austin, Texas

March 29, 1979

and and the second state of the second s

the Honorable Richard D. Lamm Governor of the State of Colorado Denver, Colorado

The Honorable Bruce King Governor of the State of New Mexico Santa Fe, New Mexico

Sirs:

The 40th annual meeting of the Rio Grande Compact Commission was held at Pagosa Springs, Colorado on March 29, 1979.

The Commission reviewed its prior reports and the current reports of the Secretary relative to streamflow at Compact gaging stations and storage in reservoirs. The Commission found that:

- (a) Deliveries of water at the Colorado-New Mexico State line by Colorado amounted to 174,500 acre-feet, which was 10,500 acre-feet in excess of the scheduled delivery in 1978. The accrued debit of Colorado was reduced to 695,000 acre-feet as of December 31, 1978. However, in light of the as yet unresolved controversy between the States, Colorado cannot agree with conclusions as to her indebtedness.
- (b) Deliveries of water into Elephant Butte Reservoir by New Mexico, as measured by the Elephant Butte Effective Supply, amounted to \$377,600 acre-feet, which was 27,800 acre-feet less than the scheduled delivery in 1978. The accrued debit of New Mexico was 28,200 acre-feet as of December 31, 1978.
- (c) Releases of usable water in 1978 from Project Storage amounted to 356,600 acre-feet.
- (d) Expenses of administration of the Rio Grande Compact were \$57,630 in the fiscal year ending June 30, 1978. The United States bore \$24,810 of this total; the balance of \$32,820 was borne equally by the three States party to the Compact.

Respectfully,

For Texas

ommiss Moner for Colorado

E. E. Reynolds, Commissioner for New Mexico

0.0**12** 

2

#### RIO GRANDE COMPACT COMMISSION REPORT

#### RIO GRANDE COMPACT

The State of Colorado, the State of New Mexico, and the State of Texas, desiring to remove all causes of present and future controversy among these States and between citizens of one of these States and citizens of another State with respect to the use of the waters of the Rio Grande above Fort Quitman, Texas, and being moved by considerations of interstate comity, and for the purpose of effecting an equitable apportionment of such waters, have resolved to conclude a Compact for the attainment of these purposes, and to that end, through their respective Governors, have named as their respective Commissioners:

For	the	State	of	Colorado	M. C. Hinderlider
For	the	State	of	New Mexico	Thomas M. McClure
For	the	State	of	Texas	Frank B. Clayton

who, after negotiations participated in by S. O. Harper, appointed by the President as the representative of the United States of America, have agreed upon the following articles, to-wit:

#### ARTICLE I

(a) The State of Colorado, the State of New Mexico, the State of Texas and the United States of America, are hereinafter designated "Colorado," "New Mexico," "Texas," and the "United States," respectively.

(b) "The Commission" means the agency created by this Compact for the administration thereof.

(c) The term "Rio Grande Basin" means all of the territory drained by the Rio Grande and its tributaries in Colorado, in New Mexico, and in Texas above Fort Quitman, including the Closed Basin in Colorado.

(d) The "Closed Basin" means that part of the Rio Grande Basin in Colorado where the streams drain into the San Luis Lakes and adjacent territory, and do not normally contribute to the flow of the Rio Grande.

(e) The term "tributary" means any stream which naturally contributes to the flow of the Rio Grande.

(f) "Transmountain Diversion" is water imported into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, exclusive of the Closed Basin.

(g) "Annual Debits" are the amounts by which actual deliveries in any calendar year fall below scheduled

#### RIO GRANDE COMPACT

502

000

and the second of the state of the second state of the second second second second second second second second s

3

(h) "Annual Credits" are the amounts by which actual deliveries in any calendar year exceed scheduled deliveries.

(i) "Accrued Debits" are the amounts by which the sum of all annual debits exceeds the sum of all annual credits over any common period of time.

(j) "Accrued Credits" are the amounts by which the sum of all annual credits exceeds the sum of all annual debits over any common period of time.

(k) "Project Storage" is the combined capacity of Elephant Butte Reservoir and all other reservoirs actually available for the storage of usable water below Elephant Butte and above the first diversion to lands of the Rio Grande Project, but not more than a total of 2,638,860 acre feet.

(1) "Usable Water" is all water, exclusive of credit water, which is in project storage and which is available for release in accordance with irrigation demands, including deliveries to Mexico.

(m) "Credit Water" is that amount of water in project storage which is equal to the accrued credit of Colorado, or New Mexico, or both.

(n) "Unfilled Capacity" is the difference between the total physical capacity of project storage and the amount of usable water then in storage.

(o) "Actual Release" is the amount of usable water released in any calendar year from the lowest reservoir comprising project storage.

(p) "Actual Spill" is all water which is actually spilled from Elephant Butte Reservoir, or is released therefrom for flood control, in excess of the current demand on project storage and which does not become usable water by storage in another reservoir; provided, that actual spill of usable water cannot occur until all credit water shall have been spilled.

(q) "Hypothetical Spill" is the time in any year at which usable water would have spilled from project storage if 790,000 acre feet had been released therefrom at rates proportional to the actual release in every year from the starting date to the end of the year in which hypothetical spill occurs; in computing hypothetical spill the initial condition shall be the amount of usable water in project storage at the beginning of the calendar year following the effective date of this Compact, and thereafter the initial condition shall be the amount of usable water in project effective date of the calendar year following the condition shall be the amount of usable water in project storage at the beginning of the calendar year following each actual spill.

#### RIO GRANDE COMPACT COMMISSION REPORT

#### ARTICLE II

The Commission shall cause to be maintained and operated a stream gaging station equipped with an automatic water stage recorder at each of the following points, to-wit:

(a) On the Rio Grande near Del Norte above the principal points of diversion to the San Luis Valley;

(b) On the Conejos River near Mogote;

(c) On the Los Pinos River near Ortiz;

- (d) On the San Antonio River at Ortiz;
- (e) On the Conejos River at its mouths near Los Sauses;
- (f) On the Rio Grande near Lobatos;
- (g) On the Rio Chama below El Vado Reservoir;

(h) On the Rio Grande at Otowi Bridge near San Ildefonso;

- (i) On the Rio Grande near San Acacia;
- (j) On the Rio Grande at San Marcial;
- (k) On the Rio Grande below Elephant Butte Reservoir;
- (1) On the Rio Grande below Caballo Reservoir.

Similar gaging stations shall be maintained and operated below any other reservoir constructed after 1929, and at such other points as may be necessary for the securing of records required for the carrying out of the Compact; and automatic water stage recorders shall be maintained and operated on each of the reservoirs mentioned, and on all others constructed after 1929.

Such gaging stations shall be equipped, maintained and operated by the Commission directly or in cooperation with an appropriate Federal or State agency, and the equipment, method and frequency of measurement at such stations shall be such as to produce reliable records at all times. (Note: See Resolution of Commission printed elsewhere in this report.)

#### ARTICLE III

The obligation of Colorado to deliver water in the Rio Grande at the Colorado-New Mexico State Line, measured at or near Lobatos. in each calendar year. shall be ten

4

#### RIO GRANDE COMPACT

thousand acre feet less than the sum of those quantities set forth in the two following tabulations of relationship, which correspond to the quantities at the upper index

#### DISCHARGE OF CONEJOS RIVER

Quantities in thousands of acre feet

350

400

450

500

The second second second second

Conejos Index Supply (1) Conejos River at Mouths (2)

86

98

112

127

TOÓ	0
150	0
200	20
200	45
250	75
300	70
350	109
400	147
400	188
450	100
500	232
EE0	278
550	, 326
600	376
650	010
700	426
100	476

Intermediate quantities shall be computed by proportional parts.

(1) Conejos Index Supply is the natural flow of Cone jos River at the U.S.G.S. gaging station near Mogote during the calendar year, plus the natural flow of Los Pinos River at the U.S.G.S. gaging station near Ortiz and the natural flow of San Antonio River at the U.S.G.S. gaging station at Ortiz, both during the months of April to October, inclusive.

(2) Conejos River at Mouths is the combined discharge of branches of this river at the U.S.G.S. gaging stations near Los Sauses during the calendar year.

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER

Quantities in thousands of acre feet

Rio Grande at Del Norte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
200 250	60
300	75

RIO GRANDE COMPACT COMMISSION REPORT

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER--Con.

Quantities in thousands of acre feet

Rio Grande at Lobatos less Conejos at Mouths (4)

Rio Grande at Del Norte (3)

550	144
600	162
650	182
700	204
750	229
800	257
850	292
900	335
950	380
L.000	430
1,100	540
1,200	640
1.300	740
1,400	840
-,	

Intermediate quantities shall be computed by proportional parts.

(3) Rio Grande at Del Norte is the recorded flow of the Rio Grande at the U.S.G.S. gaging station near Del Norte during the calendar year (measured above all principal points of diversion to San Luis Valley) corrected for the operation of reservoirs constructed after 1937.

(4) Rio Grande at Lobatos less Conejos at Mouths is the total flow of the Rio Grande at the U.S.G.S. gaging station near Lobatos, less the discharge of Conejos River at its Mouths, during the calendar year.

The application of these schedules shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) any new or increased depletion of the runoff above inflow index gaging stations; and (c) any transmountain diversions into the drainage basin of the Rio Grande above Lobatos.

In event any works are constructed after 1937 for the purpose of delivering water into the Rio Grande from the Closed Basin, Colorado shall not be credited with the amount of such water delivered, unless the proportion of sodium ions shall be less than forty-five percent of the total positive ions in that water when the total dissolved solids in such water exceeds three hundred fifty parts per million.

00012

6

#### RIO GRANDE COMPACT

#### ARTICLE IV

The obligation of New Mexico to deliver water in the Rio Grande at San Marcial, during each calendar year, exclusive of the months of July, August, and September, shall be that quantity set forth in the following tabulation of relationship, which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND AT SAN MARCIAL EXCLUSIVE OF JULY, AUGUST AND SEPTEMBER

Quantities in thousands of acre feet

Otowi Index Supply (5)

San Marcial Index Supply (6)

100 200 300 400 500 600 700 800 900 1,000 1,000 1,200 1,300 1,400 1,500 1,600 1,700 1,800 1,900 2,000 2,000	$\begin{array}{c} 0\\ 65\\ 141\\ 219\\ 300\\ 383\\ 469\\ 557\\ 648\\ 742\\ 839\\ 939\\ 1,042\\ 1,148\\ 1,257\\ 1,370\\ 1,489\\ 1,608\\ 1,730\\ 1,856\\ 1,985\\ 2,117\end{array}$
2,300	2,117 2,253

Intermediate quantities shall be computed by proportional parts.

(5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, exclusive of the flow during the months of July, August and September, corrected for the operation of reservoirs constructed after 1929 in the drain age basin of the Rio Grande between Lobatos and Otowi

030129

RIO GRANDE COMPACT COMMISSION REPORT

(6) San Marcial Index Supply is the recorded flow of the Rio Grande at the gaging station at San Marcial during the calendar year exclusive of the flow during the months of July, August and September.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico at any time of the year of the natural runoff at Otowi Bridge; (c) depletion of the runoff during July, August and September of tributaries between Otowi Bridge and San Marcial, by works constructed after 1937; and (d) any transmountain diversions into the Rio Grande between Lobatos and San Marcial.

Concurrent records shall be kept of the flow of the Rio Grande at San Marcial, near San Acacia, and of the release from Elephant Butte Reservoir to the end that the records at these three stations may be correlated. (Note: See Resolution of Commission printed elsewhere in this report.)

#### ARTICLE V

If at any time it should be the unanimous finding and determination of the Commission that because of changed physical conditions, or for any other reason, reliable records are not obtainable, or cannot be obtained, at any of the stream gaging stations herein referred to, such stations may, with the unanimous approval of the Commission, be abandoned, and with such approval another station, or other stations, shall be established and new measurements shall be substituted which, in the unanimous opinion of the Commission, will result in substantially the same results, so far as the rights and obligations to deliver water are concerned, as would have existed if such substitution of stations and measurements had not been so made. (Note: See Resolution of Commission printed elsewhere in this report.)

#### ARTICLE VI

Commencing with the year following the effective date of this Compact, all credits and debits of Colorado and New Mexico shall be computed for each calendar year; provided, that in a year of actual spill no annual credits nor annual debits shall be computed for that year.

In the case of Colorado, no annual debit nor accrued debit shall exceed 100,000 acre feet, except as either or both may be caused by holdover storage of water in reservoirs constructed after 1937 in the drainage basin of the

00130

Rio Grande above Lobatos. Within the physical limitations of storage capacity in such reservoirs, Colorado shall retain water in storage at all times to the extent of its accrued debit.

In the case of New Mexico, the accrued debit shall not exceed 200,000 acre feet at any time, except as such debit may be caused by holdover storage of water in reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and San Marcial. Within the physical limitations of storage capacity in such reservoirs, New Mexico shall retain water in storage at all times to the extent of its accrued debit. In computing the magnitude of accrued credits or debits, New Mexico shall not be charged with any greater debit in any one year than the sum of 150,000 acre-feet and all gains in the quantity of water in

The Commission by unanimous action may authorize the release from storage of any amount of water which is then being held in storage by reason of accrued debits of Colorado or New Mexico; provided, that such water shall be replaced at the first opportunity thereafter.

In computing the amount of accrued credits and accrued debits of Colorado or New Mexico, any annual credits in excess of 150,000 acre feet shall be taken as equal to that amount.

In any year in which actual spill occurs, the accrued credits of Colorado, or New Mexico, or both, at the beginning of the year shall be reduced in proportion to their respective credits by the amount of such actual spill; provided, that the amount of actual spill shall be deemed to be increased by the aggregate gain in the amount of water in storage, prior to the time of spill, in reservoirs above San Marcial constructed after 1929; provided, further, that authorize the release of part, or all, of such credits in advance of spill, the amount so released shall be deemed to constitute actual spill.

In any year in which there is actual spill of usable water, or at the time of hypothetical spill thereof, all accrued debits of Colorado, or New Mexico, or both, at the beginning of the year shall be cancelled.

In any year in which the aggregate of accrued debits of Colorado and New Mexico exceeds the minimum unfilled capacity of project storage, such debits shall be reduced proportionally to an aggregate amount equal to such minimum unfilled capacity.

#### RIO GRANDE COMPACT COMMISSION REPORT

To the extent that accrued credits are impounded in reservoirs between San Marcial and Courchesne, and to the extent that accrued debits are impounded in reservoirs above San Marcial, such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bore to the total amount of water in such reservoirs during the year.

#### ARTICLE VII

Neither Colorado nor New Mexico shall increase the amount of water in storage in reservoirs constructed after 1929 whenever there is less than 400,000 acre feet of usable water in project storage; provided, that if the actual releases of usable water from the beginning of the calendar year following the effective date of this Compact, or from the beginning of the calendar year following actual spill, have aggregated more than an average of 790,000 acre feet per annum, the time at which such minimum stage is reached shall be adjusted to compensate for the difference between the total actual release and releases at such average rate; provided, further, that Colorado, or New Mexico, or both, may rélinquish accrued credits at any time, and Texas may accept such relinquished water, and in such event the state, or states, so relinquishing shall be entitled to store water in the amount of the water so relinquished.

#### ARTICLE VIII

During the month of January of any year the Commisioner for Texas may demand of Colorado and New Mexico, and the Commissioner for New Mexico may demand of Colorado, the release of water from storage reservoirs constructed after 1929 to the amount of the accrued debits of Colorado and New Mexico, respectively, and such releases shall be made by each at the greatest rate practicable under the conditions then prevailing, and in proportion to the total debit of each, and in amounts, limited by their accrued debits, sufficient to bring the quantity of usable water in project storage to 600,000 acre feet by March first and to maintain this quantity in storage until April thirtieth, to the end that a normal release of 790,000 acre feet may be made from project storage in that year.

#### ARTICLE IX

Colorado agrees with New Mexico that in event the United States or the State of New Mexico decides to construct the necessary works for diverting the waters of the San Juan River, or any of its tributaries, into the Rio Grande, Colorado hereby consents to the construction of said works and the diversion of waters from the San Juan

C ⊂ **∓** 3

<u>C</u>2

#### RIO GRANDE COMPACT

က က

> River, or the tributaries thereof, into the Rio Grande in New Mexico, provided the present and prospective uses of water in Colorado by other diversions from the San Juan River, or its tributaries, are protected.

#### ARTICLE X

In the event water from another drainage basin shall be imported into the Rio Grande Basin by the United States or Colorado or New Mexico, or any of them jointly, the State having the right to the use of such water shall be given proper credit therefor in the application of the

#### ARTICLE XI

New Mexico and Texas agree that upon the effective date of this Compact all controversies between said States relative to the quantity or quality of the water of the Rio Grande are composed and settled; however, nothing herein shall be interpreted to prevent recourse by a signatory state to the Supreme Court of the United States for redress should the character or quality of the water, at the point of delivery, be changed hereafter by one signatory state to the injury of another. Nothing herein shall be construed as an admission by any signatory state that the use of the user is responsible in law.

#### ARTICLE XII

To administer the provisions of this Compact there shall be constituted a Commission composed of one reprecompact from each state, to be known as the Rio Grande Compact Commission. The State Engineer of Colorado shall be ex-officio the Rio Grande Compact Commissioner for Colorado. The State Engineer of New Mexico shall be exofficio the Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for Texas shall be appointed by the Governor of Texas. The President of the United States shall be requested to designate a representand such representative of the United States, if so designated by the President, shall act as Chairman of the Commission without vote.

The salaries and personal expenses of the Rio Grande Compact Commissioners for the three States shall be paid by their respective States, and all other expenses incident to the administration of this Compact, not borne by the United States, shall be borne equally by the three States.

40

#### RIO GRANDE COMPACT COMMISSION REPORT

In addition to the powers and duties hereinbefore specifically conferred upon such Commission, and the members thereof, the jurisdiction of such Commission shall extend only to the collection, correlation and presentation of factual data and the maintenance of records having a bearing upon the administration of this Compact, and, by unanimous action, to the making of recommendations to the respective States upon matters connected with the administration of this Compact. In connection therewith, the Commission may employ such engineering and clerical aid as may be reasonably necessary within the limit of funds provided for that purpose by the respective States. Annual reports compiled for each calendar year shall be made by the Commission and transmitted to the Governors of the signatory States on or before March first following the year covered by the report. The Commission may, by unanimous action, adopt rules and regulations consistent with the provisions of this Compact to govern their proceedings.

The findings of the Commission shall not be conclusive in any court or tribunal which may be called upon to interpret or enforce this Compact.

#### ARTICLE XIII

At the expiration of every five-year period after the effective date of this Compact, the Commission may, by unanimous consent, review any provisions hereof which are not substantive in character and which do not affect the basic principles upon which the Compact is founded, and shall meet for the consideration of such questions on the request of any member of the Commission; provided, however, that the provisions hereof shall remain in full force and effect until changed and amended within the intent of the Compact by unanimous action of the Commissioners, and until any changes in this Compact are ratified by the legislatures of the respective states and consented to by the Congress, in the same manner as this Compact is required to be ratified to become effective.

#### ARTICLE XIV

The schedules herein contained and the quantities of water herein allocated shall never be increased nor diminished by reason of any increase or diminution in the delivery or loss of water to Mexico.

#### RIO GRANDE COMPACT

**30** 00

#### ARTICLE XV

The physical and other conditions characteristic of the Rio Grande and peculiar to the territory drained and served thereby, and to the development thereof, have actuated this Compact and none of the signatory states admits that any provisions herein contained establishes any general principle or precedent applicable to other interstate streams.

#### ARTICLE XVI

Nothing in this Compact shall be construed as affecting the obligations of the United States of America to Mexico under existing treaties, or to the Indian Tribes, or as impairing the rights of the Indian Tribes.

#### ARTICLE XVII

This Compact shall become effective when ratified by the legislatures of each of the signatory states and consented to by the Congress of the United States. Notice of ratification shall be given by the Governor of each state to the Governors of the other states and to the President of the United States, and the President of the United States is requested to give notice to the Governors of each of the signatory states of the consent of the Congress of the United States.

IN WITNESS WHEREOF, the Commissioners have signed this Compact in quadruplicate original, one of which shall be deposited in the archives of the Department of State of the United States of America and shall be deemed the authoritative original, and of which a duly certified copy shall be forwarded to the Governor of each of the signatory States.

14

#### RIO GRANDE COMPACT COMMISSION REPORT

Done at the City of Santa Fe, in the State of New Mexico, on the 18th day of March, in the year of our Lord, One Thousand Nine Hundred and Thirty-eight.

(Sgd.) M. C. HINDERLIDER
(Sgd.) THOMAS M. McCLURE
(Sgd.) FRANK B. CLAYTON

APPROVED:

(Sgd.) S. O. HARPER

RATIFIED BY:

Colorado, February 21, 1939 New Mexico, March 1, 1939 Texas, March 1, 1939

Passed Congress as Public Act No. 96, 76th Congress, Approved by the President May 31, 1939.

RESOLUTION ADOPTED BY RIO GRANDE COMPACT COMMISSION AT THE ANNUAL MEETING HELD AT EL PASO, TEXAS, FEBRUARY 22-24, 1948, CHANGING GAGING STATIONS AND MEASUREMENTS OF DELIVERIES BY NEW MEXICO

#### $\underline{R} \ \underline{E} \ \underline{S} \ \underline{O} \ \underline{L} \ \underline{U} \ \underline{T} \ \underline{I} \ \underline{O} \ \underline{N}$

Whereas, at the Annual Meeting of the Rio Grande Compact Commission in the year 1945, the question was raised as to whether or not a schedule for delivery of water by New Mexico during the entire year could be worked out, and

Whereas, at said meeting the question was referred to the Engineering Advisers for their study, recommendations and report, and

Whereas, said Engineering Advisers have met, studied the problems and under date of February 24, 1947, did submit their Report, which said Report contains the findings of said Engineering Advisers and their recommendations, and

Whereas, the Compact Commission has examined said Report and finds that the matters and things therein found and recommended are proper and within the terms of the Rio Grande Compact, and

Whereas, the Commission has considered said Engineering Advisers' Report and all available evidence, information and material and is fully advised:

Now, Therefore, Be it Resolved:

The Commission finds as follows:

- (a) That because of change of physical conditions, reliable records of the amount of water passing San Marcial are no longer obtainable at the stream gaging station at San Marcial and that the same should be abandoned for Compact purposes.
- (b) That the need for concurrent records at San Marcial and San Acacia no longer exists and that the gaging station at San Acacia should be abandoned for Compact purposes.
- (c) That it is desirable and necessary that the obligations of New Mexico under the Compact to deliver water in the months of July, August, September, should be scheduled.

#### RIO GRANDE COMPACT COMMISSION REPORT

That the change in gaging stations and substi-(d) tution of the new measurements as hereinafter set forth will result in substantially the same results so far as the rights and obligations to deliver water are concerned, and would have existed if such substitution of stations and measurements had not been so made.

#### Be it Further Resolved:

That the following measurements and schedule thereof shall be substituted for the measurements and schedule thereof as now set forth in Article IV of the Compact:

"The obligation of New Mexico to deliver water in the Rio Grande into Elephant Butte Reservoir during each calendar year shall be measured by that quantity set forth in the following tabulation of relationship which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY

Quantities in thousands of acre-feet

Otowi Index Supply (5) Elephant Butte Effective Index Supply (6)

100 200 300 400 500 600 700 800 1,000 1,100 1,200 1,200 1,300 1,500 1,600 1,700	57 114 171 228 345 406 471 542 621 707 800 897 996 1,195 1,295
1,500 1,600 1,700 1,800 1,900 2,000	1,095 1,195 1,295 1,395 1,495 1,595

(7)(\_\_)

16

#### RESOLUTION OF COMMISSION

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY--Continued

#### Quantities in thousands of acre-feet

Otowi Index Supply (5)

တ က

**ि**>

Elephant Butte Effective Index Supply (6)

2,100	1,695
2,200	1,795
2,300	1,895
2,400	1,995
2,500	2,095
2,600	2,195
2,600	2,295
2,700	2,295
2,800	2,395
2,900	2,495
3,000	2,595

Intermediate quantities shall be computed by proportional parts.

- (5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, corrected for the operation of reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi Bridge.
- (6) Elephant Butte Effective Index Supply is the recorded flow of the Rio Grande at the gaging station below Elephant Butte Dam during the calendar year plus the net gain in storage in Elephant Butte Reservoir during the same year or minus the net loss in storage in said reservoir, as the case may be.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico of the natural runoff at Otowi Bridge; and (c) any transmountain diversions into the Rio Grande between Lobatos and Elephant Butte Reservoir."

#### RIO GRANDE COMPACT COMMISSION REPORT

Be it Further Resolved:

That the gaging stations at San Acacia and San Marcial be, and the same are hereby abandoned for Compact purposes.

Be it Further Resolved:

That this Resolution has been passed unanimously and shall be effective January 1, 1949, if within 120 days from this date the Commissioner for each State shall have received from the Attorney General of the State represented by him, an opinion approving this Resolution, and shall have so advised the Chairman of the Commission, otherwise, to be of no force and effect.

(Note: The following paragraph appears in the Minutes of the Annual Meeting of the Commission held at Denver, Colorado, February 14-16, 1949:

"The Chairman announced that he had received, pursuant to the Resolution adopted by the Commission at the Ninth Annual Meeting on February 24, 1948, opinions from the Attorneys General of Colorado, New Mexico and Texas that the substitution of stations and measurements of deliveries by New Mexico set forth in said resolution was within the powers of the Commission").

#### RULES AND REGULATIONS FOR ADMINISTRATION OF THE RIO GRANDE COMPACT

A Compact, known as the Rio Grande Compact, between the States of Colorado, New Mexico and Texas, having become effective on May 31, 1939 by consent of the Congress of the United States, which equitably apportions the waters of the Rio Grande above Fort Quitman and permits each State to develop its water resources at will, subject only to its obligations to deliver water in accordance with the schedules set forth in the Compact, the following Rules and Regulations have been adopted for its administration by the Rio Grande Compact Commission; to be and remain in force and effect only so long as the same may be satisfactory to each and all members of the Commission, and provided always that on the objection of any member of the Commission, in writing, to the remaining two members of the Commission after a period of sixty days from the date of such objection, the sentence, paragraph or any portion or all of these rules to which any such objection shall be made, shall stand abrogated and shall thereafter have no further force and effect; it being the intent and purpose of the Commission to permit these rules to obtain and be effective only so long as the same may be satisfactory to each and all of the Commissioners.

#### GAGING STATIONS /1

Responsibility for the equipping, maintenance and operation of the stream gaging stations and reservoir gaging stations required by the provisions of Article II of the Compact shall be divided among the signatory States as follows:

(a) Gaging stations on streams and reservoirs in the Rio Grande Basin above the Colorado-New Mexico boundary shall be equipped, maintained, and operated by Colorado in cooperation with the U.S. Geological Survey.

(b) Gaging stations on streams and reservoirs in the Rio Grande Basin below Lobatos and above Caballo Reservoir shall be equipped, maintained and operated by New Mexico in cooperation with the U.S. Geological Survey to the extent that such stations are not maintained and operated by some other Federal Agency.

(c) Gaging stations on Elephant Butte Reservoir and on Caballo Reservoir, and the stream gaging stations on the Rio Grande below those reservoirs shall be equipped, maintained and operated by or on behalf of Texas through the agency of the U.S. Bureau of Reclamation.

<u>Zl Amended</u> at Eleventh Annual Meeting, February 23, 1950.

20

#### RIO GRANDE COMPACT COMMISSION REPORT

The equipment, method and frequency of measurements at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Water-stage recorders on the reservoirs specifically named in Article II of the Compact shall have sufficient range below maximum reservoir level to record major fluctuations in storage. Staff gages may be used to determine fluctuations below the range of the water-stage recorders on these and other large reservoirs, and staff gages may be used upon approval of the Commission in lieu of water-stage recorders on small reservoirs, provided that the frequency of observation is sufficient in each case to establish any material changes in water levels in such reservoirs.

#### RESERVOIR CAPACITIES /1\_

Colorado shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin above Lobatos constructed after 1937; New Mexico shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin between Lobatos and San Marcial constructed after 1929; and Texas shall file with the Commission tables of areas and capacities for Elephant Butte Reservoir and for all other reservoirs actually available for the storage of water between Elephant Butte and the first diversion to lands under the Rio Grande Project.

Whenever it shall appear that any table of areas and capacities is in error by more than five per cent, the Commission shall use its best efforts to have a re-survey made and a corrected table of areas and capacities to be substituted as soon as practicable. To the end that the Elephant Butte effective supply may be computed accurately, the Commission shall use its best efforts to have the rate of accumulation and the place of deposition of silt in Elephant Butte Reservoir checked at least every three years.

#### ACTUAL SPILL /2

(a) Water released from Elephant Butte in excess of Project requirements, which is currently passed through Caballo Reservoir, prior to the time of spill, shall be deemed to have been Usable Water released in anticipation of spill, or Credit Water if such release shall have been authorized.

/1 Amended at Eleventh Annual Meeting, February 23, 1950. /2 Adopted at Fourth Annual Meeting, February 24, 1943.

#### RULES AND REGULATIONS

(b) Excess releases from Elephant Butte Reservoir, as defined in (a) above, shall be added to the quantity of water actually in storage in that reservoir, and Actual Spill shall be deemed to have commenced when this sum equals the total physical capacity of that reservoir, to the level of the uncontrolled spillway, i.e. -2,219,000 acreft in 1942.

(c) All water actually spilled at Elephant Butte Reservoir, or released therefrom, in excess of Project requirements, which is currently passed through Caballo Reservoir, after the time of spill, shall be considered as Actual Spill, provided that the total quantity of water then in storage in Elephant Butte Reservoir exceeds the physical capacity of that reservoir at the level of the sill of the spillway gates, i.e. -1,830,000 acre-ft in 1942.

(d) Water released from Caballo Reservoir in excess of Project requirements and in excess of water currently released from Elephant Butte Reservoir, shall be deemed Usable Water released, excepting only flood water entering Caballo Reservoir from tributaries below Elephant Butte

#### DEPARTURES FROM NORMAL RELEASES /3

For the purpose of computing the time of Hypothetical Spill required by Article VI and for the purpose of the adjustment set forth in Article VII, no allowance shall be made for the difference between Actual and Hypothetical Evaporation, and any under-release of usable water from Project Storage in excess of 150,000 acre-ft in any year shall be taken as equal to that amount.

#### EVAPORATION LOSSES /4, /5, /6

The Commission shall encourage the equipping, maintenance and operation, in cooperation with the U.S. Weather Bureau or other appropriate agency, of evaporation stations at Elephant Butte Reservoir and at or near each major reservoir in the Rio Grande Basin within Colorado constructed after 1937 and in New Mexico constructed after 1929. The net loss by evaporation from a reservoir surface shall be taken as the difference between the actual evaporation loss and the evapo-transpiration losses which would have occurred naturally, prior to the construction of such reservoir. Changes in evapo-transpiration losses along stream channels below reservoirs may be disregarded.

Adopted June 2, 1959; made effective January 1, 1952.
 Amended at Tenth Annual Meeting, February 15, 1949.
 Amended at Twelfth Annual Meeting, February 24, 1951.
 Amended June 2, 1959.

21

and the state of the

Net losses by evaporation, as defined above, shall be used in correcting Index Supplies for the operation of reservoirs upstream from Index Gaging Stations as required by the provisions of Article III and Article IV of the Compact.

In the application of the provisions of the last unnumbered paragraph of Article VI of the Compact:

(a) Evaporation losses for which accrued credits shall be reduced shall be taken as the difference between the gross evaporation from the water surface of Elephant Butte Reservoir and rainfall on the same surface.

(b) Evaporation losses for which accrued debits shall be reduced shall be taken as the net loss by evaporation as defined in the first paragraph.

#### ADJUSTMENT OF RECORDS

The Commission shall keep a record of the location, and description of each gaging station and evaporation station, and, in the event of change in location of any stream gaging station for any reason, it shall ascertain the increment in flow or decrease in flow between such locations for all stages. Wherever practicable, concurrent records shall be obtained for one year before abandonment of the previous station.

#### NEW OR INCREASED DEPLETIONS

In the event any works are constructed which alter or may be expected to alter the flow at any of the Index Gaging Stations mentioned in the Compact, or which may otherwise necessitate adjustments in the application of the schedules set forth in the Compact, it shall be the duty of the Commissioner specifically concerned to file with the Commission all available information pertaining thereto, and appropriate adjustments shall be made in accordance with the terms of the Compact; provided, however, that any such adjustments shall in no way increase the burden imposed upon Colorado or New Mexico under the schedules of deliveries established by the Compact.

#### TRANSMOUNTAIN DIVERSIONS

In the event any works are constructed for the delivery of waters into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, such waters shall be measured at the point of delivery into the Rio Grande Basin and proper allowances shall be made for losses in transit from such points to the Index Gaging Station on the stream with which the imported waters are comingled.

030144

へんしゃ ごうちゃく かんれいだい しょう

#### RULES AND REGULATIONS

## £00**145**

#### QUALITY OF WATER

In the event that delivery of water is made from the Closed Basin into the Rio Grande, sufficient samples of such water shall be analyzed to ascertain whether the quality thereof is within the limits established by the

#### SECRETARY /7

The Commission, subject to the approval of the Director, U.S. Geological Survey, to a cooperative agreement for such purposes shall employ the U.S. Geological Survey on a yearly basis, to render such engineering and clerical aid as may reasonably be necessary for administration of the Compact. Said agreement shall provide that the Geological Survey shall:

(1) Collect and correlate all factual data and other records having a material bearing on the administration of the Compact and keep each Commissioner advised thereof.

(2) Inspect all gaging stations required for administration of the Compact and make recommendations to the Commission as to any changes or improvements in methods of measurement or facilities for measurement which may be needed to insure that reliable records be obtained.

(3) Report to each Commissioner by letter on or before the fifteenth day of each month, except January a summary of all hydrographic data then available for the current year - on forms prescribed by the Commission -

(a) Deliveries by Colorado

(b) Deliveries by New Mexico

(c) Operation of Project Storage

(4) Make such investigations as may be requested by the Commission in aid of its administration of the Compact.

(5) Act as Secretary to the Commission and submit to the Commission at its regular meeting in February a report on its activities and a summary of all data needed for determination of debits and credits and other matters pertaining to administration of the Compact.

7 The substitution of this section for the section titled "Reports to Commissioners" was adopted at Ninth Annual Meeting, February 22, 1948.

#### RIO GRANDE COMPACT COMMISSION REPORT

#### COSTS /1

In February of each year, the Commission shall adopt a budget for the ensuing fiscal year beginning July first.

Such budget shall set forth the total cost of maintenance and operating of gaging stations, of evaporation stations, the cost of engineering and clerical aid, and all other necessary expenses excepting the salaries and personal expenses of the Rio Grande Compact Commissioners.

Contributions made directly by the United States and the cost of services rendered by the United States without cost shall be deducted from the total budget amount; the remainder shall then be allocated equally to Colorado, New Mexico and Texas.

Expenditures made directly by any State for purposes set forth in the budget shall be credited to that State; contributions in cash or in services by any State under a cooperative agreement with any federal agency shall be credited to such State, but the amount of the federal contribution shall not so be credited; in event any State, through contractual relationships, causes work to be done in the interest of the Commission, such State shall be credited with the cost thereof, unless such cost is borne by the United States.

Costs incurred by the Commission under any cooperative agreement between the Commission and any U.S. Government Agency, not borne by the United States, shall be apportioned equally to each State, and each Commissioner shall arrange for the prompt payment of one-third thereof by his State.

The Commissioner of each State shall report at the annual meeting each year the amount of money expended during the year by the State which he represents, as well as the portion thereof contributed by all cooperating federal agencies, and the Commission shall arrange for such proper reimbursement in cash or credits between States as may be necessary to equalize the contributions made by each State in the equipment, maintenance and operation of all gaging stations authorized by the Commission and established under the terms of the Compact.

It shall be the duty of each Commissioner to endeavor to secure from the Legislature of his State an appropriation of sufficient funds with which to meet the obligations of his State, as provided by the Compact.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

0014

24

#### RULES AND REGULATIONS

MEETING OF COMMISSION /1, /8

0.0147

The Commission shall meet in Santa Fe, New Mexico, on the third Thursday of February of each year for the consideration and adoption of the annual report for the calendar year preceding, and for the transaction of any other business consistent with its authority; provided that the Commission may agree to meet elsewhere. Other meetings as may be deemed necessary shall be held at any time and place set by mutual agreement, for the consideration of data collected and for the transaction of any business consis-

No action of the Commission shall be effective until approved by the Commissioner from each of the three signatory States.

(Signed) M. C. HINDERLIDER

M. C. Hinderlider Commissioner for Colorado

(Signed) THOMAS M. McCLURE

Thomas M. McClure Commissioner for New Mexico

(Signed) JULIAN P. HARRISON

Julian P. Harrison Commissioner for Texas

Adopted December 19, 1939.

<u>/l</u> Amended at Eleventh Annual Meeting, February 23, 1950. <u>78</u> Amended at Thirteenth Annual Meeting, February 25, 1952.

#### RIO GRANDE COMPACT COMMISSION REPORT

1. B. William Robert

#### RECORDS OF DELIVERIES AND RELEASES

At the annual meeting of the Compact Commission on March 29, 1979 the records of deliveries and releases for calendar year 1978 were examined and the computations of debits and credits based thereon were reviewed. The records and computations as reviewed by the Commission are reproduced on the next three pages.

The delivery of water in the Rio Grande at the Colorado-New Mexico State line was obtained from record of streamflow near Lobatos, Colorado; the obligation of Colorado to deliver water at the State line was computed as prescribed in Article III. Item C5, the Reduction of Debits prescribed in Article VI, was computed in accordance with the Rules and Regulations.

The delivery of water by New Mexico to Project Storage was computed from the actual streamflow record and the record of operation of Elephant Butte Reservoir; the scheduled delivery was computed as prescribed in the Resolution of the Commission adopted at the Tenth Annual Meeting, and published in this report. Item NM5, Reduction of Credits by Evaporation, was computed in accordance with the Rules and Regulations. Item NM6, Reduction of Credits on account of relinguishment, is in accordance with Article VII. The creation of a minimum recreation pool in Elephant Butte Reservoir was initiated in December 1975 and is in accordance with a resolution

The actual release from Project Storage during the year was measured at stations below Caballo Dam. The Accrued Department from Normal Release is an under-release but is omitted in accordance with a decision of the Commission at the meeting on February 15, 1968.

# RIO GRANDE COMPACT DELIVERIES DY COLORADO AT STATE LINE

### YEAN \_ 1978\_

# Quantities in Thousands of Acre Feet to Nearest Hundred

1		ł	ר ייייראניב ה	VIOL	12	2	4	4.4	0	1:	4	3	3	8.0	1.1				2	<u>ار ۲</u>	5	1		Т		<u></u>		
			SO1	18 1054 1054			$\overline{1}$	4	4		-	4	<u>م</u>	3 9	12	=				164	174					705	879.5	695.0
			OVVIDE-		ľ			-6	11.			~  -	25.	32	25.1	1.1				15.0	10.0	174.5			ð	H H	봅	Å
			-3088/00	5571 SS71 VIO	2			7.6	8.7	11 7		2	6.8	8.0	13.8	5.6	3.6	14.6		13.4	8.3	05.1		104	Į			<u>3</u> 45
8		5. V	/ FOS 28/0CF FOR 12/02 FOR 21/0F	CON At A Nean	8			1.8	2.7	01			2	E.4	1.3	2.1	~	1 7		•		4						
	╡		ער	101	6		╞		4					2	1	5	4	4			-	5	orr;	05 PGL		74.3	99.7	
		SUPPLY	HTU HTU HTU	76C	_	$\left  \right $	╀	- - -	1 14	8 24	31 46			1297.	5 339.	353.	364.	387	397		406		ND CAEL		+	$\left  \right $		╞
			Å]##	nn Sai	•		1	-1 -+-	~	°.	23.	7			73	13.5	11.2	23.0	8.6		2	406.1	DEBITS A					
PPLY			T Tutamiteut	70 70	-			9	0	0	0	0			0	0	0	0	o	4	, ,	Ĵ	5 2				r Feet	
DEX SU			SIN QUELSON LINE V	44 10	2	.								:	-	+	-				   ,		SUMMA	ľ		Ningr India	0 000 Acr	5
ANDE N			SHOISY2A	10				╞	+	-			<u>ں</u> م م		+	+	-	-+	-		-	¥ 		ITE-M	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Concos No Or	tios plus li	Evenue
JO GP			-394 YOU	s	-	1	- <i>-</i>	╪	+	-	-	-	ہ م		+	=+=	-	-	_	<b></b>			ļ		aginning o	livery from	ry at lobe	Lebits %
~			-30MAK	11 : 2	¥			≥  '  -	•	•	•	0	•	Ľ	∍	•	0	•	0	0	c				lonce of D	hedriked De	ual Delive	ZINCTION OF
			10 1110 10 111 01- 10 111 01-	N V ≤ S	3	1.5	5		3	1.5	1.5	1.5	1.5	-		1.5	1.5	1.5	1.5	1.5				ł	ෂ් ටි -  \			
		-3190 6101	ובינור מבר זוכ הבכסורמבט		,		7.3		:	9 <b>.</b> 8	2.3	7.6	3.6	3 5		2		0.	8	6.6	, 6 -	ļ		<u>'</u> '			်ငြ မ	1
			וסנער דרימשונענייני				4		2	<u>.</u>	<u></u>	8	·1 1.	- 			-  -	2	5	6	Ę.				BELODEL	F	JUBIBO	
	X laans	$\vdash$	HINON	+-			- 4	2		-	4	9 108	3 212	8 232	1 1		-  -	543	246	248				- - -	Commit	-		
-		-	11 11 11 10 5	8			ہ۔ 	2		<u>' </u>	24.	75.	103.	20.1			•	E C	2.8	2.4	248.9			t to	ompact	, el eur		
			LINGIMESIN COV 1971	n			٩		-		•	•	*  +			-		-	-	0				DUEALAN	the C	1978 er		
~	SUNI	SJ	NARIO NARIO	•		T	-	ő	0	,   ,	-	•	-							•	÷	-p		nade	etwen	urine	)	
TAUS	TSDLCA	 	-104/4015 II			+		1			+		+ ∞	+	+	<del>., +</del>		<u>+</u> 	╂	╀	+	nclude	•	ir waa	ence b	dita d		
		ĺ	CHANGE			-	_		+		1-	- -	+	0	ہ 	0	- C		/ ·		+	not	ompact	• BBČTVO	brond 22,00	ad cre		
			104/JOF2 10 QU 1 TA	•	ه ا ا	8	12.8	12.7	12.8	1 a		12.0	13.6	13.6	13.6	13.6	13.6	13.6		0		rvoire	pre-c	COLUMN COLUMN	3 COLTS	BOCFUE		
5			TOTAL	_			2.4	2.3	3.8	24.4	0 92	2 1	4-1-	20.7	4.9	2.6	3.0	2.8	<b>a</b> , ,	; ;	9-7-	1 Tese	e-feet t Toto	fn Plai	d Nov.	ent of	faet,	
Į			211NO 11		İ	1		-+					]_	_ -	_		1		-	╞	27		(43 acr	-feet	lution 15. an	quiahm	BCTG	
Silkra			211NO	$\left  \cdot \right $	<u> </u> 				+				-		•	9	_			-			tinus 2	0 acre	o rego Nov.	relin	nnn * 7 c	
									1	8.2	27.0	19.4		2.6	1.0	9	8						feet n n loas	of 80	. 8°	repun		
		5	CONEJO AT MOGOTI	~		7 6		2.3	3.8	13.1	42.7	82.5		10.1	3,9	2	2.1	2.8	2.4	;	Stor	nated.	acre-	torage	ited M	Crage		
	1.10			_	1	AN	e	1	<u>_</u>	-		-	╞━			<del> </del>		_		Ļ	T SAM	Est la	1017 Evapo	E: St	5 P	S i	1	

7 0.000

28

RIO GRANDE COMPACT

4

# DELIVERIES BY NEW MEXICO AT ELEPHANT BUTTE

## YEAR 1978

Quonities in Thousonds of Acre Feel to Neurest Mundred

				1000			>			Total Matte	ELEK	HANT BU	TTE EFFEC	CTIVE SUF	PLY
			>												
MONTH	Recorded			\$D1U\$	TMENTS			INDEX	SUPPLY	New Mexico	ELEPHAN	T BUTTE	Recorded Flow Below	EFFECTIV	SUPPLY
	ţ	RESERVC	<b>WRS: LOBATOS</b>	10 010W1						San Marcial		Change	Eteptant		
	Otowi	Storage- End of	Change in	Reservoir	Other	Trans- mountain	Net	During	Accumulated	at End of Month	End of Month	Gain (+) 1. ass (-)	Butte Dam	During	Accumulated Total
	26010	Month	Storage	Evaporation	n Adjustments	Diversions	Adjustment	Month	1 01 01				V.	2	9
-	2	ń	4	'n	6	2	B	6	õ	=	21	0	ł	2	?
		۲ ۲			     		1			3.6	129.0				
JAN	27 4		+			+ 0.1	+ 1.2	28.6	28.6	4.7	163.2	+ 34.2	0.5	34.7	34.7
FEB	T 70	40		0		+	+ 1.2	28,9	57.5	6.0	193.0	+ 29.8	2.4	32.2	66.9
MAR	41.2	21.2	+ 17.2				+ 17.1	58,3	115.8	24.0	179.4	- 13.6	41.7	28,1	95.0
APR	6 63	202	4 38 4	+ -		- 2.4	+ 36.3	88.5	204.3	62.7	146.4	- 33.0	39.5	6.5	101.5
MAY	176.0	- 10	+ 38.1	, y		+	+ 38.9	212.9	417.2	100.8	232.9	+ 86.5	6*6	96.4	197.9
NUL	11400	50.1				- 1-1	- 37.7	106.3	523.5	62.5	213.0	- 19.9	91.2	71.3	269.2
٦ ۲	1.89	43.1	- 17.0	+	     	- 9.7	- 26.5	41.8	565.3	44.9	137.5	- 75,5	92.5	17.0	286.2
AUG	0 07	15.8	- 27.3	-		- 4.B	- 32.2	17.7	583.0	17.3	48.5	- 89.0	92.1	3.1	289.3
SEPT			- 14.7	6		- 4.1	- 18,8	13.1	596,1	2.J	45,8	- 2.7	4.3	1.6	290.9
ост	27.1	1.2	- +	• •		-	0	27.1	623.2	2.0	48.6	+ 2.8	4.	3.2	294.1
ş	40.8	1.1	-	- - +		- 1	0	40.8	664°0	2.6	90.4	+ 41.8	.6	42.4	336.5
DEC	41.3	1.2	+	+ .3		- 6.7	- 6.3	35.0	0*669	2.0	130.8	+ 40.4		41.1	377.6
YEAR	725.8		ور •	+ 2.6	יז +	- 28.9	- 26.8	0.693				+ 1.8	375.8	377.6	
REMA	RKS: Store	ge in recre	ational res	servoirs not	t included.						SUMMARY O	F DEBITS AN	4D CREDITS		
Colur Colur	m 3 include m 12Stora	ss only Rio ge in recre	Grande wate ational poc	er in El Va ol not inclu	do and Abiqu uded.	ilu Reservol	.e.			11	N3		DEBIT	CREDIT	BALANCE
-		teden lass 6		found Tasa	and the				NM   Bolenc	e al Beginning a	if Year		1		1± 32.0
Anter	ual evapora Storace 1	n El Vado.	McClure, at	ad Nichols	reservoirs u	nder relinq	uishment of	accrued	NM 2 SChed	uled Delivery of E	Isphant Butte		405.4		0r 373.4
	credits a	iggregated 5	18,600 acre-	-feet; bala	nce remainin	g is zero.			NM 3 Actual	Elephont Butte	Effective Supply			0.1/2	X 4.2
									NM S Reduc	tion of Credits	a/c Evaporation		4.		3.8 3.8
									NM 6 ACCF	ued credit i	el inquished	to	32.0		<u>)r 28.2</u>
									NM B Bolon	ca of End of Ye					DE 28.2

TO GRANDE COMPACT COMMISSION REPORT

S. 15 (1996)

0.00151

NELEASE AND SPILL FNOM PROJECT STORAGE NIO GNANDE COMPACT

ł

ł

1978\_ 1978\_

ACCUMULATED USABLE NELEASE TOTAL 36.2 71.7 80.5 ۲, 156.9 325.4 ŋ φ 0 237.9 356.3 356.4 356.5 356.6 DALANCE 1 NUNING MONTH 35.5 81.0 87.5 -8.8 0 36.1 76.4 30.9 ŝ 356.6 CREDIT USABLE <u>-</u> 0 0 o 0 Ò 0 0 o 0 0 0 SPILL FROM STONAGE 0 0 ACCRUED DEFANTURE TROM NORMAL RELEASE GNANDE DELON CADALLO DAM 356.6 DEDIT CINEDIT VATER TIME OF SYPOTRETICAL SPILL £ ¢ 0 ò 0 0 0 0 0 0 o 0 0 o CABALLO FLOOD WATEA ₽ 0 ð 0 ç 0 0 0 0 0 0 0 0 0 kterael Okporture at Dazioning ef Year Actuel Nekaze during Year Normol Nekaze for Year Retuel Evoporation from Ekepbant Dafte Neeervoir Evoporation Loss if No Accurael Opperfure TOTAL NELEASE AUD SPILL 35.5 7 36.1 2 26.4 <u>81</u>,0 87.5 0 8.8 30,9 --356.6 2 DIVENSIONS TO CANALS NTE NVENDO ¢ ITEN Year ₽ o 0 0 7 0 4 c 0 0 Accrued Deporture of End of PLOV AT CADALLO MEISUNED GAGING 35.4 8.8 ≌ -36,1 76.4 87.4 ۰ 80.9 30,8 7 -1 356.2 Ownitities in Thousands of Acre feet to Nagresi Hundred STONAGE AT END OF MONTH 177.5 PROJECT 182.7 205,9 263.1 146.2 216.2 254.0 182.6 91,5 TOTAL WATEN 61.8 66.4 117.8 172.7 a = 8 FLOOD WATEN IN STONAGE IN CABALLO CABALLO NESERVOIA AT EUD OF MONTH k 0 0 o Q o ¢ 0 0 0 o include any of the 100,000 acce-feet of Caballo Reservoir capacity which the Regional Directory U.S. Bureau of Reclamation by letter of Feb. 12, 1960 stated is to October 1. yeer. Ċ 0 0 0 Texas accepted accrued credits relinquished by New Maxico effective March 1, 1978. The quantities of Project Storage and the unfilled portion of such storage do not Usable water in project storage was less than 400,000 acre-feet for entire WATER IN STORAGE AT END OF TOTAL MONTH 32.0 32.0 n 0 Q 0 0 0 0 0 0 0 0 Q NEW MEXICO CAEDIT VATER 32.0 32.0 0 B ol 0 Ó 0 0 0 0 0 0 0 COLORADO CNEDIT WATER **CNEDIT** Q 0 0 0 0 0 0 0 0 ¢ Q o in recreational pool. PLOJECT STORAGE AT END OF MONTH 2,269.2 UNFILLED Capacity 2,307,2 2,302.7 2,275,9 2.170.8 2.247.5 2,190.3 2.099.4 2.261.9 2,291,6 2,387.0 2,335.6 2,280.7 5 146,2 VATE'N IN STONAGE 150.7 205.9 177.5 61.8 66.4 184.2 117.8 263.1 AT HID OF 254.0 182.6 91.5 172.7 HIDON **IOTAL** See minutes of meeting Fab. 15, 1968. transmountain water CABALLO 19.5 17,2 23.2 31,1 26.5 30.2 41.0 <u>16,0</u> 27.4 45.1 43.0 17.8 <u>41,9</u> **BUTTE** NESENVOIN USAble 129.0 161.0 \_146.4 131.2 179.4 CLEPHANT 232.9 213.0 48.5 45.8 90.4 137.5 48.6 130.8 <u>اه</u> TOTAL PROJECT STONAGE CAPACITY AVAILABLE AT END OF MONTH Exclusive of 2,453.4 2.453.4 2,453.4 2,453,4 2.453.4 2,453,4 2.353.4 2,353.4 2,353.4 2,353,4 2,453.4 2,453.4 2.453.4 **NEMANKS:** NOATH Note: MAN Ngr ŧ, Ę YEAR MAY NOC 55.71 Ę âug ŝ ð ц 8 A U ÷

RECORDS OF DELIVERIES AND RELEASES

29

r jar r jar eta ena

. . . ; 

#### RIO GRANDE COMPACT COMMISSION REPORT

#### COST OF OPERATION, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1978 Adopted at the Fortieth Annual Meeting

#### Borne by Borne by Total cost Item United States New Mexico Texas Colorado GAGING STATIONS In Colorado In New Mexico, above 8,020 8,020 16,040 7,450 13,610 Caballo Reservoir In New Mexico, Caballo Reservoir and below 21,060 570 8,020 570 9,160 8,020 8,020 8,020 22,200 46,260 Subtotal 2,610 ADMINISTRATION U.S.G.S. Contract Other expense 2,610 2,610 10,440 930 2,610 310 310 310 2,920 2,920 2,920 2,610 11,370 Subtotal 10,940 10,940 10,940 57,630 24,810 GRAND TOTAL 10,940 10,940 10,940 EQUAL SHARES OF STATES 0 0 0 CASH ADJUSTMENT BETWEEN STATES

#### BUDGET, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1980

#### Adopted at the Fortieth Annual Meeting

		Total cost	Borne by		Borne by	
I Cem			United States	Colorado	New Mexico	Texas
GAGING STATIONS In Colorado In New Mexico, above Caballo Reservoir In New Mexico, Cabal Reservoir and bel	S STATIONS Colorado New Mexico, above Caballo Reservoir New Mexico, Caballo Reservoir and below Subtotal ISTRATION S.G.S. Contract her expense Subtotal		9,000 14,600 600	9,000	8,400 600	9,000
	Subtotal	51,200	24,200	9,000	9,000	9,000
ADMINISTRATION U.S.G.S. Contract		11,760 1,800	2,940	2,940 600	2,940 600	2,940 600
Other Skrones	Subtotal	13,560	2,940	3,540	3,540	3,540
	00000000	64.760	27,140	12,540	12,540	12,540
GRAND TOTAL				12,540	12,540	12,540
EQUAL SHARES OF STATES CASH ADJUSTMENT BETWEE	N STATES			0	0	Q

#### ACKNOWLEDGMENTS

The water-supply\_data contained in this report have been furnished by various Federal and State Agencies.

10

The office of the State Engineer of Colorado furnished records of discharge on the following:

> Rio Grande near Del Norte, Colo. Conejos River below Platoro Reservoir, Colo. Conejos River near Mogote, Colo. San Antonio River at Ortiz, Colo. Los Pinos River near Ortiz, Colo. Conejos River near Lasauses, Colo. Rio Grande near Lobatos, Colo.

Records of 6 transmountain diversions and of storage in Squaw and Shaw Lakes, Rito Hondo, Hermit Lakes Reservoir No. 3, Troutvale No. 2, Jumper Creek, Alberta Park, Big Meadows, Mill Creek, Fuchs, and Trujillo Meadows Reservoirs were also furnished by the office of the State Engineer of Colorado.

The U.S. Bureau of Reclamation, Albuquerque, N. Mex. furnished the following records:

> Storage in Platoro Reservoir at Platoro, Colo. Azotea tunnel at outlet, near Chama, N. Mex. Willow Creek above Heron Res., near Park View, N. Mex. Horse Lake Creek above Heron Res., near Park View, N. Mex. Storage in Heron Reservoir near Park View, N. Mex. Willow Creek below Heron Dam, N. Mex. Storage in El Vado Reservoir near Tierra Amarilla, N. Mex. Storage in Nambe Falls Reservoir near Nambe, N. Mex. Rio Nambe at Nambe Falls, near Nambe, N. Mex.

The U.S. Geological Survey supplied the record for Rio Grande below Elephant Butte Dam, and in cooperation with the New Mexico Interstate Stream Commission, also furnished the following:

Rio Chama below El Vado Dam, N. Mex. Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex. Storage in McClure Reservoir near Santa Fe, N. Mex. Santa Fe River near Santa Fe, N. Mex. Storage in Nichols Reservoir near Santa Fe, N. Mex.

The Corps of Engineers, Albuquerque, N. Mex. furnished the record of storage in Abiquiu Reservoir, Galisteo Reservoir, Cochiti Lake, and Jemez Canyon Reservoir and, in cooperation with the U.S. Geological Survey, also furnished the record for Rio Chama below Abiquiu Dam, Rio Grande below Cochiti Dam, Galisteo Creek below Galisteo Dam, and Jemez River below Jemez Canyon Dam, N. Mex.

The United Pueblos Agency, Albuquerque, N. Mex. supplied the records of storage in Acomita Reservoir near San Fidel, N. Mex.

The U.S. Bureau of Reclamation, El Paso, Texas furnished the

following records:

Storage in Elephant Butte Reservoir at Elephant Butte, Storage in Caballo Reservoir near Arrey, N. Mex. Rio Grande below Caballo Dam, N. Mex. Bonito ditch below Caballo Dam, N. Mex.

The Rio Grande Compact Commission gratefully acknowledges the cooperation received from these agencies.

31

Server Tarte Little Course Britishing - The State

The State of the second state of the State of the second second second second second second second second second

#### RIO GRANDE COMPACT COMMISSION REPORT

الماجه بأله والتحالم المراكنات المحاط للمالية المراكز أرجا

#### ACCURACY OF RECORDS

The Rules and Regulations of the Commission state that the equipment, method, and frequency of measurement at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Within the physical limitations of stream gaging, the agencies obtaining the records at Compact gaging stations have compiled with these regulations.

The accuracy of discharge data depends primarily on (1) the stability of the stage-discharge relation, or if the control is unstable, the frequency of discharge measurements, and (2) the accuracy of observations of stage, measurements of discharge, and interpretation of records.

The station description states the degree of accuracy of the daily records. "Excellent" means that about 95 percent of the daily discharges are considered to be within 5 percent of true value; "good" within 10 percent; and "fair" within 15 percent. "Poor" means that daily discharges have less than "fair" accuracy.

The phrase "within 5% of true value" used to qualify "excellent" records establishes the extremes of the probable errors for 95% of the days in a given period of time. The word "within" defines the range of errors with individual daily values falling between 95% and 105% of true value. The probable error in a monthly or annual mean discharge depends more on the distribution of the daily errors between these two limits than it does on the limits themselves. For this reason monthly and annual records are much more accurate than most daily records.

#### STREAMFLOW

Rio Grande near Del Norte, Colo.

Location.--Water-stage recorder, lat 37°41'22", long 106°27'38", in NW4 sec. 29, T. 40 N., R. 5 E., on right bank, 20 ft downstream from county highway bridge, 5 miles upstream from Pinos Creek, and 6 miles west of Del Norte. Datum of gage is 7,980.25 ft above mean sea level, datum of 1929. Prior to May 16, 1908, staff gage at site 4 miles downstream. Records are equivalent.

Drainage area.--1,320 sq mi, approximately.

Average discharge.--89 years (1890-1978), 892 ft<sup>3</sup>/s (646,300 acre-ft per year).

Extremes.--1889-1978: Maximum discharge, 18,000 ft<sup>3</sup>/s Oct. 5, 1911 (gage height, 6.80 ft), from rating curve extended above 6,000 ft<sup>3</sup>/s;minimum daily, 69 ft<sup>3</sup>/s Aug. 21, 1902.

Remarks.--Records good except for some winter months, which are fair. Flow regulated by four reservoirs, total capacity 126,100 acre-ft, and by several smaller ones. Six transmountain diversions import water into basin above station.

Monthly	and	yearly	discharge,	in	cubic	feet	Der	Second
			the second se				Lor	2000110

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October November December	3,690 3,600 4,961 11,230 39,113 87,520 21,407 6,808 5,669 11,571 4,929 4,490	135 170 208 681 2,210 4,030 1,600 368 223 770 268	85 105 118 185 462 1,740 315 149 158 160 128	119 129 160 374 1,262 2,917 691 220 189 373 164	acre-feet 7,320 7,140 9,840 22,270 77,580 173,600 42,460 13,500 11,240 22,950 9,720
Calendar year 1978	204 000		90	145	8,910
		4,030	85	562	406,600

Conejos River below Platoro Reservoir, Colo.

Location.--Water-stage recorder and concrete control, lat 37°21'18", long 106°32'37", in NW4NW4 sec. 22, T. 36 N., R. 4 E., on left bank 1,100 ft downstream from valve house for Platoro Reservoir, and 0.7 mile northwest of Platoro. Datum of gage is 9,866.60 ft above mean sea level (levels by Bureau of Reclamation).

Drainage area. -- 40 sq mi, approximately.

Average discharge.--26 years (1953-78), 86.6 ft<sup>3</sup>/s (62,740 acre-ft per year).

<u>Extremes.--1952-78</u>: Maximum discharge, 1,160 ft<sup>3</sup>/s Nov. 1, 1957; maximum gage height, 4.29 ft June 15, 1958; no flow Oct. 16-20, 1955.

<u>Remarks</u>.--Records good except those for winter months, which are fair. No diversions above station. Flow completely regulated by Platoro Reservoir (capacity, 60,000 acre-ft).

Monthly a	and	yearly	discharge,	in	cubic	feet	Der	Second

Month						
	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in	
January Feburary March April May June July August September October November December Calendar year 1070	310 271 260 1,580 6,305 16,580 3,527 455.7 226.6 101.15 176.0 184.5	10 10 11 139 510 700 294 36 40 20 7.2 6.0	10 8.0 5.0 11 37 248 32 3.0 2.4 .40 5.8 5.9	10 9.68 8.39 52.7 203 553 114 14.7 7.55 3.26 5.87 5.95	acre-feet 615 538 516 3,130 12,510 32,890 7,000 904 449 201 349 366	
Jeat 19/8	29,976.95	700	.40	82.1	59,460	

33

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Conejos River near Mogote, Colo.

Location.--Water-stage recorder, lat 37°03'14", long 106°11'13", in SE%SE% sec. 34, T. 33 N., R. 7 E. on right bank 25 ft upstream from bridge on State Highway 174, 0.4 mile downstream from Fox Creek, and 5.3 miles west of Mogote. Datum of gage is 8,271.54 ft above mean sea level.

#### Drainage area.--282 sq mi.

Average discharge.--68 years (1904, 1912-78), 327 ft<sup>3</sup>/s (236,900 acre-ft per year).

1999 1997 Allowed M. Calend & M. H. Martalaket and M. S. Channeller and Constraints of the second statement of the second second and the second s

Extremes.--1903-05, 1911-78: Maximum discharge, 9,000 ft<sup>3</sup>/s Oct. 5, 1911 (gage height, 8.50 ft, from rating curve extended above 3,000 ft<sup>3</sup>/s;minimum daily determined, 10 ft<sup>3</sup>/s July 18, 1904.

Remarks.--Records good except those for winter months, which are fair. Diversions above station for irrigation of about 500 acres. Since 1951 flow partly regulated by Platoro Reservoir.

. .

> > a.

je P

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
Topuary	1.231	48	30	39.7	2,440
February	1,175	47	36	42.0	2,330
reoruary	1,933	139	39	62.4	3,830
March Demil	6.578	404	116	219	13,050
April	21,499	1.410	190	694	42,640
May	41,600	1,950	665	1,387	82,510
June	9,133	760	111	295	18,120
Jury	1,952	116	33	63.0	3,870
August	985	60	26	32.8	1,950
September	1.075	46	25	34.7	2,130
OCEODEL	1 305	60	40	46.5	2,770
December	1,224	50	27	39.5	2,430
Calendar year 1978	89,780	1,950	25	246	178,100

#### Monthly and yearly discharge, in cubic feet per second

#### San Antonio River at Ortiz, Colo.

Location.--Water-stage recorder, lat 36°59'35", long 106°02'17", in New Mexico in NELSEL, sec. 24, T. 32 N., R. 8 E., on left bank 800 ft south of New Mexico-Colorado State line, 0.4 mile southeast of Ortiz, and 0.4 mile upstream from Los Pinos River. Altitude of gage is 7,970 ft.

#### Drainage area.--110 sq mi.

Average discharge.--38 years (1941-78), 24.0 ft<sup>3</sup>/s (17,390 acre-ft per year).

Extremes.--1920, 1925-78: Maximum discharge, 1,750 ft<sup>3</sup>/s Apr. 15, 1937 (gage height, 5.38 ft), from rating curve extended above 1,000 ft<sup>3</sup>/s; no flow at times.

<u>Remarks</u>.--Records good above 10  $ft^3/s$  and fair below. A few small diversions above station for irrigation.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff i acre-feet
January February March April May June July August September October November December	74.4 98.3 356.3 1,567 3,126 263.00 9.23 0 0 33.81 119.8 106.0	3.2 6.3 40 120 245 28 4.0 0 0 4.5 7.2 5.0	1.5 2.7 4.5 23 31 .60 0 0 0 2.8 1.5	2.40 3.51 11.5 52.2 101 8.77 .30 0 0 1.09 3.99 3.42	148 195 707 3,110 6,200 522 18 0 0 67 238 210
Calendar year 1978	5,753.84	245	0	15.8	11,410

Monthly and yearly discharge, in cubic feet per second

STREAMFLOW

#### Los Pinos River near Ortiz, Colo.

Location.--Water-stage recorder, lat 36°58'56", long 106°04'23", in New Mexico on line between secs. 26 and 27, T. 32 N., R. 8 E., on left bank 0.9 mile south of New Mexico-Colorado State line, 2.1 miles southwest of Ortiz, and 2.9 miles upstream from mouth. Altitude of gage is 8,040 ft.

Drainage area.--167 sq mi.

Average discharge.--60 years (1915-20, 1925-78), 118 ft<sup>3</sup>/s (85,490 acre-ft per year).

Extremes.--1915-20, 1925-78: Maximum discharge, 3,160 ft<sup>3</sup>/s May 12, 1941 (gage height, 5.77 ft, site and datum then in use), from rating curve extended above 1,600 ft<sup>3</sup>/s; minimum observed,

Remarks.--Records good except those for winter months, which are fair. Diversions above station for irrigation.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	, 303.5 368 540.9 4,128 13,630 9,766 1,318 506.2 r 308.8 375.1 477.0 423.0	13 19 40 340 820 564 112 25 16 18 29 19	7.0 11 8.9 48 127 131 19 8.9 8.5 9.7 8.0 7.0	9.79 13.1 17.4 138 440 326 42.5 16.3 10.3 12.1 15.9	602 730 1,070 8,190 27,040 19,370 2,610 1,000 613 744 946
Calendar year 1978	32,144.5	820	7.0	88.1	63,760

Monthly and yearly discharge, in cubic feet pe

#### Conejos River near Lasauses, Colo.

Location.--Water-stage recorders lat 37°18'01", long 105°44'47", in secs. 2 and 11 (two channels), T. 35 N., R. 11 E., on left bank of main channel 125 feet downstream from bridge on State Highway 158 and on left bank of secondary channel 230 ft upstream from bridge, 1.0 mile upstream from mouth, and 2.1 miles north of Lasauses. Datum of gage on main channel is 7,495.02 ft and on secondary (south) channel is 7,496.89 ft above mean sea level (levels by Bureau of Reclamation).

Drainage area .-- 887 sq mi.

Average discharge.--57 years (1922-78), 177 ft<sup>3</sup>/s (128,200 acre-ft per year).

Extremes.--1921-78: Maximum discharge, 3,890 ft<sup>3</sup>/s May 15, 1941; no flow at times in some years.

Remarks.--Records good except those for winter months, which are fair. Diversions for irrigation of about 75,000 acres above station.

Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in	
902 1,365 977.8 1,373.03 9,447 12,248 5,710 1,040.9 84.25 171.10 801 852	40 60 59 217 673 733 531 84 5.9 10 39 44	18 37 2.3 .15 48 216 74 3.0 .40 .90 11	29.1 48.8 31.5 45.8 305 408 184 33.9 2.81 5.52 26.7 27 5	1,790 2,710 1,940 2,720 18,740 24,290 11,330 2,080 167 339 1,590	
34,981.08	733	.15	95.8	£9.390	
	Second- foot-days 902 1,365 977.8 1,373.03 9,447 12,248 5,710 1,040.9 84.25 171.10 801 852 34,981.08	Second- foot-daysMaximum daily902401,36560977.8591,373.032179,44767312,2487335,7105311,040.98484.255.9171.1010801398524434,981.08733	Second- foot-days         Maximum daily         Minimum daily           902         40         18           1,365         60         37           977.8         59         2.3           1,373.03         217         .15           9,447         673         48           12,248         733         216           5,710         531         74           1,040.9         84         3.0           84.25         5.9         .40           171.10         10         .90           801         39         11           852         44         14           34,981.08         733         .15	Second- foot-days         Maximum daily         Minimum daily         Mean           902         40         18         29.1           1,365         60         37         48.8           977.8         59         2.3         31.5           1,373.03         217         .15         45.8           9,447         673         48         305           12,248         733         216         408           5,710         531         74         184           1,040.9         84         3.0         33.9           84.25         5.9         .40         2.81           171.10         10         .90         5.52           801         39         11         26.7           852         44         14         27.5           34,981.08         733         .15         95.8	

Monthly and yearly discharge, in cubic feet per second

 $\Gamma$ 00015

35

and all to the men the with the fight

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Rio Grande near Lobatos, Colo.

Location.--Water-stage recorder, lat 37°04'42", long 105°45'22", in sec. 22, T. 33 N., R. 11 E., on right bank just downstream from highway bridge, 6 miles north of Colorado-New Mexico State line, 10 miles east of Lobatos, and 14 miles east of Antonito. Datum of gage is 7,427.63 ft above mean sea level, datum 1929.

Drainage area. -- 7,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley).

Average discharge.--31 years (1900-30), 846 ft<sup>3</sup>/s (598,400 acre-ft per year); 48 years (1931-78) 402 ft<sup>3</sup>/s (291,200 acre-ft per year).

Extremes.--1899-1978: Maximum discharge observed, 13,200 ft<sup>3</sup>/s June 8, 1905, (gage height, 9.1 ft), from rating curve extended above 8,000 ft<sup>3</sup>/s; no flow at times in 1950-51, 1956.

<u>Remarks</u>.--Records good except those for winter months, which are fair. Natural flow of streams affected by transmountain diversions, storage reservoirs, ground-water withdrawals and diversions for irrigation, and return flow from irrigated areas.

	Housel and to the				
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	4,745 5,757 6,835 2,852 12,894 16,293 12,671 3,904 1,895 7,511 7,564 5,030	180 282 294 250 720 784 925 206 95 520 306 210	120 175 108 36 160 290 212 56 44 88 170 70	153 206 220 95.1 416 543 409 126 63.2 242 252 162	9,410 11,420 13,560 5,660 25,580 32,320 25,130 7,740 3,760 14,900 15,000 9,980
Calendar year 1978	87,951	925	36	241	1/4,500

Monthly and yearly discharge, in cubic feet per second

Willow Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°44'33", long 106°37'34", in Tierra Amarilla Grant, on right bank 200 ft downstream from bridge, 0.2 mile downstream from Iron Spring Creek, 3.3 miles west of Los Ojos, and at mile 9.7. Datum of gage is 7,196.29 ft above mean sea level. Prior to Apr. 1, 1971 at site 900 ft downstream.

Average discharge.--7 years (1963-69) 11.5 ft<sup>3</sup>/s (8,330 acre-ft per year) prior to completion of Azotea tunnel; 9 years (1970-78) 112 ft<sup>3</sup>/s (81,140 acre-ft per year) subsequent to completion of Azotea tunnel.

Extremes.--1962-78: Maximum discharge, 1,600 ft<sup>3</sup>/s Aug. 11, 1967 (gage height, 3.88 ft); no flow at times prior to 1971.

Remarks.--Records good except those for winter months, which are fair. Subsequent to Nov. 16, 1970, flow affected by transmountain diversions through Azotea tunnel. Flow in Rutheron Drain included prior to Apr. 1, 1971.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	12.3922.152,729.49,80115,15622,4933,637.852.4439.3332.4528.286.74	0.45 1.6 437 555 905 1,020 424 12 7.6 3.1 6.5 .67	0.29 .49 1.6 192 103 384 2.2 .12 .02 .18 .15 .07	0.40 .79 88.0 327 489 750 117 1.69 1.31 1.04 .94 .22	25 44 5,410 19,440 30,060 44,610 7,220 104 78 64 56 13
Calendar year 1978	54,010.98	1,020	.02	148	107,100

cubic feet per second

5 8

36

The section of the se

STREAMFLOW

Horse Lake Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°42'24", long 106°44'42", in Tierra Amarilla Grant, on right bank 3.7 miles northwest of Heron Dam, 7.8 miles downstream from Horse Lake, and 9.9 miles west of Los Ojos. Datum of gage is 7,188.85 ft above mean sea level. Prior to July 1, 1971 at site 1,100 ft upstream.

Drainage area.--45 sq mi, approximately.

Average discharge.--11 years (1963-73) 1.10 ft<sup>3</sup>/s (797 acre-ft per year).

Extremes.--1963-78: Maximum discharge, 3,960 ft<sup>3</sup>/s July 30, 1968 (gage height, 4.9 ft); no flow most

Remarks.--Records good. Diversions above station for irrigation of meadows and for off-channel stock tanks.

zeec per second						
Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in		
- 34.67 39.92 0 0 0 0 0 0	- - 15 19 0 0 0 0 0 0 0		- - 1.16 1.29 0 0 0 0 0	69 79 0 0 0 0 0		
			<del>-</del>			
	Second- foot-days - - - - - - - - - - 0 0 0 0 0 0 0 - -	Second- foot-days         Maximum daily           -         -	Second- foot-days         Maximum daily         Minimum daily           -         -         -	Second- foot-days         Maximum daily         Minimum daily         Mean daily           - <t< td=""></t<>		

Monthly and yearly discharge, in cubic feet per second

#### Willow Creek below Heron Dam, N. Mex.

Location.--Totalizing flowmeters, lat 36°39'56", long 106°42'12", in Tierra Amarilla Grant, in outlet conduits at Heron Dam, 0.2 mile upstream from Rio Chama, 5.1 miles northeast of El Vado Dam, and 8.7 miles southwest of Los Ojos.

Drainage area.--193 sq mi.

Average discharge.--5 years (1971-78) 86.0 ft<sup>3</sup>/s (2,310 acre-ft per year).

Extremes.--1971-78: Maximum daily discharge, 2,220 ft<sup>3</sup>/s Dec. 12, 1973; no flow at times.

Remarks. -- Records excellent. Flow completely regulated by Heron Dam.

#### Monthly and yearly discharge, in cubic feet per second

Month						
	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in	
January February March April May June July August September October November December	0 4,013 2,491.4 598.3 8,631 181.5 191.7 1,393.9 40.3 150 18,260	0 0 510 422 99 863 21 34 409 8.0 48 1,100		0 0 129 83.0 19.3 288 5.85 6.18 46.5 1.30 5.00	0 7,960 4,940 1,190 17,120 360 380 2,760 80 298	
Calendar year 1978	35,951.1	1,100	0	98.5	71,310	

38

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Rio Chama below El Vado Dam, N. Mex.

Location.--Water-stage recorder, lat 36°34'48", long 106°43'24", in Tierra Amarilla Grant, 1.5 miles downstream from El Vado Dam, 2.8 miles upstream from Rio Nutrias, and 13 miles southwest of Tierra Amarilla, Rio Arriba County. Datum of gage is 6,696.12 ft above mean sea level, datum of 1929. Prior to October 1935, at site 1.5 miles upstream and October 1935 to September 1938, at site 1.1 miles upstream at different datum.

Drainage area.--877 sq mi.

Average discharge.--4 years (1914, 1921-23), 444 ft<sup>3</sup>/s prior to completion of El Vado Dam; 35 years (1936-70), 372 ft<sup>3</sup>/s (269,500 acre-ft per year) subsequent to completion of El Vado Dam; but 8 years (1971-78) 343 ft<sup>3</sup>/s (248,500 acre-ft per year) subsequent to completion of Heron Dam and Azotea tunnel.

Extremes.--1914-16, 1920-24, 1936-78: Maximum discharge observed, 9,000 ft<sup>3</sup>/s May 22, 1920 (gage height, 12 ft); no flow Mar. 25, 26, 31, 1955.

<u>Remarks</u>.--Records good. Diversions above station for irrigation of about 8,000 acres. Since 1935 flow regulated by El Vado Reservoir and since October 1970 flow partly regulated by Heron Reservoir. Subsequent to May 1971 flow affected by releases of transmountain water from Heron Reservoir.

Monthly and	yearly	discharge,	in cubic	: feet	per	second
-------------	--------	------------	----------	--------	-----	--------

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January	740	25	23	23.9	1,470
February	700	25	25	25.0	1,390
March	1,060	122	26	34.2	2,100
April	7,712	1,510	26	257	15,300
May	54,834	3,340	472	1,769	108,800
June	27,762	1,680	193	925	55,070
July	10,483	1,060	35	338	20,790
August	14,433	1,030	20	466	28,630
September	9,724	1,020	15	324	19,290
October	1,139	95	19	36.7	2,260
November	2,285	127	49	76.2	4,530
December	5,183	604	30	167	10,280
Calendar year 1978	136,055	3,340	15	373	269,900

Rio Chama below Abiquiu Dam, N. Mex.

Location.--Water-stage recorder, lat 36°14'12", long 106°24'59", in SELSEL sec. 8, T. 23 N., R. 5 E., on right bank 0.8 mile downstream from Abiquiu Dam and 5.9 miles northwest of Abiquiu. Altitude of gage is 6,040 ft (from river-profile map and topographic map).

Drainage area.--2,147 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.--17 years (1962-78), 382 ft<sup>3</sup>/s (276,800 acre-feet per year).

Extremes.--1961-78: Maximum discharge, 2,990 ft $^3$ /s July 1, 1965 (gage height, 6.69 ft); minimum about 0.5 ft $^3$ /s Mar. 17, 1966.

<u>Remarks.--Records good except those for winter months, which are fair. Flow regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 17,000 acres.</u> Subsequent to May 1971 flow affected by the release of transmountain water.

nonenty and fearly aroundly in sable feet beed	Monthly	and	vearly	discharge,	in	cubic	feet	per	secon
--	---------	-----	--------	------------	----	-------	------	-----	-------

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January	1,108	67	19	35.7	2,200
February	1,064	61	25	38.0	2,110
March	3,985	317	21	129	7,900
April	11,089	1,410	120	370	22,000
Mav	43,057	1,650	458	1,389	85,400
June	42,299	1,620	637	1,410	83,900
July	15,757	1,010	77	508	31,250
August	15,975	1,270	22	515	31,690
September	10,062	1,020	36	335	19,960
October	1.393	110	18	44.9	2,760
November	2,917	155	47	97.2	5,790
December	5,808	515	50	187	11,520
Calendar year 1978	154,514	1,650	18	423	306,500

.

#### STREAMFLOW

#### Rio Nambe at Nambe Falls, near Nambe, N. Mex.

Location.--Water-stage recorder, lat 35°50'46", long 105°54'29", in NW4SW4 sec. 29, T.19 N., R.10 E., in Nambe Indian Reservation, on left bank 800 feet downstream from Nambe Falls, 2.4 miles upstream from confluence of Rio Nambe and Rio En Medio, 4.2 miles southeast of Nambe Pueblo, and 5.2 miles

#### Drainage area.--25.1 sq mi.

Average discharge.--15 years (1964-78) 10.1 ft<sup>3</sup>/s (7,320 acre-ft per year).

Extremes.--Maximum discharge 1,090 ft<sup>3</sup>/s Aug. 9, 1967 (gage height, about 6.0 feet, from floodmarks), from rating extended above 44 ft<sup>3</sup>/s on bases of field estimate of peak flow; minimum daily 0.30 ft<sup>3</sup>/s Aug. 21, 22, 1977 and Nov. 6, 1978.

Remarks.--Records good except those for winter months, which are fair. Flow completely regulated by Nambe Falls Reservoir since Feb. 22, 1976.

		rocuarde, m ct	Dic feet per se	cond	
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October November December	41.3 36.4 42.2 409.8 520 808 648.7 411.8 199.9 166.7 30.1 37.2	1.5 1.3 1.5 24 24 41 26 24 8.6 5.6 5.3 1.2	1.2 1.3 1.3 12 17 5.9 6.5 5.3 5.0 .30 1.2	1.33 1.30 1.36 13.7 16.8 26.9 20.9 13.3 6.66 5.38 1.00 1.20	82 72 84 813 1,030 1,600 1,290 817 396 331 60 74
Calendar year 1978	3,352.1	41	. 30	9.18	6,650

Monthly and yearly discharge, in

#### Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.

Location.--Water-stage recorder, lat 35°52'29", long 106°08'30", in San Ildefonso Pueblo Grant, 400 ft downstream from bridge on State Highway 4, 1.8 miles southwest of San Ildefonso Pueblo, 2.5 miles downstream from Pojoaque River, and 6.8 miles west of Pojoaque. Datum of gage is 5,488.48 ft above mean sea level, datum of 1929. Prior to May 19, 1904, and July 25 to Oct. 1, 1904, staff gage at site 180 ft upstream at datum 2.02 ft lower.

Drainage area.--14,300 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--79 years (1896-1905, 1910-78) 1,483 ft<sup>3</sup>/s (1,074,000 acre-ft per year).

Extremes.--1895-1905, 1910-78: Maximum discharge, 24,400 ft<sup>3</sup>/s May 23, 1920 (gage height, 14.1 ft); minimum daily, 60 ft<sup>3</sup>/s July 4, 5, 1902.

Remarks.--Records good. Flow partly regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 600,000 acres in Colorado and 75,000 acres In New Mexico. Subsequent to May 1971 flow affected by releases of transmountain water from Reservoir.

	tece per second					
Month	Second- foot-days	Maximum đaily	Minimum daily	Mean	Runoff in	
January Pebruary March April May June July August September October November December	13,806 13,986 20,794 26,306 87,740 72,580 34,417 25,143 16,074 13,659 20,593 20,817	491 561 952 2,230 3,780 3,210 1,740 1,930 1,230 797 1,040 1,080	388 462 511 552 1,380 1,630 570 263 248 258 576 300	445 500 671 877 2,830 2,419 1,110 811 536 441 686 672	27,380 27,740 41,240 52,180 174,000 144,000 68,270 49,870 31,880 27,090 40,850 41,290	
Calendar year 1978	365,915	3,780	248	1,003	725,800	

Monthly and yearly discharge, in cubic feet per second

40

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Santa Fe River near Santa Fe, N. Mex.

Location.--Water-stage recorder and concrete control, lat 35°41'12", long 105°50'35", in NE4SE4 sec. 23, T. 17 N., R. 10 E., 0.4 mile downstream from McClure Dam, and 5.3 miles east of Santa Fe. Datum of gage is 7,718 ft above mean sea level, datum of 1929. Prior to Nov. 4, 1930 at site 1.5 miles downstream, and Apr. 11, 1931 to Sept. 1947 at site 0.3 mile upstream.

#### Drainage area.--18.2 sq mi.

าสถานที่สมพัฒนาและเป็นสายเป็นสายแม่เห็นของและเห็นการและเป็นการและเป็นการและเป็นการและและและและเป็นการและ และกา

Average discharge.--66 years (1913-78), 7.83 ft<sup>3</sup>/s (5,670 acre-ft per year).

Extremes.--1813-78: Maximum discharge, 1,500 ft<sup>3</sup>/s Aug. 14, 1921; minimum daily, 0.1 ft<sup>3</sup>/s Feb. 7-10, 20, 21, 1927, Aug. 1-4, 1951.

Remarks.--Records good. Flow regulated by McClure Reservoir, completed in 1926, raised in 1935 and again in 1947.

Mo	onthly and yearly d	ischarge, in cu	bic feet per se	Mean	Runoff in
Month	Second- foot-days	Maximum daily	daily	Hean	acre-feet
January February March April May June July August September October November December	43.4 39.5 182 207.7 451.4 341.8 262.0 260.0 212.1 133.27 25.38 164.82	1.4 1.5 6.7 7.3 26 21 9.9 8.9 7.7 6.2 1.3 11	1.4 1.4 1.6 6.7 7.3 4.6 6.7 7.9 6.4 .78 .78 .78 .75	$ \begin{array}{r} 1.40\\ 1.41\\ 5.87\\ 6.92\\ 14.6\\ 11.4\\ 8.45\\ 8.39\\ 7.07\\ 4.30\\ .85\\ 5.32\\ \end{array} $	86 78 361 412 895 678 520 516 421 264 421 264 50 327
Calendar year 1978	2,323.37	26	.75	6.37	4,610

#### Rio Grande below Cochiti Dam, N. Mex.

Location.--Water-stage recorder, lat 35°37'05", long 106°19'26", in SW&NE& sec. 17, T. 16 N., R. 6 E., Sandoval County, in Pueblo de Cochiti Grant, on pier near right bank, 1,000 feet downstream from Cochiti Dam, and 1.4 miles northeast of Cochiti Pueblo.

Drainage area.--14,900 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--8 years (1971-78) 952 ft<sup>3</sup>/s (689,700 acre-ft per year).

Extremes.--1971-78: Maximum discharge, 10,300 ft<sup>3</sup>/s July 26, 1971, at site 2.4 miles downstream and prior to closure of Cochiti Dam, minimum discharge, 0.51 ft<sup>3</sup>/s Aug. 3-5, 1977.

Remarks.--Records good. Since Nov. 11, 1973, flow completely regulated by Cochiti Dam. Cochiti eastside main canal on left bank and Sili main canal on right bank bypass station.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	13,869 13,808 17,630 17,782 28,969 66,840 22,819 13,995.7 9,595 7,275 20,156 19,207	630 542 878 2,070 3,470 2,940 1,350 1,320 901 612 1,110 1,170	198 444 280 919 1,480 175 8.7 28 41 513 203	447 493 569 593 2,547 2,228 736 451 320 235 672 620	27,510 27,390 34,970 35,270 156,600 132,600 45,260 27,760 19,030 14,430 39,980 38,100
Calendar year 1978	301,945.7	3,470	8.7	827	598,900

the and yearly discharge, in cubic feet per second

STREAMFLOW

Galisteo Creek below Galisteo Dam, N. Mex.

Location.--Water-stage recorder, lat 35°27'56", long 106°12'57", in SELSEL sec. 5, T. 14 N., R. 7 E., on right bank, 0.6 mile downstream from Galisteo Dam, and 5.5 miles northwest of Cerrillos. Altitude of gage is 5,450 ft.

Drainage area.--597 sq mi.

000163

Average discharge.--8 years (1971-78) 6.87 ft<sup>3</sup>/s (4,980 acre-ft per year).

Extremes.--1970-78: Maximum discharge, 2,000 ft<sup>3</sup>/s July 27, 1971 (gage height, 7.00 ft); maximum gage height, 7.33 ft July 20, 1971; no flow many days.

<u>Remarks.</u>--Records poor. Flow partly regulated by uncontrolled outlet in Galisteo Dam. Capacity of outlet, 5,000 ft<sup>3</sup>/s when reservoir is full. Diversions for irrigation of about 50 acres above reservoir.

January February March April	Second- foot-days 30.67 17.60	Maximum daily 2.1	Minimum daily	Mean	Runoff in acre-feet
February March April	30.67 17.60	2.1			acre-feet
May June July August September October November December	15.62 1.37 17.47 60 4.00 341.75 30 5.35 68.61 20.78	1.5 3.6 .36 6.0 60 4.0 120 20 1.0 42 1.0		0.99 .63 .54 .05 .56 2.00 .13 11 1.00 .17 2.29	61 35 33 2.7 35 119 7.9 678 60 11 136
Calendar year 1978	614.22	120		.67	41

Monthly and yearly discharge, in cubic for

Jemez River below Jemez Canyon Dam, N. Mex.

Location.--Water-stage recorder, lat 35°23'24", long 106°32'03", in NE4 sec. 5, T. 13 N., R. 4 E., on right bank 0.8 mile downstream from Jemez Canyon Dam, 1.5 miles upstream from mouth, and 6 miles north of Bernalillo. Datum of gage is 5,095.60 ft above mean sea level, datum of 1929. Prior to April 24, 1951, at site three-quarters of a mile upstream at datum 24.51 ft higher. April 24, 1951 to June 25, 1958, at site 37 ft upstream at datum 4.40 ft higher.

Average discharge.--36 years (1937, 1944-78), 53.1 ft<sup>3</sup>/s (38,470 acre-ft per year).

Extremes.--1937, 1944-78: Maximum discharge, 16,300 ft<sup>3</sup>/s Aug. 29, 1943 (gage height, 5.62 ft); no flow at times.

Remarks.--Records poor. Flow regulated by Jemez Canyon Dam since October 1953. Diversions for irrigation of about 3,000 acres above station.

N						
	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in	
Calendar vear 1979	664.0 696.3 2,251 6,163 5,639 1,561.0 265.0 361.0 0 12.7 1,399.02 415.2	41 51 259 510 282 307 240 193 0 4.6 126 93	8.0 5.9 30 133 84 0 0 0 0 0 0 0 52 1.0	21.4 24.9 72.6 205 182 52.0 8.55 11.6 0 .41 46.6 13.4	acre-feet 1,320 1,380 4,460 12,220 11,180 3,100 526 716 0 25 2,770 824	
	19,427.22	510	0	53.2	38,530	

Monthly and yearly discharge, in cubic feet

1.1

and the second with the second se

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Rio Grande below Elephant Butte Dam, N. Mex.

Location.--Water-stage recorder, lat 33°08'54", long 107°12'22", in SWł sec. 25, T. 13 S., R. 4 W., (projected) in Pedro Armendariz Grant, on left bank 1.0 mile downstream from dam and 1.5 miles upstream from Cuchillo Negro River. Datum of gage is 4,242.09 ft above mean sea level, datum of 1929. Prior to April 23, 1942 at several different sites and datums.

Drainage area.--29,450 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley,

Average discharge.--64 years (1915-78), 977 ft<sup>3</sup>/s (707,800 acre-ft per year).

Extremes.--1915-78: Maximum daily discharge, 8,200 cfs May 22, 1942; no flow at times prior to 1929.

Remarks.--Records good except those for period May to September, which are fair. Flow regulated by Elephant Butte Reservoir. Diversions for irrigation of about 800,000 acres above station.

		-			
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	249.7 1,200.0 21,033 19,930 4,975 45,960 46,610 46,450 2,189.10 214.4 324.8 343.0	8.8 923 1,290 1,310 1,210 1,840 1,890 2,020 591 92 16 18	7.3 7.7 14 12 11 1,260 1,220 1,280 .04 2.4 5.6 8.8	8.05 42.9 678 664 160 1,532 1,504 1,498 73.0 6.92 10.8 11.1	495 2,380 41,720 39,530 9,870 91,160 92,450 92,130 4,340 4,340 425 644 680
Calendar year 1978	189,479.00	2,020	.04	519	375,800

Monthly and yearly discharge, in cubic feet per second

#### Rio Grande below Caballo Dam, N. Mex.

Location.--Water-stage recorder, lat 32°53'05", long 107°17'31", in NE%SW% sec. 30, T. 16 S., R. 4 W., 2,000 ft upstream from Interstate Highway 25, 4,200 ft downstream from Caballo Dam, 1.3 miles upstream from Percha diversion dam, and 3 miles northeast of Arrey. Datum of gage is 4,140.9 ft above mean sea level, datum of 1929. October 13, 1938 to December 31, 1945 at datum 5.0 ft higher.

Drainage area.---30,700 sg mi, approximately (includes 2,940 sg mi in closed basin in San Luis Valley, Colo.).

Average discharge.--41 years (1938-78) 851 ft<sup>3</sup>/s (616,500 acre-ft per year).

Extremes.--1938-78: Maximum daily discharge, 7,650 ft<sup>3</sup>/s May 20, 1942; minimum daily, 0.1 ft<sup>3</sup>/s Oct. 31 to Nov. 14, 1954, Nov. 7 to Dec. 31, 1955.

Remarks.--Records good. Considerable diversion above station for irrigation. Flow regulated by Caballo and Elephant Butte Reservoirs.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	25.7 28.8 18,203.2 17,852 4,418.3 38,535 40,805 44,058 15,538.4 37.4 33.6 34.3	1.1 1.2 1,400 976 946 1,570 1,990 1,970 1,440 1.9 1.5 1.2	0.8 .8 1.0 322 1.5 922 640 721 1.5 .8 .9 1.0	0.83 1.03 587 595 143 1,284 1,316 1,421 518 1.21 1.22 1.11	51 57 36,110 35,410 8,760 76,430 80,940 87,390 30,820 74 67 68
Calendar year 1978	179,569.7	1,990	.8	492	356,200

Monthly and yearly discharge, in cubic feet per second

#### Bonito ditch below Caballo Dam, N. Mex.

Records available.--January 1938 to December 1977. Published as supplementary data with Rio Grande below Caballo Dam in U.S.G.S. Water-Supply Papers beginning with October 1947.

<u>Remarks</u>.--Ditch diverts directly from Caballo Reservoir for irrigation of lands on right bank of river. The total release from Project Storage, as used in computations of Compact Commission, is the combined flow of this ditch and Rio Grande below Caballo Dam.

Monthly and	yearly	discharge,	in	cubic	feet	per	Second
			_			£	

Manuch	structure cubic feet per second									
	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in					
February February March April May June July August September October November December Calendar year 1978	$ \begin{array}{c} 0\\ 0\\ 0\\ 47.9\\ 0\\ 37.5\\ 46.5\\ 42.4\\ 40.0\\ 0\\ 0\\ 0\\ 0 \end{array} $	0 0 10 10 10 10 10 10 10 0 0 0		0 0 1.60 0 1.25 1.50 1.37 1.33 0 0	acre-feet 0 0 95 0 74 92 84 79 0 0 0					
		10	0	.59	425					

and the second in the second in the second secon

LER KANALIST IN TANIHAN MATERIA SANTA INA MATERIA.

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Squaw Lake.--Staff gage in sec. 12, T. 39 N., R. 4 W., on tributary to Squaw Creek. Completed in 1938; capacity, 162 acre-ft by 1953 survey. Water is used for irrigation below gaging station on Rio Grande near Del Norte.

Manthaond	a 2 a 6	height.	in	feet.	and	contents,	ın	acre-reet	
HOULTU-CHA	gage								Î

Nonth		Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height Contents	- 0 0	- 0 0	- 0 0	- 0 0	0	- 0 0	- 0 0	- 0 0	- 0 0	0	- 0 0	- 0 0	0

<u>Rito Hondo Reservoir</u>.--Staff gage in sec. 22, T. 42 N., R. 3 W., on Rito Hondo (Deep Creek) tributary to Clear Creek. Completed in 1957; capacity, 561 acre-ft. Originally filled during May and June 1958 with transmountain water; storage is not in debit status. Water is used for fish culture.

Month-end gage height, in feet, and contents, in acre-feet

											_	<b>.</b> .	0-1
Nonth	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	car.yr.
Ponen			20.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	
Gage height	30.0	30.0	561	561	561	561	561	561	561	561	561	561 0	0
Change	ō	0	0	0	0	0	0						

Hermit Lakes Reservoir No. 3.--In sec. 25, T. 41 N., R. 4 W., on South Clear Creek. Completed prior to 1960; capacity, 192 acre-ft. Capacity table based on elevation above bottom of outlet. Water is used for fish culture. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end gage height, in feet, and contents, in acre-feet

		TO I CI												
Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height Contents Change	8.0 192 0	- 0												

Troutvale No. 2 Reservoir.--Staff gage in E4 sec. 10, T. 41 N., R. 3 W., on South Clear Creek. Completed in 1940; capacity, 435 acre-ft. Condition of spillway limited storage to 168 acre-ft after May 1942. Repairs to spillway in 1947 increased capacity to 257 acre-ft. Water is used for fish culture with only occasional sale for irrigation. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Kanth-ond		height.	in	feet,	and	contents,	in	acre-feet
Month-end	gage	neign.,	111	TCCCI	una	•		

		Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height Contents Change	7.6 257 0	0	_											

#### STORAGE IN RESERVOIRS

#### Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Jumper Creek Reservoir.--In Sec. 5, T. 39 N., R. 2 W., on Jumper Creek, tributary to Trout Creek. Completed in 1951; capacity, 38 acre-ft. Capacity table based on elevation above bottom of outlet. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end gage height, in feet, and co	contents, in acre-feet
--	------------------------

Month	Jan	Pab	14											
		reo.	mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nou	Dee	0.1	-
Gage height	10.0	10.0	10.0	10 0	10.0	10.0						Dec.	Cal.yr.	
Contents	38	38	38	38	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	-	-
Change	0	0	0	ō	0	10	38	38	38	38	38	38	-	
				·					U	0	0	0	0	

Big Meadows Reservoir.--In NW4 sec. 17, T. 38 N., R. 2 E., On South Fork about 0.9 mile upstream from Hope Creek. Completed in 1967; capacity, 2,437 acre-ft. Capacity table based on elevation above outlet. Water is used for fish culture. Includes 140 acre-ft of transmountain water, by exchange, in 1967; 838 acre-ft by exchange, in 1968; and 347 acre-ft, by exchange, in 1969. The remainder (1,112 acre-ft) was removed from call status, as debit water, by action of the Commission on March 5, 1970.

Month-end gage height, in feet,	and	contents,	in	acre-feet
---------------------------------	-----	-----------	----	-----------

Date	Game height					
		Contents	Change in Contents			
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	45.0 45.0 45.0 45.0 45.0 45.0 45.0 45.0	2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437				
Calendar year 1978						
		<u> </u>	0			

<u>Alberta Park Reservoir</u>.--In sec. 34, T. 38 N., R. 2 E., on Pass Creek. Completed in 1953; capacity, 598 acre-ft. Capacity table based on elevation above bottom of outlet. Includes 244 acre-ft transmountain water, imported in 1963. Remainder of storage removed from call status, as debit water, by action of the Commission on March 5, 1970.

		Month-	end ga	ge hei	ght, i	n feet	, and	conten	ts, in	acre-f	Pet		
Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct	Nou		
Gage height	27.0	27.0	27 0	27 0	27.0							Dec.	cal,yr
Contents	598	598	598	598	2/.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	
Change	0	0	Q	0	Ő	0	J <b>3</b> 6	0	298	598	598	598	-

Shaw Lake.--In sec. 5, T. 38 N., R. 2 E., on tributary to Lake Creek. Capacity, 638 acre-ft by 1916 decree; enlarged in 1955 to 681 acre-ft. Only the storage in excess of 638 acre-ft is subject to terms of Rio Grande Compact. Includes 42 acre-ft transmountain water imported in 1965.

		HON LIN-	eno ga	ge nei	ght,	in feet	, and	conten	ts, in	acre-f	eet		
Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.				
Gage height	14 6	14.0	14.0									pec.	Cal.yr.
Contents Change	441	14.6 441 0	14.6 441 0	14.6 441 0	14. 441 0	6 18.4 602 +161	18.4 602 0	15.5 477 -125	14.9 453 -24	14.1 421	15.1 460	16.0 499	-
									47	- J Z	+ 39	+39	+58

Month-and --- .

Č.

9. n. jr 1. n. jr

いたのではない

<u>.</u>,

#### RIO GRANDE COMPACT COMMISSION

#### Reservoirs in Rio Grande Basin in Colorado or New Mexico (Constructed or enlarged since 1937)

<u>Mill Creek Reservoir</u>.--In sec. 16, T. 39 N., R. 3 E., on Mill Creek. Completed in 1953; capacity, 43 acreft. Capacity based on elevation above bottom of outlet. Includes 43 acre-ft of transmountain water, by exchange, in 1976.

Month-end	gage	height,	in	feet,	and	contents,	in	acre-feet
-----------	------	---------	----	-------	-----	-----------	----	-----------

Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	-
Contents	43	43	43	43	43	4.3	43	43	43	43	43	43	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

<u>Fuchs Reservoir.--Staff</u> gage in sec. 2, T. 37 N., R. 4 E., on East Pinos Creek. Completed in 1939; capacity, 237 acre-ft with 2 feet of flash boards in spillway. Pinos Creek enters Rio Grande below station near Del Norte.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	17.2	17.2	17.2	17.2	17.2	17.2	9.0	-	-	-	-	-	-
Contents	238	238	238	238	238	238	78	0	0	0	0	0	-
Change	0	0	0	0	0	0	-160	-78	0	0	0	0	-238

<u>Platoro Reservoir</u>.--Water-stage recorder in NWASWA sec. 22, T. 36 N., R. 4 E., on Conejos River. Completed in 1951; capacity, 59,570 acre-ft at crest of spillway. Reservoir is used for irrigation and flood control. Storage affects Conejos Index Supply.

Ма	onth-end elevation, in fe	et, and contents, in	nd contents, in acre-feet					
Date	Elevation	Contents	Change in Contents					
December 31, 1977	_	al2,800	-					
January 31, 1978	-	al2,800	0					
February 28	-	al2,700	-100					
March 31	9,969.2	12,850	+150					
April 30	9,969.0	12,750	-100					
May 31	9,969.2	12,850	+100					
June 30	9,970.8	13,610	+760					
July 31	9,970.8	13,610	Ō					
August 31	9,970.8	13,610	0					
September 30	9,970.7	13,560	50					
October 31	9,970.8	13,610	+50					
November 30	-	al3,610	0					
December 31	-	al3,610	0					
Calendar year 1978	-	-	+810					

a - Estimated

<u>Trujillo Meadows Reservoir.</u> In sec. 5, T. 32 N., R. 5 E., on Los Pinos River. Completed in 1957; capacity, 913 acre-ft. Water is used for fish culture. Storage is transmountain water, by exchange, in 1959.

Month-end	gage	height,	in	feet,	and	content	ts,	in	acre-	fee	t
-----------	------	---------	----	-------	-----	---------	-----	----	-------	-----	---

Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	-	
Contents	913	913	913	913	913	913	913	913	913	913	913	913	-	
Change	0	0	0	0	0	0	0	0	0	0	0	0	0	

#### Reservoirs in Rio Grande Basin in New Mexico (constructed or enlarged since 1929)

Heron Reservoir.--Lat 36°39'56", long 106°42'12", at dam on Willow Creek. Storage began in October 1970. Capacity, 401,300 acre-ft at elevation 7,186.1 ft (low point on crest of spillway); dead storage, 1,340 acre-ft at elevation 7,003.0 ft. Used for storage of trans-mountain water.

Month-end elevation, in feet, and contents, in acre-feet

Date			acre-reet
	Elevation	Contents	Change in Contents
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 Decober 31 Vovember 30 December 31 Calendar year 1978	7,118.95 7,119.12 7,119.27 7,119.70 7,125.10 7,134.29 7,141.55 7,142.90 7,142.38 7,141.26 7,141.26 7,141.00 7,140.89 7,130.64	113,690 114,140 114,540 115,700 130,960 160,150 186,230 191,360 189,190 185,140 184,160 183,750 148,050	+450 +400 +1,160 +15,260 +29,190 +26,080 +5,130 -2,170 -4,050 -980 -410 -35,700
			+34,360

El Vado Reservoir.--Water-stage recorder and surface follower, lat 36°35'39", long 106°44'00", on Rio Chama. Storage began in January 1935. Capacity, 196,500 acre-ft at gage height 6,902.0 feet (crest of spillway); dead storage, 1,060 acre-ft, below gage height 6,775.0 ft (invert of outlet works), as determined by survey in 1966. Datum of gage is 8.21 feet above mean sea level, datum of 1929. Storage includes both Rio Grande and transmountain water.

Month-end	gage	height,	in	feet.	and	Contento	4-	
			***	7066¢	and	CONTEnts.	in	JOYO Foot

Date	Comp. had up t			
	Gage height	Contents	Change in contents	
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	6,817.33 6,818.43 6,819.55 6,834.01 6,858.21 6,858.52 6,858.76 6,848.54 6,829.46 6,814.07 6,813.93 6,813.95 6,839.14	a26,430 27,520 28,650 45,570 83,460 84,030 84,470 67,250 39,820 23,310 23,190 23,210 52,550	+1,090 +1,130 +16,920 +37,890 +570 +440 -17,220 -27,430 -16,510 -120 +20	24,650 24,650 24,650 24,640 24,520 24,480 24,330 24,180 24,330 24,180 24,230 22,240 22,130
Calendar year 1978	······································		+29,340	51,370
a corrected			+26,120	-

Abiquiu Reservoir.--Water-stage recorder in SW4 sec. 8, T. 23 N., R. 5 E., on Rio Chama. Completed in February 1963; capacity, 1,215,000 acre-ft at elevation of 6,350 feet (crest of spillway). Reservoir is operated by Corps of Engineers for flood control and sediment storage. A resolution granting permission to store transmountain waters was approved by Rio Grande Compact Commission on May 3, 1974.

Month-end elevation,	in	feet,	and	contents.	in	acre-feet
		•		ooncenteo,	411	acre-reet

Date	Elevation	Contents	Channel		
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30	Elevation 6,144.49 6,144.50 6,144.67 6,145.32 6,172.61 6,157.78 6,148.27 6,148.27 6,142.48 6,142.10 6,141.89 6,141.82	Contents 19,090 19,100 19,060 19,240 19,800 56,570 32,710 22,460 17,440 17,140 16,970 16,920	Change in contents +10 -40 +180 +560 +36,770 -23,860 -10,250 -5,020 -300 -170	TM water 19,090 19,100 19,060 18,990 19,100 18,430 32,710 22,460 17,400 17,090 16,880	
Calendar year 1978	-	16,920	-2,170	16,870 16,890	

The Constant of Martin and

47

and a state of the second state of the second state of the

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Reservoirs in Rio Grande Basin New Mexico (Completed or enlarged since 1929)

<u>Nambe Falls Reservoir</u>.--Water-stage recorder in NE<sub>4</sub>SW<sub>4</sub> sec. 29, T. 19 N., R. 10 E., in Nambe Indian Reservation, on Rio Nambe. Completed in 1976; capacity 2,020 acre-ft at elevation 6,826.6 feet (crest of spillway), dead storage 358 acre-ft at elevation 6,780.0 feet. Storage is transmountain water by exchange (see resolution adopted March 27, 1975).

Month-end	elevation.	in	feet,	and	contents,	ín	acre-	tee	t
-----------	------------	----	-------	-----	-----------	----	-------	-----	---

Date	Elevation	Contents	Change in contents
December 31 1977	6.793.57	655	
	6.797.29	757	+102
January SI, 1970	6.800.33	849	+92
repruary 20	6.805.62	1,030	+181
March 31	6,806,85	1.070	+40
April 30	6 822.75	1.810	+740
May 31	6 926 16	2.000	+190
June 30	6 B1A AA	1,400	-600
July 31	6 003 63	958	-442
August 31	6,003.02	849	-109
September 30	6,800.34	812	-37
October 31	6,799.10	1 040	+228
November 30	6,806.04	1 200	+160
December 31	<b>6'8T0'00</b>	1,200	
Calendar year 1978	· -		+545

McClure (Granite Point) Reservoir.--Water-stage recorder in NE4SWA sec. 24, T. 17 N., R. 10 E., on Santa Fe River. Original reservoir completed in 1926, capacity, 561 acre-ft; in 1935, permanent flash boards were installed in spillway increasing capacity to 650 acre-ft; in 1947 both dam and spillway were reconstructed increasing capacity to 2,615 acre-ft (gage height, 96.6 ft, crest of spillway). In 1953 spillway was equipped with radial gates that opened automatically, increasing capacity to over 3,000 acre-ft. In 1972, radial gates were removed decreasing capacity to 2,615 acre-ft. Only the storage in excess of 561 acre-feet is subject to terms of Rio Grande Compact.

	Month-end gage height, in fee	et, and contents, in acre	e-feet
Date	Gage height	Contents	Change in contents
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	- - - 95.4 96.6 91.6 85.1 78.7 74.8 79.5 -	2,000 1,960 1,950 1,970 2,200 2,530 2,610 2,270 1,850 1,480 1,280 1,520 1,340	-40 -10 +20 +230 +330 +330 -420 -370 -200 +240 -180
Calendar year 1978		-	-660

Nichols Reservoir.--Water-stage recorder in E3NE3 sec. 21, T. 17 N., R. 10 E., on Santa Fe River. Completed in 1942; capacity, 685 acre-ft. Water is for municpal use in Santa Fe.

Month-end	gage	height.	in	feet,	and	contents,	in	acre-feet
-----------	------	---------	----	-------	-----	-----------	----	-----------

Month	Jan.	Feb.	Mar.	Apr.	Мау	Јиле	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr
Gage height	-	-	141.1	142.0	150.8	152.6	148.9	156.6	153.9	150.7	150.1	-	+83
Contents	115	95	153	164	294	329	262	412	354	292	281	198	
Change	0	-20	+58	+11	+130	+35	-67	+150	-58	-62	-11	-83	

#### STORAGE IN RESERVOIRS

#### Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Cochiti Lake.--Water-stage recorder and manometer in NW4SW4 sec. 16, T. 16 N., R. 6 E., in Pueblo de Cochiti Grant, in control tower. Cochiti Dam completed in 1975; capacity 498,100 acre-ft at elevation 5,450.0 ft (crest of service spillway); dead storage 2,215 acre-ft at elevation 5,255.0 ft. A 50,000 acre-foot permanent pool was authorized by Public Law 88-293, 88th Con-gress, March 26, 1964. Reservoir is operated by Corps of Engineers for flood control, sediment storage, and recreation. Storage began Nov. 12, 1973.

Month-end	elevation,	in	feet.	and	contant-		
			2000,	and	concents,	ın	acre-feet

December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31	5,321.35 5,321.28 5,321.31 5,321.25 5,321.53	Contents 47,610 47,530 47,560 47,490	Change in contents 	TM water 47,610 47,530 47,420
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31	5,321.35 5,321.28 5,321.31 5,321.25 5,321.25 5,321.53	47,610 47,530 47,560 47,490	-80 +30 -70	47,610 47,530 47,420
June 30 July 31 August 31 September 30 October 31 November 30 December 31	5,321.50 5,320.89 5,327.43 5,330.50 5,330.27 5,329.91 5,329.92 5,329.85	47,830 47,790 55,270 59,410 58,600 58,620 58,520	$ \begin{array}{r} -70 \\ +340 \\ -40 \\ -730 \\ +8,210 \\ +4,140 \\ -310 \\ -500 \\ +20 \\ -100 \end{array} $	47,360 47,650 47,050 47,050 55,230 59,410 59,040 58,600 58,620
Calendar year 1978	-			58,520

Galisteo Reservoir.--Water-stage recorder and manometer in NWM sec. 9, T. 14 N., R. 7 E., at dam on Galisteo Creek. Storage records begin in October 1970. Capacity 89,800 acre-ft at elevation 5,608.0 ft (crest of spillway). Reservoir is operated by Corps of Engineers for flood control and sediment storage. There was no storage at the end of each month during the calendar year.

n <u>Gregorio Reservoir</u>.--Staff gage in SWANE4 sec. 20, T. 21 N., R. 1 E. (projected), on Clear Creek tributary to Rio Las Vacas and Jemez River. Completed in October 1958; capacity, 254 acre-ft at elevation 9,408.0 ft (crest of spillway). Storage omitted from accounting by action of Commission in April, 1957. San

				Month	-end	content	cs, in	acre-	feet				
Month	Jan.	Feb.	Mar.	Apr.	May	June	July		East	— — — — — — — — — — — — — — — — — — —			<u>.</u>
Contents	a170	a180	a200	2240					Sept.	000.	NOV.	Dec.	Cal.yr.
Change		+10	+20	+40	280 +40	265 -15	158 -107	all0 -48	al20 +10	a150 +30	a180	a200	-
a Estimater	3											+20	+40

Jemez Canyon Reservoir.--Water-stage recorder in SW45W4 sec. 32, T. 14 N., R. 4 E., on Jemez River 2.3 miles above mouth. Completed in 1953; capacity, 176,200 acre-ft at elevation of 5,252.3 ft. Capacity at elevation 5,232.0 ft (crest of spillway), 106,100 acre-ft by 1975 survey. Reservoir is operated by Corps of Engineers for flood control and sediment storage.

Ma_11		in acre-feet												
	Jan.	Feb.	Mar.	Apr,	May	June	July	Aug.	Sept.	Oct.	Nov	Dog		
Gage height	-		52	10 62 4			<u> </u>					Dec.	cal.yr.	
Contents	0	0	544	426	187	LI - 0	0	•			50.4	41 -		-
Change	0	0	+544	-118	-239	-187	U	U	0	0	211	0	-	
a - For al				<u> </u>							+211	-211	0	

evation add 5,100 ft.

Montheend clowetter

<u>Acomita Reservoir</u>.--Staff gage in SE<sup>1</sup>/<sub>4</sub> sec. 29, T. 10 N., R. 7 W., on San Fidel Arroyo; water for reservoir is diverted from Rio San Jose. Completed in 1938; original capacity, 850 acre-ft; present capacity 650 acre-ft on basis of 1956 sediment survey. Water is used for irrigation on Acoma and Laguna Indian Reservations.

			<u> </u>	Month	-end	conten	ts, in	acre-f	leet					
Month	Jan,	Feb.	Mar,	Apr.	May	June	July	Aug.	Sent	0+				-
Contents	300	400	500	600							- NOV -	Dec.	Cal.yr.	
Change	+12	+100	+100	+100	580 -20	480 -100	360 -120	320 -40	370 +50	420 +50	550 +130	650	+362	

49

- 25 

المراجع والمؤلج المواجع والمجتز ومستوحه وتصلح الأوم المؤلم فتتحصف

an an the second second second and the second s

#### RIO GRANDE COMPACT COMMISSION REPORT

#### Reservoirs in Rio Grande Basin in New Mexico (Project storage)

Elephant Butte Reservoir.--Water-stage recorder in NW4 sec. 30, T. 13 S., R. 3 W., at dam on Rio Grande. Storage began Jan. 6, 1915; capacity, 2,109,400 acre-ft at gage height 4,407.0 ft (crest of spillway), by survey of 1974. Datum of gage is 43.3 ft above mean sea level, datum of 1929. Water is used for power development and irrigation in New Mexico and Texas. Records furnished by Bureau of Reclamation. Delivery of transmountain water for minimum recreation pool was initiated in December 1975. Beginning Jan. 1, 1977 gage readings are midnight readings.

Month-end gag	e height,	in	feet,	and	contents,	in	acre-	·reet
---------------	-----------	----	-------	-----	-----------	----	-------	-------

Date	Gage height	Contents	Change in contents	TM water
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	4,305,50 4,309,91 4,313,45 4,311,79 4,307,58 4,317,68 4,315,40 4,306,09 4,291,25 4,290,50 4,290,95 4,298,71 4,305,67	181,400 215,400 245,000 230,900 196,900 282,600 262,100 185,700 95,810 92,240 94,370 136,300 182,600	+34,000 +29,600 -14,100 -34,000 +85,700 -20,500 -76,400 -89,890 -3,570 +2,130 +41,930 +46,300	52,360 52,220 51,980 51,550 50,480 49,670 49,090 48,220 47,300 46,450 45,820 45,820 51,760
Calendar year 1978	_	-	+1,200	

<u>Caballo Reservoir</u>.--Water-stage recorder in SE4SW4 sec. 19, T. 16 S., R. 4 W., at dam on Rio Grande. Storage began Feb. 8, 1938; capacity, 344,000 acre-ft (by 1958 survey), at gage height 4,182.0 ft (above which spillway gates open automatically). Datum of gage is 43.3 ft above mean sea level, datum of 1929. 100,000 acre-ft of storage reserved for flood control. Records furnished by Bureau of Reclamation. Beginning Jan. 1, 1977 gage readings are midnight readings.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1977 January 31, 1978 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	4,131.23 4,132.26 4,133.87 4,135.18 4,136.92 4,136.57 4,140.22 4,141.44 4,140.83 4,130.63 4,131.48 4,135.53 4,140.49	17,220 19,470 23,220 26,480 31,120 30,160 41,030 45,110 43,030 15,980 17,760 27,390 41,920	+2,250 +3,750 +3,260 +4,640 -960 +10,870 +4,080 -2,080 -27,050 +1,780 +9,630 +14,530
Calendar year 1978		-	+24,700

<u>Project Storage</u>.--This is the combined storage in Elephant Butte and Caballo Reservoirs. Total Project storage capacity is 2,353,400 acre-ft which excludes the 100,000 acre-ft reserved for flood control in Caballo Reservoir.

Nontheand gage	beight.	in	feet,	and	contents,	in	acre-feet

Date	Gage height	Contents	Change in contents
		198,500	-
December 31, 1977	-	234,900	+36,300
January 31, 1978	-	268,200	+33,300
February 28	_	257.400	-10,800
March 31	-	228.000	~29,400
pril 30	-	312,800	+84,800
lay 31	-	203 100	-9,700
une 30	-	220 800	-72,300
uly 31	-	129 800	-92,000
uqust 31	-	108 200	-30,600
eptember 30	-	112 100	+3,900
ctober 31	-	163 700	+51,600
lovember 30	-	163,700	+60,800
ecember 31	-	224,500	
			+25,900
alendar year 1978			

т., ч.

<u>Pine River - Weminuche Pass ditch (Fuchs ditch).--Water-stage recorder and 3-ft Parshall flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from North Fork Los Pinos River in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.</u>

- <u>Weminuche Pass ditch (Raber-Lohr ditch)</u>.--Water-stage recorder and 4-ft rectangular flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from Rincon la Vaca Creek in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.
- Williams Creek Squaw Pass ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 21, T. 39 N., R. 3 W., at Squaw Pass in Colorado. Diversion is from Williams Creek in San Juan River Basin into Squaw Creek in Rio Grande Basin. Constructed in 1938. Diversion for irrigation is from Rio Grande below Del Norte gaging station.
- Tabor ditch.--Water-stage recorder and 3-ft Parshall flume in sec. 35, T. 43 N., R. 3 W., at Spring Creek Pass in Colorado. Diversion is from Cebolla Creek in Gunnison River Basin into tributary of Clear Creek in Rio Grande Basin. Completed in 1910 or 1911. Diversion for irrigation is from Rio Grande below Del Norte gaging station.
- Don La Font No. 1 & No. 2 ditches (Piedra Pass ditch).--Water-stage recorder and 2-ft Parshall flume in sec. 4, T. 38 N., R. 1 W., at Piedra Pass in Colorado. Diversion is from tributaries of Piedra River in San Juan River Basin to South River in Rio Grande Basin. Original ditch completed in 1938, first enlargement completed in 1940. Water is imported by Colorado Game and Fish Department, beginning in 1959, to offset losses from fish culture reservoirs.
- Treasure Pass diversion ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 31, T. 38 N., R. 2 E., at Wolf Creek Pass in Colorado. Diversion is from Wolf Creek in San Juan River Basin to a tributary of South Fork Rio Grande. Completed in 1923 or 1924. Water is diverted for irrigation from Rio Grande above the Del Norte gaging station, beginning in 1959. Prior to 1959 it was diverted below gaging station.
- Azotea tunnel.--Water-stage recorder and 10-ft Parshall flume, lat 36°51'12", long 106°40'18", at south portal of Azotea tunnel, San Juan-Chama Project. Diversion is from Rio Blanco, Little Navajo River, and Navajo River in Colorado and discharge is into Azotea Creek in New Mexico. Construction completed in 1970.

Month	Pine River- Weminuche Pass ditch	Weminuche Pass ditch	Williams Creek- Squaw Pass ditch	Tabor ditch	Don La Font ditches	Treasure Pass diversion ditch	Azotea tunnel
January	0	0	n	0			
rebruary	0	0	ň	0	0	0	92
March	0	õ	0	0	0	ñ	54
April	0	õ	U	0	0	õ	55
May	õ	0	0	0	0	0	1,970
June	40	0	0	94	ñ	10	19,350
July		1,270	0	451	00	17	30,780
August	14	284	٥	172	80	248	44,680
August	0	20	õ	132	12	39	7.000
September	0	ō		4.3	0	n	.,
October	0	õ	U	0	0	ŏ	11
November	n	ě	U	0	n	ŏ	40
December	å	U	0	0	ň	0	26
		0	0	ō	ő	U	58
Cal. year	63	1 574				0	17
			U	720	92	304	104,150

Imported quantities, in acre-feet, 1978

\_\_\_\_\_

and the second address

275

.

147.7

4 (NY 4 - 22 19 - 24)

Read of the construction of the production of the second second second second second second second second second

#### RIO GRANDE COMPACT COMMISSION REPORT

#### EVAPORATION AND PRECIPITATION

The last paragraph of Article VI of the Compact states, in part, --- "such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bear to the total amount of water in such reservoirs during the year."

To provide the data needed for the computation of such evaporation losses, the Commission has encouraged the establishment and operation of evaporation stations near each major reservoir in the basin and at other selected locations.

Evaporation and other climatological data collected at the several stations in Colorado and New Mexico are tabulated on the next page. At some of the stations, it was not possible to obtain evaporation records throughout the winter period.

The measurements of evaporation were made in accordance with standard practice for the type of pan in use. Measurements of precipitation were made in standard 8-inch rain gages, which were supplemented at some of the stations by recording rain gages.

Records for the evaporation stations at the State University, Elephant Butte Dam, and El Vado Dam antedated the creation of the Commission; the stations at Abiguiu Dam, Cochiti Dam, and Jemez Canyon Dam were established by the Corps of Engineers. All others were established at the request of the Commission.

The Rio Grande Compact Commission gratefully acknowledges the cooperation of the U.S. Environmental Science Services Administration, U.S. Corps of Engineers, and U.S. Bureau of Reclamation for furnishing the climatological records contained in this report.

Alamosa Airport.--Lat 37°27', long 105°52", in Alamosa County at airport near Alamosa, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 7,536 ft.

- <u>Platoro Dam.--Lat 37°21', long 106°30', in Conejos County near Platoro, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, fan type psychrometer, standard 8-inch and recording rain gages at elevation 9,826 ft. Records furnished by Bureau of Reclamation.</u>
- El Vado Dam.--Lat 36°36', long 106°44', in Rio Arriba County at El Vado Dam near Tierra Amarilla, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,750 ft.
- <u>Abiquiu Dam.--Lat 36°14', long 106°26', in Rio Arriba County at Abiguiu Dam near Abiquiu, N. Mex.</u> Standard class A pan, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,380 ft.

Santa Fe College.--Lat 35°39', long 105°58', in Santa Fe, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,800 ft.

- Cochiti Dam.--Lat 35°38", long 106°19", in Sandoval County at operations building, at Cochiti Damsite, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,560 ft.
- Jemez Dam.--Lat 35°23', long 106°32", in Sandoval County at Jemez Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,388 ft.
- Elephant Butte Dam.--Lat 33°09', long 107°11', in Sierra County at Elephant Butte Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, and standard 8-inch rain gage at elevation 4,576 ft.
- <u>Caballo Dam.--Lat 32°54', long 107°18', in Sierra County at Caballo Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 4,190 ft.</u>
- New Mexico State University.--Lat 32°17', long 106°45', in Dona Ana County at University Park, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 3,881 ft.

#### EVAPORATION AND PRECIPITATION

Evaporation and precipitation, in inches Station Jan. Feb. Mar. Apr. May June July Aug. Sept. Oct. Nov. Dec. Alamosa Evap. Precip. Annual 8.64 8.87 Airport 11.67 10.27 8.64 .33 .07 7.97 .13 . 20 1.59 1.23 1.04 .27 .19 .51 .90 \_ Platoro Evap. \_ 7.95 .66 -2,20 Dam 7.27 Preclp. 6.39 4.84 ---.00 3.51 3.79 -----.71 1.06 .74 . 89 \_ El Vado Evap. Precip. 6.44 6.46 Dam 9.00 9.42 7.62 1.58 1.20 2,55 5.55 4.38 .40 2.90 . 59 .83 .66 1.12 1.19 1.75 1.88 Abiquiu 16.65 Evap. 8.38 8.05 2.23 10.70 Dan 12.18 Precip. . 26 10.21 8.48 . 29 .62 6.13 .96 1.25 .93 .42 1.63 .54 .61 Santa Fe 9.78 Evap. -College 9.46 11.56 Precip. 11.80 10.09 . 85 .48 .86 8.10 .17 2.67 2.29 .66 .99 .85 1.06 2.64 .47 Cochiti 13.99 Evap. Precip. -10.91 10.65 2.47 Dam 14.54 14.12 12.53 1.10 . 69 •45 9.87 1.00 7.35 .05 1.86 . 60 . 78 1.13 2.88 1.44 Jemez 14.45 Evap. 12.12 15.66 13.49 Dam 12.07 16.03 Precip. .53 10.42 8.68 .94 .66 .65 .24 1.48 . 80 .96 • 53 1.47 . 69 Elephant 9.27 Evap. Precip. 3.22 1.13 4.29 8.01 14.55 13.65 16.88 Butte 15.35 12.80 -95 1.58 9.23 .49 7.20 .28 0.00 3.32 2.79 111.29 . 99 .97 2.93 Caballo .60 13.16 Evap. Precip. \_ 4.12 7.81 12.77 14.39 Dam .61 16.67 15.43 12.30 9.16 6.72 .37 3.59 3.09 .00 .00 2.69 .91 .73 1.28 1.70 . 86 . 81 10.92 State Evap. 2.90 6.87 3.77 12.54 14.10 1.02 1.03 10.49 Univer. 13.68 Precip. 11.16 .73 7.88 5.74 1.86 .35 .00 3.23 2.89 95.25 14.98 2.60 2.99 2.59 . 77

53

C. Marka har M. Check Sec.



5.88.98.89

~





というない

ζ,

Service Services