

Construction of the

States and the states 1

of the state of th





CONTENTS

のないで、「「「「「」」」

052300

and the state of the state

1.10

5.53.5

	Page
Forty-second Annual Report to Governors	1
Rio Grande Compact	*
Resolution of the Commission	2
Resolution of the commission	15
Rules and Regulations	10
Records of Deliveries and Release	17
Deliveries by Colorado at State line	26
Deliveries by New Mexico at Elephant Butte	27
Release and Spill from Project Storage	28
	29
cost of Operation and Budget	~ ~
Acknowl adamante	30
ACKNOWLEDGMENTS	21
Accuracy of Pegorde	15
Accuracy of Records	32
Streamflow	<u> </u>
	3-43
Rio Grande near Del Norte, Colorado	
Conejos River below Platoro Reservoir, Colorado	33
Conejos River near Mogote, Colorado	33
San Antonio River at Ortiz, Colorado	_34
Los Pinos River near Ortiz, Colorado	34
Conejos River near Lasauses, Colorado	35
Rio Grande near Lobatos, Colorado	35
Willow Creek above Heron Reservoir, near Los Ojos, New Movies	36
Horse Lake Creek above Heron Reservoir, near Los Ojos New Movies	36
Willow Creek below Heron Dam, New Mexico	37
Rio Chama below El Vado Dam, New Mexico	3/
Rio Chama below Abiquiu Dam, New Mexico	38
Rio Rande below Nambe Falls Dam, near Nambe, New Mexico.	20
Santa Fe Biyor near San Ildefonso, New Mexico.	30
Rio Grande bolou Contition	10
Galisteo Crock bolow Colliti Dam, New Mexico	40
Jemez River below Galisteo Dam, New Mexico	40
Rio Grande below Flophant Dam, New Mexico,	41
Rio Grande below Caballa Dutte Dam, New Mexico	42
Bonito ditch below Caballo Dam, New Mexico.	42
alson below Caballo Dam, New Mexico	43
Storage in Reservoirs	_
Cransmountain Diversions	-50
	51
vaporation and Precipitation	50
52,	J

ILLUSTRATIONS

1.51	K10	Grande	Basin	above	Ft.	Quitman	, Те	xasFrontispi	.ece
• p ,	Rio	Grande	Basin	above	Bern	nalillo,	New	Mexico	, 55

े देखे देखे देखे देखे

RIO GRANDE COMPACT COMMISSION

COLORADO TEXAS

NEW MEXICO

The Honorable Bruce King Governor of the State of New Mexico Santa Fe, New Mexico

March 26, 1981

The Honorable William P. Clements, Jr. Governor of the State of Texas Austin, Texas

The Honorable Richard D. Lamm Governor of the State of Colorado Denver, Colorado

Sirs:

The 42nd annual meeting of the Rio Grande Compact Commission was held at El Paso, Texas on March 26, 1981.

The Commission reviewed its prior reports and the current reports of the Secretary relative to streamflow at Compact gaging stations and storage in reservoirs. The Commission found that:

- (a) Deliveries of water at the Colorado-New Mexico State line by Colorado amounted to 451,700 acre-feet, which was 24,600 acre-feet in excess of the scheduled delivery in 1980. The accrued debit of Colorado was reduced to 674,600 acre-feet as of December 31, 1980. However, in light of the as yet unresolved controversy between the States, Colorado cannot agree with conclusions as to her indebtedness.
- (b) Deliveries of water into Elephant Butte Reservoir by New Mexico, as measured by the Elephant Butte Effective Supply, amounted to 967,000 in 1980. The accrued debit of New Mexico was 148,000 acre-feet as of December 31, 1980.
- (c) Releases of usable water from Project Storage in 1980 amounted to 659,300 acre-feet.
- (d) Expenses of administration of the Rio Grande Compact were \$64,991 in the fiscal year ending June 30, 1980. The United States bore \$27,140 of this total; the balance of \$37,851 was borne equally by the three States party to the Compact.

Respectfully, S. E. Reynolds, mmissioner for New Mexico Commissi **T**exas anielson, Commissioner for Colorado

RIO GRANDE COMPACT COMMISSION REPORT

RIO GRANDE COMPACT

The State of Colorado, the State of New Mexico, and the State of Texas, desiring to remove all causes of present and future controversy among these States and between citizens of one of these States and citizens of another State with respect to the use of the waters of the Rio Grande above Fort Quitman, Texas, and being moved by considerations of interstate comity, and for the purpose of effecting an equitable apportionment of such waters, have resolved to conclude a Compact for the attainment of these purposes, and to that end, through their respective Governors, have named as their respective Commissioners:

For	the	State	of	Colorado	M. C. Hinderlider
For	the	State	of	New Mexico	Thomas M. McClure
For	the	State	of	Texas	Frank B. Clayton

who, after negotiations participated in by S. O. Harper, appointed by the President as the representative of the United States of America, have agreed upon the following articles, to-wit:

ARTICLE I

(a) The State of Colorado, the State of New Mexico, the State of Texas and the United States of America, are hereinafter designated "Colorado," "New Mexico," "Texas," and the "United States," respectively.

(b) "The Commission" means the agency created by this Compact for the administration thereof.

(c) The term "Rio Grande Basin" means all of the territory drained by the Rio Grande and its tributaries in Colorado, in New Mexico, and in Texas above Fort Quitman, including the Closed Basin in Colorado.

(d) The "Closed Basin" means that part of the Rio Grande Basin in Colorado where the streams drain into the San Luis Lakes and adjacent territory, and do not normally contribute to the flow of the Rio Grande.

(e) The term "tributary" means any stream which naturally contributes to the flow of the Rio Grande.

(f) "Transmountain Diversion" is water imported into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, exclusive of the Closed Basin.

(g) "Annual Debits" are the amounts by which actual deliveries in any calendar year fall below scheduled deliveries

reality and the second second second second

RIO GRANDE COMPACT

A STATE OF A

ে ন্থা

බි ල

2. the Station

3

(h) "Annual Credits" are the amounts by which actual deliveries in any calendar year exceed scheduled deliveries.

(i) "Accrued Debits" are the amounts by which the sum of all annual debits exceeds the sum of all annual credits over any common period of time.

(j) "Accrued Credits" are the amounts by which the sum of all annual credits exceeds the sum of all annual debits over any common period of time.

(k) "Project Storage" is the combined capacity of Elephant Butte Reservoir and all other reservoirs actually available for the storage of usable water below Elephant Butte and above the first diversion to lands of the Rio Grande Project, but not more than a total of 2,638,860

(1) "Usable Water" is all water, exclusive of credit water, which is in project storage and which is available for release in accordance with irrigation demands, including deliveries to Mexico.

(m) "Credit Water" is that amount of water in project storage which is equal to the accrued credit of Colorado, or New Mexico, or both.

(n) "Unfilled Capacity" is the difference between the total physical capacity of project storage and the amount of usable water then in storage.

(o) "Actual Release" is the amount of usable water released in any calendar year from the lowest reservoir comprising project storage.

(p) "Actual Spill" is all water which is actually spilled from Elephant Butte Reservoir, or is released therefrom for flood control, in excess of the current demand on project storage and which does not become usable water by storage in another reservoir; provided, that actual spill of usable water cannot occur until all credit water shall have been spilled.

(q) "Hypothetical Spill" is the time in any year at which usable water would have spilled from project storage proportional to the actual release therefrom at rates starting date to the end of the year in which hypothetical spill occurs; in computing hypothetical spill the initial condition shall be the amount of usable water in project storage at the beginning of the calendar year following the condition shall be the amount of usable water in project effective date of this Compact, and thereafter the initial storage at the beginning of the calendar year following the condition shall be the amount of usable water in project effective date of this Compact, and thereafter the initial storage at the beginning of the calendar year following

RIO GRANDE COMPACT COMMISSION REPORT

ARTICLE II

The Commission shall cause to be maintained and operated a stream gaging station equipped with an automatic water stage recorder at each of the following points, to-wit:

(a) On the Rio Grande near Del Norte above the principal points of diversion to the San Luis Valley;

(b) On the Conejos River near Mogote;

(c) On the Los Pinos River near Ortiz;

(d) On the San Antonio River at Ortiz;

(e) On the Conejos River at its mouths near Los Sauces;

(f) On the Rio Grande near Lobatos;

(g) On the Rio Chama below El Vado Reservoir;

(h) On the Rio Grande at Otowi Bridge near San Ildefonso;

(i) On the Rio Grande near San Acacia;

(j) On the Rio Grande at San Marcial;

(k) On the Rio Grande below Elephant Butte Reservoir;

(1) On the Rio Grande below Caballo Reservoir.

Similar gaging stations shall be maintained and operated below any other reservoir constructed after 1929, and at such other points as may be necessary for the securing of records required for the carrying out of the Compact; and automatic water stage recorders shall be maintained and operated on each of the reservoirs mentioned, and on all others constructed after 1929.

Such gaging stations shall be equipped, maintained and operated by the Commission directly or in cooperation with an appropriate Federal or State agency, and the equipment, method and frequency of measurement at such stations shall be such as to produce reliable records at all times. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE III

The obligation of Colorado to deliver water in the Rio Grande at the Colorado-New Mexico State Line, measured at or near Lobatos in each calendar year. shall be ten

0023

5

the feature of the second for the second second

RIO GRANDE COMPACT

thousand acre feet less than the sum of those quantities set forth in the two following tabulations of relationship, which correspond to the quantities at the upper index stations:

DISCHARGE OF CONEJOS RIVER

Quantities in thousands of acre feet

Conejos Index Supply (1)

Conejos River at Mouths (2)

0

100
150
100
200
250
200
000
350
400
150
400
500
550
000
000
650

700

400

450

500

86

98

112

127

Intermediate quantities shall be computed by proportional parts.

(1) Conejos Index Supply is the natural flow of Conejos River at the U.S.G.S. gaging station near Mogote during the calendar year, plus the natural flow of Los Pinos River at the U.S.G.S. gaging station near Ortiz and the natural flow of San Antonio River at the U.S.G.S. gaging station at Ortiz, both during the months of April to October, inclusive.

(2) Conejos River at Mouths is the combined discharge of branches of this river at the U.S.G.S. gaging stations near Los Sauces during the calendar year.

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER

Quantities in thousands of acre feet

Rio Grande at Del Norte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
200 250	60
300	65
350	75

5

아이아 씨는 아이가 가지 않는 아이는 것을 알았는 것을 못 가지 않는 것을 했다.

RIO GRANDE COMPACT COMMISSION REPORT

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER--Con.

Quantities in thousands of acre feet

Rio Grande at Lobatos less Conejos at Mouths (4)

Rio Grande at Del Norte (3)

the second and the little little scheme and the

6

000246

144 550 162 600 182 650 204 700 229 750 257800 292 850 335 900 380 950 430 1.000 540 1,100 640 1,200 740 1,300 840 1,400

Intermediate quantities shall be computed by proportional parts.

(3) Rio Grande at Del Norte is the recorded flow of the Rio Grande at the U.S.G.S. gaging station near Del Norte during the calendar year (measured above all principal points of diversion to San Luis Valley) corrected for the operation of reservoirs constructed after 1937.

(4) Rio Grande at Lobatos less Conejos at Mouths is the total flow of the Rio Grande at the U.S.G.S. gaging station near Lobatos, less the discharge of Conejos River at its Mouths, during the calendar year.

The application of these schedules shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) any new or increased depletion of the runoff above inflow index gaging stations; and (c) any transmountain diversions into the drainage basin of the Rio Grande above Lobatos.

In event any works are constructed after 1937 for the purpose of delivering water into the Rio Grande from the Closed Basin, Colorado shall not be credited with the amount of such water delivered, unless the proportion of sodium ions shall be less than forty-five percent of the total positive ions in that water when the total dissolved solids in such water exceeds three hundred fifty parts per million. RIO GRANDE COMPACT

ARTICLE IV

The obligation of New Mexico to deliver water in the Rio Grande at San Marcial, during each calendar year, exclusive of the months of July, August, and September, shall be that quantity set forth in the following tabulation of relationship, which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND AT SAN MARCIAL EXCLUSIVE OF JULY, AUGUST AND SEPTEMBER

Quantities in thousands of acre feet

Otowi Index Supply (5)

100

San Marcial Index Supply (6)

200	Ο
200	65
400	141
400	141
500	213
600	300
700	383
800	469
900	557
1,000	648
1,100	742
1,200	839
1,300	939
1,400	1,042
1,500	1,148
1,600	1,257
1,700	1,370
1,800	1,489
1,900	1,608
2,000	1.730
2,000	1,856
2,200	1 985
9 300	2,000
4,000	2,117
2,200 2,300	1,985 2,117 2,253

Intermediate quantities shall be computed by proportional parts.

(5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, exclusive of the flow during the months of July, August and September, corrected for the operation of reservoirs constructed after 1929 in the drain age basin of the Rio Grande between Lobatos and Otowi

RIO GRANDE COMPACT COMMISSION REPORT

(6) San Marcial Index Supply is the recorded flow of the Rio Grande at the gaging station at San Marcial during the calendar year exclusive of the flow during the months of July, August and September.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico at any time of the year of the natural runoff at Otowi Bridge; (c) depletion of the runoff during July, August and September of tributaries between Otowi Bridge and San Marcial, by works constructed after 1937; and (d) any transmountain diversions into the Rio Grande between Lobatos and San Marcial.

Concurrent records shall be kept of the flow of the Rio Grande at San Marcial, near San Acacia, and of the release from Elephant Butte Reservoir to the end that the records at these three stations may be correlated. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE V

If at any time it should be the unanimous finding and determination of the Commission that because of changed physical conditions, or for any other reason, reliable records are not obtainable, or cannot be obtained, at any of the stream gaging stations herein referred to, such stations may, with the unanimous approval of the Commission, be abandoned, and with such approval another station, or other stations, shall be established and new measurements shall be substituted which, in the unanimous opinion of the Commission, will result in substantially the same results, so far as the rights and obligations to deliver water are concerned, as would have existed if such substitution of stations and measurements had not been so made. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE VI

Commencing with the year following the effective date of this Compact, all credits and debits of Colorado and New Mexico shall be computed for each calendar year; provided, that in a year of actual spill no annual credits nor annual debits shall be computed for that year.

In the case of Colorado, no annual debit nor accrued debit shall exceed 100,000 acre feet, except as either or both may be caused by holdover storage of water in reservoirs constructed after 1937 in the drainage basin of the

50**24**

 $\boldsymbol{\infty}$

ha dhalan a shakala ka na maraka na barada na baran na shaka a

RIO GRANDE COMPACT

ন্দ ত

S. W. W. W. W. Burnston

Rio Grande above Lobatos. Within the physical limitations of storage capacity in such reservoirs, Colorado shall retain water in storage at all times to the extent of its accrued debit.

In the case of New Mexico, the accrued debit shall not exceed 200,000 acre feet at any time, except as such debit may be caused by holdover storage of water in reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and San Marcial. Within the physical limitations of storage capacity in such reservoirs, New Mexico shall retain water in storage at all times to the extent of its accrued debit. In computing the magnitude of accrued credits or debits, New Mexico shall not be charged with any greater debit in any one year than the sum of 150,000 acre-feet and all gains in the quantity of water in storage in such year.

The Commission by unanimous action may authorize the release from storage of any amount of water which is then being held in storage by reason of accrued debits of Colorado or New Mexico; provided, that such water shall be replaced at the first opportunity thereafter.

In computing the amount of accrued credits and accrued debits of Colorado or New Mexico, any annual credits in excess of 150,000 acre feet shall be taken as equal to that amount.

In any year in which actual spill occurs, the accrued credits of Colorado, or New Mexico, or both, at the beginning of the year shall be reduced in proportion to their respective credits by the amount of such actual spill; provided, that the amount of actual spill shall be deemed to be increased by the aggregate gain in the amount of water in storage, prior to the time of spill, in reservoirs above San Marcial constructed after 1929; provided, further, that authorize the release of part, or all, of such credits in advance of spill, the amount so released shall be deemed to constitute actual spill.

In any year in which there is actual spill of usable water, or at the time of hypothetical spill thereof, all accrued debits of Colorado, or New Mexico, or both, at the beginning of the year shall be cancelled.

In any year in which the aggregate of accrued debits of Colorado and New Mexico exceeds the minimum unfilled capacity of project storage, such debits shall be reduced proportionally to an aggregate amount equal to such minimum unfilled capacity.

ः **२३३०**

10

RIO GRANDE COMPACT COMMISSION REPORT

To the extent that accrued credits are impounded in reservoirs between San Marcial and Courchesne, and to the extent that accrued debits are impounded in reservoirs above San Marcial, such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bore to the total amount of water in such reservoirs during the year.

ARTICLE VII

Neither Colorado nor New Mexico shall increase the amount of water in storage in reservoirs constructed after 1929 whenever there is less than 400,000 acre feet of usable water in project storage; provided, that if the actual releases of usable water from the beginning of the calendar year following the effective date of this Compact, or from the beginning of the calendar year following actual spill, have aggregated more than an average of 790,000 acre feet per annum, the time at which such minimum stage is reached shall be adjusted to compensate for the difference between the total actual release and releases at such average rate; provided, further, that Colorado, or New Mexico, or both, may rélinquish accrued credits at any time, and Texas may accept such relinquished water, and in such event the state, or states, so relinquishing shall be entitled to store water in the amount of the water so relinquished.

ARTICLE VIII

During the month of January of any year the Commisioner for Texas may demand of Colorado and New Mexico, and the Commissioner for New Mexico may demand of Colorado, the release of water from storage reservoirs constructed after 1929 to the amount of the accrued debits of Colorado and New Mexico, respectively, and such releases shall be made by each at the greatest rate practicable under the conditions then prevailing, and in proportion to the total debit of each, and in amounts, limited by their accrued debits, sufficient to bring the quantity of usable water in project storage to 600,000 acre feet by March first and to maintain this quantity in storage until April thirtieth, to the end that a normal release of 790,000 acre feet may be made from project storage in that year.

ARTICLE IX

Colorado agrees with New Mexico that in event the United States or the State of New Mexico decides to construct the necessary works for diverting the waters of the San Juan River, or any of its tributaries, into the Rio Grande, Colorado hereby consents to the construction of said works and the diversion of waters from the San Juan

RIO GRANDE COMPACT

River, or the tributaries thereof, into the Rio Grande in New Mexico, provided the present and prospective uses of water in Colorado by other diversions from the San Juan River, or its tributaries, are protected.

State of the state

ARTICLE X

In the event water from another drainage basin shall be imported into the Rio Grande Basin by the United States or Colorado or New Mexico, or any of them jointly, the State having the right to the use of such water shall be given proper credit therefor in the application of the

ARTICLE XI

New Mexico and Texas agree that upon the effective date of this Compact all controversies between said States relative to the quantity or quality of the water of the Rio Grande are composed and settled; however, nothing herein shall be interpreted to prevent recourse by a signatory state to the Supreme Court of the United States for redress should the character or quality of the water, at the point of delivery, be changed hereafter by one signatory state to the injury of another. Nothing herein shall be construed as an admission by any signatory state that the use of water for irrigation causes increase of salinity for which the user is responsible in law.

ARTICLE XII

To administer the provisions of this Compact there shall be constituted a Commission composed of one representative from each state, to be known as the Rio Grande Compact Commission. The State Engineer of Colorado shall be ex-officio the Rio Grande Compact Commissioner for Colorado. The State Engineer of New Mexico shall be exofficio the Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for Texas shall be appointed by the Governor of Texas. The President of the United States shall be requested to designate a representative of the United States to sit with such Commission, and such representative of the United States, if so designated by the President, shall act as Chairman of the Commission without vote.

The salaries and personal expenses of the Rio Grande Compact Commissioners for the three States shall be paid by their respective States, and all other expenses incident to the administration of this Compact, not borne by the United States, shall be borne equally by the three States.

RIO GRANDE COMPACT COMMISSION REPORT

In addition to the powers and duties hereinbefore specifically conferred upon such Commission, and the members thereof, the jurisdiction of such Commission shall extend only to the collection, correlation and presentation of factual data and the maintenance of records having a bearing upon the administration of this Compact, and, by unanimous action, to the making of recommendations to the respective States upon matters connected with the administration of this Compact. In connection therewith, the Commission may employ such engineering and clerical aid as may be reasonably necessary within the limit of funds provided for that purpose by the respective States. Annual reports compiled for each calendar year shall be made by the Commission and transmitted to the Governors of the signatory States on or before March first following the year covered by the report. The Commission may, by unanimous action, adopt rules and regulations consistent with the provisions of this Compact to govern their proceedings.

The findings of the Commission shall not be conclusive in any court or tribunal which may be called upon to interpret on enforce this Compact.

ARTICLE XIII

At the expiration of every five-year period after the effective date of this Compact, the Commission may, by unanimous consent, review any provisions hereof which are not substantive in character and which do not affect the basic principles upon which the Compact is founded, and shall meet for the consideration of such questions on the request of any member of the Commission; provided, however, that the provisions hereof shall remain in full force and effect until changed and amended within the intent of the Compact by unanimous action of the Commissioners, and until any changes in this Compact are ratified by the legislatures of the respective states and consented to by the Congress, in the same manner as this Compact is required to be ratified to become effective.

ARTICLE XIV

The schedules herein contained and the quantities of water herein allocated shall never be increased nor diminished by reason of any increase or diminution in the delivery or loss of water to Mexico.

03025

12

CJ.

RIO GRANDE COMPACT

States and the second second

300

CV2

 ϵ)

ARTICLE XV

The physical and other conditions characteristic of the Rio Grande and peculiar to the territory drained and served thereby, and to the development thereof, have actuated this Compact and none of the signatory states admits that any provisions herein contained establishes any general principle or precedent applicable to other interstate streams.

ARTICLE XVI

Nothing in this Compact shall be construed as affecting the obligations of the United States of America to Mexico under existing treaties, or to the Indian Tribes, or as impairing the rights of the Indian Tribes.

ARTICLE XVII

This Compact shall become effective when ratified by the legislatures of each of the signatory states and conratification shall be given by the Governor of each state to the Governors of the other states and to the President of the United States, and the President of the United States is requested to give notice to the Governors of each of the Signatory states of the consent of the Congress of the United States.

IN WITNESS WHEREOF, the Commissioners have signed this Compact in quadruplicate original, one of which shall be deposited in the archives of the Department of State of the United States of America and shall be deemed the authoritative original, and of which a duly certified copy shall be forwarded to the Governor of each of the signatory

14

ىن ئىيىلى لەتلاكىكى ئەردى ئىچەن م

RIO GRANDE COMPACT COMMISSION REPORT

Done at the City of Santa Fe, in the State of New Mexico, on the 18th day of March, in the year of our Lord, One Thousand Nine Hundred and Thirty-eight.

> (Sgd.) M. C. HINDERLIDER (Sgd.) THOMAS M. McCLURE (Sgd.) FRANK B. CLAYTON

APPROVED:

(Sgd.) S. O. HARPER

RATIFIED BY:

Colorado, February 21, 1939 New Mexico, March 1, 1939 Texas, March 1, 1939

Passed Congress as Public Act No. 96, 76th Congress, Approved by the President May 31, 1939.

RESOLUTION ADOPTED BY RIO GRANDE COMPACT COMMISSION AT THE ANNUAL MEETING HELD AT EL PASO, TEXAS, FEBRUARY 22-24, 1948, CHANGING GAGING STATIONS AND MEASUREMENTS OF DELIVERIES BY NEW MEXICO

$\underline{\mathbf{R}} \ \underline{\mathbf{E}} \ \underline{\mathbf{S}} \ \underline{\mathbf{O}} \ \underline{\mathbf{L}} \ \underline{\mathbf{U}} \ \underline{\mathbf{T}} \ \underline{\mathbf{I}} \ \underline{\mathbf{O}} \ \underline{\mathbf{N}}$

Whereas, at the Annual Meeting of the Rio Grande Compact Commission in the year 1945, the question was raised as to whether or not a schedule for delivery of water by New Mexico during the entire year could be worked out, and

Whereas, at said meeting the question was referred to the Engineering Advisers for their study, recommendations and report, and

Whereas, said Engineering Advisers have met, studied the problems and under date of February 24, 1947, did submit their Report, which said Report contains the findings of said Engineering Advisers and their recommendations, and

Whereas, the Compact Commission has examined said Report and finds that the matters and things therein found and recommended are proper and within the terms of the Rio Grande Compact, and

Whereas, the Commission has considered said Engineering Advisers' Report and all available evidence, information and material and is fully advised:

Now, Therefore, Be it Resolved:

The Commission finds as follows:

- (a) That because of change of physical conditions, reliable records of the amount of water passing San Marcial are no longer obtainable at the stream gaging station at San Marcial and that the same should be abandoned for Compact purposes.
- (b) That the need for concurrent records at San Marcial and San Acacia no longer exists and that the gaging station at San Acacia should be abandoned for Compact purposes.
- (c) That it is desirable and necessary that the obligations of New Mexico under the Compact to deliver water in the months of July, August, September, should be scheduled.

15

an also well. The art and the first start the statistical

16

and the second secon

RIO GRANDE COMPACT COMMISSION REPORT

(d) That the change in gaging stations and substitution of the new measurements as hereinafter set forth will result in substantially the same results so far as the rights and obligations to deliver water are concerned, and would have existed if such substitution of stations and measurements had not been so made.

Be it Further Resolved:

That the following measurements and schedule thereof shall be substituted for the measurements and schedule thereof as now set forth in Article IV of the Compact:

"The obligation of New Mexico to deliver water in the Rio Grande into Elephant Butte Reservoir during each calendar year shall be measured by that quantity set forth in the following tabulation of relationship which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY

Quantities in thousands of acre-feet

Otowi Index Supply (5)

Elephant Butte Effective Index Supply (6)

100	57
200	114
300	171
400	228
500	286
600	345
700	406
800	471
900	542
000	621
1.100	707
1.200	800
1,300	897
1,400	996
1,500	1,095
1,600	1,195
1,700	1,295
1,800	1,395 1,406
1,900	1,490 1,600
2,000	1,090

RESOLUTION OF COMMISSION

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY--Continued

Quantities in thousands of acre-feet

2~ :52

ରୁ ଚୁ

Otowi Index Supply (5) Elephant Butte Effective Index Supply (6)

2,100 2,200 2,300 2,400 2,500 2,600 2,700 2,800 2,800	1,695 1,795 1,895 1,995 2,095 2,195 2,295 2,395
2,800	2,295
3,000	2,495
,	2,595

Intermediate quantities shall be computed by proportional parts.

- The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station (5) at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, corrected for the operation of reser-voirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi Bridge.
- Elephant Butte Effective Index Supply is the (6) recorded flow of the Rio Grande at the gaging station below Elephant Butte Dam during the calendar year plus the net gain in storage in Elephant Butte Reservoir during the same year or minus the net loss in storage in said reservoir, as the case may be.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico of the natural runoff at Otowi Bridge; and (c) any transmountain diversions into the Rio Grande between Lobatos and Elephant Butte

18

00

RIO GRANDE COMPACT COMMISSION REPORT

Be it Further Resolved:

That the gaging stations at San Acacia and San Marcial be, and the same are hereby abandoned for Compact purposes.

Be it Further Resolved:

That this Resolution has been passed unanimously and shall be effective January 1, 1949, if within 120 days from this date the Commissioner for each State shall have received from the Attorney General of the State represented by him, an opinion approving this Resolution, and shall have so advised the Chairman of the Commission, otherwise, to be of no force and effect.

(Note: The following paragraph appears in the Minutes of the Annual Meeting of the Commission held at Denver, Colorado, February 14-16, 1949:

"The Chairman announced that he had received, pursuant to the Resolution adopted by the Commission at the Ninth Annual Meeting on February 24, 1948, opinions from the Attorneys General of Colorado, New Mexico and Texas that the substitution of stations and measurements of deliveries by New Mexico set forth in said resolution was within the powers of the Commission").

RULES AND REGULATIONS FOR ADMINISTRATION OF THE RIO GRANDE COMPACT

A Compact, known as the Rio Grande Compact, between the States of Colorado, New Mexico and Texas, having become effective on May 31, 1939 by consent of the Congress of the United States, which equitably apportions the waters of the Rio Grande above Fort Quitman and permits each State to develop its water resources at will, subject only to its obligations to deliver water in accordance with the schedules set forth in the Compact, the following Rules and Regulations have been adopted for its administration by the Rio Grande Compact Commission; to be and remain in force and effect only so long as the same may be satisfactory to each and all members of the Commission, and provided always that on the objection of any member of the Commission, in writing, to the remaining two members of the Commission after a period of sixty days from the date of such objection, the sentence, paragraph or any portion or all of these rules to which any such objection shall be made, shall stand abrogated and shall thereafter have no further force and effect; it being the intent and purpose of the Commission to permit these rules to obtain and be effective only so long as the same may be satisfactory to each and all of the Commissioners.

GAGING STATIONS /1

002200

Responsibility for the equipping, maintenance and operation of the stream gaging stations and reservoir gaging stations required by the provisions of Article II of the Compact shall be divided among the signatory States as follows:

(a) Gaging stations on streams and reservoirs in the Rio Grande Basin above the Colorado-New Mexico boundary shall be equipped, maintained, and operated by Colorado in cooperation with the U.S. Geological Survey.

(b) Gaging stations on streams and reservoirs in the Rio Grande Basin below Lobatos and above Caballo Reservoir shall be equipped, maintained and operated by New Mexico in cooperation with the U.S. Geological Survey to the extent that such stations are not maintained and operated by some other Federal Agency.

(c) Gaging stations on Elephant Butte Reservoir and on Caballo Reservoir, and the stream gaging stations on the Rio Grande below those reservoirs shall be equipped, maintained and operated by or on behalf of Texas through the agency of the U.S. Bureau of Reclamation.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

19

a a stanting of the

رس بعانية خلومتيه لمعروضه بنار والمنتسب في الم

0**93**00

RIO GRANDE COMPACT COMMISSION REPORT

The equipment, method and frequency of measurements at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Water-stage recorders on the reservoirs specifically named in Article II of the Compact shall have sufficient range below maximum reservoir level to record major fluctuations in storage. Staff gages may be used to determine fluctuations below the range of the water-stage recorders on these and other large reservoirs, and staff gages may be used upon approval of the Commission in lieu of water-stage recorders on small reservoirs, provided that the frequency of observation is sufficient in each case to establish any material changes in water levels in such reservoirs.

RESERVOIR CAPACITIES /1_

Colorado shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin above Lobatos constructed after 1937; New Mexico shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin between Lobatos and San Marcial constructed after 1929; and Texas shall file with the Commission tables of areas and capacities for Elephant Butte Reservoir and for all other reservoirs actually available for the storage of water between Elephant Butte and the first diversion to lands under the Rio Grande Project.

Whenever it shall appear that any table of areas and capacities is in error by more than five per cent, the Commission shall use its best efforts to have a re-survey made and a corrected table of areas and capacities to be substituted as soon as practicable. To the end that the Elephant Butte effective supply may be computed accurately, the Commission shall use its best efforts to have the rate of accumulation and the place of deposition of silt in Elephant Butte Reservoir checked at least every three years.

ACTUAL SPILL /2

(a) Water released from Elephant Butte in excess of Project requirements, which is currently passed through Caballo Reservoir, prior to the time of spill, shall be deemed to have been Usable Water released in anticipation of spill, or Credit Water if such release shall have been authorized.

71 Amended at Eleventh Annual Meeting, February 23, 1950.
72 Adopted at Fourth Annual Meeting, February 24, 1943.

RULES AND REGULATIONS

(b) Excess releases from Elephant Butte Reservoir, as defined in (a) above, shall be added to the quantity of water actually in storage in that reservoir, and Actual Spill shall be deemed to have commenced when this sum equals the total physical capacity of that reservoir, to the level of the uncontrolled spillway, i.e. -2,219,000 acreft in 1942.

(c) All water actually spilled at Elephant Butte Reservoir, or released therefrom, in excess of Project requirements, which is currently passed through Caballo Reservoir, after the time of spill, shall be considered as Actual Spill, provided that the total quantity of water then in storage in Elephant Butte Reservoir exceeds the physical capacity of that reservoir at the level of the sill of the spillway gates, i.e.-1,830,000 acre-ft in 1942.

(d) Water released from Caballo Reservoir in excess of Project requirements and in excess of water currently released from Elephant Butte Reservoir, shall be deemed Usable Water released, excepting only flood water entering Caballo Reservoir from tributaries below Elephant Butte Reservoir.

DEPARTURES FROM NORMAL RELEASES /3

5

For the purpose of computing the time of Hypothetical Spill required by Article VI and for the purpose of the adjustment set forth in Article VII, no allowance shall be made for the difference between Actual and Hypothetical Evaporation, and any under-release of usable water from Project Storage in excess of 150,000 acre-ft in any year shall be taken as equal to that amount.

EVAPORATION LOSSES /4, /5, /6

The Commission shall encourage the equipping, maintenance and operation, in cooperation with the U.S. Weather Bureau or other appropriate agency, of evaporation stations at Elephant Butte Reservoir and at or near each major reservoir in the Rio Grande Basin within Colorado constructed after 1937 and in New Mexico constructed after 1929. The net loss by evaporation from a reservoir surface shall be taken as the difference between the actual evaporation loss and the evapo-transpiration losses which would have occurred naturally, prior to the construction of such reservoir. Changes in evapo-transpiration losses along stream channels below reservoirs may be disregarded.

Adopted June 2, 1959; made effective January 1, 1952.
 Amended at Tenth Annual Meeting, February 15, 1949.
 Amended at Twelfth Annual Meeting, February 24, 1951.
 Amended June 2, 1959.

RIO GRANDE COMPACT COMMISSION REPORT

Net losses by evaporation, as defined above, shall be used in correcting Index Supplies for the operation of reservoirs upstream from Index Gaging Stations as required by the provisions of Article III and Article IV of the Compact.

In the application of the provisions of the last unnumbered paragraph of Article VI of the Compact:

(a) Evaporation losses for which accrued credits shall be reduced shall be taken as the difference between the gross evaporation from the water surface of Elephant Butte Reservoir and rainfall on the same surface.

(b) Evaporation losses for which accrued debits shall be reduced shall be taken as the net loss by evaporation as defined in the first paragraph.

ADJUSTMENT OF RECORDS

The Commission shall keep a record of the location, and description of each gaging station and evaporation station, and, in the event of change in location of any stream gaging station for any reason, it shall ascertain the increment in flow or decrease in flow between such locations for all stages. Wherever practicable, concurrent records shall be obtained for one year before abandonment of the previous station.

NEW OR INCREASED DEPLETIONS

In the event any works are constructed which alter or may be expected to alter the flow at any of the Index Gaging Stations mentioned in the Compact, or which may otherwise necessitate adjustments in the application of the schedules set forth in the Compact, it shall be the duty of the Commissioner specifically concerned to file with the Commission all available information pertaining thereto, and appropriate adjustments shall be made in accordance with the terms of the Compact; provided, however, that any such adjustments shall in no way increase the burden imposed upon Colorado or New Mexico under the schedules of deliveries established by the Compact.

TRANSMOUNTAIN DIVERSIONS

In the event_any works are constructed for the delivery of waters into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, such waters shall be measured at the point of delivery into the Rio Grande Basin and proper allowances shall be made for losses in transit from such points to the Index Gaging Station on the stream with which the imported waters are

QUALITY OF WATER

In the event that delivery of water is made from the Closed Basin into the Rio Grande, sufficient samples of such water shall be analyzed to ascertain whether the quality thereof is within the limits established by the Compact.

SECRETARY /7

The Commission, subject to the approval of the Director, U.S. Geological Survey, to a cooperative agreement for such purposes shall employ the U.S. Geological Survey on a yearly basis, to render such engineering and clerical aid as may reasonably be necessary for administration of the Compact. Said agreement shall provide that the Geological Survey shall:

(1) Collect and correlate all factual data and other records having a material bearing on the administration of the Compact and keep each Commissioner advised thereof.

(2) Inspect all gaging stations required for administration of the Compact and make recommendations to the Commission as to any changes or improvements in methods of measurement or facilities for measurement which may be needed to insure that reliable records be obtained.

(3) Report to each Commissioner by letter on or before the fifteenth day of each month, except January a summary of all hydrographic data then available for the current year - on forms prescribed by the Commission pertaining to:

- (a) Deliveries by Colorado
- (b) Deliveries by New Mexico
- (c) Operation of Project Storage

(4) Make such investigations as may be requested by the Commission in aid of its administration of the Compact.

(5) Act as Secretary to the Commission and submit to the Commission at its regular meeting in February a report on its activities and a summary of all data needed for determination of debits and credits and other matters pertaining to administration of the Compact.

7 The substitution of this section for the section titled "Reports to Commissioners" was adopted at Ninth Annual Meeting, February 22, 1948. RIO GRANDE COMPACT COMMISSION REPORT

COSTS /1

24

In February of each year, the Commission shall adopt a budget for the ensuing fiscal year beginning July first.

Such budget shall set forth the total cost of maintenance and operating of gaging stations, of evaporation stations, the cost of engineering and clerical aid, and all other necessary expenses excepting the salaries and personal expenses of the Rio Grande Compact Commissioners.

Contributions made directly by the United States and the cost of services rendered by the United States without cost shall be deducted from the total budget amount; the remainder shall then be allocated equally to Colorado, New Mexico and Texas.

Expenditures made directly by any State for purposes set forth in the budget shall be credited to that State; contributions in cash or in services by any State under a cooperative agreement with any federal agency shall be credited to such State, but the amount of the federal contribution shall not so be credited; in event any State, through contractual relationships, causes work to be done in the interest of the Commission, such State shall be credited with the cost thereof, unless such cost is borne by the United States.

Costs incurred by the Commission under any cooperative agreement between the Commission and any U.S. Government Agency, not borne by the United States, shall be apportioned equally to each State, and each Commissioner shall arrange for the prompt payment of one-third thereof by his State.

The Commissioner of each State shall report at the annual meeting each year the amount of money expended during the year by the State which he represents, as well as the portion thereof contributed by all cooperating federal agencies, and the Commission shall arrange for such proper reimbursement in cash or credits between States as may be necessary to equalize the contributions made by each State in the equipment, maintenance and operation of all gaging stations authorized by the Commission and established under the terms of the Compact.

It shall be the duty of each Commissioner to endeavor to secure from the Legislature of his State an appropriation of sufficient funds with which to meet the obligations of his State, as provided by the Compact.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

000564

1

Prover the second second and the second second second second

RULES AND REGULATIONS

MEETING OF COMMISSION 1, 8

LΩ

ය දා

> The Commission shall meet in Santa Fe, New Mexico, on the third Thursday of February of each year for the consideration and adoption of the annual report for the calendar year preceding, and for the transaction of any other business consistent with its authority; provided that the Commission may agree to meet elsewhere. Other meetings as may be deemed necessary shall be held at any time and place set by mutual agreement, for the consideration of data collected and for the transaction of any business consistent with its authority.

No action of the Commission shall be effective until approved by the Commissioner from each of the three signatory States.

(Signed) M. C. HINDERLIDER

M. C. Hinderlider Commissioner for Colorado

(Signed) THOMAS M. McCLURE

Thomas M. McClure Commissioner for New Mexico

(Signed) JULIAN P. HARRISON

Julian P. Harrison Commissioner for Texas

Adopted December 19, 1939.

/1 Amended at Eleventh Annual Meeting, February 23, 1950. /8 Amended at Thirteenth Annual Meeting, February 25, 1952.

26

and an an a star and a star a star and a star and a star

RIO GRANDE COMPACT COMMISSION REPORT

RECORDS OF DELIVERIES AND RELEASES

At the annual meeting of the Compact Commission on March 26, 1981 the records of deliveries and releases for calendar year 1980 were examined and the computations of debits and credits based thereon were reviewed. The records and computations as reviewed by the Commission are reproduced on the next three pages. 1

The delivery of water in the Rio Grande at the Colorado-New Mexico State line was obtained from record of streamflow near Lobatos, Colorado; the obligation of Colorado to deliver water at the State line was computed as prescribed in Article III. Item C5, the Reduction of Debits prescribed in Article VI, was computed in accordance with the Rules and Regulations.

The delivery of water by New Mexico to Project Storage was computed from the actual streamflow record and the record of operation of Elephant Butte Reservoir; the scheduled delivery was computed as prescribed in the Resolution of the Commission adopted at the Tenth Annual Meeting, and published in this report. Item NM4, Reduction of Debits by Evaporation, was computed in accordance with the Rules and Regulations. The creation of a minimum recreation pool in Elephant Butte Reservoir was initiated in December 1975 and is in accordance with a resolution adopted May 3, 1974.

The actual release from Project Storage during the year was measured at gaging stations below Caballo Dam. The Accrued Departure from Normal Release is an under-release but is ommitted in accordance with a decision of the Commission at the meeting on February 15, 1968.

NIO GRANDE COMPACT

ı.

I

I

100500 (F

DELIVERIES DY COLORADO AT STATE LINE

YEAN, 1980

Quantifies in Thousands of Acre fant to

					ປ	I SOLTING	NDPX SUF	y I qc		ļ			Kal in Madresi	Rundred										
	L	-/	MEASUNEE	LIOV										9V 9	GRANDE	INDEX SU	PPLY				DELIVE	2414		
Ň		F						SINCUIS			JPPLY	<u></u>		-	IN-JWL SN CO			i				1100		_
	50		30	CAN				12	1		0	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							11	24 V	N.			
	OL 3NO.,	10000H		0196 462 14 217/90	10146	HTHOM HTHOM	CHANGE IN STORAGE		NJWISALAV 198	NINON NI ATJJANS	ICCUMULATE: DTAL	גיור מנד וא יר-כסרימרים	100,466 1 END OF 0,011H	06446F	SNOISVQ NIVINRONSNI	ארית ארית ארית	INGMITOU	11H БГА	זאטראדרס זי	105 AIVE 00145 105 2002	ENOS VINE	102 Cvynof-	0.01416 201430	
-	Ľ		~	-	5	ľ	-				;	N V	114 15	LS N1 10	נגיו נגיו	10 10	ro# .7N	902 10 10	101 101	CONI M TA MEAN	000 5531 140	AIO 1 14 14 10 00	40224 10701 01 14	
		$\left \frac{1}{1} \right $				a 20 5		, 		•	=	2	5	Ŧ	2	2	=	g	<u> </u>	V.				
	ſ	+	╋								\$		1.5							3	5	22	ຂ	_
!		·			2.4	² 30.5	0	0	0	2.4	2.4	10 3	-		,				\$				¢	_
e	~	~	-		3.2	^a 30.5	0	0	0	C.E				-			•	12.3	12, 3	3.0	14.0	17.0	17.0	
MAA	4				4.1	30.7	+ 5	0	+			77	I.S	•			0	12.7	25.0	3.9	15.6	19.5	36.5	
A A	22.	<u>م</u>	6.5	5.2	34.6	^a 20.6	-10.1	-			~~~	13.2	1.5	•			0	13.2	38.2	5.3	17.9			
MAY	65.	5	49.5	20.3	135.3	14.2	- 9-9-	> -		24.5	34.4	33.3	1.5	-			0	33.3	71.5	C-12	2 0 0	7 ° ° ′		
Ę	109.	 	44.6	2.6	156.8	, , ,	1 0 10	+	E.0-	129.0	163.4	155.0	1.5	0				155.0	226 5			7 74	6.101	
3		┼.	+-			2	9./24	+ .2	+28.0	184.8	348.2	295.6	1.5	0		, , , , , , , , , , , , , , , , , , ,				7.1	2.2	134.7	236.6	
{	i		20		51.8	36.4	-5.6	+	-5.5	46.3	394.5	130 8		, ,		-+	6° 1	294.7	521.2	68.1	68.4	136.5	373.1	
¥	25.		1.6	0	27.4	19.7	-16.7	: +	-16.6	8.01	4 US			•			-	130.8	652.0	24.5	14.7	39.2	412.3	
۶.	<u>ق</u>	•	0.1	0	7.0	19.7	0	+	+	-	C. C.	1.05	1.5	•			•	30.7	682.7	7.8	2.9	10.7	423.0	
8	m		1.0		4.6	19.7	0	 -+		; ; ;	+ 77+	27.3	1.5	•		-	0	27.3	710.0	1.0	1.1	2	1 2 6	
≩	е П	-			3.0	19.6		+			1.1.4	16.1	1.5	0			0	16.1	726.1	17.	0.1		26.0	
¥	5.5	-			2.5	19.7		0			1.024	11.6	1.5	0	= +		-	11.6	737.7		5.6	6		
YEAR	293.4	11	11.0	28.3 4	32.7		-10.8	8.0			1.224	12.4	1.5	-			0	12.4	1.00.1	3.2	14.4			
Ment.	95 St	Crage Tued C	in reci	reation	al rese	rvoirs nt	ot inclu	ded. St		1.12		751.0		0	-1.2	+0.3	6.	750.1	5	12.1	39.65	451.7		
				aur rug	. 1980 ec	quals ze,	ro. Bal.	ance ren	uaining .	is 51,00	lnquísh- O acre_f					SUWMAI	년 이 전	DITS AND C	A FDITS					
а́д́	36t fmat ,484 a	ed. cre-fe	et minu	a 243	BCTE-fee	t ave				•		• <u> </u>											7	
	vapora	tion 1	038 p08	t-comp	act rese	Troirs.	mpact.						CIDAN	ice of Deginn	ing of Year				5	3	101	DALANCE	<u> </u>	
												╧┷╼	C2 + Srle	duled Deliver	V from Cone jo	05 Niver			208.0			r 6	29-3	
												μĨ	C4 Actua	if Delivery al	Lobatos plus	Urande 5 10 000 Arra	Faat		229 1				1	
												<u> </u>	C5 Acduc	then of Debi	ts a'r Evepore	5				461			1 - 7	
												1	C6 P.c3uc	ction of Cred	its is two or	attoo .				-				

RECORDS OF DELIVERIES AND RELEASES

27

674.6

Evaporation

90 ൗ

Dolance of the of

10 A.

Ż

.

Ľ

RIO GRANDE COMPACT

i

DELIVERIES BY NEW MEXICO AT ELEPHANT BUTTE

YEAR 1980

Quuntities in Thousands of Acre Feet to Nearest Mundred

						100110	>			Total Water	ELEP	HANT BUT	TE EFFEC	TIVE SUPP	
			10	IMO					T	Stored in	STORAG	E IN	Recorded	CEECTIVE	SUPPLY
<u>, </u>	Recorded			ADJUS'	TMENTS			INDEX S	SUPPLY	New Mexico	ELEPHANT RESER	BUTTE VOIR	Flow Below		
MONTH	Flow	RESERVOI	IRS: LOBATOS 14	010WI						San Marcial at End of		Change	Elephoni	001200	comulated
	Otowi	Storage -	Change	Reservoir	Other	Tra ns- mountain	Ne:	During	Accumulated	Month	Month		Dom	Month	olal
	Bridge	Month	Storage	Evoporation	Adjustments	Diversions	Adjustment	Month	01	===	12	13	14	15	16
-	2	£	4	2	9			,							
		^a 50.1								50.7	5-049 		49.9	42.3	42.3
NĂIJ	41.7	51.5	+1.4	+0.2		+0.1	+1.7	43.4	43.4	2.26	004.7	- 7 E -	56.7	53.3	95.6
FEB	49.8	53.4	+1.9	+ •2		+	+2.2	52.0	95.4	C.+C	0 3 5 0	737.3	1.8	39.1	134.7
MAR	62.6	50.2	-3.2	+ 2			-6.0	56.6	152.0	8.02	0.016		107.9	763	211.0
APR	157 0	70.6	+20.4	+		2	+20.4	173.3	325.3	82.0	885.9	2°05 -	9 L 1	7 904	\$10.4
MAY	247CT	177.9	+107.3	+1.2		0	+108.5	499.0	824.3	198.0	1.067.5	+181.6	0 • / 11	0 3/0	6 922
				73 B	1.0+ ^d < :	0	80 1	352.8	1,177.1	176.0	1,227.1	+159.6	106.2	0.02	7 0 7
NUL	353.6	1/4.2				5 71	1.02.	78.1	1,225.2	145.7	1,194.4	-32.7	85.7	53.0	829.2
JUL	120.2	144.9	-29.3		-				1 284 6	143.7	1,115.0	-79.4	81.2	1.8	831.0
AUG	48.4	143.1	-1.8	+1.2		-18.4	0.61-	73.4	2 202 7	14.3 0	1.125.3	+10.3	14.2	24.5	855.5
SEPT	32.5	142.5	- 9	+1.1	+-	-15.7	-15.2	17.3	1010		100 8	-15.5	80	-14.7	840.8
00.1	30.2	141.4	-1.1	+1.0		6-6-	-10.0	20.2	1,322.1	1 00 1	1 159.5	7-67+	2.5	52.2	893.0
NON NON	77.1	91.0	-50.4	7. +		+	-49-9	27.2	1,349.3	1.26		+14.6	59.4	74.0	967.0
DEC	85.5	49.9	-41.1	+ .2		-1.7	-42.6	42.9	1,392.2	+• TC		A. F.8C+	683.4	967.0	
YEAR	1,445.0		-0.2	+10.4	9	1	-52.8	1 1, 392.2		 		L DERITS AN	AD CREDITS		
AF N	AFKS. SEOF	rage in recr	eational re	servoirs no	st included.	Cols. 3,	11 & 12 inc	ude only						1030-	A ALANCE
Rio	Grande watei	r in storage	•							-	TEM		DEBI		1.29.1
حدي	the set of	apacity tabl	le for Abiqu	ilu Reservo:	ir effective	Jan. 1, 1	980.		NM I BOID	חרכה כו אבקותהות	of Year		988.3		1.117.4
a. 5	Annual evap	oration loss	s from recre	estional re	servoirs.				NM 2 SCH	eduled Del ery of	e Effective Supp			967.0	n 150.4
									A M A	Juction of Debils	Vic Exaporation			1	
يتدرين									2 1 0 M Z	JUCTION OF LIEU.					

Balance of End of Year

8 W N

RIO GRANDE COMPACT COMMISSION REPORT

28

00268

1. The metal and the metal we address to the

NIO GNANDE COMPACT Réléase and spill fnom project storage

ī

i

YC15, 1980_

Ouchitics in thousands of Acre Feet to Nearest Hundred

_						RECO	RDS	OF	DEL.	VER	IES	AND	REI	LEAS	ES												
	NELEASE	ACCUMULATED TOTAL		Ð	\$	7.4	26.5	116.4	192.3	277.5		196.7	523.4	617.9	659.0	659.1	6 659		د. برده			Lauce	4	Ì			
	UCABLE	NCT BUNING BONTH		3		7.4	19.1	89.9	75.9	85.2	C 011	7 617	120.7	94.5	41.1	.1	-	-	:	659.3		10					_
l v	AGE	USABLE		2		0	0	0	0	0		-		•	0	0	0	c	,	0	ILLASE	CNEE			-	 +	
DALLO DAN	FLOM STCIN	CAEDIT VATER		٩		0	0	0	0	0			5	0	0	Q	0	c	, ,		I NONMAL NO	DEDI					
DELOV CA	SPILL	CABALLO FLOOD VATEN		<u>∽</u>		0	0	0	0	0	c	, c	,	0	0	0	_	0		 >	JUNE FROM						
GNANDE (Netese Auto Sree		2		7.4	19.1	89.9	75.9	85.2	119.2	196.7		5*46	41.1	.1	.1	.1	KEN 3	£*60	NUED DEPAR		cor			utte Neservoir	porture
QŽ		DIVENSIONS TO CANALS	-	<u>•</u>		0	•	-	0	.1	.2		•	-	•	0	Ð	0	4		ACCT	ITEM.	Deginning of Y	A Kar	Year	tom trepnent D	
		AT CADALLO GAGING STATION	5	21		7.4	19.1	89.8	75.9	85.1	119.0	126.6	i i	74.4	41.1		•1	.1	65R 7	1.000			ued Departure at	ol Neleose duri	al helease for	oration loss if	
	MICA	PROJECT STONAGE AT END OF MONTH	-	=	964.1	8.966	1,027.6	977.4	978.4	1,183.7	1,322,5	1,243,1	1 155 0		1,142.5	0,0E1,1	1,184,1	1,257.3					PI Accr	PC Actu		PS I Ever	2 8
	IN STONAGE	CADALLO ALSERVOIA AT END OF HOUTH	ç	2		5	5	•	0	0	0	0	c	> «	5	0	0	0						2000			
STONAGE		AT FND OF MONTH	n		> c		>	0	0	0	0	0				0	0	0				storage d ity which	12, 1960	dind toin			
VALEN IN		LAFT TEXICO	•	c				0	•	0	0	0	0			0	0	0			rage.	oir capac	r of Feb. Flood cor			ear.	
CNEDIT			-	с	, c			5	0	0	0	0	0	-	, ,	0	0	0			ter in sto	a portion llo Reserv) by lette tion for	107 107 1		centire y	
INTEL FO	CAPACITY	TROJECT STORAGE AT END OF MONTH	6	1.489.3	1.454.6	1.425.8	0 9 2 4	1,4/0.0	1,475.0	1,269.7	1,030.9	1,110.3	1,197.6	P 016 1		1,323.4	1,269.3	1,196.1			brance wai	t of Cabal	ectamation of Reclams		.	e-feet for	
STONAGE		AT THE CF MONTH	2	964.1	998.8	1,027.6	1 670	+•//2	978.4	1,183.7	1,322.5	1,243.1	1,155.8	1.142.5	0 06 1 1	1°001 °1	1,184.1	1,257.3		orlu Die	outy Atto	asc and r acre-fee	e Bureau		y 15, 196	0,000 acr	
VATEN IN		SECTION SECTION	4	73.6	115.9	148,1	YU Y	••••	92.5	116.2	95.4	48.7	40.8	17.2		7.03	24.6	83.2		include	tinct stor	ie 100,000	ate by th	к 1. ́	ig Februar	ceeded 40	
USADLF	ELEPRANT	butte Nesenvo: A	Ŷ	890.5	882.9	879.5	916.8		6 283	1,067.5	1,227.1	1,194.4	1,115.0	1,125.3	1 100 R	D	1,159.5	1,174,1		3. 5 6 11	ies of Pro	any of th	eld inviol	to Octobe	of meetin	storage ex	
TOTAL	PROJECT STONAGE CAPACITY	AVAILADET AT END OF MONTH	61	2,453.4	2,453.4	2,453.4	2.453.4		4,004,4	2,403.4	2,353.4	⁸ 2,353.4	^a 2,353.4	^a 2,353.4	2.453.4		4.604.5	2,453.4		ic. Cola	e quantity	t include	ated is he	om June 1	e minutes	-Project :	
	N. NON		-		NAL.	4) 12:	K K K				XOL	Jar	DUA	StPT	130			ц Ц	YEAR	KEN1A K	dT -B	54	st	fr	b. Se	Note.=	

29

TIME OF KYPOTHETICAL SPILL

Accruzed Departure of End of Year

14

.



RIO GRANDE COMPACT COMMISSION REPORT

COST OF OPERATION, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1980

Adopted at the Forty-second Annual Meeting

Item		Total cost	Borne by	-	Borne by	
1 Cem			United States	Colorado	New Mexico	Texas
GAGING STATIONS In Colorado In New Mexico, abov	2	18,000	9,000	9,000	8,400	
Caballo Reservoi In New Mexico, Caba Reservoir and be	llo low	10,200	600		600	9,000
	Subtotal	51,200	24,200	9,000	9,000	9,000
ADMINISTRATION U.S.G.S. Contract		11,760	2,940	2 ,94 0 677	2,940	2,940 <u>677</u>
Other expense	Cubbotal	13 791	2,940	3,617	3,617	3,617
	Subtorar	64 991	27.140	12,617	12,617	12,617
GRAND TOTAL		04/321		12,617	12,617	12,617
EQUAL SHARES OF STATES CASH ADJUSTMENT BETWEE	N STATES			0	0	0

BUDGET, IN DOLLARS, FOR FISCAL YEAR ENDING JUNE 30, 1982

Adopted at the Forty-second Annual Meeting

		Total cost	Borne by		Borne by			
Item			United States	Colorado	New Mexico	Texas		
GAGING STATIONS In Colorado In New Mexico, above Caballo Reservoin In New Mexico, Caba Reservoir and be	llo Llow	20,860 26,620 11,830	10,430 16,890 700	10,430	9,730 700	10,430		
	Subtotal	59,310	28,020	10,430	10,450	10/100		
ADMINISTRATION U.S.G.S. Contract		13,000	3,250	3,250 800	3,250 800	3,250 800		
Other expense	1	15.400	3,250	4,050	4,050	4,050		
	Subtotal	74 710	31,270	14,480	14,480	14,480		
GRAND TOTAL			-	14,480	14,480	14,480		
EQUAL SHARES OF STATES CASH ADJUSTMENT BETWEEN STATES			-	0	0	0		

ACKNOWLEDGMENTS

The water-supply data contained in this report have been furnished by various Federal and State Agencies.

The office of the State Engineer of Colorado furnished records of discharge for the following:

Rio Grande near Del Norte, Colo. Conejos River below Platoro Reservoir, Colo. Conejos River near Mogote, Colo. San Antonio River at Ortiz, Colo. Los Pinos River near Ortiz, Colo. Conejos River near Lasauses, Colo. Rio Grande near Lobatos, Colo.

< 0

Records of 6 transmountain diversions and of storage in Squaw and Shaw Lakes, Rito Hondo, Hermit Lakes Reservoir No. 3, Troutvale No. 2, Jumper Creek, Alberta Park, Big Meadows, Mill Creek, Fuchs, and Trujillo Meadows Reservoirs were also furnished by the office of the State Engineer of Colorado.

The U.S. Bureau of Reclamation, Albuquerque, N. Mex., furnished the following records:

Storage in Platoro Reservoir at Platoro, Colo. Azotea tunnel at outlet, near Chama, N. Mex. Willow Creek above Heron Res., near Los Ojos, N. Mex. Horse Lake Creek above Heron Res., near Los Ojos, N. Mex. Storage in Heron Reservoir near Los Ojos, N. Mex. Willow Creek below Heron Dam, N. Mex. Storage in El Vado Reservoir near Tierra Amarilla, N. Mex. Storage in Nambe Falls Reservoir near Nambe, N. Mex. Rio Nambe below Nambe Falls Dam, near Nambe, N. Mex.

The U.S. Geological Survey supplied the record for Rio Grande below Elephant Butte Dam, and in cooperation with the New Mexico Interstate Stream Commission, also furnished the following:

Rio Chama below El Vado Dam, N. Mex. Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex. Storage in McClure Reservoir near Santa Fe, N. Mex. Santa Fe River near Santa Fe N. Mex. Storage in Nichols Reservoir near Santa Fe, N. Mex.

The Corps of Engineers, Albuquerque, N. Mex., furnished the records of storage in Abiquiu, Galisteo, and Jemez Canyon Reservoirs and in Cochiti Lake and, in cooperation with the U.S. Geological Survey, also furnished the records for Rio Chama below Abiquiu Dam, Rio Grande below Cochiti Dam, Galisteo Creek below Galisteo Dam, and Jemez River below Jemez Canyon Dam, N. Mex.

The New Mexico Interstate Stream Commission furnished the record of storage in San Gregorio Reservoir.

The Southern Pueblos Agency, Albuquerque, N. Mex., supplied the records of storage in Acomita and Seama Reservoirs.

The U.S. Bureau of Reclamation, El Paso, Texas, furnished the following records:

Storage in Elephant Butte Reservoir at Elephant Butte, N. Mex. Storage in Caballo Reservoir near Arrey, N. Mex. Rio Grande below Caballo Dam, N. Mex. Bonito ditch below Caballo Dam, N. Mex.

The Rio Grande Compact Commission gratefully acknowledges the cooperation received from these agencies.

31

E William Margaria Constraint and a survey and a survey of the second second second second second second second

00272

32

RIO GRANDE COMPACT COMMISSION REPORT

ACCURACY OF RECORDS

The Rules and Regulations of the Commission state that the equipment, method, and frequency of measurement at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Within the physical limitations of stream gaging, the agencies obtaining the records at Compact gaging stations have complied with these regulations.

The accuracy of discharge data depends primarily on (1) the stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements, and (2) the accuracy of observations of stage, measurements of discharge, and interpretation of records.

The station description states the degree of accuracy of the daily records. "Excellent" means that about 95 percent of the daily discharges are considered to be within 5 percent of true value; "good" within 10 percent; and "fair" within 15 percent. "Poor" means that daily discharges have less than "fair" accuracy.

The phrase "within 5% of true value" used to "qualify "excellent" records establishes the extremes of the probable errors for 95% of the days in a given period of time. The word "within" defines the range of errors with individual daily values falling between 95% and 105% of true value. The probable error in a monthly or annual mean discharge depends more on the distribution of the daily errors between these two limits than it does on the limits themselves. For this reason monthly and annual records are much more accurate than most daily records.

STREAMFLOW

Rio Grande near Del Norte, Colo.

Location.--Water-stage recorder, lat 37°41'22", long 106°27'38", in NW% sec. 29, T. 40 N., R. 5 E., on right bank, 20 ft downstream from county highway bridge, 6 miles west of Del Norte, and 6.8 miles upstream from Pinos Creek. Datum of gage is 7,980.25 ft above mean sea level, datum of 1929. Prior to May 16, 1908, staff gage at site 4 miles downstream. Records are equivalent.

Drainage area.--1,320 sq mi, approximately.

Average discharge.--91 years (1890-1980), 898 ft³/s (650,600 acre-ft per year).

Extremes.--1889-1980: Maximum discharge, 18,000 ft³/s Oct. 5, 1911 (gage height, 6.80 ft), from rating curve extended above 12,900 ft³/s; minimum daily, 69 ft³/s Aug. 21, 1902.

Remarks.--Records good except those for winter months, which are fair. Flow regulated by four reservoirs, total capacity 126,100 acre-ft, and by several smaller ones. Six transmountain diversions import water into basin above station.

Monthly and yearly discharge, in cubic feet per second

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October November December	6,195 6,428 6,641 16,794 78,130 149,020 65,950 15,495 13,743 8,133 5,866 6,251	225 240 231 1,250 4,870 7,250 3,150 1,150 1,150 1,190 340 235 227	180 200 198 185 1,120 3,140 1,220 286 310 208 160 146	200 222 214 560 2,520 4,967 2,127 500 458 262 196	12,290 12,750 13,170 33,310 155,000 295,600 130,800 30,730 27,260 16,130 11,640
alendar year 1980	378,646	7,250	146	1,035	751,000

Conejos River below Platoro Reservoir, Colo.

Location.--Water-stage recorder and concrete control, lat 37°21'18", long 106°32'37", in NWANWA sec. 22, T. 36 N., R. 4 E., on left bank 1,100 ft downstream from valve house for Platoro Reservoir, and 0.7 mile northwest of Platoro. Datum of gage is 9,866.60 ft above mean sea

Drainage_area.--40 sq mi, approximately.

Average discharge.--28 years (1953-80), 89.1 ft³/s (64,550 acre-ft per year).

Extremes.--1952-80: Maximum discharge, 1,160 ft³/s Nov. 1, 1957; maximum gage height, 4.29 ft June 15, 1958; no flow Oct. 16-20, 1955.

Remarks. -- Records good except those for winter months, which are fair. No diversions above station. Flow completely regulated by Platoro Reservoir (capacity, 60,000 acre-ft).

		in cur	old feet per se	cond	
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January Feburary March April May June July August September October November December	155.0 400.0 465 6,112 8,536 9,403.6 10,637 9,803.4 1,024.7 300.9 390.2 240.3	5.0 15 15 640 627 586 532 434 161 28 20 12	5.0 5.0 15 15 30 7.8 76 7.4 7.8 6.4 5.8 3.5	5.00 13.8 15.0 204 275 313 343 316 34.2 9.71 13.0 7.75	307 793 922 12,120 16,930 18,650 21,100 19,450 2,030 597 774 477
Calendar year 1980	47,468.1	640	3.5	130	94,150

Monthly and yearly discharge, in cubic

1 ((

and the lot and the second second and a second

34

RIO GRANDE COMPACT COMMISSION REPORT

Conejos River near Mogote, Colo.

Location.--Water-stage recorder, lat 37°03'14", long 106°11'13", in SEASEA sec. 34, T. 33 N., R. 7 E., on right bank 25 ft upstream from bridge on State Highway 174, 0.4 mile downstream from Fox Creek, and 5.3 miles west of Mogote. Datum of gage is 8,271.54 ft above mean sea level.

Drainage area.--282 sq mi.

Average discharge.--70 years (1904, 1912-80), 329 ft³/s (238,400 acre-ft per year).

Extremes.--1903-05, 1911-80: Maximum discharge, 9,000 ft³/s Oct. 5, 1911 (gage height, 8.50 ft), from rating curve extended above 3,100 ft³/s; minimum daily determined, 10 ft³/s July 18, 1904.

Remarks.--Records good except those for winter months, which are fair. Diversions above station for irrigation of about 500 acres. Since 1951 flow partly regulated by Platoro Reservoir.

Мс	onthly and yearly d	ischarge, in cu	bic feet per	second	
Month .	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May 33,000 June 55,270 July 22,607 August September October November December	1,206 1,592 2,043 11,557 1,800 2,470 1,460 13,019 3,037 1,775 1,519 1,275	48 48 77 1,060 579 1,420 316 579 336 77 68 50	32 32 59 53 1,065 1,842 729 82 57 48 30 37	38.9 38.9 65.9 385 65,460 109,600 44,840 420 101 57.3 50.6 41.1	2,390 2,390 4,050 22,920 25,820 6,020 3,520 3,010 2,530
Calendar year 1980	147,900	2,470	30	404	293,400

San Antonio River at Ortiz, Colo.

Location.--Water-stage recorder, lat 36°59'35", long 106°02'17", in New Mexico in NE%SE%, sec. 24, T. 32 N., R. 8 E., on left bank 800 ft south of New Mexico-Colorado State line, 0.4 mile southeast of Ortiz, and 0.4 mile upstream from Los Pinos River. Altitude of gage is 7,970 ft.

Drainage area.--110 sq mi.

Average discharge.--40 years (1941-80), 25.0 ft³/s (18,110 acre-ft per year).

Extremes.--1920, 1925-80: Maximum discharge, 1,750 ft³/s Apr. 15, 1937 (gage height, 5.38 ft), from rating curve extended above 1,100 ft³/s; no flow at times.

Rémarks.--Records good except those for winter months, which are fair. A few small diversions above station for irrigation.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	111.0 141.0 181.3 2,621.0 10,257 1,288.8 32.77 0 0 55.1 88.7 111.4	5.0 6.0 7.0 295 612 135 4.0 0 0 4.5 4.5 5.0	2.0 4.0 5.0 5.2 148 4.2 0 0 0 0 0 1.4 2.4	3.58 4.86 5.85 87.4 331 43.0 1.06 0 0 1.78 2.96 3.59	220 280 360 5,200 20,340 2,560 65 0 0 109 176 221
Calendar year 1980	14,888.07	612	0	40.7	29,530

which we want wischarge, in cubic feet per second

STREAMFLOW

Los Pinos River near Ortiz, Colo.

Location.--Water-stage recorder, lat 36°58'56", long 106°04'23", in New Mexico on line between secs. 26 and 27, T. 32 N., R. 8 E., on left bank 0.9 mile south of New Mexico-Colorado State line, 2.1 miles southwest of Ortiz, and 2.9 miles upstream from mouth. Altitude of gage is 8,040 ft.

Drainage area -- 167 sq mi.

N. Sold Manager

Average discharge.--62 years (1915-20, 1925-80), 120 ft³/s (86,940 acre-ft per year).

Extremes.--1915-20, 1925-80: Maximum discharge, 3,160 ft³/s May 12, 1941 (gage height, 5.77 ft, site and datum then in use), from rating curve extended above 1,600 ft³/s; minimum observed, 4.0 ft³/s Dec. 17, 1945.

Remarks .-- Records good except those for winter months, which are fair. Diversions above station

		discharge, in c	ubic feet per s	econd	
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September Dctober November December	444 579 641 3,303 790 528 491 551 551 543	17 26 25 382 24,955 22,468 3,436 33 33 23 24 22	11 15 16 18 1,340 1,150 326 17 11 12 15 14	14.3 20.0 20.7 110 309 312 34 25.5 17.6 15.8 18.4 17.5	881 1,150 1,270 6,550 805 49,500 749 44,570 111 6,820 1,570 1,050 974 1,090 1,080
atendar year 1980	58,729	1,340	11	160	116,500

Monthly and yearly discharge in . .

Conejos River near Lasauses, Colo.

Location.--Water-stage recorders lat 37°18'01", long 105°44'47", in secs. 2 and 11 (two channels), T. 35 N., R. 11 E., on left bank of main channel 125 feet downstream from bridge on State Highway 158 and on left bank of secondary channel 230 ft upstream from bridge, 1.0 mile upstream from mouth, and 2.1 miles north of Lasauses. Datum of gage on main channel is 7,495.02 ft and on secondary (south) channel is 7,496.89 ft above mean sea level (levels by Bureau of Reclamation).

Drainage area .-- 887 sq mi.

Average discharge.--59 years (1922-80), 182 ft³/s (131,900 acre-ft per year).

Extremes.--1921-80: Maximum discharge, 3,890 ft³/s May 15, 1941; no flow at times in some years.

Remarks. -- Records good except those for winter months, which are fair. Diversions for irrigation of

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July Sugust September Setober Ovember Secomber	1,488 1,939 2,690 10,938 35,879 34,325 12,371 3,941 511.6 350.0 865 1,631	64 99 98 1,160 1,510 1,550 965 289 126 14 56 64	32 48 76 68 692 722 136 18 7.1 7.7 14	48.0 66.9 86.8 365 1,157 1,144 399 127 17.1 11.3 28.8	2,950 3,850 5,340 21,700 71,170 68,080 24,540 7,820 1,010 694 1,720
alendar year 1980	106,928.6	1,550		292	3,240

Monthly and yearly discharge, in

35

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande near Lobatos, Colo.

Location.--Water-stage recorder, lat 37°04'42", long 105°45'22", in sec. 22, T. 33 N., R. 11 E., on right bank just downstream from highway bridge, 6 miles north of Colorado-New Mexico State line, 10 miles east of Lobatos, and 14 miles east of Antonito. Datum of gage is 7,427.63 ft above mean sea level, datum 1929.

Drainage area.--7,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley).

Average discharge.--31 years (1900-30), 846 ft³/s (598,400 acre-ft per year); 50 years (1931-80) $\frac{115 \text{ ft}^3}{300,700}$ acre-ft per year).

Extremes.--1899-1980: Maximum discharge observed, 13,200 ft³/s June 8, 1905, (gage height, 9.1 ft), from rating curve extended above 8,000 ft³/s; no flow at times in 1950-51, 1956.

Remarks.--Records good except those for winter months, which are fair. Natural flow of stream affected by transmountain diversions, storage reservoirs, ground-water withdrawals and diversions for irrigation, and return flow from irrigated areas.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	8,570 9,815 11,690 21,280 67,890 68,810 19,748 5,376 1,057 875 3,704 8,896	330 425 410 1,570 3,060 3,140 1,320 340 154 41 275 350	200 230 345 360 1,440 1,350 238 43 17 21 40 160	276 338 377 709 2,190 2,294 637 173 35.2 28.2 123 287	17,000 19,470 23,190 42,210 134,700 136,500 39,170 10,660 2,100 1,740 7,350 17,650
Calendar year 1980	227,711	3,140	17	622	451,700

Monthly and yearly discharge, in cubic feet per second

Willow Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°44'33", long 106°37'34", in Tierra Amarilla Grant, on right bank 200 ft downstream from bridge, 0.2 mile downstream from Iron Spring Creek, 3.3 miles west of Los Ojos, and at mile 9.7. Datum of gage is 7,196.29 ft above mean sea level. Prior to Apr. 1, 1971, at site 900 ft downstream.

Drainage area.--112 sq mi.

Children Carlo H. Son Summer Martin - and - and - and -

36

Average discharge.--7 years (1963-69) 11.5 ft³/s (8,330 acre-ft per year) prior to completion of Azotea tunnel; 11 years (1970-80) 134 ft³/s (97,080 acre-ft per year) subsequent to completion of Azotea tunnel.

Extremes.--1962-80: Maximum discharge, 1,600 ft³/s Aug. 11, 1967 (gage height, 3.88 ft); no flow at times prior to 1971.

Remarks.--Records good except those for winter months, which are fair. Subsequent to Nov. 16, 1970, flow affected by transmountain diversions through Azotea tunnel. Flow in Rutheron Drain included prior to Apr. 1, 1971.

Monthly and yearly discharge,	in	cubic	feet	per	second	
-------------------------------	----	-------	------	-----	--------	--

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	7.21 54.42 672.1 16,156 23,620 29,904 8,908 1,361.8 904.8 30.26 5.52 5.74	0.30 8.5 64 1,220 1,100 1,080 842 201 302 12 .26 .34	0.18 .24 6.8 23 420 863 33 1.0 .29 .07 .13 .12	0.23 1.88 21.7 539 762 997 287 43.9 30.2 .98 .18 .19	14 108 1,330 32,050 46,850 59,310 17,670 2,700 1,790 60 11 11
Calendar year 1980	81,629.85	1,220	0.07	223	161,900

STREAMFLOW

Horse Lake Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°42'24", long 106°44'42", in Tierra Amarilla Grant, on right bank 3.7 miles northwest of Heron Dam, 7.8 miles downstream from Horse Lake, and 9.9 miles west of Los Ojos. Datum of gage is 7,188.85 ft above mean sea level. Prior to July 1, 1971, at site

Drainage area.--45 sq mi, approximately.

 ∞ 1 CN

 $\in \mathbb{R}$

C...

Average discharge.--11 years (1963-73) 1.10 ft³/s (797 acre-ft per year).

Extremes.---1963-80: Maximum discharge, 3,960 ft³/s July 30, 1968 (gage height, 4.9 ft); no flow most

Remarks. ~- Records good. Diversions above station for irrigation of meadows and for off-channel stock

			Teer ber Se	cona	
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October November Secember	- 257.9 1,214.1 127.69 .72 9.79 59.95 92.04 8.06 -	- 37 78 18 .30 3.0 6.0 6.0 2.0 -	- 2.4 5.0 .48 0 0 0 .20 .01	- 8.32 40.5 4.12 .024 .32 1.93 3.07 .26	512 2,410 253 1.4 19 119 183 16
alendar year 1980	-				
					-

Monthly and yearly discharge, in cubic feet per second

Willow Creek below Heron Dam, N. Mex.

Location.--Totalizing flowmeters, lat 36°39'56", long 106°42'12", in Tierra Amarilla Grant, in outlet conduits at Heron Dam, 0.2 mile upstream from Rio Chama, 5.1 miles northeast of El Vado Dam, and 8.7 miles southwest of Los Ojos.

Drainage area.--193 sq mi.

Average discharge.--10 years (1971-80) 92.8 ft³/s (67,230 acre-ft per year).

Extremes.--1971-80: Maximum daily discharge, 2,220 ft³/s Dec. 12, 1973; no flow at times.

Remarks.--Records excellent. Flow completely regulated by Heron Dam.

14 - 1 1 1				econa	
	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October November December	0 1,223 3,854 10,832 1,801.7 1,058 7,847 4,206 588.5 603 0 12,510	0 222 297 969 197 100 733 627 98 146 0 1,150	0 0 67 0 0 0 0 0 0 0 0 0	0 42.2 124 361 58.1 35.3 253 136 19.6 19.5 0	0 2,430 7,640 21,490 3,570 2,100 15,560 8,340 1,170 1,200 0
Calendar year 1980	44,523.2	1.150			24,810
				122	88,310

Monthly and yearly discharge, in cubic feet per second

37

the construction was able to Participation

Berlet sedered 11. In the electricity of a contractive or an experimental and the set of the second of the

000279

38

RIO GRANDE COMPACT COMMISSION REPORT

Rio Chama below El Vado Dam, N. Mex.

Location.--Water-stage recorder, lat 36°34'48", long 106°43'24", in Tierra Amarilla Grant, on left bank 1.5 miles downstream from El Vado Dam, 2.8 miles upstream from Rio Nutrias, and 13 miles southwest of Tierra Amarilla. Datum of gage is 6,696.12 ft above mean sea level, datum of 1929. Prior to October 1935, at site 1.5 miles upstream and October 1935 to September 1938, at site 1.1 miles upstream at different datums.

Drainage area. -- 877 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.--4 years (1914, 1921-23), 444 ft³/s (321,700 acre-ft per year) prior to completion of El Vado Dam; 35 years (1936-70), 372 ft³/s (269,500 acre-ft per year), prior to release of transmountain water; 10 years (1971-80) 403 ft³/s (292,000 acre-ft per year).

Extremes.--1914-16, 1920-24, 1936-80: Maximum discharge observed, 9,000 ft³/s May 22, 1920 (gage height, 12 ft); no flow Mar. 25, 26, 31, 1955.

Remarks.--Records good. Diversions above station for irrigation of about 10,600 acres. Since 1935 flow regulated by El Vado Reservoir and since October 1970 flow partly regulated by Heron Reservoir. Subsequent to May 1971 flow affected by releases of transmountain water from Heron Reservoir.

the and meanly discharge in cubic feet per second

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet	
	2 025	126	26	65.6	4,040	
inuary	2,030	177	31	136	7,840	
bruary	3,900	577	74	225	13,850	
rch	6,983	1 2 2 6 0	155	1.193	70,970	
ril	35,779	2,200	1.660	2.955	181,700	
2	91,610	4,040	617	1,833	109,100	
ie	55,000	3,610	01	433	26,600	
ly	13,412	/04	<u>91</u>	360	22.130	
lust	11,155	1,050	40	242	20,350	
ptember	10,258	904	51	242	14,130	
tober	7,125	679	27	230	2 500	
vember	1,767	107	20	58.9	5,500	
cember	2,665	294	16	86.0	5,290	
lendar vear 1980	241,744	4,640	16	661	479,500	

Rio Chama below Abiquiu Dam, N. Mex.

Location.--Water-stage recorder, lat 36°14'12", long 106°24'59", in SE%SE% sec. 8, T. 23 N., R. 5 E., on right bank 0.8 mile downstream from Abiquiu Dam and 5.9 miles northwest of Abiquiu. Altitude of gage is 6,040 ft (from river-profile map and topographic map).

Drainage_area.--2,147 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.--9 years (1962-70), 376 ft³/s (272,400 acre-feet per year), prior to release of transmountain water; 10 years (1971-80), 459 ft³/s (332,500 acre-ft per year).

Extremes.--1961-80: Maximum discharge, 2,990 ft³/s July 1, 1965 (gage height, 6.69 ft); minimum, about 0.5 ft³/s Mar. 17, 1966.

Remarks.--Records good except those for winter months, which are fair. Flow regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 17,000 acres. Subsequent to May 1971 flow affected by the release of transmountain water from Heron Reservoir.

Monthly	and	vearly	díscharge,	in	cubic	feet	per	secona
		-	T					

Month	Second- foot-days	Maximum Minimu daily daily		Mean	Runoff in acre-feet	
January February March April May June July August September October November December	2,205 6,215 9,879 34,614 51,830 64,230 29,089 13,392 10,428 7,463 28,705 24,790	175 506 523 1,780 2,240 2,200 1,370 958 760 1,120 1,290	30 35 127 252 518 1,810 151 84 80 25 555 498	71.1 214 319 1,154 1,672 2,141 938 432 348 241 957 800	4,370 12,330 19,590 68,660 102,800 127,400 57,700 26,560 20,680 14,800 56,940 49,170	
Calendar year 1980	282,840	2,240	25	773	561,000	

STREAMFLOW

Rio Nambe below Nambe Falls Dam, near Nambe, N. Mex.

Location.--Totalizing flowmeters, lat 35°50'46", long 105°54'17", in NE4SW4 sec. 29, T.19 N., R.10 E., in Nambe Indian Reservation, in outlet conduits at Nambe Falls Dam, 300 feet upstream from Nambe Falls, 2.6 miles upstream from confluence of Rio Nambe and Rio En Medio, 4.4 miles southeast of Nambe Pueblo, and 5.4 miles southeast of Nambe.

Drainage area .-- 34.1 sq mi.

Extremes.--1978-80: Maximum discharge, 312 ft³/s June 9, 1979 (gage height, 1.96 feet), at site 1,100 feet downstream; mimimum discharge, 0.21 ft³/s November 12-19, 1980.

<u>Remarks</u>.--Records good except those for May to November, which are fair. Daily discharges for period May 3 to November 11 were computed from gage at site 1,100 feet downstream, which included inflow from the intervening area.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	Second- foot-days Maximum daily Minimum daily Mean 13.96 0.46 0.45 0.45 13.05 .45 .45 .45 17.23 .59 .45 .56 359.93 30 .59 12.0 1,214 54 23 39.2 1,645 79 31 54.8 743 45 12 24.0 388.5 19 2.0 12.5 296.9 14 7.0 9.90 242.9 15 .85 7.84 116.14 15 .21 3.87 15.55 .51 .49 .50	28 26 34 714 2,410 3,260 1,470 771 589 482 230			
Calendar year 1980	5,066.16	79	.21	13.8	10,050

Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.

Location.--Water-stage recorder, lat 35°52'29", long 106°08'30", in San Ildefonso Pueblo Grant, 400 ft downstream from bridge on State Highway 4, 1.8 miles southwest of San Ildefonso Pueblo, 2.5 miles downstream from Pojoaque River, and 6.8 miles west of Pojoaque. Datum of gage is 5,488.48 ft above mean sea level, datum of 1929. Prior to May 19, 1904, and July 25 to Oct. 1, 1904, staff gage at site 180 ft upstream at datum 2.02 ft lower.

Drainage area.--14,300 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--81 years (1896-1905, 1910-80) 1,503 ft³/s (1,089,000 acre-ft per year).

Extremes.--1895-1905, 1910-80: Maximum discharge, 24,400 ft³/s May 23, 1920 (gage height, 14.1 ft); minimum daily, 60 ft³/s July 4, 5, 1902.

<u>Remarks</u>.--Records good. Flow partly regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 620,000 acres in Colorado and 75,000 acres in New Mexico. Subsequent to May 1971 flow affected by releases of transmountain water from Heron Reservoir.

	foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	21,001 25,127 31,558 77,101 196,070 178,290 60,589 24,372 16,356 15,202 38,879 43,120	805 1,190 1,300 4,620 7,980 7,490 4,070 1,340 1,050 895 1,490 1,950	532 707 796 968 4,840 4,180 786 255 255 255 318 429	677 866 1,018 2,570 6,351 5,943 1,954 786 545 490 1,296	41,660 49,840 62,600 152,900 390,500 353,600 120,200 48,340 32,440 30,150 77,120

39

The second second second

an a costa.

RIO GRANDE COMPACT COMMISSION REPORT

Santa Fe River near Santa Fe, N. Mex.

Location.--Water-stage recorder and concrete control, lat 35°41'12", long 105°50'35", in NEASEA sec. 23, T. 17 N., R. 10 E., 0.4 mile downstream from McClure Dam, and 5.3 miles east of Santa Fe. Altitude of gage is 7,718 ft. Prior to Nov. 4, 1930, at site 1.5 miles downstream, and Apr. 11, 1931 to Sept. 30, 1947, at site 0.3 mile upstream, each at different datum.

Drainage area.--18.2 sq mi.

Average discharge.--68 years (1913-80), 7.94 ft³/s (5,750 acre-ft per year).

Extremes.--1913-80: Maximum discharge, 1,500 ft³/s Aug. 14, 1921; minimum daily, 0.1 ft³/s Feb. 7-10, 20, 21, 1927, Aug. 1-4, 1951.

Remarks.--Records good. Flow regulated by McClure Reservoir, completed in 1926, raised in 1935 and again in 1947.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February Aarch April May June July August September October November December	28.67 32.2 32.22 140.0 996.1 1,037.8 353.6 311.6 146.1 145.3 92.54 167.4	1.0 1.3 1.1 7.8 52 71 13 12 6.0 6.1 4.4 8.8	0.89 1.0 .98 1.1 7.1 9.8 9.1 4.4 4.4 2.8 .89 .90	0.92 1.11 1.04 4.67 32.1 34.6 11.4 10.1 4.87 4.69 3.08 5.40	57 64 64 278 1,980 2,060 701 618 290 288 184 332
Calendar year 1980	3,483.53	71	. 89	9.52	6,910

Monthly and yearly discharge, in cubic feet per second

Rio Grande below Cochiti Dam, N. Mex.

Location.--Water-stage recorder, lat 35°37'05", long 106°19'24", in SW1NE1 sec. 17, T. 16 N., R. 6 E., in Pueblo de Cochiti Grant, 320 feet upstream from bridge on State Highway 22, 700 feet downstream from Cochiti Dam, and 1.4 miles northeast of Cochiti Pueblo. Datum of gage is 5,226.08 ft above mean sea level, datum of 1929. Prior to Nov. 14, 1973, at site 2.4 mi downstream at altitude 5,210 ft. Nov. 14, 1973 to Jan. 8, 1976, at site 320 ft downstream at datum 1.79 ft lower.

Drainage area.--14,900 sg mi, approximately (includes 2,940 sg mi in closed basin in San Luis Valley, Colo.).

Average discharge.--10 years (1971-80) 1,182 ft³/s (856,400 acre-ft per year).

Extremes.--1971-80: Maximum discharge, 10,300 ft³/s July 26, 1971, at site 2.4 miles downstream and prior to closure of Cochiti Dam; minimum discharge, 0.51 ft³/s Aug. 3-5, 1977, Aug. 27-28, 1978.

Remarks.--Records good. Since Nov. 12, 1973, flow completely regulated by Cochiti Dam. Cochiti eastside main canal on left bank and Sili main canal on right bank bypass station.

Monthly and yearly discharge, in cubic feet per second

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet	
anuary ebruary larch pril lay une vune vuly september october lovember becember	21,297 26,094 26,122 66,074 187,260 175,690 54,324 17,265 10,287 9,202 36,386 41,450	820 1,210 1,360 4,710 6,840 6,580 3,950 1,030 763 713 1,340 1,630	567 772 491 610 4,660 4,030 562 52 49 82 342 1,160	687 900 843 2,202 6,041 5,856 1,752 557 343 297 1,213 1,337	42,240 51,760 51,810 371,400 348,500 107,800 34,250 20,400 18,250 72,170 82,220	
alendar year 1980	671,451	6,840	49	1,835	1,332,000	

STREAMFLOW

Galisteo Creek below Galisteo Dam, N. Mex.

Location.--Water-stage recorder, lat 35°27'56", long 106°12'57", in SE%SE% sec. 5, T. 14 N., R. 7 E., 0.6 mile downstream from Galisteo Dam, and 5.5 miles northwest of Cerrillos. Altitude of gage is

Drainage area .-- 597 sq mi.

Average discharge.--10 years (1971-80) 6.19 ft³/s (4,480 acre-ft per year).

Extremes.--1970-80: Maximum discharge, 2,000 ft³/s July 27, 1971 (gage height, 7.00 ft); maximum gage height, 7.33 ft July 20, 1971; no flow many days each year.

<u>Remarks.--Records poor. Flow partly regulated by uncontrolled outlet in Galisteo Dam. Capacity of outlet, 5,000 ft³/s when reservoir is full. Diversions for irrigation of about 50 acres above reservoir.</u>

	record							
Month	Second- foot-days	Maximum daily	Minimum đaily	Mean	Runoff in			
January February March April May June July August September Dotober November December	12.31 95.93 12.93 6.62 69.88 29.07 29.81 115.6 95.65 0 0	3.0 14 1.0 1.2 27 18 20 47 69 0 0 0	0 .35 .08 0 0 0 0 0 0 0 0	0.40 3.31 .42 .22 2.25 .97 .96 3.73 3.19 0	24 190 26 13 139 58 59 229 190 0 0			
alendar year 1980	467.80	69			0			

Monthly and yearly discharge, in cubic feet per second

Jemez River below Jemez Canyon Dam, N. Mex.

Location.--Water-stage recorder, lat 35°23'24", long l06°32'03", in NEA sec. 5, T. 13 N., R. 4 E., 0.6 mile downstream from Jemez Canyon Dam, 2.0 miles upstream from mouth, and 6 miles north of Bernalillo. Datum of gage is 5,095.60 ft above mean sea level, datum of 1929. Prior to April 24, 1951, at site three-quarters of a mile upstream at datum 24.51 ft higher. April 24, 1951 to June 25, 1958, at site 37 ft upstream at datum 4.40 ft higher.

Drainage area.--1,038 sg mi.

Average discharge.--38 years (1937, 1944-80), 56.4 ft³/s (40,860 acre-ft per year).

Extremes.--1937, 1944-80: Maximum discharge, 16,300 ft³/s Aug. 29, 1943 (gage height, 5.62 ft);

Remarks .-- Records good. Flow regulated by Jemez Canyon Dam since October 1953. Diversions for irrigation of about 3,000 acres above station.

	foot-days	daily	Minimum daily	Mean	Runoff in
January February March April May June July August September October Rovember December	913 880 1,047 8,044 18,144 3,865.8 48.7 36.22 188.00 31.77 432.45 700	42 65 115 703 685 475 1.9 1.5 113 2.1 21 45	11 17 11 43 215 1.9 1.3 .70 0 .45 .45	29.5 30.3 33.8 268 585 129 1.57 1.17 6.27 1.02 14.4	1,810 1,750 2,080 15,960 35,990 7,670 97 72 373 63 858
alendar year 1980	24 220 04				1,390

41

a Francisco March 199

HERE SEE STATISTICS THE ALL AND

42

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande below Elephant Butte Dam, N. Mex.

Location.--Water-stage recorder, lat 33°08'54", long 107°12'22", in SW½ sec. 25, T. 13 S., R. 4 W., (projected) in Pedro Armendariz Grant, 1.0 mile downstream from dam and 1.5 miles upstream from Cuchillo Negro River. Datum of gage is 4,242.09 ft above mean sea level, datum of 1929. Prior to April 23, 1942, at several different sites and datums.

Drainage area.--29,450 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--66 years (1915-80), 975 ft³/s (706,400 acre-ft per year).

<u>Extremes.--1915-80:</u> Maximum daily discharge, 8,200 ft³/s May 22, 1942; no flow at times prior to 1929 and March 2-4, 1979.

Remarks.--Records good. Flow regulated by Elephant Butte Reservoir. Diversions for irrigation of about 800,000 acres above station.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet	
anuary 'ebruary larch spril lay fune fuly August September October November December	25,139 28,594 905 54,050 59,370 53,550 43,190 40,963 7,163.7 409.8 1,255 29,963	1,280 1,990 283 1,890 1,940 1,880 1,460 1,840 992 36 745 1,430	20 25 13 1,760 1,890 1,720 1,260 685 7.0 6.1 15 24	811 986 29.2 1,802 1,915 1,785 1,393 1,321 239 13.2 41.8 967	49,860 56,720 1,800 107,200 117,800 106,200 85,670 81,250 14,210 813 2,490 59,430	
Calendar year 1980	344,552.5	1,990	6.1	941	683,400	

Monthly and yearly discharge, in cubic feet per second

Rio Grande below Caballo Dam, N. Mex.

Location.--Water-stage recorder, lat 32°53'05", long 107°17'31", in NEASWA sec. 30, T. 16 S., R. 4 W., 2,000 ft upstream from Interstate Highway 25, 4,200 ft downstream from Caballo Dam, 1.3 miles upstream from Percha diversion dam, and 3 miles northeast of Arrey. Datum of gage is 4,140.9 ft above mean sea level, datum of 1929. October 13, 1938 to December 31, 1945, at datum 5.0 ft higher.

Drainage area.--30,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.--43 years (1938-80) 852 ft³/s (617,300 acre-ft per year).

Extremes.--1938-80: Maximum daily discharge, 7,650 ft³/s May 20, 1942; minimum daily, 0.1 ft³/s Oct. 31 to Nov. 14, 1954, Nov. 7 to Dec. 31, 1955.

Remarks.--Records good. Flow regulated by Elephant Butte and Caballo Reservoirs. Diversions for irrigation of about 800,000 acres above station.

P1	onicity and years, a				
Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	3708.4 9,648 45,270 38,289 42,903 60,013 63,803 47,615 20,733.4 39.4 31.8 37.7	397 1,210 1,817 1,659 2,043 2,485 2,403 2,396 1,906 1.5 1.7 1.6	1.4 3.0 1,012 899 924 1,652 1,723 804 1.2 .9 .7 .7	120 333 1,460 1,276 1,384 2,000 2,058 1,536 691 1.3 1.1 1.2	7,360 19,140 89,790 75,950 85,100 119,000 126,600 94,440 41,120 78 63 75 63 75
Calendar year 1980	332,091.7	2,485	.7	907	0101100

Monthly and yearly discharge, in cubic feet per second

STREAMFLOW

Bonito ditch below Caballo Dam, N. Mex.

<u>Records available</u>.--January 1938 to December 1977. Published as supplementary data with Rio Grande below Caballo Dam in U.S.G.S. Water-Supply Papers and Water-Data Reports beginning with October 1947.

<u>Remarks</u>.--Ditch diverts directly from Caballo Reservoir for irrigation of lands on right bank of river. The total release from Project Storage, as used in computations of Compact Commission, is the combined flow of this ditch and Rio Grande below Caballo Dam.

Monthly	and	yearly	discharge,	in	cubic	feet	ner	Focond
-				****	CUDIC	reer	per	second

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
January February March April May June July August September October November December	0 6.2 67.4 2.5 23.8 89.7 64.0 39.2 9.1 0 0 0	0 6.2 2.5 10 10 5.8 7.5 6.2 0 0		0 .21 2.17 .083 .77 2.99 2.06 1.26 .30 0 0	0 12 134 5.0 47 178 127 78 18 0 0
alendar year 1980	301.9	10	0	.82	

Sec. 2. Sec. 2.

1. 6. 30

والمراجع والمراجع

الارتياج والافترانية ومعيد ما

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Squaw Lake.--Staff gage in sec. 12, T. 39 N., R. 4 W., on tributary to Squaw Creek. Completed in 1938; capacity, 162 acre-ft by 1953 survey. Water is used for irrigation below gaging station on Rio Grande near Del Norte.

								6 1
Month-end	qaqe	height,	in	feet,	and	contents,	in	acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height Contents Change	- 0 0	- 0 0	- 0 0	 0 0	- 0 0	_ 0 0	- 0 0	- 0 0	0 0	0	0	0	0

Rito Hondo Reservoir.--Staff gage in sec. 22, T. 42 N., R. 3 W., on Rito Hondo (Deep Creek) tributary to Clear Creek. Completed in 1957; capacity, 561 acre-ft. Originally filled during May and June 1958 with transmountain water; storage is not in debit status. Water is used for fish culture.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	-
Contents	561	561	561	561	561	561	561	561	561	561	561	561	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

Hermit Lakes Reservoir No. 3.--In sec. 25, T. 41 N., R. 4 W., on South Clear Creek. Completed prior to 1960; capacity, 192 acre-ft. Capacity table based on elevation above bottom of outlet. Water is used for fish culture. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end	gage	height,	in	feet,	and	contents,	in	acre-feet

Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	
Contents	192	192	192	192	192	192	192	192	192	192	192	192	
Change	0	0	0	0	0	0	0	0	0	0	0	0	

Troutvale No. 2 Reservoir.--Staff gage in EL sec. 10, T. 41 N., R. 3 W., on South Clear Creek. Completed in 1940; capacity, 435 acre-ft. Condition of spillway limited storage to 168 acre-ft after May 1942. Repairs to spillway in 1947 increased capacity to 257 acre-ft. Water is used for fish culture with only occasional sale for irrigation. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end gage height	, in	feet,	and	contents,	in	acre-feet
-----------------------	------	-------	-----	-----------	----	-----------

Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	-	
Contents	257	257	257	257	257	257	257	257	257	257	257	257	-	
Change	0	0	0	0	0	0	0	0	0	0	0	0	0	

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Jumper Creek Reservoir.--In sec. 5, T. 39 N., R. 2 W., on Jumper Creek, tributary to Trout Creek. Completed in 1951; capacity, 38 acre-ft. Capacity table based on elevation above bottom of outlet. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end gage height.	in	feet	and			-
		recer	anu	concents,	1n	acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	 Dec		
Gage height	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	-	
Contents	38	38	38	38	38	38	38	38	38	38	38	38	-	
Change	0	0	0	0	0	0	0	0	0	0	0	0	0	

Big Meadows Reservoir.--In NWA sec. 17, T. 38 N., R. 2 E., on South Fork about 0.9 mile upstream from Hope Creek. Completed in 1967; capacity, 2,437 acre-ft. Capacity table based on elevation above outlet. Water is used for fish culture. Includes 140 acre-ft of transmountain water, by exchange, in 1967; 838 acre-ft by exchange, in 1968; and 347 acre-ft, by exchange, in 1969. The remainder (1,112 acre-ft) was removed from call status, as debit water, by action of the Com-

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in Contont-
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 December 30 December 31	45.0 45.0 45.0 45.0 45.0 45.0 45.0 45.0	2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437 2,437	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Calendar year 1980			

 $\langle \mathcal{O} \rangle$

00 **C**U

 ϵ

Alberta Park Reservoir. -- In sec. 34, T. 38 N., R. 2 E., on Pass Creek. Completed in 1953; capacity, <u>Seria Park Reservoir</u>.--in sec. 34, T. 38 N., K. 2 E., On Pass Creek. Completed in 1953; capacity 598 acre-ft. Capacity table based on elevation above bottom of outlet. Includes 244 acre-ft transmountain water, imported in 1963. Remainder of storage removed from call status, as debit water, by action of the Commission on March 5, 1970.

Month-end gage height, in feet, and contents, in acre-feet

										acre-r	eet			
Month	Jan.	Feb.	Mar.	Apr.	Mav	June	T111+*	<u> </u>				<u> </u>		
Gage height	27 0	27.0					July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Contents	598	598	27.U 598	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0	27.0		
Change	0	0	0	Ō	Ő	0	730	298	598	598	598	598	-	
							<u> </u>			Ū	0	0	0	

Shaw Lake.--In sec. 5, T. 38 N., R. 2 E., on tributary to Lake Creek. Capacity, 638 acre-ft by 1916 decree; enlarged in 1955 to 681 acre-ft. Only the storage in excess of 638 acre-ft is subject to terms of Rio Grande Compact. Includes 42 acre-ft transmountain water imported in 1965.

Month-end	gage height,	in	feet,	and	contents,	in acre-feet	
						AN GOLE LEEL	

Month	Jan.	Feb.	Mar	Apr	M	-					·		
				API	may	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.vr.
Gage height Contents Change	20.0 680 +23	20.0 680 0	+23										

45

and the man was a start with the start of the

ช้อาชีวสีวิธีสินให้ปฏิบัติสันกับ 1995 (1995) และสารสารสารสารสารสารสารสารสารสารสารการและ เป็นสารสารสารสารสารสาร

RIO GRANDE COMPACT COMMISSION

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Mill Creek Reservoir. -- In sec. 16, T. 39 N., R. 3 E., on Mill Creek. Completed in 1953; capacity, 43 acre-ft. Capacity based on elevation above bottom of outlet. Includes 43 acre-ft of transmountain water, by exchange, in 1976.

Month-end	gage	height,	in	feet,	and	contents,	in	acre-feet

.

Month	Jan.	Feb.	Mar.	Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height Contents Change	15.0 43 0	-	`											

Fuchs Reservoir.--Staff gage in sec. 2, T. 37 N., R. 4 E., on East Pinos Creek. Completed in 1939; capacity, 237 acre-ft with 2 feet of flash boards in spillway. Pinos Creek enters Rio Grande below station near Del Norte.

Month-end	gage	height,	in	feet,	and	contents,	in	acre-	feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height Contents	14.2 170	14.2 170	14.2 170	14.2 170 0	14.2 170 0	14.2 170 0	11.2 113 -57	3.6 16 -97	0.9 1 -15	0.9 1 0	0.9 1 0	0.9 1 0	-169	
Change	0	•	•	•	-		_							

Platoro Reservoir.--Water-stage recorder in NW\SW\ sec. 22, T. 36 N., R. 4 E., on Conejos River. Completed in 1951; capacity, 59,570 acre-ft at crest of spillway. Reservoir is used for irrigation and flood control. Storage affects Conejos Index Supply.

Month-end elevation,	in f	eet, and	d contents,	in	acre-feet
----------------------	------	----------	-------------	----	-----------

Date	Elevation	Contents	Change in Contents						
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30	- - 9,999.6 9,983.8 9,972.0 10,014.4 10,007.3 9,982.4 9,982.4 9,982.4 9,982.4	a 30,480 a 30,480 a 30,480 30,690 20,500 14,200 42,040 36,370 19,690 19,690 19,690	- 0 +210 -10,190 -6,300 +27,840 -5,670 -16,680 0 0						
December 31	9,982.4	19,690	0						
Calendar year 1980		-	-10,790						

a - Estimated

Trujillo Meadows Reservoir.--In sec. 5, T. 32 N., R. 5 E., on Los Pinos River. Completed in 1957; capacity, 913 acre-ft. Water is used for fish culture. Storage is transmountain water, by exchange, in 1959.

Month-end	gage	height,	in	feet,	and	contents,	in	acre-feet

Nonth	Tan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height	31.0	31.0	31.0	31.0	31.0 913	-								
Contents	0	0	0	0	0	0	0	0	0	0	0	0	0	

A State State State State

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (constructed or enlarged since 1929)

Heron Reservoir.--Water-stage recorder, lat 36°39'56", long 106°42'13", on Willow Creek. Storage began in October 1970. Capacity, 401,300 acre-ft at elevation 7,186.1 ft (low point on crest of spillway); dead storage, 1,340 acre-ft at elevation 7,003.0 ft. Used for storage of trans-

Month-end	elevation,	in	feet.	and	contents.	in	acre-feet
			2000,	unu	COULCUIDS	T11	acte-reec

Date	Elevation	Contents	Change in Contents
December 31, 1979	7,155,56	243.700	
January 31, 1980	7,155.83	244,900	+1 200
February 29	7,155.67	244 190	+1,200
March 31	7,154,76	240 190	-710
April 30	7,158,48	256 830	+4,000
May 31	7,167,53	300 150	+10,040
June 30	7,178,17	356 040	+43,320
July 31	7,178,14	255 970	+55,890
August 31	7,176,58	247 240	-170
September 30	7 176 37	347,340	-8,530
October 31	7 175 95	340,180	-1,160
November 30	7 175 65	343,380	-2,800
December 31	7,170.00	342,300	-1,080
	7,170.98	31/,650	-24,650
Calendar year 1980	_	_	+73,950

El Vado Reservoir.--Water-stage recorder and surface follower, lat 36°35'39", long 106°44'00", on Rio Chama. Storage began in January 1935. Capacity, 196,500 acre-ft at gage height 6,902.0 feet (crest of spillway); dead storage, 1,060 acre-ft, below gage height 6,775.0 ft (invert of outlet works), as determined by survey in 1966. Datum of gage is 8.21 feet above mean sea level, datum of 1929. Storage includes both Rio Grande and transmountain water.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents	TM Water	
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	6,876.98 6,877.12 6,877.23 6,877.06 6,877.05 6,877.06 6,876.76 6,876.76 6,876.39 6,871.74 6,864.40 6,859.32 6,859.35 6,870.39	123,230 123,580 123,850 123,430 123,410 123,430 122,690 121,790 110,870 95,280 85,510 85,560	$ \begin{array}{r} +350 \\ +270 \\ -420 \\ -20 \\ +20 \\ -740 \\ -900 \\ -10,920 \\ -15,590 \\ -9,770 \\ +50 \\ -300 \end{array} $	73,350 73,440 73,460 73,380 73,200 72,880 72,230 71,740 61,070 45,280 35,720 35,680	
Calendar year 1980			-15,370	57,940	

<u>Abiquiu Reservoir.--Water-stage recorder in SWM sec. 8, T. 23 N., R. 5 E., on Rio Chama. Completed in February 1963; capacity, 1,212,000 acre-ft at elevation 6,350 feet (crest of spillway). Reservoir is operated by Corps of Engineers for flood control and sediment storage. A resolution granting permission to store transmountain waters was approved by Rio Grande Compact Commission on May 3, 1974.</u>

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation	Contents	Change in contents	TM water
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	6,165.51 6,167.10 6,167.97 6,166.13 6,176.58 6,212.37 6,211.34 6,203.21 6,202.67 6,202.35 6,202.00 6,184.65 6,164.48	a42,020 44,730 46,250 43,060 62,990 169,580 165,660 136,330 134,480 133,350 132,200 81,680 40,320	+2,710 +1,520 -3,190 +19,930 +106,590 -3,920 -29,330 -1,850 -1,130 -1,150 -50,520 -41,360	41,820 43,380 43,190 42,940 42,580 42,260 41,940 41,520 41,180 40,880 40,630 40,540 40,320
Calendar year 1980		_	-1,700	

a Computed on basis of revised capacity table put into use Jan. 1, 1980.

47

- Zn

an are maintenant and an an an ar an an ar an ar

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin New Mexico (Completed or enlarged since 1929)

<u>Nambe Falls Reservoir.--Water-stage recorder in NELSWA sec. 29, T. 19 N., R. 10 E., in Nambe Indian Reservation, on Rio Nambe. Completed in 1976; capacity 2,020 acre-ft at elevation 6,826.6 feet (crest of spillway), dead storage 121 acre-ft at elevation 6,760.9 feet. Storage is transmountain water by exchange (see resolution adopted March 27, 1975).</u>

Month-end elevation.	. in feet.	and contents,	in acre-feet
----------------------	------------	---------------	--------------

HOIN	th end createrony an int		
Date	Elevation	Contents	Change in contents
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	6,816.55 6,819.45 6,822.34 6,825.26 6,826.70 6,826.81 6,826.69 6,817.30 6,810.22 6,807.76 6,802.60 6,802.37 6,806.60	1,490 1,630 1,780 1,940 2,030 2,040 2,030 1,530 1,210 1,110 923 915 1,060	$ \begin{array}{r} +140 \\ +150 \\ +160 \\ +90 \\ +10 \\ -10 \\ -500 \\ -320 \\ -100 \\ -187 \\ -8 \\ +145 \\ \end{array} $
Calendar year 1980		-	-430

McClure (Granite Point) Reservoir.--Water-stage recorder in NE4SW4 sec. 24, T. 17 N., R. 10 E., on Santa Fe River. Original reservoir completed in 1926, capacity, 561 acre-ft; in 1935, permanent flash boards were installed in spillway increasing capacity to 650 acre-ft; in 1947 both dam and spillway were reconstructed increasing capacity to 2,615 acre-ft (gage height, 96.6 ft, crest of spillway). In 1953 spillway was equipped with radial gates that opened automatically, increasing capacity to over 3,000 acre-ft. In 1972, radial gates were removed decreasing capacity to 2,615 acre-ft. No dead storage. Altitude of gage is 7,788 ft. Only the storage in excess of 561 acre-feet is subject to terms of Rio Grande Compact.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Changes in contents
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30	75.8 76.45 78.52 82.56 94.23 96.98 96.66 89.90 82.36 80.83	1,320 1,360 1,470 1,700 2,450 2,640 2,620 2,150 1,690 1,600	- +40 +110 +230 +750 +190 -20 -470 -460 -90
September 30 October 31 November 30 December 31	77.15 75.50 69.66	1,390 1,310 1,040	-210 -80 -270
Calendar year 1980		-	-280

Nichols Reservoir.--Water-stage recorder inSELNEL sec. 21, T. 17 N., R. 10 E., on Santa Fe River. Completed in 1942; capacity, 685 acre-ft at gage height 167.0 feet (crest of spillway), dead storage 14 acre-ft at gage height 121.1 feet. Datum of gage is 7,313.2 feet above mean sea level, datum of 1929. Water is for municpal use in Santa Fe.

Month-end gage he	eight, 🗆	in	feet,	and	content	s,	1n	acre-	ree	τ
-------------------	----------	----	-------	-----	---------	----	----	-------	-----	---

Date	Gage height	Contents	Change in contents
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31	160.3 156.61 154.16 149.56 159.85 167.53 165.99 158.45 161.83 156.61 158.23 158.23	499 412 359 272 487 702 655 455 540 412 450 394	$ \begin{array}{r} -87\\ -53\\ -87\\ +215\\ +215\\ -47\\ -200\\ +85\\ -128\\ +38\\ -56\end{array} $
December 31	150.87	296	-98
Calendar vear 1980		-	-203

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Cochiti Lake.--Water-stage recorder and manometer in NWASWA sec. 16, T. 16 N., R. 6 E., in Pueblo de Cochiti Grant, on Rio Grande. Completed in 1975; capacity 496,600 acre-ft at elevation 5,450.0 ft (crest of service spillway); dead storage 1,480 acre-ft at elevation 5,255.0 ft., from 1978 survey. A 50,000 acre-foot permanent pool was authorized by Public Law 88-293, 88th Congress, March 26, 1964. Reservoir is operated by Corps of Engineers for flood control, sediment storage, and recreation. Storage began Nov. 12, 1973.

Month-end	elevation,	in	feet,	and	contents.	in	acre-feet
				anu	concents,	ın	acre-teet

Date	Elevation	Contents	Change in contents	TM water
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31 Calendar year 1980	5,321.41 5,321.61 5,321.59 5,321.56 5,327.78 5,335.33 5,322.13 5,321.56 5,321.42 5,321.42 5,321.39 5,321.58 5,321.62 5,322.17	46,170 46,410 46,390 46,350 54,180 64,720 47,040 46,350 46,180 46,180 46,150 46,380 46,420 47,080	$ \begin{array}{r} +240 \\ -20 \\ -40 \\ +7,830 \\ +10,540 \\ -17,680 \\ -690 \\ -170 \\ -30 \\ +230 \\ +40 \\ +660 \\ \end{array} $	46,170 46,190 46,050 46,260 46,910 46,540 45,860 46,110 46,180 46,120 46,140 45,980 46,220
		-	+910	

Galisteo Reservoir.--Water-stage recorder and manometer in NW% sec. 9, T. 14 N., R. 7 E., on Galisteo Creek. Storage records begin in October 1970. Capacity 88,990 acre-ft at elevation 5,608.0 ft (crest of spillway). No dead storage. Reservoir is operated by Corps of Engineers for flood control and sediment storage. There was no storage at the end of each month during the calendar year.

San Gregorio Reservoir.--Staff gage in SWANEL sec. 20, T. 21 N., R. 1 E. (projected), on Clear Creek tributary to Rio Las Vacas and Jemez River. Completed in October 1958; capacity, 254 acre-ft at elevation 9,408.0 ft (crest of spillway). Storage omitted from accounting by action of Commission in April, 1957.

Month-end contents, in acre-feet														
MONEN	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Contents Change	-			-	305	192 -113	104 -88	138 +34	-	-	-	-		

Jemez Canyon Reservoir.--Water-stage recorder in SW\sW\sec. 32, T. 14 N., R. 4 E., on Jemez River. Completed in 1953; capacity, 176,200 acre-ft at elevation 5,252.3 ft. Capacity at elevation 5,232.0 ft (crest of spillway), 106,100 acre-ft by 1975 survey. Reservoir is operated by Corps of Engineers for flood control and sediment storage. A sediment pool of about 2,000 acre-ft of transmountain water has been maintained since August 1979.

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation	Contents	Change is and	
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31 Calendar year 1980	5,159.89 5,159.79 5,159.87 5,160.21 5,168.99 5,164.08 5,160.64 5,159.51 5,159.21 5,158.53 5,158.89 5,159.02 5,158.88	1,950 1,950 2,050 5,630 3,340 2,170 1,850 1,770 1,590 1,680 1,720 1,680	Change in contents -30 +30 +100 +3,580 -2,290 -1,170 -320 -80 -180 +90 +40 -40	TM Water 1,950 1,920 1,950 1,990 2,000 1,950 1,990 1,760 1,710 1,590 1,680 1,720 1,680
			_ 270	

<u>Acomita Reservoir</u>.--Staff gage in SE¹/₄ sec. 29, T. 10 N., R. 7 W., on San Fidel Arroyo; water for reservoir is diverted from Rio San Jose. Completed in 1938; original capacity, 850 acre-ft; present capacity 650 acre-ft on basis of 1956 sediment survey. Water is used for irrigation on Acoma and Laguna Indian Reservations.

				Month	n-end a	content	s in	acre-f	leet				
Month	Jan.	Feb.	Mar.	Apr.	May_	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	(a) un
Change	a500 0	a550 +50	600 +50	490 -110	490 0	480 -10	550 +70	550 0	550 0	600 +50	600 0	650 +50	+150

a Estimated

Seama Reservoir.--In sec. 36, T. 10 N., R. 7 W., off channel from Rio San Jose. Completed in October 1980; capacity approximately 400 acre-ft. Water is used for irrigation on Laguna Indian Reservation. No storage at end of each month during calendar year.

water a change of the sector

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in New Mexico (Project storage)

Elephant Butte Reservoir.--Water-stage recorder in NWA sec. 30, T. 13 S., R. 3 W., on Rio Grande. Storage began Jan. 6, 1915; capacity, 2,109,400 acre-ft at gage height 4,407.0 ft (crest of spillway), by survey of 1974. Datum of gage is 43.3 ft above mean sea level, datum of 1929. Water is used for power development and irrigation in New Mexico and Texas. Records furnished by Bureau of Reclamation. Delivery of transmountain water for minimum recreation pool was initiated in December 1975. Beginning Jan. 1, 1977 gage readings are midnight readings.

Man	th-ond	a	height.	in	feet.	and	contents,	in	acre-feet
Mon	rn-ena	dade	nerduci	T17	TCCCI				

Date	Gage height	Contents	Change in contents	TM water
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	4,364.97 4,364.58 4,364.40 4,366.25 4,364.68 4,373.28 4,373.28 4,379.92 4,378.58 4,375.25 4,375.68 4,375.00 4,377.09 4,377.69	943,500 935,800 932,300 969,100 937,800 1,118,700 1,277,400 1,244,000 1,164,000 1,156,200 1,207,600 1,222,200	-7,700 -3,500 +36,800 -31,300 +180,900 +158,700 -80,000 +10,100 -15,900 +49,400 +14,600	53,000 52,910 52,740 51,880 51,220 50,320 49,550 49,020 48,740 48,360 48,180 48,040
Calendar year 1980	-		+278,700	

<u>Caballo Reservoir</u>.--Water-stage recorder in SELSW1 sec. 19, T. 16 S., R. 4 W., on Rio Grande. Storage began Feb. 8, 1938; capacity, 344,000 acre-ft (by 1958 survey), at gage height 4,182.0 ft (above whic spillway gates open automatically). Datum of gage is 43.3 ft above mean sea level, datum of 1929. 100,000 acre-ft of storage reserved for flood control. Records furnished by Bureau of Reclamation. Beginning Jan. 1, 1977, gage readings are midnight readings.

Wanth and	a	haight.	in	feet.	and	contents,	in	acre-feet
Month-end	yaye	nengner		2000,				

Date	Gage height	Contents	Change in contents		
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	4,148.49 4,156.22 4,160.89 4,145.53 4,152.27 4,152.80 4,142.46 4,140.14 4,131.20 4,132.58 4,134.44 4,150.48	73,560 115,900 148,100 60,560 92,510 116,200 95,410 48,690 40,770 17,160 20,200 24,620 83,170	- +42,340 +32,200 -87,540 +31,950 +23,690 -20,790 -46,720 -7,920 -23,610 +3,040 +4,420 +58,550		
Calendar year 1980			+9,610		

Project Storage.--This is the combined usable storage in Elephant Butte and Caballo Reservoirs. Total Project storage capacity is 2,353,400 acre-ft which excludes the 100,000 acre-ft reserved for flood control in Caballo Reservoir.

Month-end contents, in acre-feet								
Date	Contents	Change in contents						
December 31, 1979 January 31, 1980 February 29 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31	964,100 998,800 1,027,600 977,400 978,400 1,183,700 1,322,500 1,243,100 1,155,800 1,142,500 1,130,000 1,184,100 1,257,300	+34,700 +28,800 -50,200 +1,000 +205,300 +138,800 -79,400 -87,300 -13,300 -12,500 +54,100 +73,200						
Calendar year 1980		+293,200	··					

NOTE .-- Values of combined contents may not agree with sum of individual values because of rounding.

TRANSMOUNTAIN DIVERSIONS

<u>sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado.</u> Diversion is from North Fork Los Pinos River in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was Pine River completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.

- Weminuche Pass ditch (Raber-Lohr ditch).--Water-stage recorder and 4-ft rectangular flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from Rincon la Vaca Creek in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.
- <u>11iams Creek Squaw Pass ditch.--Water-stage recorder and 2-ft Parshall flume in sec. 21, T.</u> 39 N., R. 3 W., at Squaw Pass in Colorado. Diversion is from Williams Creek in San Juan River Basin into Squaw Creek in Rio Grande Basin. Constructed in 1938. Diversion for irrigation is Williams Creek from Rio Grande below Del Norte gaging station.
- Tabor ditch.--Water-stage recorder and 3-ft Parshall flume in sec. 35, T. 43 N., R. 3 W., at Spring Creek Pass in Colorado. Diversion is from Cebolla Creek in Gunnison River Basin into tributary of Clear Creek in Rio Grande Basin. Completed in 1910 or 1911. Diversion for irrigation is from Rio Grande below Del Norte gaging station.

Don La Font No. 1 & No. 2 ditches (Piedra Pass ditch).--Water-stage recorder and 2-ft Parshall flume in sec. 4, T. 38 N., R. 1 W., at Piedra Pass in Colorado. Diversion is from tributaries of Piedra River in San Juan River Basin to South River in Rio Grande Basin. Original ditch com-pleted in 1938, first enlargement completed in 1940. Water is imported by Colorado Game and Fish Department, beginning in 1959, to offect losses from fish culture recorrected. Fish Department, beginning in 1959, to offset losses from fish culture reservoirs.

C-2 တ CV \subset .

 $\subset \supset$

 \sim

Treasure Pass diversion ditch. -- Water-stage recorder and 2-ft Parshall flume in sec. 31, T. 38 N., R. 2 E., at Wolf Creek Pass in Colorado. Diversion is from Wolf Creek in San Juan River Basin to a tributary of South Fork Rio Grande. Completed in 1923 or 1924. Water is diverted for irrigation from Rio Grande above the Del Norte gaging station, beginning in 1959. Prior to 1959

Azotea tunnel.--Water-stage recorder and 10-ft Parshall flume, lat 36°51'12", long 106°40'18", at Navajo River, and Navajo River in Colorado and discharge is into Azotea Creek in New Mexico.

<u> </u>	Imported guantities, in acre-feet, 1980											
Month	Pine River- Weminuche Pass ditch	Weminuche Pass ditch	Williams Creek- Squaw Pass ditch	Tabor ditch	Don La Font ditches	Treasure Pass diversion ditch	Azotea tunnel					
January February March April May June July August September October November December	0 0 0 41 109 0 0 0 0 0	0 0 0 0 1,140 790 0 0 0 0 0 0		0 0 0 13 558 192 72 59 0 0 0	0 0 0 0 0 3 3 0 0 0 0 0 0 0	0 0 0 180 110 0 0 0 0 0	0 0 17,470 44,970 59,690 17,460 2,270 1,690 44 14 10					
	150	1,930	0	894	33	290	143,600					

and the conclusion texts with the state of the second second second second second second second second second s

han half a ferre and an and a ferrit for the state of the second state of the second state of the second states

RIO GRANDE COMPACT COMMISSION REPORT

EVAPORATION AND PRECIPITATION

The last paragraph of Article VI of the Compact states, in part, --- "such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bear to the total amount of water in such reservoirs during the year."

To provide the data needed for the computation of such evaporation losses, the Commission has encouraged the establishment and operation of evaporation stations near each major reservoir in the basin and at other selected locations.

Evaporation and other climatological data collected at the several stations in Colorado and New Mexico are tabulated on the next page. At some of the stations, it was not possible to obtain evaporation records throughout the winter period.

The measurements of evaporation were made in accordance with standard practice for the type of pan in use. Measurements of precipitation were made in standard 8-inch rain gages, which were supplemented at some of the stations by recording rain gages.

Records for the evaporation stations at the State University, Elephant Butte Dam, and El Vado Dam antedated the creation of the Commission; the stations at Abiguiu Dam, Cochiti Dam, and Jemez Canyon Dam were established by the Corps of Engineers. All others were established at the request of the Commission.

The Rio Grande Compact Commission gratefully acknowledges the cooperation of the National Oceanic and Atmospheric Administration, U.S. Corps of Engineers, and U.S. Bureau of Reclamation for furnishing the climatological records contained in this report.

- <u>Alamosa Airport</u>.--Lat 37°27', long 105°52", in Alamosa County at airport near Alamosa, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 7,536 ft.
- Platoro Dam.--Lat 37°21', long 106°30', in Conejos County near Platoro, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, fan type psychrometer, standard 8-inch and recording rain gages at elevation 9,826 ft. Records furnished by Bureau of Reclamation.
- El Vado Dam.--Lat 36°36', long 106°44', in Rio Arriba County at El Vado Dam near Tierra Amarilla, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,750 ft.
- <u>Abiquiu Dam.--Lat 36°14', long 106°26', in Rio Arriba County at Abiquiu Dam near Abiquiu, N. Mex.</u> Standard class A pan, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,380 ft.
- <u>Nambe Falls Dam</u>.--Lat 35°51', long 105°54', in Santa Fe County at Nambe Falls Dam, N. Mex. Standard class A pan, maximum and minimum thermometers, recording thermograph, standard 8-inch and recording rain gages at elevation 6,840 ft.
- <u>Cochiti Dam</u>.--Lat 35°38", long 106°19", in Sandoval County at operations building, at Cochiti Dam N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,560 ft.
- Jemez Dam.--Lat 35°23', long 106°32", in Sandoval County at Jemez Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,388 ft.
- Elephant Butte Dam.--Lat 33°09', long 107°11', in Sierra County at Elephant Butte Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, and standard 8-inch rain gage at elevation 4,576 ft.
- Caballo Dam.--Lat 32°54', long 107°18', in Sierra County at Caballo Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 4,190 ft.
- <u>New Mexico State University</u>.-Lat 32°17', long 106°45', in Dona Ana County at University Park, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 3,881 ft.

EVAPORATION AND PRECIPITATION 1980

Evaporation and precipitation, in inches

Station		.Tan	Dob										_	
			reb.	Mar	Apr	• May	June	Jul	y Aug.	Sept	. Oct	Nov		- Annual
Alamosa Airport	Evap. Precip.		.31	- 65	- 5 1.48	8.5 8 1.2	7 12.91 1 T	10.8	0 8.65	7.53	50	-	-	-
Platoro Dam	Evap. Precip.	-	_	-	-		9.76	7.63	3 5.92	5,12			<u> </u>	5.71
El Vado Dam	Evap.	-	-		4.66	6.84	10.52	9.18	<u> </u>	1.33	2.11			
	Trecip.		1.57	1.57	1.25	1.13	.02		2.42	1.48	4.17 1.48	-	-	-
Dam	Evap. Precip.	.28	.19	86	3.36 1.24	8.85 1.14	12.98	11.22	9.82	7.53	6.08		-	
Nambe Falls Dam	Evap. Precip.	- .71	_ 1.21	- 1.23	- 1.19	- 1.59	05	9.60	8.25	-	51		09	
Cochiti Dam	Evap. Precip.	95	61	25	6.83	10.44	15.70	15.37	11.59	9.54	.58 6.93	54 		12.09
Jemez Dam	Evap. Precip.	94	 - .79		-	11.75	15.38	16.00	13.20	<u>1.55</u> 8.40	.22 7.37	.34	.12	6.90
Elephant	Evap.	3.45	4.27	9 11		.12	• • • • •	.72	1.85	1.75	.04	.08	•20	7.54
Butte Dam	Precip.	.92	.36	.02	.28	.57	18.22	17.03 .20	12.48 1.09	9.11 2.43	7.82	4.13	3.41	114.28
Dam	Evap. Precip.	.23	4.54 3.00	9.17 .00	9.67	-	15.87	- 72	-	8.44	7.15	_	4.24	
State Univer.	Evap. Precip.	3.18	4.32	7.66	9.25	10.97	14.19	4.47	10.59	7.04	<u>.08</u> 6.51	<u>- 00</u>	.46	7.69
								.15	1.59	2.07	.49	.35	т	8.05



/ . .

S. . .

Ę

