REPORT

630594

ويليله بالمحاط ولايتين والماري الماري المارت المترشم فالله

of the

RIO GRANDE COMPACT COMMISSION

1991

6

TO THE GOVERNORS OF Colorado, New Mexico and Texas



RIO GRANDE COMPACT COMMISSION

COLORADO

TEXAS NEW MEXICO

The Honorable Roy Romer Governor of the State of Colorado Denver, Colorado

March 26, 1992

and a set of the state of the s

The Honorable Bruce King Governor of the State of New Mexico Santa Fe, New Mexico

The Honorable Ann Richards Governor of the State of Texas Austin, Texas

Dear Governors:

 \odot တ

HO. Ċ

 \bigcirc

The 53rd Annual Meeting of the Rio Grande Compact Commission was held in Alamosa,

he Commission reviewed its prior reports and the current reports of the Secretary elative to streamflow at Compact gaging stations and storage in reservoirs for 1991.

- Deliveries of water at the Colorado-New Mexico state line by Colorado a) amounted to 311,400 acre-feet in 1991 and the scheduled delivery for the year was 310,200 acre-feet. The accrued credit of Colorado was 22,900 acre-feet on January 1, 1992. The increase in storage in 1991 in reservoirs in Colorado constructed after 1937 aggregated 10,200
- Deliveries of water into Elephant Butte Reservoir, as measured by)) the Elephant Butte Effective Supply, amounted to 942,100 acre-feet in 1991 and the scheduled delivery for the year was 837,800 acre-feet. The accrued credit of New Mexico was 54,000 acre-feet on January 1, 1992. Water stored in reservoirs in New Mexico above San Marcial totalled 20,900 acre-feet on December 31, 1991. The decrease in storage in 1991 in reservoirs in New Mexico above San Marcial constructed after 1929 aggregated 2,500 acre-feet.
- Releases of usable water in 1991 from Project Storage amounted to

Expenses of the administration of the Rio Grande Compact were \$118,999 in the fiscal year ending June 30, 1991. The United States bore \$49,870 of this total; the balance of \$69,129 was borne equally by the three States party to the Compact.

Respectfully,

Simpson, Acting Commissioner for Colorado Eluid L. Martinez, Commissioner for New Mexico Jack Mammond, Commissioner for

Texas

RIO GRANDE COMPACT COMMISSION REPORT

RIO GRANDE COMPACT

The State of Colorado, the State of New Mexico, and the State of Texas, desiring to remove all causes of present and future controversy among these States and between citizens of one of these States and citizens of another State with respect to the use of the waters of the Rio Grande above Fort Quitman, Texas, and being moved by con-Grande above fort Quitman, Texas, and for the purpose of siderations of interstate comity, and for the purpose of effecting an equitable apportionment of such waters, have resolved to conclude a Compact for the attainment of these purposes, and to that end, through their respective Governors, have named as their respective Commissioners:

For For	the the	State State	of of of	Colorado New Mexico Texas	M. C. Hinderlider Thomas M. McClure Frank B. Clayton
For	the	State	01	Tevas	-

who, after negotiations participated in by S. O. Harper, appointed by the President as the representative of the United States of America, have agreed upon the following articles, to-wit:

ARTICLE I

(a) The State of Colorado, the State of New Mexico, the State of Texas, and the United States of America, are hereinafter designated "Colorado," "New Mexico," "Texas," and the "United States," respectively.

(b) "The Commission" means the agency created by this Compact for the administration thereof.

(c) The term "Rio Grande Basin" means all of the territory drained by the Rio Grande and its tributaries in Colorado, in New Mexico, and in Texas above Fort Quitman, including the Closed Basin in Colorado.

(d) The "Closed Basin" means that part of the Rio Grande Basin in Colorado where the streams drain into the San Luis Lakes and adjacent territory, and do not normally contribute to the flow of the Rio Grande.

(e) The term "tributary" means any stream which naturally contributes to the flow of the Rio Grande.

(f) "Transmountain Diversion" is water imported into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, exclusive of the Closed Basin.

(g) "Annual Debits" are the amounts by which actual deliveries in any calendar year fall below scheduled deliveries.

ି : ି **ଅଟ**୍ଟି

2

California California al Calendra Calendra

CONTENTS -

00598

Fifty-third Annual Report to Courses	-
Rio Grande Compact	`Page
Resolution of the Commission	
Rules and Regulations	
Records of Deliveries and Release	
Deliveries by Colorado at State line	
Deliveries by New Mayico at Flands in B	
Release and Spill from Project Stores	
Cost of Operation and Budget	
Acknowledgments	
Accuracy of Records	
Streamflow	
Rio Grande near Del Norte Colorado	
Conejos River below Platoro Posonicia C 1	
Conejos River near Mogote Colorado.	
San Antonio River at Ortiz Colorado	
Los Pinos River near Ortiz Colorado	
Conejos River near Lasauses Colorado	
Rio Grande near Lobatos, Colorado	
Willow Creek above Heron Recention and the Recention	35
Horse Lake Creek above Heron Recent in a	
Willow Creek below Heron Dam New Mexico	
Rio Chama below El Vado Dam, New Mexico	
Rio Chama below Abiouju Dam, New Mexico.	
Rio Nambe below Nambe Falls Dam, new Mexico	
Rio Grande at Otowi Bridge, pear San Ildefana, New Mexico	
Santa Fe River near Santa Fe, New Marian	
Rio Grande below Cochiti Dam, New Maxies	
Galisteo Creek below Galisteo Dam, Nove Maria	40
Jemez River below Jemez Canvon Dam, New Mexico	
Rio Grande below Elephant Butte Dam, New Mexico	
Rio Grande below Caballo Dam, New Mexico	41.
Bonito ditch below Caballo Dam, New Mexico	42
itorage in Reservoirs	42
ransmountain Diversions	
vaporation and Precipitation	•••••••••••••••••••••••••••••••••••••••

ILLUSTRATIONS

1	ILLOSI RATIONS
ap, Rio Grande Basin above Et Ouitman Taura	
ap. Rio Grando Besin al	
-p, No Grande basin above Bernalillo, New Mexico	Frontispiece

والمي المجالي المراجع الموالي المحالي المحالية المحالية

RIO GRANDE COMPACT

တဘ

5

(h) "Annual Credits" are the amounts by which actual deliveries in any calendar year exceed scheduled deliveries.

(i) "Accrued Debits" are the amounts by which the sum of all annual debits exceeds the sum of all annual credits over any common period of time.

(j) "Accrued Credits" are the amounts by which the sum of all annual credits exceeds the sum of all annual debits over any common period of time.

(k) "Project Storage" is the combined capacity of Elephant Butte Reservoir and all other reservoirs actually available for the storage of usable water below Elephant Butte and above the first diversion to lands of the Rio Grande Project, but not more than a total of 2,638,860

(1) "Usable Water" is all water, exclusive of credit water, which is in project storage and which is available for release in accordance with irrigation demands, including deliveries to Mexico.

(m) "Credit Water" is that amount of water in project storage which is equal to the accrued credit of Colorado, or New Mexico, or both.

(n) "Unfilled Capacity" is the difference between the total physical capacity of project storage and the amount of usable water then in storage.

(o) "Actual Release" is the amount of usable water released in any calendar year from the lowest reservoir comprising project storage.

(p) "Actual Spill" is all water which is actually spilled from Elephant Butte Reservoir, or is released therefrom for flood control, in excess of the current demand on project storage and which does not become usable water by storage in another reservoir; provided, that actual spill of usable water cannot occur until all credit water shall have been spilled.

(q) "Hypothetical Spill" is the time in any year at which usable water would have spilled from project storage if 790,000 acre feet had been released therefrom at rates proportional to the actual release in every year from the starting date to the end of the year in which hypothetical condition shall be the amount of usable water in project storage at the beginning of the calendar year following the condition shall be the amount of usable water in project effective date of this Compact, and thereafter the initial storage at the beginning of the calendar year following the condition shall be the amount of usable water in project effective date of this Compact, and thereafter the initial storage at the beginning of the calendar year following the storage at the beginning of the calendar year following 3

an starte

ARTICLE II

The Commission shall cause to be maintained and operated a stream gaging station equipped with an automatic water stage recorder at each of the following points, to-wit:

(a) On the Rio Grande near Del Norte above the principal points of diversion to the San Luis Valley;

- (b) On the Conejos River near Mogote;
- (c) On the Los Pinos River near Ortiz;
- (d) On the San Antonio River at Ortiz;
- (e) On the Conejos River at its mouths near Los Sauces;
- (f) On the Rio Grande near Lobatos;
- (g) On the Rio Chama below El Vado Reservoir;
- (h) On the Rio Grande at Otowi Bridge near San

Ildefonso;

- (1) On the Rio Grande near San Acacia;
- (j) On the Rio Grande at San Marcial;
- (k) On the Rio Grande below Elephant Butte Reservoir;
- (1) On the Rio Grande below Caballo Reservoir.

Similar gaging stations shall be maintained and operated below any other reservoir constructed after 1929, and at such other points as may be necessary for the securing of records required for the carrying out of the Compact; and automatic water stage recorders shall be maintained and operated on each of the reservoirs mentioned, and on all others constructed after 1929.

Such gaging stations shall be equipped, maintained and operated by the Commission directly or in cooperation with an appropriate Federal or State agency, and the equipment, method and frequency of measurement at such stations shall be such as to produce reliable records at all times. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE III

The obligation of Colorado to deliver water in the Rio Grande at the Colorado-New Mexico State Line, measured at or near Lobatos, in each calendar year, shall be ten

00**0**000

RIO GRANDE COMPACT

thousand acre feet less than the sum of those quantities set forth in the two following tabulations of relationship, which correspond to the quantities at the upper index

DISCHARGE OF CONEJOS RIVER

Quantities in thousands of acre feet

Conejos Index Supply (1)

09000

Conejos River at Mouths (2)

0

20

45

75

109

147

188

232

278

326

376

426

476

127

700

Intermediate quantities shall be computed by proportional parts.

(1) Conejos Index Supply is the natural flow of Conejos River at the U.S.G.S. gaging station near Mogote during the calendar year, plus the natural flow of Los Pinos River at the U.S.G.S. gaging station near Ortiz and the natural flow of San Antonio River at the U.S.G.S. gaging station at Ortiz, both during the months of April to October, inclusive.

(2) Conejos River at Mouths is the combined discharge of branches of this river at the U.S.G.S. gaging stations near Los Sauces during the calendar year.

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER

Quantities in thousands of acre feet

Rio Grande at Del Norte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
200 250 300	60 65
350	75 86
450 500	98 112

্য

RIO GRANDE COMPACT COMMISSION REPORT

DISCHARGE OF RIO GRANDE EXCLUSIVE OF CONEJOS RIVER--Con.

Quantities in thousands of acre feet

Rio Grande at Del No	orte (3)	Rio Grande at Lobatos less Conejos at Mouths (4)
550 600 650 700 750 800 850 900 950 1,000 1,100 1,200 1,300 1,400		144 162 182 204 229 257 292 335 380 430 540 640 740 840

Intermediate quantities shall be computed by proportional parts.

(3) Rio Grande at Del Norte is the recorded flow of the Rio Grande at the U.S.G.S. gaging station near Del Norte during the calendar year (measured above all principal points of diversion to San Luis Valley) corrected for the operation of reservoirs constructed after 1937.

(4) Rio Grande at Lobatos less Conejos at Mouths is the total flow of the Rio Grande at the U.S.G.S. gaging station near Lobatos, less the discharge of Conejos River at its Mouths, during the calendar year.

The application of these schedules shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) any new or increased depletion of the runoff above inflow index gaging stations; and (c) any transmountain diversions into the drainage basin of the Rio Grande above Lobatos.

In event any works are constructed after 1937 for the purpose of delivering water into the Rio Grande from the Closed Basin, Colorado shall not be credited with the amount of such water delivered, unless the proportion of sodium ions shall be less than forty-five percent of the total positive ions in that water when the total dissolved solids in such water exceeds three hundred fifty parts per million.

RIO GRANDE COMPACT

ARTICLE IV

The obligation of New Mexico to deliver water in the Rio Grande at San Marcial, during each calendar year, exclusive of the months of July, August, and September, shall be that quantity set forth in the following tabulation of relationship, which corresponds to the quantity at

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND AT SAN MARCIAL EXCLUSIVE OF JULY, AUGUST AND SEPTEMBER

Quantities in thousands of acre feet

Otowi Index Supply (5)

San Marcial Index Supply (6)

0 65 141

100
200
300
400
500
600
600
700
800
900
1.000
1,100
1,200
1,200
1,000
1,400
1,500
1,600
1,700
1.800
1,900
2,000
9 100
<i>6</i> ,100
2,200
2,300

219 300 383 469 557 648 742 839 939 1.042 1.1481,257 1.370 1.489 1.608 1,730 1,856 1,985 2,117

2,253

Intermediate quantities shall be computed by proportional parts.

(5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, exclusive of the flow during the months of July, August and September, corrected for the operation of reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi

RIO GRANDE COMPACT COMMISSION REPORT

(6) San Marcial Index Supply is the recorded flow of the Rio Grande at the gaging station at San Marcial during the calendar year exclusive of the flow during the months of July, August and September.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico at any time of the year of the natural runoff at Otowi Bridge; (c) depletion of the runoff during July, August and September of tributaries between Otowi Bridge and San Marcial, by works constructed after 1937; and (d) any transmountain diversions into the Rio Grande between Lobatos and San Marcial.

Concurrent records shall be kept of the flow of the Rio Grande at San Marcial, near San Acacia, and of the release from Elephant Butte Reservoir to the end that the records at these three stations may be correlated. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE V

If at any time it should be the unanimous finding and determination of the Commission that because of changed physical conditions, or for any other reason, reliable records are not obtainable, or cannot be obtained, at any of the stream gaging stations herein referred to, such stations may, with the unanimous approval of the Commission, be abandoned, and with such approval another station, or other stations, shall be established and new measurements shall be substituted which, in the unanimous opinion of the Commission, will result in substantially the same results, so far as the rights and obligations to deliver water are concerned, as would have existed if such substitution of stations and measurements had not been so made. (Note: See Resolution of Commission printed elsewhere in this report.)

ARTICLE VI

Commencing with the year following the effective date of this Compact, all credits and debits of Colorado and New Mexico shall be computed for each calendar year; provided, that in a year of actual spill no annual credits nor annual debits shall be computed for that year.

In the case of Colorado, no annual debit nor accrued debit shall exceed 100,000 acre feet, except as either or both may be caused by holdover storage of water in reservoirs constructed after 1937 in the drainage basin of the

000004

 $\tilde{\bigcirc}$

Rio Grande above Lobatos. Within the physical limitations of storage capacity in such reservoirs, Colorado shall retain water in storage at all times to the extent of its accrued debit.

In the case of New Mexico, the accrued debit shall not exceed 200,000 acre feet at any time, except as such debit may be caused by holdover storage of water in reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and San Marcial. Within the physical limitations of storage capacity in such reservoirs, New Mexico shall retain water in storage at all times to the extent of its accrued debit. In computing the magnitude of accrued credits or debits, New Mexico shall not be charged with any greater debit in any one year than the sum of 150,000 acre-feet and all gains in the quantity of water in

The Commission by unanimous action may authorize the release from storage of any amount of water which is then being held in storage by reason of accrued debits of Colorado or New Mexico; provided, that such water shall be replaced at the first opportunity thereafter.

In computing the amount of accrued credits and accrued debits of Colorado or New Mexico, any annual credits in excess of 150,000 acre feet shall be taken as equal to that amount.

In any year in which actual spill occurs, the accrued credits of Colorado, or New Mexico, or both, at the beginning of the year shall be reduced in proportion to their respective credits by the amount of such actual spill; provided, that the amount of actual spill shall be deemed to be increased by the aggregate gain in the amount of water in storage, prior to the time of spill, in reservoirs above San Marcial constructed after 1929; provided, further, that authorize the release of part, or all, of such credits in advance of spill, the amount so released shall be deemed to

In any year in which there is actual spill of usable water, or at the time of hypothetical spill thereof, all accrued debits of Colorado, or New Mexico, or both, at the beginning of the year shall be cancelled.

In any year in which the aggregate of accrued debits of Colorado and New Mexico exceeds the minimum unfilled capacity of project storage, such debits shall be reduced proportionally to an aggregate amount equal to such minimum unfilled capacity.

an set in the contract of the

10

RIO GRANDE COMPACT COMMISSION REPORT

To the extent that accrued credits are impounded in reservoirs between San Marcial and Courchesne, and to the extent that accrued debits are impounded in reservoirs above San Marcial, such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bore to the total amount of water in such reservoirs during the year.

ARTICLE VII

Neither Colorado nor New Mexico shall increase the amount of water in storage in reservoirs constructed after 1929 whenever there is less than 400,000 acre feet of usable water in project storage; provided, that if the actual releases of usable water from the beginning of the calendar year following the effective date of this Compact, or from the beginning of the calendar year following actual spill, have aggregated more than an average of 790,000 acre feet per annum, the time at which such minimum stage is reached shall be adjusted to compensate for the difference between the total actual release and releases at such average rate; provided, further, that Colorado, or New Mexico, or both, may relinquish accrued credits at any time, and Texas may accept such relinquished water, and in such event the state, or states, so relinquishing shall be entitled to store water in the amount of the water so relinquished.

ARTICLE VIII

During the month of January of any year the Commisioner for Texas may demand of Colorado and New Mexico, and the Commissioner for New Mexico may demand of Colorado, the release of water from storage reservoirs constructed after 1929 to the amount of the accrued debits of Colorado and New Mexico, respectively, and such releases shall be made by each at the greatest rate practicable under the conditions then prevailing, and in proportion to the total debit of each, and in amounts, limited by their accrued debits, sufficient to bring the quantity of usable water in project storage to 600,000 acre feet by March first and to maintain this quantity in storage until April thirtieth, to the end that a normal release of 790,000 acre feet may be made from project storage in that year.

ARTICLE IX

Colorado agrees with New Mexico that in event the United States or the State of New Mexico decides to construct the necessary works for diverting the waters of the San Juan River, or any of its tributaries, into the Rio Grande, Colorado hereby consents to the construction of said works and the diversion of waters from the San Juan

RIO GRANDE COMPACT

9

River, or the tributaries thereof, into the Rio Grande in New Mexico, provided the present and prospective uses of water in Colorado by other diversions from the San Juan River, or its tributaries, are protected.

ARTICLE X

In the event water from another drainage basin shall be imported into the Rio Grande Basin by the United States or Colorado or New Mexico, or any of them jointly, the State having the right to the use of such water shall be given proper credit therefor in the application of the schedules.

ARTICLE XI

New Mexico and Texas agree that upon the effective date of this Compact all controversies between said States relative to the quantity or quality of the water of the Rio Grande are composed and settled; however, nothing herein shall be interpreted to prevent recourse by a signatory state to the Supreme Court of the United States for redress should the character or quality of the water, at the point of delivery, be changed hereafter by one signatory state to the injury of another. Nothing herein shall be construed as an admission by any signatory state that the use of water for irrigation causes increase of salinity for which the user is responsible in law.

ARTICLE XII

To administer the provisions of this Compact there shall be constituted a Commission composed of one representative from each state, to be known as the Rio Grande Compact Commission. The State Engineer of Colorado shall be ex-officio the Rio Grande Compact Commissioner for Colorado. The State Engineer of New Mexico shall be exofficio the Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for New Mexico. The Rio Grande Compact Commissioner for Texas shall be appointed by the Governor of Texas. The President of the United States shall be requested to designate a representative of the United States to sit with such Commission, and such representative of the United States, if so designated by the President, shall act as Chairman of the Commission without vote.

The salaries and personal expenses of the Rio Grande Compact Commissioners for the three States shall be paid by their respective States, and all other expenses incident to the administration of this Compact, not borne by the United States, shall be borne equally by the three States.

RIO GRANDE COMPACT COMMISSION REPORT

The second and the second

000**0**08

12

In addition to the powers and duties hereinbefore

specifically conferred upon such Commission, and the members thereof, the jurisdiction of such Commission shall extend only to the collection, correlation and presentation of factual data and the maintenance of records having a bearing upon the administration of this Compact, and, by unanimous action, to the making of recommendations to the respective States upon matters connected with the administration of this Compact. In connection therewith, the Commission may employ such engineering and clerical aid as may be reasonably necessary within the limit of funds provided for that purpose by the respective States. Annual provided for that purpose by the respective states. Annual reports compiled for each calendar year shall be made by the Commission and transmitted to the Governors of the signatory States on or before March first following the year covered by the report. The Commission may, by unanimous action, adopt rules and regulations consistent with the provisions of this Compact to govern their proceedings.

The findings of the Commission shall not be conclusive in any court or tribunal which may be called upon to interpret or enforce this Compact.

ARTICLE XIII

At the expiration of every five-year period after the effective date of this Compact, the Commission may, by unanimous consent, review any provisions hereof which are not substantive in character and which do not affect the basic principles upon which the Compact is founded, and shall meet for the consideration of such questions on the request of any member of the Commission; provided, however, that the provisions hereof shall remain in full force and effect until changed and amended within the intent of the Compact by unanimous action of the Commissioners, and until any changes in this Compact are retified by the logical type any changes in this Compact are ratified by the legislatures of the respective states and consented to by the Congress, in the same manner as this Compact is required to be ratified to become effective.

ARTICLE XIV

The schedules herein contained and the quantities of water herein allocated shall never be increased nor diminished by reason of any increase or diminution in the delivery or loss of water to Mexico.

RIO GRANDE COMPACT

တာ

ARTICLE XV

The physical and other conditions characteristic of the Rio Grande and peculiar to the territory drained and served thereby, and to the development thereof, have actuated this Compact and none of the signatory states admits that any provisions herein contained establishes any general principle or precedent applicable to other interstate streams.

ARTICLE XVI

Nothing in this Compact shall be construed as affecting the obligations of the United States of America to Mexico under existing treaties, or to the Indian Tribes, or as impairing the rights of the Indian Tribes.

ARTICLE XVII

This Compact shall become effective when ratified by the legislatures of each of the signatory states and consented to by the Congress of the United States. Notice of ratification shall be given by the Governor of each state to the Governors of the other states and to the President of the United States, and the President of the United States is requested to give notice to the Governors of each of the signatory states of the consent of the Congress of the United States.

IN WITNESS WHEREOF, the Commissioners have signed this Compact in quadruplicate original, one of which shall be deposited in the archives of the Department of State of the United States of America and shall be deemed the authoritative original, and of which a duly certified copy shall be forwarded to the Governor of each of the signatory States.

13

a contractor there is the first interest in the first in the

Done at the City of Santa Fe, in the State of New Mexico, on the 18th day of March, in the year of our Lord, One Thousand Nine Hundred and Thirty-eight.

(Sgd.) M. C. HINDERLIDER (Sgd.) THOMAS M. McCLURE (Sgd.) FRANK B. CLAYTON

(Sgd.) S. O. HARPER APPROVED:

RATIFIED BY:

n a statisti statisti anda et esta statisti ta setta tatisti tatisti tatisti a surato surato ante ante antenno Na sa statisti statisti da esta statisti della tatisti tatisti tatisti a surato surato ante antenno da surato d

Colorado, February 21, 1939 New Mexico, March 1, 1939 Texas, March 1, 1939 Passed Congress as Public Act No. 96, 76th Congress, Approved by the President May 31, 1939.

14

013000

RESOLUTION ADOPTED BY RIO GRANDE COMPACT COMMISSION AT THE ANNUAL MEETING HELD AT EL PASO, TEXAS, FEBRUARY 22-24, 1948, CHANGING GAGING STATIONS AND MEASUREMENTS OF DELIVERIES BY NEW MEXICO

<u>R E S O L U T I O N</u>

Whereas, at the Annual Meeting of the Rio Grande Compact Commission in the year 1945, the question was raised as to whether or not a schedule for delivery of water by New Mexico during the entire year could be worked out, and

Whereas, at said meeting the question was referred to the Engineering Advisers for their study, recommendations and report, and

Whereas, said Engineering Advisers have met, studied the problems and under date of February 24, 1947, did submit their Report, which said Report contains the findings of said Engineering Advisers and their recommendations, and

Whereas, the Compact Commission has examined said Report and finds that the matters and things therein found and recommended are proper and within the terms of the Rio Grande Compact, and

Whereas, the Commission has considered said Engineering Advisers' Report and all available evidence, information and material and is fully advised:

Now, Therefore, Be it Resolved:

The Commission finds as follows:

- (a) That because of change of physical conditions, reliable records of the amount of water passing San Marcial are no longer obtainable at the stream gaging station at San Marcial and that the same should be abandoned for Compact purposes.
- (b) That the need for concurrent records at San Marcial and San Acacia no longer exists and that the gaging station at San Acacia should be abandoned for Compact purposes.
- (c) That it is desirable and necessary that the obligations of New Mexico under the Compact to deliver water in the months of July, August, September, should be scheduled.

15

RIO GRANDE COMPACT COMMISSION REPORT

That the change in gaging stations and substitution of the new measurements as hereinafter set forth will result in substantially the same (d) results so far as the rights and obligations to deliver water are concerned, and would have existed if such substitution of stations and measurements had not been so made.

Be it Further Resolved:

That the following measurements and schedule thereof shall be substituted for the measurements and schedule thereof as now set forth in Article IV of the Compact:

"The obligation of New Mexico to deliver water in the Rio Grande into Elephant Butte Reservoir during each calendar year shall be measured by that quantity set forth in the following tabulation of relationship which corresponds to the quantity at the upper index station:

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY

Quantities in thousands of acre-feet Elephant Butte Effective Index Supply (6)

57

114

171

228

286

345

406

471

542

621

707

800

897

996

1,095

1,195

1,295

1,395 1,495

1,595

Otowi Index Supply (5)

100 200 300 400 500 600 700 800 900 1,000 1,100 1,200 1,300 1,400 1,500 1,600 1,800 1,900

2,000

16

-C COB # 2

RESOLUTION OF COMMISSION

DISCHARGE OF RIO GRANDE AT OTOWI BRIDGE AND ELEPHANT BUTTE EFFECTIVE SUPPLY--Continued

Quantities in thousands of acre-feet

Otowi Index Supply (5)

Elephant Butte Effective Index Supply (6)

> 1,695 1,795 1,895 1,995 2,095 2,195 2,295 2,295 2,395 2,495 2,595

100	
200	
300	
400	
500	
600	
700	
800	
900	
000	
	100 200 300 500 600 700 800 900

Intermediate quantities shall be computed by proportional parts.

- (5) The Otowi Index Supply is the recorded flow of the Rio Grande at the U.S.G.S. gaging station at Otowi Bridge near San Ildefonso (formerly station near Buckman) during the calendar year, corrected for the operation of reservoirs constructed after 1929 in the drainage basin of the Rio Grande between Lobatos and Otowi Bridge.
- (6) Elephant Butte Effective Index Supply is the recorded flow of the Rio Grande at the gaging station below Elephant Butte Dam during the calendar year plus the net gain in storage in Elephant Butte Reservoir during the same year or minus the net loss in storage in said reservoir, as the case may be.

The application of this schedule shall be subject to the provisions hereinafter set forth and appropriate adjustments shall be made for (a) any change in location of gaging stations; (b) depletion after 1929 in New Mexico of the natural runoff at Otowi Bridge; and (c) any transmountain diversions into the Rio Grande between Lobatos and Elephant Butte Reservoir."

RIO GRANDE COMPACT COMMISSION REPORT

Be it Further Resolved: That the gaging stations at San Acacia and San Marcial be, and the same are hereby abandoned for Compact purposes.

Be it Further Resolved:

Berthan S. A. C.

That this Resolution has been passed unanimously and shall be effective January 1, 1949, if within 120 days from this date the Commissioner for each State shall have received from the Attorney General of the State represented by him, an opinion approving this Resolution, and shall have so advised the Chairman of the Commission, otherwise, to be of no force and effect.

(Note: The following paragraph appears in the Minutes of the Annual Meeting of the Commission held at Denver, Colorado, February 14-16, 1949:

"The Chairman announced that he had received, pursuant to the Resolution adopted by the Commission at the Ninth Annual Meeting on February 24, 1948, opinions from the Attorneys General of Colorado, New Mexico and Texas that the substitution of stations and measurements of deliveries by New Mexico set forth in said resolution was within the powers of the Commission").

RULES AND REGULATIONS FOR ADMINISTRATION OF THE RIO GRANDE COMPACT

A Compact, known as the Rio Grande Compact, between the States of Colorado, New Mexico and Texas, having become effective on May 31, 1939 by consent of the Congress of the United States, which equitably apportions the waters of the Rio Grande above Fort Quitman and permits each State to develop its water resources at will, subject only to its obligations to deliver water in accordance with the schedules set forth in the Compact, the following Rules and Regulations have been adopted for its administration by the Rio Grande Compact Commission; to be and remain in force and effect only so long as the same may be satisfactory to each and all members of the Commission, and provided always that on the objection of any member of the Commission, in writing, to the remaining two members of the Commission after a period of sixty days from the date of such objection, the sentence, paragraph or any portion or all of these rules to which any such objection shall be made, shall stand abrogated and shall thereafter have no further force and effect; it being the intent and purpose of the Commission to permit these rules to obtain and be effective only so long as the same may be satisfactory to each and all of the Commissioners.

GAGING STATIONS /1

Responsibility for the equipping, maintenance and operation of the stream gaging stations and reservoir gaging stations required by the provisions of Article II of the Compact shall be divided among the signatory States as follows:

(a) Gaging stations on streams and reservoirs in the Rio Grande Basin above the Colorado-New Mexico boundary shall be equipped, maintained, and operated by Colorado in cooperation with the U.S. Geological Survey.

(b) Gaging stations on streams and reservoirs in the Rio Grande Basin below Lobatos and above Caballo Reservoir shall be equipped, maintained and operated by New Mexico in cooperation with the U.S. Geological Survey to the extent that such stations are not maintained and operated by some other Federal Agency.

(c) Gaging stations on Elephant Butte Reservoir and on Caballo Reservoir, and the stream gaging stations on the Rio Grande below those reservoirs shall be equipped, maintained and operated by or on behalf of Texas through the agency of the U.S. Bureau of Reclamation.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

RIO GRANDE COMPACT COMMISSION REPORT

The equipment, method and frequency of measurements at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Water-stage recorders on the reservoirs specifically named in Article II of the Compact shall have sufficient range below maximum reservoir level to record major fluctuations in storage. be used to determine fluctuations below the range of the water-stage recorders on these and other large reservoirs, and staff gages may be used upon approval of the Commission in lieu of water-stage recorders on small reservoirs, provided that the frequency of observation is sufficient in each case to establish any material changes in water levels in such reservoirs.

RESERVOIR CAPACITIES /1_

A start of the second of the

20

030616

Colorado shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin above Lobatos constructed after 1937; New Mexico shall file with the Commission a table of areas and capacities for each reservoir in the Rio Grande Basin between Lobatos and San Marcial constructed after 1929; and Texas shall file with the Commission tables of areas and capacities for Elephant Butte Reservoir and for all other reservoirs actually available for the storage of water between Elephant Butte and the first diversion to lands under the Rio Grande Project.

Whenever it shall appear that any table of areas and capacities is in error by more than five per cent, the Commission shall use its best efforts to have a re-survey made and a corrected table of areas and capacities to be substituted as soon as practicable. To the end that the Elephant Butte effective supply may be computed accurately, the Commission shall use its best efforts to have the rate of accumulation and the place of deposition of silt in Elephant Butte Reservoir checked at least every three years.

ACTUAL SPILL /2

(a) Water released from Elephant Butte in excess of Project requirements, which is currently passed through Caballo Reservoir, prior to the time of spill, shall be deemed to have been Usable Water released in anticipation of spill, or Credit Water if such release shall have been authorized.

Amended at Eleventh Annual Meeting, February 23, 1950. ZZ Adopted at Fourth Annual Meeting, February 24, 1943.

RULES AND REGULATIONS

(b) Excess releases from Elephant Butte Reservoir, as defined in (a) above, shall be added to the quantity of water actually in storage in that reservoir, and Actual Spill shall be deemed to have commenced when this sum equals the total physical capacity of that reservoir, to the level of the uncontrolled spillway, i.e. -2,219,000 acreft in 1942.

(c) All water actually spilled at Elephant Butte Reservoir, or released therefrom, in excess of Project requirements, which is currently passed through Caballo Reservoir, after the time of spill, shall be considered as Actual Spill, provided that the total quantity of water then in storage in Elephant Butte Reservoir exceeds the physical capacity of that reservoir at the level of the sill of the spillway gates, i.e.-1,830,000 acre-ft in 1942.

(d) Water released from Caballo Reservoir in excess of Project requirements and in excess of water currently released from Elephant Butte Reservoir, shall be deemed Usable Water released, excepting only flood water entering Caballo Reservoir from tributaries below Elephant Butte Reservoir.

DEPARTURES FROM NORMAL RELEASES /3

For the purpose of computing the time of Hypothetical Spill required by Article VI and for the purpose of the adjustment set forth in Article VII, no allowance shall be made for the difference between Actual and Hypothetical Evaporation, and any under-release of usable water from Project Storage in excess of 150,000 acre-ft in any year shall be taken as equal to that amount.

EVAPORATION LOSSES $\underline{4}, \underline{5}, \underline{6}$

The Commission shall encourage the equipping, maintenance and operation, in cooperation with the U.S. Weather Bureau or other appropriate agency, of evaporation stations at Elephant Butte Reservoir and at or near each major reservoir in the Rio Grande Basin within Colorado constructed after 1937 and in New Mexico constructed after 1929. The net loss by evaporation from a reservoir surface shall be taken as the difference between the actual evaporation loss and the evapo-transpiration losses which would have occurred naturally, prior to the construction of such reservoir. Changes in evapo-transpiration losses along stream channels below reservoirs may be disregarded.

Adopted June 2, 1959; made effective January 1, 1952.
Amended at Tenth Annual Meeting, February 15, 1949.
Amended at Twelfth Annual Meeting, February 24, 1951.
Amended June 2, 1959.

RIO GRANDE COMPACT COMMISSION REPORT

Net losses by evaporation, as defined above, shall be used in correcting Index Supplies for the operation of reservoirs upstream from Index Gaging Stations as required by the provisions of Article III and Article IV of the Compact.

In the application of the provisions of the last unnumbered paragraph of Article VI of the Compact:

(a) Evaporation losses for which accrued credits shall be reduced shall be taken as the difference between the gross evaporation from the water surface of Elephant Butte Reservoir and rainfall on the same surface.

(b) Evaporation losses for which accrued debits shall be reduced shall be taken as the net loss by evaporation as defined in the first paragraph.

ADJUSTMENT OF RECORDS

The Commission shall keep a record of the location, and description of each gaging station and evaporation station, and, in the event of change in location of any stream gaging station for any reason, it shall ascertain the increment in flow or decrease in flow between such locations for all stages. Wherever practicable, concurrent records shall be obtained for one year before abandonment of the previous station.

NEW OR INCREASED DEPLETIONS

In the event any works are constructed which alter or may be expected to alter the flow at any of the Index Gaging Stations mentioned in the Compact, or which may otherwise necessitate adjustments in the application of the schedules set forth in the Compact, it shall be the duty of the Commissioner specifically concerned to file with the Commission all available information pertaining thereto, and appropriate adjustments shall be made in accordance with the terms of the Compact; provided, however, that any such adjustments shall in no way increase the burden imposed upon Colorado or New Mexico under the schedules of deliveries established by the Compact.

TRANSMOUNTAIN DIVERSIONS

In the event any works are constructed for the delivery of waters into the drainage basin of the Rio Grande from any stream system outside of the Rio Grande Basin, such waters shall be measured at the point of delivery into the Rio Grande Basin and proper allowances shall be made for losses in transit from such points to the Index Gaging Station on the stream with which the imported waters are comingled.

CD 000011

QUALITY OF WATER

In the event that delivery of water is made from the Closed Basin into the Rio Grande, sufficient samples of such water shall be analyzed to ascertain whether the quality thereof is within the limits established by the Compact.

SECRETARY /7

The Commission, subject to the approval of the Director, U.S. Geological Survey, to a cooperative agreement for such purposes, shall employ the U.S. Geological Survey on a yearly basis, to render such engineering and clerical aid as may reasonably be necessary for administration of the Compact. Said agreement shall provide that the Geological Survey shall:

(1) Collect and correlate all factual data and other records having a material bearing on the administration of the Compact and keep each Commissioner advised thereof.

(2) Inspect all gaging stations required for administration of the Compact and make recommendations to the Commission as to any changes or improvements in methods of measurement or facilities for measurement which may be needed to insure that reliable records be obtained.

(3) Report to each Commissioner by letter on or before the fifteenth day of each month, except January, a summary of all hydrographic data then available for the current year - on forms prescribed by the Commission pertaining to:

- (a) Deliveries by Colorado
- (b) Deliveries by New Mexico
- (c) Operation of Project Storage

(4) Make such investigations as may be requested by the Commission in aid of its administration of the Compact.

(5) Act as Secretary to the Commission and submit to the Commission at its regular meeting in February a report on its activities and a summary of all data needed for determination of debits and credits and other matters pertaining to administration of the Compact.

⁷ The substitution of this section for the section titled "Reports to Commissioners" was adopted at Ninth Annual Meeting, February 22, 1948.

RIO GRANDE COMPACT COMMISSION REPORT

24 COSTS /1

In February of each year, the Commission shall adopt a budget for the ensuing fiscal year beginning July first.

Such budget shall set forth the total cost of maintenance and operating of gaging stations, of evaporation stations, the cost of engineering and clerical aid, and all other necessary expenses excepting the salaries and personal expenses of the Rio Grande Compact Commissioners.

Contributions made directly by the United States and the cost of services rendered by the United States without cost shall be deducted from the total budget amount; the remainder shall then be allocated equally to Colorado, New Mexico and Texas.

Expenditures made directly by any State for purposes set forth in the budget shall be credited to that State; set forth in the budget shall be credited to that State; contributions in cash or in services by any State under a cooperative agreement with any federal agency shall be credited to such State, but the amount of the federal concredited to such State, but the amount of the federal contribution shall not so be credited; in event any State, tribution contractual relationships, causes work to be done through contractual relationships, such State shall be in the interest of the Commission, such State shall be in the interest of thereof, unless such cost is borne by the United States.

Costs incurred by the Commission under any cooperative agreement between the Commission and any U.S. Government Agency, not borne by the United States, shall be appor-Agency, not borne by the United States, shall be apportioned equally to each State, and each Commissioner shall arrange for the prompt payment of one-third thereof by his State.

The Commissioner of each State shall report at the annual meeting each year the amount of money expended during the year by the State which he represents, as well as the portion thereof contributed by all cooperating federal agencies, and the Commission shall arrange for such proper reimbursement in cash or credits between States as may be necessary to equalize the contributions made by may be necessary to equipment, maintenance and operation of each State in the equipment, maintenance and operation of all gaging stations authorized by the Commission and established under the terms of the Compact.

It shall be the duty of each Commissioner to endeavor to secure from the Legislature of his State an appropriation of sufficient funds with which to meet the obligations of his State, as provided by the Compact.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.

RULES AND REGULATIONS

\$C062

MEETING OF COMMISSION /1, /8

The Commission shall meet in Santa Fe, New Mexico, on the third Thursday of February of each year for the consideration and adoption of the annual report for the calendar year preceding, and for the transaction of any other business consistent with its authority; provided that the Commission may agree to meet elsewhere. Other meetings as may be deemed necessary shall be held at any time and place set by mutual agreement, for the consideration of data collected and for the transaction of any business consistent with its authority.

No action of the Commission shall be effective until approved by the Commissioner from each of the three signatory States.

(Signed) M. C. HINDERLIDER

M. C. Hinderlider Commissioner for Colorado

(Signed) THOMAS M. McCLURE

Thomas M. McClure Commissioner for New Mexico

(Signed) JULIAN P. HARRISON

Julian P. Harrison Commissioner for Texas

Adopted December 19, 1939.

/1 Amended at Eleventh Annual Meeting, February 23, 1950.
/8 Amended at Thirteenth Annual Meeting, February 25, 1952.



RIO GRANDE COMPACT COMMISSION REPORT RECORDS OF DELIVERIES AND RELEASES

At the annual meeting of the Compact Commission on March 26, 1992, the records of deliveries and releases and computations of debits and credits for calendar year 1991 were reported. The records and computations as approved by the Commission are reproduced on the next three pages.

The delivery of water in the Rio Grande at the Colorado-New Mexico State line was obtained from the record of streamflow near Lobatos, Colorado; the scheduled delivery was computed as prescribed in Article III.

The delivery of water by New Mexico to Elephant Butte was computed from the record of streamflow below Elephant Butte Dam and the record of operation of Elephant Butte Reservoir; the scheduled delivery was computed as prescribed in the Resolution of the Commission adopted at the Ninth Annual Meeting held February 22-24, 1948, and published in this report.

The actual release from Project Storage during the year was measured at gaging stations below Caballo Dam. The balance for items P2 through P7 will not be computed until needed. As long as actual release was less than cumulative normal release, item P7 has no application in the accounting.

27¹ NT LOPATOS 107AL ACCUMULATED 35.5 278.0 182.6 227.3 247.1 273.4 261.0 16.5 294.5 17. 63 3 119. 311. **PILLIC** 19.8 28.2 17.7 17.3 55.5 63.4 44.7 L3.9 12.4 \$01+901 4.6 υ, 16.9 Ħ VI. VIO EVYNDF-DELIVERALES 311 CONFIOS VINEN FESS 14.0 13.4 21.1 24.7 18.4 27.8 **6**.9 5.7 169.8 6.1 12.2 13.4 1.5 CLEDIT JUNTUS ON ANALOS SIDERS 3.7 4.4 7.1 30.8 45.0 16.9 6.6 141.6 8.2 3.5 6.3 L.5 4.3 8 164 10.7 21.6 86.6 266.4 35.3 SUMMANY OF DEDITS AND CALDITS 493.5 70101 433.3 525.4 562.9 581.0 13.9 594.9 10.6 605.5 ٠ e 031978361009 RIO GRANDE COMPACT - DELIVERIES BY COLORADO AT STATE LINE **J** 179.8 166.9 60.2 31.9 RENOW NI ATJURS 37.5 18.1 605.5 10.9 13.7 10.7 51.3 ⊴ INTRACOUNT o 0 ο 0 -2.0 q 0 c 0 c o -2.0 0 138 NUTA SUPPLY Stimulual Definitive firm Comunicy None-Submitted Definitive firms Non Comunit Actimal Definitive of Laboration alors 10:0000 Arrow 1 +0.1^ª :-9 SINGRISACON # A1110 Ē LOUGSTINENTS NO GLAIDT -2.1^b SHORSYGAN -2.1 ú time of October & KIY2.MORSHIVE Distant Card of Arthorition of Dubits Arthorition of Crudits Determined to the -707/1013 Quantifies in Ricessands of Acre feet to liteatest flandrad in Chiract z 0 0 0 o 0 0 0 0 0 0 o 0 0 NOUTH MOUTH 0 0 C 2 0 0 0 Ò 0 0 0 0 c 301-015 3 **YEAR** 1991 10.7 10.9 51.3 179.8 13.7 166.9 62.2 91.9 37.5 10.6 18.1 13.9 JINOR 336 MEDI 607.5 2,354 ac-ft minus 243 ac-ft pre-compact; report of Eng. Adv. for Colorado AOTI 630NODON Gaged flow minus 510 ac-ft Closed Basin delivery not creditable; report 197.9 66.6 TVIOL 3.4 6.6 11.2 288.2 313.3 333.0 346.5 352.0 356.8 361.0 ф COMMITTEED Evaporation loss post-compact reservoirs; report of Eng. Adv. for SPR1 131.3 3.4 4.6 55.4 **MOR** 3.2 50.3 19.7 25.1 13.5 4.8 4.2 r 361.0 1 9 c A14485 ÷.0+ 10.3 +1.7 9.01 +7.9 -8.0 -4.9 -1.3 2.7 4 +16.38. 9 +10.5 **LEJILLSOCOV** n 4 120 +0.1^a +0.1ª +0.1^a SLRØRLSOFOR ADUISTNET ÷. NJBO CONEJON NUCLA SUPPLY Col. 6 does not include transmountain water. JDF VOIS ک.5 ۳. 4 9.0 +7.9 +10.2 41.7 -8.1 -5.0 +16.2 -1.3 1.4-10.7 10.8 12 -108182 NON1N VI CHO OL 6.5 7.0 7.3 17.5 25.6 33.7 7.9 9.6 20.6 16.7 16.5 15.2 15.9 JOINOIS 2.9 74.0 33.1 17.6 0 53.7 6.8 123.4 24.6 4.1 3.4 350.5 WOI 4 2111/10 11.8 8.0 0.8 JOL 0.1 0.3 0.1 0.1 LV CUNCERT RUS 21. **GUNDSHITE** 2/11/10 17.2 19.2 43.5 4.3 90.8 NYAN 3.3 SONU SOI 1992 10000 2.9 4.0 71.9 22.7 56.0 21.0 Colorado. 28.7 238.5 15.3 9 3.4 4. I ١¥ 4 SOL \$103 larch SINNAN **NOIT** ž ₹ £ Í ś ł. Ĕ Ę ¥ 8 ŝ ž Ę æ o, υ

	2
	2
	5
	-
	Ļ
	1
	i
1	
5	
19 - FR	
i.	
i.	
X	
'n,	
i.	
j.	ą.
,	1
	2
2	1
	J
	17. 41.
	1
	2
	÷.
	1
	28
l	Хî
ŀ	
I	22
1	
	- 1

												ANT BU)ТТЕ ⁽⁾	000	28	
		RIO	GRAN	DE CO	MPACT	- DE	LIVERIES YEAR	3 BY NE 1991	w mex							
	_					Quantities	in Thousands of	Acre Faet to N	earest Hundrid		ELEP	HANT BUTT	E EFFECT	IVE SUPPI	7	
arch 4,	1992		10	IMO.	INDEX	SUPPL	~			lored in	STORAG		tecorded	EFFECTIVE	SUPPLY	
<u>l</u> _				SHICK	TMENTS			INDEX SI		Isw Mexico Above	RESER	VOIR				
HTNOM	Recorded		ALL CHATOS	ALJU2					<u> </u>	San Marcial at End of	End of	Change Gain (+)	Suite	During	.coumulated	
	10	Stor 0 0 0	Change	Deservoir	Other	Trons- mountain	Nei	During Month	locumulated otal	Month	Manth	L055 (-)	14 	M004	91	
	Bridge	End of Month	in Storage	Evaporatio	Adjustments	Divertions	0	6	ō	=	21					
-	2	2	4	~						23.4	1364.4		, , , , , , , , , , , , , , , , , , ,	47.3	47.3	
-		20.2 ⁸	Ì						51.0	21.4	1411.0	+46.6			0 00	
		19.7	-0.5	0	 	-0.6			, 00 r	21.2	1437.8	+26.8	24.9	51.7	157 4	
NAU				0		-0.6	6.0-	58.2	200 6	20.9	1409.2	-28.6	82.0	53.4		
8 3 3	59.1	19.4		1.0	 	-0.3	е 9	93.4	0 707 707	0.00	1411.7	+2.5	82.8	85.3	1.157	
MAR	2.59	19.3	7.7			-0.4	+44.4	226.2	4.25.8		1457 5	+45.8	93.3	139.1	376.8	
APR	181.8	63.7	+44.4			7.04	+42.6	323.1	751.9	1 185.3	7 0 5 3 5	41.9	114.5	176.4	553.2	
MAY	280.5	104.8	1-19-1				-50.3	155.6	907.5	78.6	***TCT		89.2	87.5	640.7	
No,	205.9	55.8	-49.0	0.7			<u>A</u> -21.5	64.0	971.5	64.5	1517.7		38.8	. 90.2	730.9	T
튁	85.5	56.3	±0.5	0.4	-+-		, -7.2	86.4	1057.9	56.8	1569.1	9 U-	45.0	44.4	775.3	
M	93.6	54.9	-1-4	0			6 -14.9	51.4	1109.3	56.0	1505.3	α [c	26.5	4.7	780.0	
8	T 66.3	54.2	ې 				1-15.1	27.4	1136.7	55.3	1546.7		7.0	67.1	847.1	-7
8	42.5	53.6	i 	é 10.			-19.6	52.	4 1189.	1 35.7	1613.4	- 00+	0.5	9.26	942.1	T
ļ ģ	v 72.3	33.8	-19.	8	2		-19.	5 49.	9 1239.1	0 20.9	170/.3	E VET	598.6	942.1		
18	C 69.4	1.61	-14.				7.0 -63.	7 1239.				OF DEBITS	AND CREDI	LS		
ΥĒ.	JR 1302.7		71 	₹ 							UTTIMINENS			L COLUT	BALANCE	
Ľ	steres St	torage in	n recreat	ional res	ervolrs no	t include	•	÷			ITEM				Dr 51.1	Π
Ξ. 	Is. 3, 11 al	nd 12 do	not incl	ude trans	mouncaru *			- affective	1 1 1 1 1	General Bagn	and of Year 		837.8	1 079	<u>pr 888 - 9</u> rr 53.2	Π
	Con Lon	tents ba	sed on ne	ew capacit	y table fu	r Abiquiu	I Reservor		S MH	Scheduled USH	Jurse Effective	suopiy ation		10 12 10	Cr 54.0	
10	Revised 199 Jan. 1, 199	-							S MN	Reduction of Us Reduction of Cr	edite Or Even	ration			$\frac{1}{1}$	Π
									NH C						Cr 54. (
									N N N	Belance at En	of Yaur					

NETHER COLLEGE CONTRACTOR

		i				12))		- KELE	ASE A	ND SP	111 FR			ł				
Mar	ch 4, 199;	2	ļ					~	EAR 19	- [6				.1 210	JRAG			ଅ ପ୍ର ପ୍ର
	10TML	USAbl	WITH H	STONAGE		China	NTH O	Hins in These	10 10 10 10 10 10 10 10 10 10 10 10 10 1	fo literari finai	, par					-	5	020
0	STONIGE								HOD WITH	IOT ML		Ñ	GNANDE C	TTOV CA	DALLO DAU			ſ
		CLEPHANT DUTTE NESTAVOIA	CADALLO	Total At two of	MOITCI STORAGE	COLON 150	REA REACO	TOTH.			ILOW TOW	B TENEDISC	Ĩ	I TULS	NON STON	V	USIDIE (LEASE
	LION				AT THE OF	WITH.	-		NSHIOIN II LED OF	STORAGE ME THE OF	LT CIDALLO GAGING	TO DI	Ntrist	CLIDALLO	141		L L	
-]			-	ù		,	ŀ				STATION		JWI	001 111 111	MILL	US 4 OLT	Landa Landa	ACCONDLATED TOTAL
	8	1345.5	51.5	1307 0			•	•	2	=	P	0	3	 ,				
AAL		1387.3	г У	0.7524		18.9	0	18.9		1415 0					<u>_</u>	-	5	£
£		C 7171		1443.0		23.7	0	23.7			1	1						\$
Ĩ		2 2051	~	1480.9		23.6	0	23.6	T	1400.7	7.0	 0 0	- - a				,	
<u>s</u>	T	6.001	6.44	1430.8		23.3	0	c cc	Ť	<u>1504.5</u>	13.1	0	- T E					
		1388.7	52.8	1441.5		23.0			T	1454.1	105.6	0.0	105.6					7 67
		1434.9	55.1	1490.0		2.20	> (0.62		1464.5	71.5	0.0	71.5				105.6	118.8
i i		1497.2	50.0	1547 2			∍	22.6		512.6	88.1	0.1	, a		╋		21-5	190.3
Ę		1495.7	†		+	27.2	-	22.2		569.4 1	14.5			+	+-		88.2	278.5
8		15/7 0		1.0401	1	22.0	0	22.0	<u> </u>	562 1	, , ,						14.5	393.0
Ę		, , , , ,		1566.3		21.9	0	21.9		1.400	74.7		94.4				94.4	, 70,
Į		1546.7	23.1	1569.8		21.8			╬	208.2	56.8	0.1	6.9					1 0/-4
		1525.0	28.6	1553.6		21.7			1	591.6	19.7	0.0	19.7	ļ			2 00	554.3
		591.8	31.5	1623.3				1.17	1	575.3 2	2.1	0.0	22.1	<u> </u>	+-	+	49.7	604.0
ž	1	686.2	38.3	77% =	+-			21.6	Ĩ	544.9	0.1			╏	╋		22.1	626.1
Ę						21 7		21.7	17	46.2				╎	╎	╉	- - -	626.2
NHIN			1			-		1			6.0	0.3 63	0.1	╎	╉			526.3
a Ag	reement of	1 Drojert	. stores								1			-	-	62	.9.3	
ΡŲ	visers' r	sport.		e capací	ty not r	eached,	see Engi	neer				in Ner	10 OCTANU		OVABLE NTLE			Γ
b Cor	aputation	DOT need	, t , t															T
th	in cumulat	Tve norm	al reles	USE CUBU	lative ac	stual re	lease is	less			Destine of D	Limit of Yes						រួ
of	Engineer	Advisers	for the	Vear 10	90,000 ac 189	:-ft., r	efer to ₁	eport			Action of the	<u>,</u>			626.3			T
				i 	•••••				<u>s Ir</u>	i i i	wherether free	Cleaner Catta	Acresi			790-0		1.
												Accrued Depert	E					Π
									<u>-</u>		Cumbers of La	d of Year						Ţ
]			4	T
													Ĕ	Y EVIOTECTIC	ור צעור	Did no	t occur	29

RIO GRANDE COMPACT COMMISSION REPORT COST OF OPERATION FOR FISCAL YEAR ENDING JUNE 30, 1991

05.0			-	BORNE BY	TEVAC
ITEM	TOTAL COST	BORNE BY UNITED STATES	COLORADO	NEW MEXICO	
			\$16,980	-	-
GAGING STATIONS In Colorado	\$33,960	\$10,500	-	\$15,840	
In New Mexico, above Caballo Reservoir	42,480	26,640	_	1,140	\$16,980
In New Mexico, Caballo Reservoir and below	19,260	1,140		\$16,980	\$16,980
Reservoir Les	\$95,700	\$44,760	\$16,980		
ADMINISTRATION	\$20,440	\$ 5,110	\$ 5,110 953	\$ 5,110 953	\$ 5,110 953
Other expense	2,859		\$ 6,063	\$ 6,063	\$ 6,063
Subtotals	\$23,299	\$ 5,110	\$23,043	\$23,043	\$23,043
GRAND TOTALS:	\$118,999	\$49,870	\$23,043	\$23,043	\$23,043
EQUAL SHARES OF STATES:	-				

BUDGET FOR FISCAL YEAR ENDING JUNE 30, 1993

	DODEL			BORNE BY	
ITEM	TOTAL COST T	BORNE BY	COLORADO	NEW MEXICO	TEXAS
112.02					
CACING STATIONS	#377 44 0	\$16,590	\$20,850		
In Colorado	\$37,990	27 380	·	\$19,450	
Caballo Reservoir	46,830	1 190		1,400	\$ <u>2</u> 0,850
In New Mexico, Cabano Reservoir and below	23,370		\$20,850	\$20,850	\$20,850
	\$107,640	\$45,090			
Subtotals: ADMINISTRATION	\$18,580	\$ 4,645	\$ 4,645 860	\$ 4,645 860	\$ 4,645 860
USGS Contract Other expense	2,580		\$5,505	\$ 5,505	\$ 5,505
Subtotals:	\$21,160	\$ 4,645	\$26,355	\$26,355	\$26,355
GRAND TOTALS:	\$128,800	\$49,735		\$26,355	\$26,355
FOULL SHARES OF STATES			\$20,200		

ACKNOWLEDGMENTS

This report was prepared by the U.S. Geological Survey, secretary to the Rio Grande Compact Commission. The watersupply data contained in this report have been provided by various Federal and State agencies.

The office of the State Engineer of Colorado provided records of discharge for the following:

Rio Grande near Del Norte, Colo. Conejos River below Platoro Reservoir, Colo. Conejos River near Mogote, Colo. San Antonio River at Ortiz, Colo. Los Pinos River near Ortiz, Colo. Conejos River near Lasauses, Colo. Rio Grande near Lobatos, Colo.

Records of six transmountain diversions and of storage in Squaw and Shaw Lakes, Rito Hondo, Hermit Lakes Reservoir No. 3, Troutvale No. 2, Jumper Creek, Alberta Park, Big Meadows, Mill Creek, Fuchs, and Trujillo Meadows Reservoirs were also provided by the office of the State Engineer of Colorado.

The U.S. Bureau of Reclamation, Albuquerque, N. Mex., provided the following records: Storage in Platoro Reservoir at Platoro, Colo. Azotea tunnel at outlet, near Chama, N. Mex. Willow Creek above Heron Res., near Los Ojos, N. Mex. Horse Lake Creek above Heron Res., near Los Ojos, N. Mex. Storage in Heron Reservoir near Los Ojos, N. Mex. Willow Creek below Heron Dam, N. Mex. Storage in El Vado Reservoir near Tierra Amarilla, N. Mex. Storage in Nambe Falls Reservoir near Nambe, N. Mex. Rio Nambe below Nambe Falls Dam, near Nambe, N. Mex.

The U.S. Geological Survey supplied the record for Rio Grande below Elephant Butte Dam, and in cooperation with the New Mexico Interstate Stream Commission, also provided the following:

Rio Chama below El Vado Dam, N. Mex. Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex. Storage in McClure Reservoir near Santa Fe, N. Mex.

Santa Fe River near Santa Fe, N. Mex.

Storage in Nichols Reservoir near Santa Fe, N. Mex.

records:

The U.S. Geological Survey, in cooperation with the Corps of Engineers, Albuquerque, N. Mex., also provided the following

Rio Chama below Abiquiu Dam, N. Mex. Rio Grande below Cochiti Dam, N. Mex. Galisteo Creek below Galisteo Dam, N. Mex. Jemez River below Jemez Canyon Dam, N. Mex.

The Corps of Engineers, Albuquerque, N. Mex., provided the records of storage in Abiquiu, Galisteo, and Jemez Canyon teservoirs and in Cochiti Lake,

The Southern Pueblos Agency, Bureau of Indian Affairs, Albuquerque, N. Mex., supplied the records of storage in Acomita eservoir

The Laguna Agency, Bureau of Indian Affairs, Laguna, N. Mex., supplied the records of storage in Seama Reservoir.

The U.S. Bureau of Reclamation, El Paso, Texas, provided the following records: Storage in Elephant Butte Reservoir at Elephant Butte, N. Mex. Storage in Caballo Reservoir near Arrey, N. Mex. Rio Grande below Caballo Dam, N. Mex. Bonito ditch below Caballo Dam, N. Mex.

The Rio Grande Compact Commission gratefully acknowledges the cooperation received from these agencies.

31

) (\sim Ċ 32 5

RIO GRANDE COMPACT COMMISSION REPORT ACCURACY OF RECORDS

The Rules and Regulations of the Commission state that the equipment, method, and frequency of measurement at each gaging station shall be sufficient to obtain records at least equal in accuracy to those classified as "good" by the U.S. Geological Survey. Within the physical limitations of stream gaging, the agencies obtaining the records at Compact gaging stations have complied with these regulations.

The accuracy of streamflow records depends primarily on (I) the stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements, and (2) the accuracy of observations of stage, measurements of discharge, and interpretation of records.

The station description states the degree of accuracy attributed to the records. "Excellent" means that about 95 percent of the daily discharges are within 5 percent of the true value; "good" within 10 percent; and "fair" within 15 percent. Records that do not meet the criteria mentioned are rated "poor." Different accuracies may be attributed to different parts of a given record. The probable error in a monthly or annual mean discharge depends more on the distribution of the daily errors between the limits than it does on the limits themselves. For this reason, monthly and annual records are more accurate than most daily records. The number of significant figures and rounding limits used are those as employed by the U.S. Geological Survey.

STREAMFLOW

Rio Grande near Del Norte, Colo.

Location -- Water-stage recorder, lat 37°41'22", long 106°27'38", in NW1/4 sec. 29, T. 40 N., R. 5 E., on right bank, 20 ft downstream from county highway bridge, 6 miles west of Del Norte, and 18 miles upstream from Pinos Creek. Datum of gage is 7,980.25 ft above mean sea level, datum of 1929. Prior to May 16, 1908, staff gage at site 4 miles downstream. Records are equivalent. Drainage area.-1,320 sq mi, approximately. Average discharge -- 102 years (1890-1991), 905 ft³/s (655,700 acre-ft per year).

Remarks.-Records good except those for winter months, which are fair. Flow regulated by four reservoirs, total capacity 126,100 acreft, and by several smaller ones. Six transmountain diversions import water into basin above station.

839

607,500

	Face 1		F	second	
Month	foot-days	Maximum daily	Minimum		
January February March April May June July August September October November December Calendar year 1991	5,410 5,500 6,899 25,846 90,666 84,120 31,384 16,078 18,892 9,117 7,008 5,336 306,256	200 220 260 1,490 4,540 4,340 1,910 722 1,080 410 305 200 4,540	daily 150 170 192 273 741 1,860 580 335 315 248 146 150 146	Mean 175 196 223 862 2,925 2,804 1,012 519 630 294 234 172	Runoff in acre-feet 10,730 10,910 13,680 51,270 179,800 166,900 62,250 31,890 37,470 18,080 13,900 10 580

Monthly and yearly discharge, in cubic feet per second

Conejos River below Platoro Reservoir, Colo.

Location -- Water-stage recorder and concrete control, lat 37°21'18", long 106°32'37", in NW1/4NW1/4 sec. 22, T. 36 N., R. 4 E., on left bank 1,100 ft downstream from valve house for Platoro Reservoir, and 0.7 mile northwest of Platoro. Datum of gage is 9,866.60 ft Drainage area.-40 sq mi, approximately. Average discharge -39 years (1953-91), 93.0 ft³/s (67,380 acre-ft per year).

Extremes.--1952-91: Maximum discharge, 1,160 ft³/s Nov. 1, 1957; maximum gage height, 4.29 ft June 15, 1958; no flow Oct. 16-20, 1955. Remarks. - Records good except those for winter months, which are fair. No diversions above station. Flow completely regulated by

	Second		per second			
Month	foot-days	Maximum daily	Minimum		Pup di i	
inuary ebruary larch pril ay ne ly igust otember tober vember rember rember endår year 1991	99.2 89.6 99.2 993.6 6,620 6,155 7,822 4,959 4,076 827.2 114.3 117.8 31,972.9	3.2 3.2 3.2 108 629 576 398 295 204 55 4.1 3.8 629	daily 3.2 3.2 3.2 3.2 3.2 40 41 140 64 68 3.8 3.8 3.8 3.8 3.8 3.8 3.2	Mean 3.20 3.20 3.20 33.1 214 205 252 160 136 26.7 3.81 3.80 87.6	Runoff in acre-feet 197 178 197 1,970 13,130 12,210 15,510 9,840 8,080 1,640 227 234	
				0,10	63,420	

Monthly and yearly discharge, in cubic feet per se

3.1

en and the second second second

34

RIO GRANDE COMPACT COMMISSION REPORT

Conejos River near Mogote, Colo.

Location.-Water-stage recorder, lat 37°03'14", long 106°11'13", in SE1/4SE1/4 sec. 34, T. 33 N., R. 7 E., on right bank 25 ft upstream from bridge on State Highway 174, 0.4 mile downstream from Fox Creek, and 5.3 miles west of Mogote. Datum of gage is 8,271.54 ft above mean sea level.

Drainage area.--282 sq mi.

Average discharge .- 81 years (1904, 1912-91), 330 ft³/s (239,100 acre-ft per year).

Extremes.-1903-05, 1911-91: Maximum discharge, 9,000 ft³/s Oct. 5, 1911 (gage height, 8.50 ft), from rating curve extended above 3,100 ft³/s; minimum daily determined, 10 ft³/s July 18, 1904.

Remarks.-Records good except those for winter months, which are fair. Diversions above station for irrigation of about 500 acres. Since 1951 flow partly regulated by Platoro Reservoir.

Monthly	and yearly	discharge,	in cubic fee	et per second	l

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
					0.0/0
January	1,440	60	39	46.5	2,860
February	1.446	59	43	51.6	2,870
March	1.999	83	53	64.5	3,970
Anril	11.431	702	77	381	22,670
Mav	36.271	1,840	362	1,170	71,940
lune	28.224	1,540	650	941	55,980
July	14,485	729	278	467	28,730
Anmist	10 602	642	191	342	21,030
Fontombor	7 701	411	180	257	15,270
Octobor	2 839	185	48	91.6	5,630
November	2 088	90	41	69.6	4,140
Desember	1 716	64	48	55.4	3,400
Calendar year 1991	120,242	1,840	39	329	238,500

San Antonio River at Ortiz, Colo.

Location.--Water-stage recorder, lat 36°59'35", long 106°02'17", in New Mexico in NE1/4SE1/4, sec. 24, T. 32 N., R. 8 E., on left bank 800 ft south of New Mexico-Colorado State line, 0.4 mile southeast of Ortiz, and 0.4 mile upstream from Los Pinos River. Altitude of gage is 7,970 ft.

Drainage area.--110 sq mi.

Average discharge .- 51 years (1941-91), 25.7 ft³/s (18,620 acre-ft per year).

Extremes.-1920, 1925-91: Maximum discharge, 1,750 ft³/s Apr. 15, 1937 (gage height, 5.38 ft), from rating curve extended above 1,100 ft³/s; no flow at times.

Remarks.--Records good except those for winter months, which are fair. A few small diversions above station for irrigation.

Monthly and yearly discharge, in cubic feet per second

	Second-	Maximum	Minimum	Mean	Runoff in acre-feet
Month	root-days	ually	dany		
lanuarv	76.0	3.5	1.5	2.45	151
February	68.0	3.5	1.5	2.43	135
March	488.5	48	2.5	15.8	969
April	5.950	460	70	198	11,800
Mav	4.009	284	39	129	7,950
lune	397.07	35	.97	13.2	788
lulv	54.05	10	.00	1.74	107
August	142.26	23	.86	4.59	282
September	59.22	5.8	.43	1.97	117
October	62.1	3.1	1.6	2.00	123
November	182.5	12	2.5	6.08	362
December	108.0	4.0	3.0	3.48	214
Calendar vear 1991	11,596.70	460	.00	31.8	23,000

STREAMFLOW

Los Pinos River near Ortiz, Colo.

Location -- Water-stage recorder, lat 36°58'56", long 106°04'23", in New Mexico on line between secs. 26 and 27, T. 32 N., R. 8 E., on left bank 0.9 mile south of New Mexico-Colorado State line, 2.1 miles southwest of Ortiz, and 2.9 miles upstream from mouth. Altitude Drainage area.-167 sq mi.

Average discharge -- 73 years (1915-20, 1925-91), 120 ft³/s (86,940 acre-ft per year).

Extremes, -1915-20, 1925-91: Maximum discharge, 3,160 ft³/s May 12, 1941 (gage height, 5.77 ft, site and datum then in use), from rating Remarks.-Records good except those for winter months, which are fair. Diversions above station for irrigation.

	Station
Monthly and years to a	
and yearly discharge in milities	
	Der second
	P~ Second

Month	Second- foot-days	Maximum	Minimum		
January February March April May June July August September October November December Calendar year 1991	705 435 823 9,697 21,908 8,679 2,179 1,670 1,122 556 654 647 49,075	30 18 35 674 1,170 463 133 110 82 27 35 25 1,170	daily 12 12 22 41 234 122 33 27 22 14 16 17 12	Mean 22.7 15.5 26.5 323 707 289 70.3 53.9 37.4 17.9 21.8 20.9 134	Runoff in acre-feet 1,400 863 1,630 19,230 43,450 17,210 4,320 3,310 2,230 1,100 1,300 1,280
		Const. D.		ALC'E	97,340

Conejos River near Lasauses, Colo.

Location -- Water-stage recorders, lat 37°18'01", long 105°44'47", in secs. 2 and 11 (two channels), T. 35 N., R. 11 E., on left bank of main channel 125 feet downstream from bridge on State Highway 158 and on left bank of secondary channel 230 ft upstream from bridge, 1.0 mile upstream from mouth, and 2.1 miles north of Lasauses. Datum of gage on main channel is 7,495.02 ft and on secondary (south) channel is 7,496.89 ft above mean sea level (levels by Bureau of Reclamation). Drainage area.—887 sq mi. Average discharge -- 70 years (1922-91), 186 ft³/s (134,800 acre-ft per year). Extremes -- 1921-91: Maximum discharge, 3,890 ft³/s May 15, 1941; no flow at times in some years.

Records good except those for winter months, which are fair. Diversions for irrigation of about 75,000 acres above station.

	Second				
Month	foot-days	Maximum daily	Minimum		Pupetti
nuary Ibruary arch Dril 1y 1e 8 gust Itember ober (ember ember ember Indar year 1991	1,866 2,210 3,565 15,502 22,691 8,528 5,007 4,152 3,174 780 2,151 1,760 71,386	70 102 141 896 1,540 578 334 372 276 59 102 70 1,540	39 58 103 127 256 47 68 47 68 47 29 14 27 49 14	Mean 60.2 78.9 115 517 732 284 162 134 106 25.2 71.7 56.8 196	Kunoff in acre-feet 3,700 4,380 7,070 30,750 45,010 16,920 9,930 8,240 6,300 1,550 4,270 3,490 141,600

Monthly and yearly discharge, in cubic feet per second

35

الم المالية المراجع ال المراجع المراجع

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande near Lobatos, Colo.

Location.--Water-stage recorder, lat 37°04′42″, long 105°45′22″, in sec. 22, T. 33 N., R. II E., on right bank at highway bridge, 6 miles north of Colorado-New Mexico State line, 10 miles east of Lobatos, and 14 miles east of Antonito. Datum of gage is 7,427.63 ft above mean sea level, datum of 1929.

Drainage area.-7,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley).

Average discharge .-- 31 years (1900-30), 846 ft³/s (612,900 acre-ft per year); 61 years (1931-91) 448 ft³/s (324,600 acre-ft per year). Extremes.--1899-1991: Maximum discharge observed, 13,200 ft³/s June 8, 1905 (gage height, 9.1 ft), from rating curve extended above

8,000 ft³/s; no flow at times in 1950-51, 1956. Remarks.--Records good except those for winter months, which are fair. Natural flow of stream affected by transmountain diversions, storage reservoirs, ground-water withdrawals and diversions for irrigation, and return flow from irrigated areas.

Monthly and yearly discharge,	in cubic feet	per second
-------------------------------	---------------	------------

<u> </u>	Second-	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
Month	1001-uays				
	a 000	210	250	287	17,650
January	8,900	310	270	321	17,820
February	8,985	400	200	459	28,200
March	14,216	53/	350	933	55,520
April	27,989	1,660	403	1 032	63,440
Mav	31,986	2,010	427	751	44 670
Iune	22,519	1,330	345	201	20,060
July	10,114	649	162	326	14 140
Anguet	7.139	541	94	230	19,100
Contombor	6.236	519	53	208	12,370
September	2,336	114	55	75.4	4,630
Uctober	9 215	371	92	277	16,490
November	0,010	310	210	274	16,870
December		2 010	53	431	311,900
Calondar year 1991	137.240	2,010			

Willow Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°44'33", long 106°37'34", in Tierra Amarilla Grant, on right bank 200 ft downstream from bridge, 0.2 mile downstream from Iron Spring Creek, 3.3 miles west of Los Ojos, and at mile 9.7. Datum of gage is 7,196.29 ft above mean sea level. Prior to Apr. 1, 1971, at site 900 ft downstream.

Drainage area.--112 sq mi.

Average discharge. -7 years (1963-69), 11.5 ft³/s (8,330 acre-ft per year) prior to completion of Azotea tunnel; 22 years (1970-91), 137 ft³/s (99,260 acre-ft per year) subsequent to completion of Azotea tunnel.

Extremes.-1962-91: Maximum discharge, 1,610 ft³/s Mar. 12, 1985 (gage height, 6.65 ft); no flow at times prior to 1971.

Remarks.-Records good except those for winter months, which are fair. Subsequent to Nov. 16, 1970, flow affected by transmountain diversions through Azotea tunnel. Flow in Rutheron Drain included prior to Apr. 1, 1971.

Manth	Second-	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
Month January February March April May June July August September October	foot-days 18.0 96.1 2,190.9 16,000 21,111 17,822 3,202 657.0 836.20 36.00	daily 1.0 8.1 144 926 931 992 263 83 324 5.0 2.2	50 1.0 7.6 150 199 326 17 2.0 .00 .50	.58 3.43 70.7 533 681 594 103 21.2 27.9 1.16 1.33	36 191 4,350 31,740 41,870 35,350 6,350 1,300 1,660 71 79
November December Calendar year 1990	40.00 16.50 62,025.70	1.0 992	.00 .00	.53 170	33 123,000

(T)

STREAMFLOW

Horse Lake Creek above Heron Reservoir, near Los Ojos, N. Mex.

Location.--Water-stage recorder, lat 36°42'24", long 106°44'42", in Tierra Amarilla Grant, on right bank 3.7 miles northwest of Heron Dam, 7.8 miles downstream from Horse Lake, and 9.9 miles west of Los Ojos. Datum of gage is 7,188.85 ft above mean sea level. Drainage area.-45 sq mi, approximately.

Average discharge -12 years (1963-73, 86), 1.17 ft³/s (848 acre-ft per year).

Extremes.--1963-91: Maximum discharge, 3,960 ft³/s July 30, 1968 (gage height, 4.9 ft); no flow most of time. Remarks.-Records good. Diversions above station for irrigation of meadows and for off-channel stock tanks.

Monthly and yearly discharge, in cubic feet per second

Month	Second- foot-days	Maximum daily	Minimum		Runoff in
January February March April May June July August September October November December	18.00 137.12 4.76 2.12 0.00 0.00 0.00 0.00			Mean 	acre-feet
Calendar year 1991	-	-			

Willow Creek below Heron Dam, N. Mex.

Location -- Totalizing flowmeters, lat 36°39'56", long 106°42'12", in Tierra Amarilla Grant, in outlet conduits at Heron Dam, 0.2 mile upstream from Rio Chama, 5.1 miles northeast of El Vado Dam, and 8.7 miles southwest of Los Ojos. Average discharge,-21 years (1971-91) 111 ft³/s (80,420 acre-ft per year).

Remarks.-Records excellent. Flow completely regulated by Heron Dam.

Extremes.--1971-91: Maximum daily discharge, 2,780 ft³/s Dec. 18, 19, 1982; no flow at times each year.

Month	Second- foot-days	Maximum daily	Minimum		Rupoffin
anuary ⁷ ebruary March april fay ane ally ugust sptember ctober ovember exember alendar year 1991	2,301 4,564 15,264 29,490.00 152.00 0.00 498.30 701.90 0.00 659.00 1,493.00 55,120.20	165 164 754 1,640 52 .00 53 244 .00 .00 71 137 1,640	20 162 162 .00 .00 .00 .00 .00 .00 .00 .00 .00 .0	Mean 74.2 163 492 983 4.90 .000 16.1 22.6 .000 .000 22.0 48.2 151	acre-feet 4,560 9,050 30,280 58,490 301 .00 988 1,390 .00 .00 1,310 2,960 109 300

ି **ପ୍ରେ** ଜୁନ୍ତି ଅନ

a share and a start and a start and a start a s

新 · · · · · ·

38

RIO GRANDE COMPACT COMMISSION REPORT

Rio Chama below El Vado Dam, N. Mex.

Location.—Water-stage recorder, lat 36°34'48", long 106°43'24", in Tierra Amarilla Grant, on left bank 1.5 miles downstream from El Vado Dam, 2.8 miles upstream from Rio Nutrias, and 13 miles southwest of Tierra Amarilla. Datum of gage is 6,696.12 ft above mean sea level, datum of 1929. Prior to October 1935, at site 1.5 miles upstream and October 1935 to September 1938, at site 1.1 miles upstream at different datums.

Drainage area.-877 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.-4 years (1914, 1921-23), 444 ft³/s (321,700 acre-ft per year) prior to completion of El Vado Dam; 35 years (1936-70), 372 ft³/s (269,500 acre-ft per year), prior to release of transmountain water; 21 years (1971-91) 465 ft³/s (336,900 acre-ft per year).

Extremes.—1914-16, 1920-24, 1936-91: Maximum discharge observed, 9,000 ft³/s May 22, 1920 (gage height, 12 ft); no flow Mar. 25, 26, 31, 1955.

<u>Remarks</u>—Records good. Diversions above station for irrigation of about 10,600 acres. Since 1935 flow regulated by El Vado Reservoir and since October 1970 flow partly regulated by Heron Reservoir. Subsequent to May 1971 flow affected by releases of transmountain water from Heron Reservoir.

Monthly and yearly discharge, in cubic feet per second

	Second-	Maximum	Minimum		Runoff in	
Month	foot-days	daily	daily	Mean	acre-feet	
January	6.674	232	198	215	13.240	
February	6,303	233	219	225	12,500	
March	9,253	480	219	298	18,350	
April	41,772	2,620	423	1,392	82,850	
May	67,554	3,800	888	2,179	134,000	
June	24,574	1,180	256	819	48,740	
July	7,622	955	61	246	15,120	
August	8,558	1,020	81	276	16,970	
September	5,476	930	32	183	10,860	
October	5,841	1,640	48	188	11,590	
November	5,074	236	121	169	10,060	
December	7,9 9 2	328	222	258	15,850	
Calendar year 1991	196,693	3,800	32	539	390,100	

Rio Chama below Abiquiu Dam, N. Mex.

Location.--Water-stage recorder, lat 36°14'12", long 106°24'59", in SE1/4SE1/4 sec. 8, T. 23 N., R. 5 E., on right bank 0.8 mile downstream from Abiquiu Dam and 5.9 miles northwest of Abiquiu. Altitude of gage is 6,040 ft (from river-profile map and topographic map). Drainage area.-2,147 sq mi of which about 100 sq mi is probably noncontributing.

Average discharge.--9 years (1962-70), 376 ft³/s (272,400 acre-feet per year), prior to release of transmountain water; 21 years (1971-91), 516 ft³/s (373,800 acre-ft per year).

Extremes.--1961-91: Maximum discharge, 2,990 ft³/s July 1, 1965 (gage height, 6.69 ft); minimum, about 0.5 ft³/s Mar. 17, 1966, Jan. 28, 1972.

<u>Remarks</u>.-Records good. Flow regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation of about 17,600 acres. Subsequent to May 1971 flow affected by the release of transmountain water from Heron Reservoir.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
anuary	3,443	277	76	111	6.830
February	4,916	595	70	176	9,750
March	12,674	718	55	409	25,140
April	27,273	1,410	526	909	54,100
May	54,770	1,970	1,430	1,767	108,600
une	48,570	1,680	1,460	1,619	96,340
uly	15,499	1,740	116	500	30,740
August	10,119	706	113	326	20,070
leptember	10,979	723	101	366	21,780
October	8,417	535	75	272	16,700
Vovember	14,453	555	255	482	28,670
December	12,965	571	173	418	25,720
Calendar vear 1991	224.078	1.970	55	614	444,500

STREAMFLOW

Rio Nambe below Nambe Falls Dam, near Nambe, N. Mex.

Location.-Totalizing flow meters, lat 35°50'46", long 105°54'17", in NE1/4SW1/4 sec. 29, T.19 N., R.10 E., in Nambe Indian Reservation, in outlet conduits at Nambe Fails Dam, 300 feet upstream from Nambe Fails, 2.6 miles upstream from confluence of Rio Nambe and Drainage area.--34.1 sq mi. Average discharge -- 13 years (1979-91), 15.9 ft³/s (11,520 acre-feet per year).

Extremes.—1979-91: Maximum discharge, 312 ft³/s June 9, 1979 (gage height, 1.96 feet), at site 1,100 feet downstream; minimum daily Remarks.-Records good. Flow completely regulated by Nambe Falls Reservoir.

Monthly and yearly discharge, in cubic feet per second

	Second-			a second		
Month	foot-days	Maximum daily	Minimum			_
January February March April May June July August September October Jovember Secember alendar year 1991	113.0 102.14 150.72 468.5 1153 1270 638.5 1,004 660 307.9 243.5 172.3 6,283.56	11 4.1 20 21 72 60 47 60 34 15 9.5 8.1 72	daily 1.1 58 58 4.1 23 19 2.0 15 14 7.0 7.1 3.1 58	Mean 3.65 3.65 4.86 15.6 37.2 42.3 20.6 32.4 22.0 9.93 8.12 5.56	Runoff in acre-feet 224 203 299 929 2,290 2,520 1,270 1,990 1,310 611 483 342	-
Cation Ma	Rio Grand	e at Otowi Bridge	_	17.2	12,460	

Rio Grande at Otowi Bridge, near San Ildefonso, N. Mex.

cation -- Water-stage recorder, lat 35°52'29", long 106°08'30", in San Ildefonso Pueblo Grant, 400 ft downstream from bridge on State Highway 4, 1.8 miles south west of San Ildefonso Pueblo, 2.5 miles downstream from Pojoaque River, and 6.8 miles west of Pojoaque. Datum of gage is 5,488.48 ft above mean sea level, datum of 1929. Prior to May 19, 1904, and July 25 to Oct. 1, 1904, staff gage at site inage area.—14,300 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.). rage discharge.--92 years (1896-1905, 1910-91), 1,530 ft³/s (1,108,000 acre-ft per year).

emes.-1895-1905, 1910-91: Maximum discharge, 24,400 ft³/s May 23, 1920 (gage height, 14.1 ft); minimum daily, 60 ft³/s July 4, 5, arks.-Records good. Flow partly regulated by Heron, El Vado, and Abiquiu Reservoirs. Diversions above station for irrigation about 620,000 acres in Colorado and 75,000 acres in New Mexico. Subsequent to May 1971 flow affected by releases of

Monthly and yearly discharge, in cubic feet per second

<u>ы.</u>	Second-			a second	
Month	foot-days	Maximum daily	Minimum		
y ry er :r year 1991	26,279 29,774 47,230 91,640 141,410 103,810 43,090 47,206 33,446 21,452 36,442 34,991 656,770	1,060 1,710 1,970 4,360 8,400 4,490 2,730 3,430 1,740 1,040 1,760 1,370 8,400	daily 669 799 1,000 1,620 2,550 2,280 724 704 762 479 483 791 479	Mean 848 1,063 1,524 3,055 4,562 3,460 1,390 1,523 1,115 692 1,215 1,129 1,799	Runoff in acre-feet 52,120 59,060 93,680 181,800 280,500 205,900 85,470 93,630 66,340 42,550 72,280 69,400 1,302 700



the second state in the second state and

40

RIO GRANDE COMPACT COMMISSION REPORT

Santa Fe River near Santa Fe, N. Mex.

Location.--Water-stage recorder and concrete control, lat 35°41'12", long 105°50'35", in NE1/4SE1/4 sec. 23, T. 17 N., R. 10 E., 0.4 mile downstream from McClure Dam, and 5.3 miles east of Santa Fe. Altitude of gage is 7,718 ft. Prior to Nov. 4, 1930, at site 1.5 miles downstream, and Apr. 11, 1931 to Sept. 30, 1947, at site 0.3 mile upstream, each at different datum.

Drainage area.--18.2 sq mi.

Average discharge .- 79 years (1913-91), 8.07 ft³/s (5,850 acre-ft per year).

Extremes.-1913-91: Maximum discharge, 1,500 ft³/s Aug. 14, 1921; minimum, 0.05 ft³/s Apr. 7, 8, 1981.

Remarks.--Records good. Flow regulated by McClure Reservoir, completed in 1926, raised in 1935 and again in 1947.

M	onthl	y and	yearly	y disc	harge,	in cu	bic	feet	per s	second
---	-------	-------	--------	--------	--------	-------	-----	------	-------	--------

	Second-	Maximum	Minimum		Runoff in	
Month	foot-days	daily	daily	Mean	acre-feet	
lanuary	159.0	5.2	4.9	5.13	315	
February	138.2	5.2	4.9	4.94	274	
March	158.7	5.2	4.8	5.12	315	
April	172.5	6.2	4.9	5.75	342	
May	440.6	56	6.2	14.2	874	
June	499.2	45	5.8	16.6	990	
July	547.2	70	4.6	17.7	1,090	
August	1,034.2	75	6.2	33.4	2,050	
September	577.4	62	6.2	19.2	1,150	
October	109.3	6.2	3.0	3.53	217	
November	92.5	3.4	2.9	3.08	183	
December	90.1	3.1	2.8	2.91	179	
Calendar year 1991	4,018.9	75	2.8	11.0	7,970	

Rio Grande below Cochiti Dam, N. Mex.

Location.--Water-stage recorder, lat 35°37'05", long 106°19'24", in SW1/4NE1/4 sec. 17, T. 16 N., R. 6 E., in Pueblo de Cochiti Grant, 320 feet upstream from bridge on State Highway 22, 700 feet downstream from Cochiti Dam, and 1.4 miles northeast of Cochiti Pueblo. Datum of gage is 5,226.08 ft above mean sea level, datum of 1929. Prior to Nov. 14, 1973, at site 2.4 mi downstream at altitude 5,210 ft. Nov. 14, 1973 to Jan. 8, 1976, at site 320 ft downstream at datum 1.79 ft lower.

Drainage area.--14,900 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge, -- 21 years (1971-91) 1,387 ft³/s (1,005,000 acre-ft per year).

Extremes.--1971-91: Maximum discharge, 10,300 ft³/s July 26, 1971, at site 2.4 miles downstream prior to closure of Cochiti Dam; minimum discharge, 0.51 ft³/s Aug. 3-5, 1977, Aug. 27-28, 1978.

Remarks.--Records good. Since Nov. 12, 1973, flow completely regulated by Cochiti Dam. Cochiti eastside main canal on left bank and Sili main canal on right bank bypass station.

Monthly	v and	vearlv	discharge	. in cu	bic fee	et per	second
TATOMETER	,	y can sy	***************************************		~.~.~		

	<u> </u>) <i>(</i> := :		
Manak	Second-	Maximum	Minimum	Moon	KUNOM IN
Month	root-days	Gally	uany		acreteet
January	23,443	1,160	287	756	46,500
February	26,324	1,180	783	940	52,210
March	37,286	1,540	722	1,203	73,96 0
April	75,120	3,480	1,420	2,504	149,000
May	104,650	4,080	2,910	3,376	207,600
une	131,490	5,120	3,600	4,383	260,800
uly	38,782	3,320	519	1,251	76,920
August	39,249	2,960	600	1,266	77,850
September	2 9 ,162	1,370	5 99	972	57,840
October	16,672	713	335	538	33,070
November	34,779	1,500	494	1,159	68,980
December	34,901	1,380	701	1,126	69,230
Calendar year 1991	591,858	5,120	287	1,622	1,174,000

 \sim

STREAMFLOW

Galisteo Creek below Galisteo Dam, N. Mex.

Location.-Water-stage recorder, lat 35°27'56", long 106°12'57", in SE1/4SE1/4 sec. 5, T. 14 N., R. 7 E., 0.6 mile downstream from Drainage area.--597 sq mi. Average discharge -21 years (1971-91), 6.25 ft³/s (4,530 acre-ft per year).

•

Extremes.-1970-91: Maximum discharge, 2,000 ft³/s July 27, 1971 (gage height, 7.00 ft); maximum gage height, 7.33 ft July 20, 1971; no Remarks.-Records poor. Flow partly regulated by uncontrolled outlet in Galisteo Dam. Capacity of outlet, 5,000 ft³/s when reservoir

Monthly and yearly disch

 <i>.</i>	Jeany	discharge,	in	cubic	feet	per	second	ł
 -	Jaily	uischarge,	in	cubic	feet	per	second	

Month	foot-days	Maximum daily	Minimum		Runoff in	-
January February March April May June July August September October November December Calendar year 1991	28.00 19.13 22.90 1.30 11.45 148.31 1,029.61 1,727.66 397.14 11.01 19.92 19.65 3,436.08	1.5 .80 1.9 .63 8.7 94 330 513 226 2.1 1.3 .90 513	.00 .50 .41 .00 .00 .00 .00 .00 .23 .18 .00 .00 .00 .00 .00 .00	Mean .90 .68 .74 .043 .37 4.94 33.2 55.7 13.2 .36 .66 .63 9.41	acre-feet 56 38 45 2.6 23 294 2,040 3,430 788 22 40 39	
	Iomo	~ D: •		2.41	6.820	

Jemez River below Jemez Canyon Dam, N. Mex.

Location.-Water-stage recorder, lat 35°23'24", long 106°32'03", in NE1/4 sec. 5, T. 13 N., R. 4 E., 0.8 mile downstream from Jemez Canyon Dam, 2.0 miles upstream from mouth, and 6 miles north of Bernalillo. Datum of gage is 5,095.60 ft above mean sea level, datum of 1929. Prior to April 24, 1951, at site three-quarters of a mile upstream at datum 24.51 ft higher. April 24, 1951 to June 25, 1958, Drainage area - 1,038 sq mi. Average discharge. 49 years (1937, 1944-91), 61.9 ft³/s (44,850 acre-ft per year).

Extremes.--1937, 1944-91: Maximum discharge, 16,300 ft³/s Aug. 29, 1943 (gage height, 5.62 ft); no flow at times. Remarks,-Records good. Flow regulated by Jemez Canyon Dam since October 1953. Diversions for irrigation of about 3,000 acres

	N	onthly and yearly disch	5000- d	acre	
Month	Second- foot-days	Maximum daily	Minimum		Runoffin
inuary ebruary larch pril ay ne ly igust ptember tober vember cember cember endar year 1991	922.8 808 1,925 5,191.8 78.27 9.75 2,876.32 7,649.16 3,881.27 467.5 2,043 2,088 27,940.87	135 43 88 306 4.2 .38 624 1,320 870 53 292 160 1,320	2.1 20 48 2.1 .28 .28 .28 .22 .28 .78 1.1 16 24 .22	Mean 29.8 28.9 62.1 173 2.52 32 92.8 247 129 15.1 68.1 67.4 76.6	1,830 1,600 3,820 10,300 155 19 5,710 15,170 7,700 927 4,050 4,140 55,420

5 8 9 J C J 42 - J

and the second second

RIO GRANDE COMPACT COMMISSION REPORT

Rio Grande below Elephant Butte Dam, N. Mex.

Location.-Water-stage recorder, lat 33°08'54", long 107°12'22", in SW1/4 sec. 25, T. 13 S., R. 4 W., (projected) in Pedro Armendariz Grant, 1.0 mile downstream from dam and 1.5 miles upstream from Cuchillo Negro River. Datum of gage is 4,242.09 ft above mean sea level, datum of 1929. Prior to April 23, 1942, at several different sites and datums.

Drainage area. -- 29,450 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge .-- 77 years (1915-91), 995 ft3/s (720,900 acre-ft per year).

Extremes.-1915-91: Maximum daily discharge, 8,220 ft³/s May 22, 1942; no flow at times prior to 1929 and March 2-4, 1979.

Remarks.--Records good. Flow regulated by Elephant Butte Reservoir. Diversions for irrigation of about 800,000 acres above station.

Monthly and yearly discharge, in cubic feet per second

	Second-	Maximum	Minimum	Mean	Runoff in acre-feet
Month	toot-days	dany	dany		
January	365.3	14	9.2	11.8	725
February	12,537.8	1,300	8.6	448	24,870
March	41,331	1,510	665	1,333	81,980
April	41.768	1,560	948	1,392	82,850
Mav	47,020	2,040	919	1,517	93,260
lune	57,710	2,130	1,400	1,924	114,500
luiv	44,988	2,000	683	1,451	89,230
August	19,589	1,490	23	632	38,850
September	22,691	1,570	13	756	45,010
October	13,361.0	1,280	6.0	431	26,500
November	210.4	72	6.8	7.01	417
December	228.2	7.7	6.5	7.36	453
Calendar year 1991	301,799.7	2,130	6.0	827	598,600

Rio Grande below Caballo Dam, N. Mex.

Location.-Water-stage recorder, lat 32°53′05", long 107°17′31", in NE1/4SW1/4 sec. 30, T. 16 S., R. 4 W., 2,000 ft upstream from Interstate Highway 25, 4,200 ft downstream from Caballo Dam, 1.3 miles upstream from Percha diversion dam, and 3 miles northeast of Arrey. Datum of gage is 4,140.90 ft above mean sea level, datum of 1929. October 13, 1938 to December 31, 1945, at datum 5.0 ft higher.

Drainage area. -- 30,700 sq mi, approximately (includes 2,940 sq mi in closed basin in San Luis Valley, Colo.).

Average discharge.-54 years (1938-91) 905 ft³/s (655,700 acre-ft per year).

Extremes.--1938-91: Maximum daily discharge, 7,650 ft³/s May 20, 1942; minimum daily, 0.1 ft³/s Oct. 31 to Nov. 14, 1954, Nov. 7 to Dec. 31, 1955, Feb. 15-29, 1972.

Remarks.--Records good. Flow regulated by Elephant Butte and Caballo Reservoirs. Diversions for irrigation of about 800,000 acres above station.

Month	Second- foot-days	Maximum daily	Minimum daily	Mean	Runoff in acre-feet
lanuary	35.0	2.0	1.0	1.13	69
February	6.616.0	848	2.0	236	13,120
March	53,237	2.190	777	1,717	105,600
April	36.059	1.440	929	1,202	71,520
Mav	44,400	1.890	1,010	1,432	88,070
lune	57.740	2,250	1,620	1,925	114,500
July	47.530	2.140	1,300	1,533	94,280
Angust	33,692	2.000	100	1,087	66,830
Sentember	25 043	1.900	25	835	49,670
October	11 135.0	926	3.0	359	22,090
November	73.0	3.0	2.0	2.43	145
December	52.0	2.0	1.0	1.68	. 103
Calendar year 1991	315,612.0	2,250	1.0	865	626,000

STREAMFLOW

Bonito ditch below Caballo Dam, N. Mex.

Records available.-January 1938 to December 1991. Published as supplementary data with Rio Grande below Caballo Dam in U.S.G.S.

Remarks.-Ditch diverts directly from Caballo Reservoir for irrigation of lands on right bank of river. The total release from Project Storage, as used in computations of Compact Commission, is the combined flow of this ditch and Rio Grande below Caballo Dam.

Diversion, in a	cre-feet
January	
February	0
March	0
April	1
Mav	1
June	84
lulv	54
August	70
September	82
October	22
Novembor	7
December	0
	0
Calendar year 1991	20.4
	321

an a said a said

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Squaw Lake.-Staff gage in sec. 12, T. 39 N., R. 4 W., on tributary to Squaw Creek. Completed in 1938; capacity, 162 acre-ft by 1953 survey. Water is used for irrigation below gaging station on Rio Grande near Del Norte.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	_
Gage height	2.4	4.7	6.9	9.1	9.1	9.1	0.0	0.0	0.0	0.0	1.2	2.4	-	
Contents	40	80	120	162	162	162	0	0	0	0	20	40	•	
Change	+40	+40	+40	+42	0	0	-162	0	0	0	+20	+20	+40	

<u>Rito Hondo Reservoir</u>.-Staff gage in sec. 22, T. 42 N., R. 3 W., on Rito Hondo (Deep Creek) tributary to Clear Creek. Completed in 1957; capacity, 561 acre-ft. Originally filled during May and June 1958 with transmountain water; storage is not in debit status. Water is used for fish culture.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	•
Contents Change	561 0	561 0	561 0	561 0	561 0	56 0	561 0	561 0	561 0	561 0	561 0	561 0	- 0

Hermit Lakes Reservoir No. 3.—In sec. 25, T. 41 N., R. 4 W., on South Clear Creek. Completed prior to 1960; capacity, 192 acre-ft. Capacity table based on elevation above bottom of outlet. Water is used for fish culture. Includes 169 acre-ft of transmountain water by exchange in 1984 and 23 acre-ft of transmountain water by exchange in 1985.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	-
Contents	192	192	192	192	192	192	192	192	192	192	192	192	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

Troutvale No. 2 Reservoir.--Staff gage in E1/2 sec. 10, T. 41 N., R. 3 W., on South Clear Creek. Completed in 1940; capacity, 435 acre-ft. Condition of spillway limited storage to 168 acre-ft after May 1942. Repairs to spillway in 1947 increased capacity to 257 acre-ft. Water is used for fish culture with only occasional sale for irrigation. Storage omitted from accounting by action of Commission on Feb. 15, 1962.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Арт.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.	
Gage height	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	-	
Contents	257	257	257	257	257	257	257	257	257	257	257	257	-	
Change	0	0	0	0	0	0	0	0	0	0	0	0	0	

Month

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Jumper Creek Reservoir.-In sec. 5, T. 39 N., R. 2 W., on Jumper Creek, tributary to Trout Creek. Completed in 1951; capacity, 38 acreft. Capacity table based on elevation above bottom of outlet. Storage omitted from accounting by action of Commission on Feb. 15,

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb	Man		_									
Gage height	4.0	4.0	14141.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Calum	
Contents Change	12 0	4.0 12 0	4.0 12 0	4.0 12 0	4.0 12	4.0 12	4.0 12	4.0 12	4.0 12	4.0 12	4.0	4.0	- Cal.yr.	
Big Mondau	Ð				Ŭ	U	0	0	0	0	0	12	-	

Big Meadows Reservoir.-In NW1/4 sec. 17, T. 38 N., R. 2 E., on South Fork about 0.9 mile upstream from Hope Creek. Completed in 1967; capacity, 2,437 acre-ft. Capacity table based on elevation above outlet. Water is used for fish culture. Includes 140 acre-ft of transmountain water, by exchange, in 1967; 838 acre-ft, by exchange, in 1968; and 347 acre-ft, by exchange, in 1969, and 1,112 acre-ft,

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Anr	¥	-				_	_	_		
Gage height	45.0	45.0	45.0		May	June	July	Aug.	Sept.	Oct,	Nov.	Dec.	Cal.vr.	
Contents Change	2,437 0	2,437 0	40.0 2,437 0	45.0 2,437 0	45.0 2,437 0	45.0 2,437 0	45.0 2,437	45.0 2,437	45.0 2,437	45.0 2,437	45.0 2,437	45.0	-	
Alberta Daul	D	_				-	U	U	0	0	0	0	0	

rta Park Reservoir. - In sec. 34, T. 38 N., R. 2 E., on Pass Creek. Completed in 1953; capacity, 598 acre-ft. Capacity table based on elevation above bottom of outlet. Storage prior to June 30, 1983 included 244 acre-ft of transmountain water imported in 1963. By a 1983 resolution of the Rio Grande Compact Commission, the reservoir was drained for repairs in July 1983; recovery was completed in 1984. The reservoir also contains 100 acre-ft of transmountain water stored by exchange in 1983 and 254 acre-ft of

Month-end gage height, in feet, and contents, in acre-feet

Nonth	Jan.	Feb.	Mar	4					_					
age height	27.0	27.0		Apr.	Мау	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.vr	
Contents hange	598 0	598 0	27.0 598 0	27.0 598	27.0 598	27.0 598	<u>_</u>							
									v	U		^	_	

law Lake Enlargement. In sec. 5, T. 38 N., R. 2 E., on tributary to Lake Creek. Capacity, 638 acre-ft by 1916 decree; enlarged in 1955 to 681 acre-ft. Only the storage in excess of 638 acre-ft is subject to terms of Rio Grande Compact. Includes 42 acre-ft of

Month-end gage height, in feet, and contents, in acre-feet

nth	Jan.	Feb.	Mar.	Apr.	May	Јиле	July	Aug.	Sept.	Oct	Nov			
e height tents nge	- 42 0	- 42 0	- 42 0	42 0	- 42 0	- 42 0	- 42 0	42	42	42	- 42	 42	Cai.yr.	
						-	U	0	0	0	0	0	٥	

45

me wassed at a county for the

RIO GRANDE COMPACT COMMISSION

Reservoirs in Rio Grande Basin in Colorado (Constructed or enlarged since 1937)

Mill Creek Reservoir.-In sec. 16, T. 39 N., R. 3 E., on Mill Creek. Completed in 1953; capacity, 43 acre-ft. Capacity based on elevation above bottom of outlet. Includes 43 acre-ft of transmountain water, by exchange, in 1976.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	-
Contents	43	43	43	43	43	43	43	43	43	43	43	43	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

Fuchs Reservoir.--Staff gage in . ec. 2, T. 37 N., R. 4 E., on East Pinos Creek. Completed in 1939; capacity, 237 acre-ft with 2 feet of flash boards in spillway. Pinos Creek enters Rio Grande below station near Del Norte.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	15.1	17.2	1 7.2	17.2	17.2	17.2	14.9	14.6	12.8	0.0	7.0	10.4	-
Contents	190	238	238	238	238	238	186	180	143	0	50	100	-
Change	+30	+48	0	0	0	0	-52	-6	-37	-143	+50	+50	-60

<u>Platoro Reservoir</u>.-Water-stage recorder in NW1/4 sec. 22, T. 36 N., R. 4 E., on Conejos River. Completed in 1951; capacity, 59,570 acreft at crest of spillway. Reservoir is used for irrigation and flood control. Storage affects Conejos Index Supply. Contents include 3,000 acre-ft of transmountain water stored by exchange in April 1985 on behalf of the Colorado Division of Wildlife.

Month-end elevation, in feet, and contents; in acre-feet

Data	Flevation	Contents	Change in Contents
	Bievanon		citatigo in contaito
December 31, 1990	9,961.13	9,240	-
January 31, 1991	9,962.31	9,741	+501
February 28	9,963.03	10,051	+310
March 31	9,964.48	10,687	+636
April 30	9,968.18	12,370	+1,683
May 31	9,983.42	20,277	+7,907
June 30	10,007.40	36,449	+16,172
July 31	9,996.31	28,400	-8,049
August 31	9,988.59	23,373	-5,027
September 30	9,981.72	19,306	-4,067
October 31	9,979.37	18,002	-1,304
November 30	9,980.64	18,701	+699
December 31	9,982.04	19,487	+786
Calendar year 1991	-	-	+10,247

Trujillo Meadows Reservoir.-In sec. 5, T. 32 N., R. 5 E., on Los Pinos River. Completed in 1957; capacity, 913 acre-ft. Water is used for fish culture. Storage is transmountain water, by exchange, in 1959.

Month-end gage height, in feet, and contents, in acre-feet

Month	Jan.	Feb.	Mar.	Арг.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Gage height	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	-
Contents	913	9 13	913	913	913	913	913	913	913	913	913	913	-
Change	0	0	0	0	0	0	0	0	0	0	0	0	0

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Heron Reservoir.-Water-stage recorder, lat 36°39'56", long 106°42'13", on Willow Creek. Storage began in October 1970. Capacity, 401,300 acre-ft at elevation 7,186.1 ft (low point on crest of spillway); dead storage, 1,340 acre-ft at elevation 7,003.0 ft. Used for storage

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation		
December 31, 1990 January 31, 1991 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31 Calendar year 1991	7,182.50 7,181.74 7,180.28 7,176.21 7,171.55 7,179.33 7,185.46 7,186.05 7,185.84 7,185.87 7,185.59 7,185.38 7,185.38 7,184.91	Contents 380,390 376,060 367,800 345,350 320,650 362,490 397,560 401,040 399,800 399,800 399,800 399,800 397,100 394,340	Change in Contents -4,330 -8,260 -22,450 -24,700 +41,840 +35,070 +3,480 -1,240 +180 -1,650 -1,230 -2,760
Vado Paramas III			T 10,700

do Reservoir.-Water-stage recorder and surface follower, lat 36°35'39", long 106°44'00", on Rio Chama. Storage began in January 1935. Capacity, 186,250 acre-ft at gage height 6,902.0 feet (crest of spillway); dead storage, 480 acre-ft, below gage height 6,775.0 ft (invert of outlet works), as determined by survey in 1984. Datum of gage is 8.21 feet above mean sea level, datum of 1929. Storage

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height			
		Contents	Change in contents	
ecember 31, 1990 nuary 31, 1991 bruary 28 arch 31 oril 30 iy 31 ie 30 y 31 gust 31 otember 30 ober 31 /ember 30 ember 31 indar year 1991	6,872.08 6,870.07 6,870.70 6,880.60 6,897.50 6,897.33 6,894.27 6,891.74 6,888.88 6,886.71 6,882.85 6,881.33 6,877.65	104,500 100,170 101,510 124,520 172,010 171,490 162,160 154,680 146,490 140,480 130,250 126,360 117,270	-4,330 +1,340 +23,010 +47,490 -520 -9,330 -7,480 -8,190 -6,010 -10,230 -3,890 -9,090 +12,770	TM Water 85,690 80,720 81,530 104,650 152,220 151,270 143,440 136,010 127,840 121,980 111,780 107,140 98,170

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Abiquiu Reservoir.-Water-stage recorder, lat 36°14'24", long 106°25'44", on Rlo Chama. Completed in February 1963; capacity, 1,201,200 acre-ft at elevation 6,350 feet (crest of spillway) by 1984 survey. Reservoir is operated by Corps of Engineers for flood control and sediment storage. A resolution granting permission to store transmountain waters was approved by Rio Grande Compact Commission on May 3, 1974. Storage includes both Rio Grande and transmountain water.

Month-end elevation, in feet, and contents, in acre-feet

		·			
Date	Elevation	Contents	Change in contents	TM water	
December 31, 1990	6,211.65	156,500*	-	155,100	
January 31, 1991	6,213.62	164,000	+7,500	163,660	
February 28	6,215.25	170,300	+6,300	170,800	
March 3	6,215.38	170,800	+500	171,220	
April 30	6,226.08	214,850	+44,050	170,660	
May 31	6,234.86	254,910	+40,060	169,890	
June 30	6,225.30	211,490	-43,420	173,980	
lulv 31	6,221.42	195,170	-16,320	156,970	
August 31	6,221.54	195,670	+500	158,660	
September 30	6,219.02	185,310	-10,360	148,750	
October 31	6,217.35	178,580	-6,730	142,520	
November 30	6,213.54	163,690	-14,890	148,170	
December 31	6.211.50	155,940	-7,750	154,950	
Calendar year 1991	-	-	-560	-	

*Revised contents based on new capacity table effective Jan. 1, 1991.

West Sections

48

Nambe Falls Reservoir.-Water-stage recorder in NE1/4SW1/4 sec. 29, T. 19 N., R. 10 E., in Nambe Indian Reservation, on Rio Nambe. Completed in 1976; capacity 2,023 acre-ft at elevation 6,826.6 feet (crest of spillway), dead storage 121 acre-ft at elevation 6,760.9 feet. Storage is transmountain water by exchange (see resolution adopted March 27, 1975).

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation	Contents	Change in contents
December 31, 1990	6,823.58	1,850	-
January 31, 1991	6,824.40	1,900	+50
February 28	6,825.00	1,930	+30
March 31	6,825.93	1,980	+50
April 30	6,825.56	1,960	-20
May 31	6,826.76	2,030	+70
June 30	6,826.65	2,030	0
July 31	6,826.63	2,020	-10
August 31	6,826.68	2,030	+10
September 30	6,826.66	2,030	0
October 31	6,825.63	1,970	-60
November 30	6,824.62	1,910	-60
December 3ì	6.824.76	1,920	+10
Calendar year 1991	-	-	+70

RIO CRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

McClure (Granite Point) Reservoir.--Water-stage recorder in NE1/4SW1/4 sec. 24, T. 17 N., R. 10 E., on Santa Fe River. Original reservoir completed in 1926, capacity, 561 acre-ft; in 1935, permanent flash boards were installed in spillway increasing capacity to 650 acre-ft; in 1947 both dam and spillway were reconstructed increasing capacity to 2,615 acre-ft (gage height, 96.6 ft, crest of spillway). In 1953 spillway was equipped with radial gates that opened automatically, increasing capacity to over 3,000 acre-ft. In 1972, radial gates were removed decreasing capacity to 2,615 acre-ft. In 1989, modifications to the dam and spillway increased capacity to 2,813 acre-ft. No dead storage. Altitude of gage is 7,790 ft. Water is for municipal use in Santa Fe. Storage includes both Rio Grande water and transmountain water by exchange. Only the storage of Rio Grande water in excess of 561 acre-feet is subject to terms of Rio Grande Compact.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents	Pre-compact	
December 31, 1990 January 31, 1991 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 Dectober 31 Jovember 30 December 31 alendar year 1991	80.95* 77.03 73.28 73.65 - 99.67 99.71 99.52 99.58 99.07 99.28 99.50	1,610 1,390 1,230 1,230 1,760 2,850 2,840 2,840 2,840 2,830 2,830 2,830 2,830 2,830 2,830	$ \begin{array}{r} -220 \\ -160 \\ 0 \\ +530 \\ +1,090 \\ -10 \\ 0 \\ -10 \\ 0 \\ -30 \\ +10 \\ +20 \\ +1 220 \\ \end{array} $	water 561 355 195 205 561 561 561 561 561 561 561 561 561 56	TM water 469 1,035 1,035 1,025 1,199 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252 2,252

*Revised

Nichols Reservoir.-Water-stage recorder in SE1/4NE1/4 sec. 21, T. 17 N., R. 10 E., on Santa Fe River. Completed in 1942; capacity, 685 acre-ft at gage height 167.0 feet (crest of spillway), dead storage, 14 acre-ft at gage height 121.1 feet. Datum of gage is 7,313.2 feet above mean sea level, datum of 1929. Water is for municipal use in Santa Fe. Storage includes both Rio Grande water and transmountain

Date	Gage height				
		Contents	Change in contents	TM united	
ecember 31, 1990 nuary 31, 1991 bruary 28 arch 31 wil 30 wy 31 ie 30 y 31 gust 31 tember 30 ober 31 rember 31 mber 31 mdar year 1991	152.66 151.80 142.72 153.68 153.31 167.22 167.20 167.18 166.98 167.10 164.70 167.00 167.10	330 314 173 350 342 692 692 691 685 688 617 685 688	-16 -141 +177 -8 +350 0 -1 -6 +3 -71 +68 +3 +358	120 314 173 350 342 685 685 685 685 685 685 685 685 685 685	
				-	

the states

50

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Cochiti Lake.-Water-stage recorder and manometer in NW1/4SW1/4 sec. 16, T. 16 N., R. 6 E., in Pueblo de Cochiti Grant, on Rio Grande. Completed in 1975; capacity 502,300 acre-ft at elevation 5,450.0 ft (crest of service spillway); dead storage 560 acre-ft at elevation 5,255.0 ft, from 1986 survey. A 50,000 acre-foot permanent pool was authorized by Public Law 88-293, 88th Congress, March 26, 1964. Reservoir is operated by Corps of Engineers for flood control, sediment storage, and recreation. Storage began Nov. 12, 1973.

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation	Contents	Change in contents	TM water	
December 31, 1990	5,332.33	50.210	<u> </u>	47.040	
January 31, 1991	5,332.39	50,290	+80	47,040	
February 28	5,332.96	50,990	+30	47,860	
March 3	5,332.78	50,770	-220	48,440	
April 30	5,341.03	61,860	+11.090	40,240	
May 31	5,365.97	111.140	+49 280	40,330	
June 30	5,333.41	51.560	-59 580	47,030	
July 31	5,331.43	49.150	-2 410	47,370	
August 31	5,331.44	49.160	+10	40,920 AE 840	
September 30	5,331.60*	49.340	+180	45,000	
October 31	5,331.45	49,170	-170	45,000	
November 30	5,331.40	49,120	-50	45,420	
December 31	5,331.53	49,270	-50	43,350	
Calendar year 1991	· -	-	-940	43,440 -	

*Revised

<u>Calisteo Reservoir</u>.-Water-stage recorder and manometer in NW1/4 sec. 9, T. 14 N., R. 7 E., on Galisteo Creek. Storage records begin in October 1970. Capacity 88,990 acre-ft at elevation 5,608.0 ft (crest of spillway). No dead storage. Reservoir is operated by Corps of Engineers for flood control and sediment storage.

Month-end	contents	, in	acre-	fæt
-----------	----------	------	-------	-----

Month	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Cal.yr.
Contents Change	0 0	0 0	0 0	0 0	0	0	0	0	0 0	0	0	0	0

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico (Constructed or enlarged since 1929)

Jemez Canyon Reservoir.--Water-stage recorder in SW1/4SW1/4 sec. 32, T. 14 N., R. 4 E., on Jemez River. Completed in 1953; capacity, 172,800 acre-ft at elevation 5,252.3 ft. Maximum controlled capacity at elevation 5,232.0 ft (floor of spillway) is 102,700 acre-ft by 1983 survey. Reservoir is operated by Corps of Engineers for flood control and sediment storage. A sediment pool of about 2,000 acre-

Month-end elevation, in feet, and contents, in acre-feet

Date	Elevation			
December 31, 1990	5.186.37	Contents	Change in contents	TM Water
January 31, 1991 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31 Calendar year 1991	5,186.35 5,186.26 5,185.99 5,192.68 5,200.17 5,201.11 5,200.06 5,194.83 5,194.57 5,194.15 5,194.30	16,810 16,790 16,700 16,420 24,070 34,350 35,750 34,190 26,830 26,490 25,940 26,210 26,210 26,140	- -20 -90 -280 +7,650 +10,280 +1,400 -1,560 -7,360 -340 -550 +270 -70 +9,330	11,730 11,690 11,540 11,260 10,830 10,530 10,240 20,980 20,560 20,160 19,600 19,550 19,550

Acomita Reservoir.—Staff gage in SE1/4 sec. 29, T. 10 N., R. 7 W., on San Fidel Arroyo; water for reservoir is diverted from Rio San Jose. Completed in 1938; original capacity, 850 acre-ft; present capacity 650 acre-ft on basis of 1956 sediment survey. Water is used for

Month-end contents, in acre-feet

onth	Jan.	Feb.	Man											
			wiar.	Apr.	May	June	July	Aug.	Sept.	Oct	NTerr			
ontents	0	0	0	0							Nov.	Dec.	Cal.yr.	
uange	0	0	õ	0	0	0	0	0	0	Λ				
			-	v	U	0	0	0	ñ	0	U	0	0	
Den								•	U	U	0	n	0	

ama Reservoir.-In sec. 36, T. 10 N., R. 7 W., off channel from Rio San Jose. Completed in October 1980; capacity approximately 400

storage during 1991.

1 E 14 1 1 - 1

 σ 1 52 C, I

RIO GRANDE COMPACT COMMISSION REPORT

Reservoirs in Rio Grande Basin in New Mexico (Project storage)

Elephant Butte Reservoir.--Water-stage recorder in NW1/4 sec. 30, T. 13 S., R. 3 W., on Rio Grande. Storage began Jan. 6, 1915; capacity, 2,065,000 acre-ft at gage height 4,407.0 ft (crest of spillway), by survey of 1988. Datum of gage is 43.3 ft above mean sea level, datum of 1929. Water is used for power development and irrigation in New Mexico and Texas. Records furnished by Bureau of Reclamation. Delivery of transmountain water for minimum recreation pool was initiated in December 1975. Beginning Jan. 1, 1977 gage readings are midnight readings.

Month-end gage height, in feet, and contents, in acre-fe	æt
--	----

Date	Gage height	Contents	Change in contents	TM water		
December 31, 1990	4,384.97	1,369,600	-	5.180		
January 31, 1991	4,386.69	1,416,200	+46.600	5,170		
February 28	4,387.66	1,443,000	+26.800	5.160		
March 3	4,386.62	1,414,300	-28.700	5,120		
April 30	4,386.71	1,416,700	+2.400	5,070		
May 31	4,388.36	1,462,500	+45.800	5,010		
June 30	4,390.53	1,524,400	+61.900	4 940		
July 31	4,390.47	1,522,600	-1.800	4 910		
August 31	4,392.22	1.574.000	+51,400	4 880		
September 30	4,392.20	1.573.400	-600	4.870		
October 31	4,391.46	1.551.500	-21.900	4,840		
November 30	4,393,69	1.618.200	+66 700	4 860		
December 31	4,396,76	1.713.900	+95 700	6 030		
Calendar year 1991	-		+344,300	-		

<u>Caballo Reservoir</u>.-Water-stage recorder in SE1/4SW1/4 sec. 19, T. 16 S., R. 4 W., on Rio Grande. Storage began Feb. 8, 1938; capacity, 331,500 acre-ft (by 1981 resurvey), at gage height 4,182.0 ft (above which spillway gates open automatically). Datum of gage is 43.3 ft above mean sea level, datum of 1929. 100,000 acre-ft of storage reserved for flood control. Records furnished by Bureau of Reclamation. Beginning Jan. 1, 1977, gage readings are midnight readings.

Month-end gage height, in feet, and contents, in acre-feet

Date	Gage height	Contents	Change in contents
December 31, 1990	4,145.34*	51,500	-
January 31, 1991	4,146.40	55,690	+4.190
February 28	4,148.92	66,660	+10.970
March 31	4,143.55	44,940	-21.720
April 30	4,145.67	52,770	+7.830
May 31	4,146.26	55,120	+2,350
June 30	4,144.96	50,050	-5.070
July 31	4,143.39	44,380	-5.670
August 31	4,143.03	19,100	-25.280
September 30	4,135.85	23,130	+4,030
October 31	4,138.07	28,580	+5.450
November 30	4,138.18	31,510	+2.930
December 31	4,141.52	38,260	+6.750
Calendar year 1991	-	-	-13.240

*Revised

STORAGE IN RESERVOIRS

Reservoirs in Rio Grande Basin in New Mexico

Project Storage.—The combined usable storage in Elephant Butte and Caballo Reservoirs.

Month-end contents, in acre-feet

December 21 Joon	Contents	
December 31, 1990 January 31, 1991 February 28 March 31 April 30 May 31 June 30 July 31 August 31 September 30 October 31 November 30 December 31 Calendar year 1991	1,397,000 1,443,000 1,480,900 1,430,800 1,430,000 1,547,200 1,540,100 1,566,300 1,569,800 1,553,600 1,623,300 1,724,500	Change in contents +46,000 +37,900 -50,100 +10,700 +48,500 +57,200 -7,100 +26,200 +3,500 -16,200 +69,700 +101,200 +327,500

5

And the State of the State

ိုင်ရှိ

54

TRANSMOUNTAIN DIVERSIONS

- <u>Pine River Weminuche Pass ditch (Fuchs ditch)</u>.--Water-stage recorder and 3-ft Parshall flume in sec. 33, T. 40 N., R. 4 W., at Weminuche Pass in Colorado. Diversion is from North Fork Los Pinos River in San Juan River Basin into Weminuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.
- Werninuche Pass ditch (Raber-Lohr ditch).--Water-stage recorder and 4-ft rectangular flume in sec. 33, T. 40 N., R. 4 W., at Werninuche Pass in Colorado. Diversion is from Rincon la Vaca Creek in San Juan River Basin into Werninuche Creek in Rio Grande Basin. Second enlargement was completed in 1936. Diversion for irrigation is from Rio Grande above the Del Norte gaging station.
- <u>Williams Creek Squaw Pass ditch</u>—Water-stage recorder and 2-ft Parshall flume in sec. 21, T. 39 N., R. 3 W., at Squaw Pass in Colorado. Diversion is from Williams Creek in San Juan River Basin into Squaw Creek in Rio Grande Basin. Constructed in 1938. Diversion for irrigation is from Rio Grande below Del Norte gaging station.
- <u>Tabor ditch</u>.--Water-stage n corder and 3-ft Parshall flume in sec. 35, T. 43 N., R. 3 W., at Spring Creek Pass in Colorado. Diversion is from Cebolla Creek in Gunnison River Basin into tributary of Clear Creek in Rio Grande Basin. Completed in 1910 or 1911. Diversion for irrigation is from Rio Grande below Del Norte gaging station.
- Don La Font No. 1 & 2 ditches (Piedra Pass ditch).—Water-stage recorder and 2-ft Parshall flume in sec. 4, T. 38 N., R. 1 W., at Piedra Pass in Colorado. Diversion is from tributaries of Piedra River in San Juan River Basin to South River in Rio Grande Basin. Original ditch completed in 1938, first enlargement completed in 1940. Water is imported by Colorado Game and Fish Department, beginning in 1959, to offset losses from fish culture reservoirs.
- <u>Treasure Pass diversion ditch</u>.-Water-stage recorder and 2-ft Parshall flume in sec. 31, T. 38 N., R. 2 E., at Wolf Creek Pass in Colorado. Diversion is from Wolf Creek in San Juan River Basin to a tributary of South Fork Rio Grande. Completed in 1923 or 1924. Water is diverted for irrigation from Rio Grande above the Del Norte gaging station, beginning in 1959. Prior to 1959 it was diverted below gaging station.
- Azotea tunnel.-Water-stage recorder and 10-ft Parshall flume, lat 36°51'12", long 106°40'18", at south portal of Azotea tunnel, San Juan-Chama Project. Diversion is from Rio Blanco, Little Navajo River, and Navajo River in Colorado and discharge is into Azotea Creek in New Mexico. Construction completed in 1970.

	Pine River- Weminuche	Weminuche	Williams Creek-			Treasure Pass		
	Pass	Pass	Squaw Pass	Tabor	Don La Font	diversion	Azotea	
Month	ditch	ditch	ditch	ditch	ditches	ditch	tunnel	
January	0	0	0	0	0	0	0	
February	0	0	0	0	Ō	0	Ō	
March	0	0	0	0	Ó	Ō	250	
April	0	0	0	0	0	0	27.020	
May	0	12	0	322	0	0	42.650	
June	185	673	172	378	288	9	35.650	
July	0	0	5 9	131	56	0	5,700	
August	0	0	4	88	61	0	1,030	
September	73	0	0	57	68	0	1.080	
October	17	0	0	19	0	0	20	
November	0	0	0	0	0	0	0	
December	0	0	0	0	0	0	Ō	
Cal. year	275	685	235	9 95	473	9	113,400	

Imported quantities, in acre-feet, 1991

RIO GRANDE COMPACT COMMISSION REPORT

EVAPORATION AND PRECIPITATION The last paragraph of Article VI of the Compact states, in part, — "such credits and debits shall be reduced annually to compensate for evaporation losses in the proportion that such credits or debits bear to the total amount of water in such reservoirs during the year." To provide the data needed for the computation of such evaporation losses, the Commission has encouraged the establishment and operation of evaporation stations near each major reservoir in the basin and at other selected locations. Evaporation and other climatological data collected at the several stations in Colorado and New Mexico are tabulated on the next page. At some of the stations, it was not possible to obtain evaporation records throughout the winter period. The measurements of evaporation were made in accordance with standard practice for the type of pan in use. Measurements of precipitation were made in standard 8-inch rain gages, which were supplemented at some of the stations by recording rain gages. Records for the evaporation stations at the State University, Elephant Butte Dam, and El Vado Dam antedated the creation of the Commission; the stations at Abiquiu Dam, Cochiti Dam, and Jemez Canyon Dam were established by the Corps of Engineers. All The Rio Grande Compact Commission gratefully acknowledges the cooperation of the National Oceanic and Atmospheric Administration, U.S. Army Corps of Engineers, and U.S. Bureau of Reclamation for furnishing the climatological records contained in Alamosa Airport.--Lat 37°27', long 105°52', in Alamosa County at airport near Alamosa, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 7,536 ft. Platoro Dam.--Lat 37°21', long 106°30', in Conejos County near Platoro, Colo. Standard class A pan, anemometer, maximum and minimum thermometers, fan type psychrometer, standard 8-inch and recording rain gages at elevation 9,826 ft. Heron Dam.-Lat 36°40', long 106°42', in Rio Arriba County about 4 mi. northeast of Heron Dam near Tierra Amarilla, N. Mex. Standard class A pan, maximum and minimum thermometers, and standard 8-inch rain gage at elevation 7,310 ft. El Vado Dam.-Lat 36°36', long 106°44', in Rio Arriba County at El Vado Dam near Tierra Amarilla, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,750 ft. Abiquiu Dam.--Lat 36°14', long 106°26', in Rio Arriba County at Abiquiu Dam near Abiquiu, N. Mex. Standard class A pan, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 6,380 ft. Nambe Falls Dam.--Lat 35°51', long 105°54', in Santa Fe County at Nambe Falls Dam, N. Mex. Standard class A pan, maximum and minimum thermometers, recording thermograph, standard 8-inch and recording rain gages at elevation 6,840 ft. Cochiti Dam.-Lat 35°38', long 106°19', in Sandoval County at operations building, at Cochiti Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,560 ft. Jemez Canyon Dam.-Lat 35°23', long 106°32', in Sandoval County at Jemez Canyon Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 5,388 ft. Elephant Butte Dam,-Lat 33°09', long 107°11', in Sierra County at Elephant Butte Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, and standard 8-inch rain gage at elevation 4,576 ft. Caballo Dam.-Lat 32°54', long 107°18', in Sierra County at Caballo Dam, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 4,190 ft. <u>New Mexico State University</u>.-Lat 32°17', long 106°45', in Doña Ana County at University Park, N. Mex. Standard class A pan, anemometer, maximum and minimum thermometers, standard 8-inch and recording rain gages at elevation 3,881 ft.

55

0€**653**

56

EVAPORATION AND PRECIPITATION 1991

Evaporation and precipitation, in inches

Station		Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Annual
Alamosa	Evap.	-	-	-	-	-	-	-	-	-	-	-	-	-
Airport	Precip.	0.14	0.36	0.32	0.16	0.66	0.30	0.59	0.88	0.70	0,95	1.23	0.98	7.27
Platoro	Evap.	-	-	-	-	-	5.06	6.36	3.70	3.94	-	-	-	-
Dam	Precip	-	-	-	-	-	1.41	2.67	5.53	2.66	0.01	-	-	-
Heron	Evap.	-	-	-	4.06	6.84	9.30	6.77	6,04	4.96	2. 98	-	-	-
Dam	Precip.	0.84	0.79	1.63	2.0 5	1.39	0.73	3.00	2.94	2.37	1.92	1.55	3.05	22.26
El Vado	Évap.	-	-	-	6.12	8.43	7.35	8.01	6.65	5.27	4.63	-	-	-
Dam	Precip.	0.55	0.06	1.67	0.09	0.65	1.23	1.99	3.34	1.51	0.95	1.87	1.21	15.12
Abiquiu	Evap.	-	-	-	7.82	10.00	9.08	8.96	7.89	5.97	5.78	-	-	55 <i>.</i> 50
Dam	Precip.	0.07	0.00	0.11	0.07	1.25	1.81	2.87	2.81	1.04	0.24	1.85	0.80	12. 92
Nambe	Evap.	-	-	-	6.76	10.74	9.71	9,39	7.98	6.57	5.29	-	-	-
Falls Dam	Precip.	0.18	0.00	0.95	0.17	2.88	1.61	4.67	3.83	2.76	0.56	1 .76	1.43	20.80
Cochiti	Evap.	-	-	-	0.92	12.98	12.59	11 .63	9.10	7.75	7.30	-	-	-
Dam	Precip.	0 .2 7	0.55	1,10	0.00	2.69	3.01	2.67	1. 9 4	2.32	0.38	1.46	2.37	18.76
Jemez	Evap.	-	-	-	11.30	14.90	14.16	13.84	10.86	8.79	8.43	-	-	-
Canyon Dam	Precip.	0.03	0.01	0.10	0.00	1.18	0.79	3.70	1.94	1.85	0.23	1.93	1.38	13.14
									•					
Elephant	Evap.	2.38	3.85	8.88	12.83	16.61	15.79	11.46	9.44	6.87	7.17	3.43	1.87	100.58
Butte Dam	Precip.	0.61	0.34	0.12	0.00	0.15	0.38	3.63	2.03	3.46	0.37	0.82	4.35	16.26
Caballo	Evap.	-	-	•	11.43	14.36	13.49	11.33	10.75	7.48	7.24	-	-	-
Dam	Precip.	0.47	0.75	0.23	0.00	0.10	0.23	2.71	3.02	2.78	0.38	0.76	3.84	15.27
State	Evap.	-	-	7.17	10. 47	12.64	12.37	10.12	9.34	6.75	6.20	-	-	-
Univer.	Precip.	0.44	0,35	0.69	0.00	0.32	0.12	1.70	5.19	2.23	0.40	0.31	2.91	14.66



 γ_{i}

